


Service Service Service



Service Manual



Contents	Page
1 Technical Specifications and Connection Facilities	2
Diversity Matrix	2
PCB Locations	5
2 Safety Information, General Notes	6
3 Directions for Use	8
4 Mechanical Instructions	45
5 Diagnostic Software	49
6 Block Diagrams, Waveforms, Wiring Diagram	89
Wiring Diagram	92
Waveforms	93
Testpoints	97
7 Circuit Diagrams and PWB Layouts	102
Display Panel (Diagram 1)	102
Front Connector (FC) (Diagram 2)	103
Standby Panel (STBY) (Diagram 3)	107
Tray Left Panel (TRL) (Diagram 4)	108
Tray Right Panel (TRR) (Diagram 5)	109
Analog Board: Fronted Video (FV) (Diagram 1)	110
Analog Board: In / Out Video (IOV) (Diagram 2)	111
Analog Board: In / Out Audio (IOA) (Diagram 3)	112
An. Brd for VAE8020: Power Supply (PS) (Diagram 4)	113
An. Brd for VAD8031: Power Supply (PS) (Diagram 5)	114
Analog Board: Multi Sound Processing (MSP) (Diagram 5)	115
Analog Board: VPS (Diagram 6)	116
Analog Board: Follow Me (FOME) (Diagram 7)	116
Analog Board: Digital In/Out (DIGIO) (Diagram 8)	117
Analog Board: Audio Converter 603 3033 (DAC_ADC) (Diagram 9)	118
Analog Board: Audio Converter 603 3028 (DAC_ADC) (Diagram 10)	119

Contents	Page
UP Sub Board: Central Controller (CECO) (Diagram 11)	128
UP Sub Board: Fan Control (FACO) (Diagram 12)	129
DVIO Board: 1394 Interface (Diagram 1)	132
DVIO Board: Link + Codec (Diagram 2)	133
DVIO Board: uP Part (Diagram 3)	134
DVIO Board: Interface + DAC (Diagram 4)	135
DVIO Board: Clock (Diagram 5)	136
Digital Board 1.5: VSM Buffer Memory and Bit Engine Interface (Diagram 1)	140
Digital Board 1.5: AV Dec. ST15519 (Diagram 2)	141
Digital Board 1.5: AV Decoder Mem. (Diagram 3)	142
Digital Board 1.5: Video Enc. Empress (Diagram 4)	143
Digital Board 1.5: VIP CVBS Y/C Video Input (Diagram 5)	144
Digital Board 1.5: Analog Board Cons. Video In/Out (Diagram 6)	145
Digital Board 1.5: Progressive Scan (Diagram 7)	146
Digital Board 1.5: Progressive Scan (Diagram 8)	147
Digital Board 1.5: Power, Clock and Reset (Diagram 9)	148
DB Chrysalis 2.1: IDE, UARTS, RESET, BE (Diagram 1)	155
DB Chrysalis 2.1: 1394 (Diagram 2)	156
DB Chrysalis 2.1: Audio PLL (Diagram 3)	157
DB Chrysalis 2.1: Chrysalis (Diagram 4)	158
DB Chrysalis 2.1: 1.8V Power (Diagram 5)	159
DB Chrysalis 2.1: Prog. scan DAC (Diagram 6)	160
DB Chrysalis 2.1: Flash SDRAM EEPROM (Diagram 7)	161
DB Chrysalis 2.1: Video IO (Diagram 8)	162
DB Chrysalis 2.1: VIPs (Diagram 9)	163
8 Alignments	167
9 Circuit-, IC Descriptions and List of Abbreviations	170
10 Spare Parts List	246
11 Revision List	260

©Copyright 2002 Philips Consumer Electronics B.V. Eindhoven, The Netherlands.
All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, or otherwise without the prior permission of Philips.

For service manual of Basic Engine VAE8020 please refer to 3122 785 12473.
For service manual of Basic Engine VAD8031 please refer to 3122 785 13680.



PHILIPS

1. Technical Specifications and Connection Facilities

1.1 Diversity Matrix for sets with drive VAE8020 (AV2)

Type		DVDR	75/001	75/021	75/051	70/001	70/021	70/051
		Version						
		A' Lead	X	X	X			
		A Lead				X	X	X
DVIO		DVIO 1.8	<VN05	<VN05	<VN05			
Digital Board (Chrysalis) 2.1		E1	>VN04	>VN04	>VN04			
		E2				>VN04	>VN04	>VN04
Digital Board (Empress) 1.5		E1	<VN05	<VN05	<VN05	<VN05	<VN05	<VN05
Basic Engine	VAE 8020		X	X	X	X	X	X
UP Sub		AL E1	X	X	X	X	X	X
Analog-Board	3103 603 3033	AL E2/PS			<VN04			<VN04
		AL E1/PS	<VN03	<VN04		<VN03	<VN04	
	3103 603 3028	AL E2			>VN03			>VN03
		AL E1	>VN02	>VN03		>VN02	>VN03	
Display Board		DC1 AL	X	X	X	X	X	X

Remarks:

<VN03 ... This module is used in sets with production codes VN01 and VN02. Please see the type plate of the set for the production code.

>VN02 ... This module is used in sets with production code VN03 and higher.

E1 ... Digital Board Chrysalis Version Euro 1 for sets with DV input

E2 ... Digital Board Chrysalis Version Euro 2 for sets without DV input

AL E1/PS ... Analog Board version A-Lead Euro 1, used from production start onwards.

AL E2/PS ... Analog Board version A-Lead Euro 2 for UK, used from Production Start onwards.

The Analog Board versions "AL Ex/PS" are based on the PWB layout code 3103 603 3033.

This layout code can also be seen on the underside of the Analog Board in the copper near the power supply part.

AL E1 ... Analog Board version A-Lead Euro 1 replaces "AL E1/PS" at a certain production date.

AL E2 ... Analog Board version A-Lead Euro 2 for UK replaces "AL E2/PS" at a certain production date.

The Analog Board versions "AL Ex" are based on the PWB layout code 3103 603 3028.

The main difference to the Analog Board used at production start is the used audio digital/analogue converter; see Analog Board circuit diagram 9.

1.2 Diversity Matrix for sets with drive VAD8031 (AV3)

Sets with VAD8031 can be identified by the production code starting with VN1A, (then VN1B, VN1C...) and by the presence of a set fan.

Type		DVDR	75/001	75/021	75/051	70/001	70/021	70/051
		Version						
		A' Lead	X	X	X			
		A Lead				X	X	X
Digital Board (Chrysalis) 2.1		E1 /AV3	X	X	X			
		E2 /AV3				X	X	X
BasicEngine	VAD 8031		X	X	X	X	X	X
UP Sub		AL E1/AV3	X	X	X	X	X	X
Analog-Board	use PWB drawing 603 3028	AL E2/AV3			X			X
		AL E1/AV3	X	X		X	X	
Display Board		DC1 AL	X	X	X	X	X	X

1.3 General:

Mains voltage	: 198V-276V
Mains frequency	: 43 Hz - 63Hz
Power consumption mains	: 28 W
Power consumption standby	: < 7 W
Power consumption low power stand-by	: < 3 W

Maximum tuning error of a recalled program	: ± 62.5 kHz
Maximum tuning error during operation	: ± 100 kHz

Tuning Principle

automatic B,G, I, DK and L/L' detection
manual selection in "STORE" mode

1.4 RF Tuner

Test equipment: Fluke 54200 TV Signal generator
Test streams: PAL BG Philips Standard test pattern

1.4.1 System:

PAL B/G, PAL D/K, SECAM L/L', PAL I

1.4.2 RF - Loop Through:

Frequency range	: 45 MHz - 860 MHz
Gain: (ANT IN - ANT OUT)	: -6 dB to 0dB

1.4.3 Radio Interference:

input voltage /3 tone method (+40 dB min)	: no limit
---	------------

1.4.4 Receiver:

PLL tuning with AFC for optimum reception
Frequency range: : 45.25 MHz - 857 MHz
Sensitivity at 40 dB S/N : $\geq 60\text{dB}\mu\text{V}$ at 75 Ω
(video unweighted)

1.4.5 Video Performance:

Channel 25 / 503,25 MHz,
Test pattern: PAL BG PHILIPS standard test pattern,
RF Level 74 dBV
Measured on SCART 1
Frequency response: : 0 - 4.00 MHz +0-4dB
Group delay (0.1 MHz - 4.4 MHz) : 0 nsec \pm 150nsec

1.4.6 Audio Performance:**Audio Performance Analogue - HiFi:**

Frequency response at SCART 1
(L+R) output: : 100 Hz - 12 kHz / 0 \pm 3dB
S/N according to DIN 45405, 7, 1967 :
and PHILIPS standard test pattern
video signal: : FM: $\geq 50\text{dB}$; AM $\geq 45\text{dB}$, unweighted
Harmonic distortion (1 kHz, ± 25 kHz deviation): : FM $\leq 1.5\%$; AM $\leq 2\%$

Audio Performance NICAM:































Frequency response at SCART
1(L+R) output: : 40 Hz - 15 kHz 0 \pm 3dB
S/N according to DIN 45405, 7, 1967 :
and PHILIPS standard test pattern
video signal: : ≥ 60 dB unweighted
Harmonic distortion (1 kHz): : $\leq 0.5\%$

1.4.7 Tuning**Automatic Search Tuning**

scanning time without antenna : typ. 3 min. PAL
stop level (vision carrier) : $\geq 37\text{dB}\mu\text{V}$






















1.5 Analogue Inputs**1.5.1 SCART 1 (Connected to TV)**

Pin Signals:


1	- Audio R	1.8V RMS	
2	- Audio R		
3	- Audio L	1.8V RMS	
4	- Audio GND		
5	- Blue/Chroma		
	GND		
6	- Audio L		
7	- Blue out/		
	Chroma in	0.7Vpp \pm 0.1V into 75 Ohm (*)	
8	- Function		
	switch	<2V = TV >4.5V / <7V = asp. ratio 16:9 DVD >9.5V / <12V = asp. ratio 4:3 DVD	
9	- Green GND		
10	- P50 control		
11	- Green	0.7Vpp \pm 0.1V into 75 Ohm (*)	
12	- Nc		
13	- Red/Chroma		
	GND		
14	- fast switch		
	GND		
15	- Red out/		
	Chroma out	0.7Vpp \pm 0.1V into 75 Ohm (*) $\pm 3\text{dB}$ 0.3Vpp Chroma (burst)	
16	- fast switch		
	RGB/ CVBS	or Y <0.4V into 75 Ohm = CVBS >1V / <3V into 75 Ohm = RGB	
17	- Y/CVBS GND		
	OUT		
18	- Y/CVBS GND		
	IN		
19	- CVBS/Y	1Vpp \pm 0.1V into 75 Ohm (*)	
20	- CVBS/Y		
21	- Shield		

1.5.2 SCART 2 (Connected to AUX)

Pin Signals:

1	-Audio R	1.8V RMS	
2	-Audio R		
3	-Audio L	1.8V RMS	
4	-Audio GND		
5	-Blue/Chroma		
	GND		
6	-Audio L		
7	-Blue in/		
	Chroma out	$\pm 3\text{dB}$ 0.3Vpp Chroma (burst)	
8	-Function		
	switch		
9	-Green GND		
10	-P50 control		
11	-Green		
12	-Nc		
13	-Red/Chroma		
	GND		
14	-fast switch		
	GND		
15	-Red in/		
	Chroma in		

16	-fast switch RGB/ CVBS or Y	
17	-CVBS GND OUT	
18	-CVBS GND IN	
19	-CVBS/Y/RGB sync	1Vpp ± 0.1V into 75 Ohm (*)
20	-CVBS/Y	
21	-Shield	



(*) for 100% white

Intermodulation distortion	: >70dB
Mute (spin-up, pause, access)	: >85dB
Outband attenuation:	: >40dB above 25kHz

1.8 Digital Output

1.8.1 Coaxial

CDDA/ LPCM (incl MPEG1)	: according IEC958
MPEG2, AC3 audio	: according IEC1937
DTS	: according IEC1937, amendment 1

1.5.3 Audio/Video Front Input Connectors

Audio

Input voltage	: 2 Vrms
Input impedance	: >10kΩ

Video - Cinch

Input voltage	: 1 Vpp ± 3dB
Input impedance	: 75 Ω

Video - YC (Hosiden)

Input voltage Y	: 1Vpp ± 3dB
Input impedance Y	: 75 Ω
Input voltage C	: burst 300 mVpp ± 3 dB
Input impedance C	: 75 Ω

1.6 Video Performance

All outputs loaded with 75 Ohm
SNR measurements over full bandwidth without weighting.

1.6.1 SCART (RGB)

SNR	: > -65 dB on all output
Bandwidth	: 4.8 MHz ± 2dB

1.7 Audio Performance CD

1.7.1 Cinch Output Rear

Output voltage 2 channel mode	: 2Vrms ± 2dB
Channel unbalance (1kHz)	: <1dB
Crosstalk 1kHz	: >95dB
Crosstalk 20Hz-20kHz	: >85dB
Frequency response 20Hz- 20kHz	: ±0.2dB max
Signal to noise ratio	: >95 dB
Dynamic range 1kHz	: >85dB
Dynamic range 20Hz-20kHz	: >80dB
Distortion and noise 1kHz	: >85dB
Distortion and noise 20Hz-20kHz	: >75dB
Intermodulation distortion	: >77dB
Mute	: >95dB
Outband attenuation:	: >40dB above 30kHz

1.7.2 Scart Audio

Output voltage 2 channel mode	: 1.6Vrms ± 2dB
Channel unbalance (1kHz)	: <1dB
Crosstalk 1kHz	: >85dB
Crosstalk 20Hz-20kHz	: >70dB
Frequency response 20Hz- 20kHz	: ± 0.2dB max
Signal to noise ratio	: >85 dB
Dynamic range 1kHz	: >75dB
Dynamic range 20Hz-20kHz	: >70dB
Distortion and noise 1kHz	: >75dB
Distortion and noise 20Hz-20kHz	: >65dB

1.9 Digital Video Input (IEEE 1394)

1.9.1 Applicable Standards

Implementation according:
IEEE Std 1394-1995
IEC 61883 - Part 1
IEC 61883 - Part 2 SD-DVCR (02-01-1997)
Specification of consumer use digital VCR's using 6.3 mm magnetic tape - dec.1994
Mechanical connection according:
Annex A of 61883-1

1.10 P50 System Control

Via SCART pin nr 10

1.11 Dimensions and Weight

Height of feet	: 10mm
Apparatus tray closed	: WxDxH :435 x 324.5 x 88cm
Apparatus tray open	: WxDxH :435 x 366 x 88cm
Weight without packaging	: app. 4 kg ± 0.5 kg
Weight in packaging	: app. 6.5 kg

1.12 Laser Output Power & Wavelength


1.12.1 DVD

Output power during reading	: 0.8mW
Output power during writing	: 20mW
Wavelength	: 660nm

1.12.2 CD

Output power	: 0.3mW
Wavelength	: 780nm

1.13 PCB Locations

**Remarks:**

The EPG Board and the In/Out Extension Board IOE are only used in the DVDR80.


The DVIO Board is only present in the DVDR75 and only in combination with the Digital Board 1.5 (Empress). It is not present in DVDR75 with Digital Board 2.1 (Chrysalis).

2. Safety Information, General Notes

2.1 Safety Instructions

2.1.1 General Safety

Safety regulations require that during a repair:

- Connect the unit to the mains via an isolation transformer.
- Replace safety components, indicated by the symbol , only by components identical to the original ones. Any other component substitution (other than original type) may increase risk of fire or electrical shock hazard.

Safety regulations require that after a repair, you must return the unit in its original condition. Pay, in particular, attention to the following points:

- Route the wires/cables correctly, and fix them with the mounted cable clamps.
- Check the insulation of the mains lead for external damage.
- Check the electrical DC resistance between the mains plug and the secondary side:
 1. Unplug the mains cord, and connect a wire between the two pins of the mains plug.
 2. Set the mains switch to the 'on' position (keep the mains cord unplugged!).
 3. Measure the resistance value between the mains plug and the front panel, controls, and chassis bottom.
 4. Repair or correct unit when the resistance measurement is less than 1 MΩ.
 5. Verify this, before you return the unit to the customer/user (ref. UL-standard no. 1492).
 6. Switch the unit 'off', and remove the wire between the two pins of the mains plug.

2.1.2 Laser Safety

This unit employs a laser. Only qualified service personnel may remove the cover, or attempt to service this device (due to possible eye injury).

Laser Device Unit

Type	: Semiconductor laser GaAlAs
Wavelength	: 650 nm (DVD) : 780 nm (VCD/CD)
Output Power	: 20 mW (DVD+RW writing) : 0.8 mW (DVD reading) : 0.3 mW (VCD/CD reading)
Beam divergence	: 60 degree





Figure 2-1

Note: Use of controls or adjustments or performance of procedure other than those specified herein, may result in hazardous radiation exposure. Avoid direct exposure to beam.

2.2 Warnings

2.2.1 General

- All ICs and many other semiconductors are susceptible to electrostatic discharges (ESD, ) . Careless handling during repair can reduce life drastically. Make sure that, during repair, you are at the same potential as the mass of the set by a wristband with resistance. Keep components and tools at this same potential.

Available ESD protection equipment:

- Complete kit ESD3 (small tablemat, wristband, connection box, extension cable and earth cable) 4822 310 10671.
- Wristband tester 4822 344 13999.
- Be careful during measurements in the live voltage section. The primary side of the power supply (pos. 1005), including the heatsink, carries live mains voltage when you connect the player to the mains (even when the player is 'off!'). It is possible to touch copper tracks and/or components in this unshielded primary area, when you service the player. Service personnel must take precautions to prevent touching this area or components in this area. A 'lightning stroke' and a stripe-marked printing on the printed wiring board, indicate the primary side of the power supply.
- Never replace modules, or components, while the unit is 'on'.

2.2.2 Laser

- The use of optical instruments with this product, will increase eye hazard.
- Only qualified service personnel may remove the cover or attempt to service this device, due to possible eye injury.
- Repair handling should take place as much as possible with a disc loaded inside the player.
- Text below is placed inside the unit, on the laser cover shield:

CAUTION VISIBLE AND INVISIBLE LASER RADIATION WHEN OPEN AVOID EXPOSURE TO BEAM
 ADVARSEL SYNLIG OG USYNLIG LASERSTRÅLING VED ÅBNING UNDGÅ UDSÆTTELSE FOR STRÅLING
 ADVARSEL SYNLIG OCH USYNLIG LASERSTRÅLING NÄR DEKSEL ÅPNES UNNGÅ EKSPOSITION FÖR STRÅLEN
 VARNING SYNLIG OCH OSYNLIG LASERSTRÅLING NÄR DENNA DEL ÄR ÖPPNAD BETRÄKTA EJ STRÅLEN
 VAROJ AVATT AESSA OLET ALTTIINA NÄKYVÄLLE JA NÄKYMÄTTÖMÄLLE LASER SÄTEILYLLE. ÄLÄ KATSO SÄTEESEEN
 VORSICHT SICHTBARE UND UNSICHTBARE LASERSTRAHLUNG WENN ABDECKUNG GEÖFFNET NICHT DEM STRAHL AUSSETZEN
 DANGER VISIBLE AND INVISIBLE LASER RADIATION WHEN OPEN AVOID DIRECT EXPOSURE TO BEAM
 ATTENTION RAYO NNEMENT LASER VISIBLE ET INVISIBLE EN CAS D'OUVERTURE EXPOSITION DANGEREUSE AU FAISCEAU

Figure 2-2

2.2.3 Notes

Dolby

Manufactured under licence from Dolby Laboratories. "Dolby", "Pro Logic" and the double-D symbol are trademarks of Dolby Laboratories. Confidential Unpublished Works.

©1992-1997 Dolby Laboratories, Inc. All rights reserved.



Figure 2-3

Trusurround

TRUSURROUND, SRS and symbol (fig 2-4) are trademarks of SRS Labs, Inc. TRUSURROUND technology is manufactured under licence from SRS Labs, Inc.



Figure 2-4

Video Plus

"Video Plus+" and "PlusCode" are registered trademarks of the Gemstar Development Corporation. The "Video Plus+" system is manufactured under licence from the Gemstar Development Corporation.



Figure 2-5

Macrovision

This product incorporates copyright protection technology that is protected by method claims of certain U.S. patents and other intellectual property rights owned by Macrovision Corporation and other rights owners.

Use of this copyright protection technology must be authorized by Macrovision Corporation, and is intended for home and other limited viewing uses only unless otherwise authorized by Macrovision Corporation. Reverse engineering or disassembly is prohibited.

3. Directions For Use

◀◀

Select previous title/search backwards :
Briefly press the button during playback: Previous chapter/film or previous title
Hold down the button: Search backwards
Hold down button during still picture, slow motion backwards

▶▶

Select next title/search forwards :
Briefly press the button during playback: Next chapter/film or next title
Hold down the button: Search forwards
Hold down button during still picture, slow motion forwards

■

STOP
Stop: Stop playback/recording, except with programmed recordings (TIMER)
Hold down button, opens and closes the disc tray.

AUDIO
Audio: Select the audio language. For recording language 1 or 2

●

RECOTR
Record: Record the current TV channel

II

PAUSE II
Pause (still picture) If this button is pressed during playback, the DVD recorder switches to pause. You will see a still picture. If this button is pressed during recording, the DVD recorder will also switch to pause.

Additional TV functions

This will only work with TV sets with the same remote control code #RC5 (e.g. Philips TV sets)


TV VOLUME +	TV volume: Increase TV volume
TV VOLUME -	TV volume: Reduce TV volume

For the following functions you need to hold down the button at the side **DVD/TV** and then select the function you need with the appropriate button.


STANDBY ⏻	Switching the TV off:
0.9	Number buttons 0 - 9
CH+ ▲	TV programme number: To select a higher programme number
CH- ▼	TV programme number: To select a lower programme number

The remote control

MONITOR	Monitor: This button lets you switch between the TV receiver (internal tuner) in the DVD recorder (TV picture on the TV set) and playback on the DVD recorder.
STANDBY ⏻	Switch on or off: To switch set on or off; interrupt menu function, interrupt a programmed recording (TIMER)
TV/DVD	TV/DVD switch: Switches the start socket EXT 2 AUX-IO directly to the TV set. This lets you watch the picture from any unit connected to this start socket (set-top box, video recorder or satellite receiver) and at the same time record from another source. If you have not connected a device to the EXT 2 AUX-IO socket, use this button to switch between TV reception and the DVD recorder. But this only works if you use a start cable to connect the TV set to your DVD recorder (EXT 1 TO TV-IO socket) and your TV set responds to this switch-over.
T/C	Title/Chapter: Choose the T (Title) C (Chapter) directly from the menu bar If T or C appears in the display, the index menu from a recorded disc or an introductory film will be shown. In this case, this function is not available.
PLAY MODE	Playback type: Choose between repeat, shuffle play and intro-scan
REC MODE	Record type (quality): To select the maximum possible record time
0.9	Number buttons: 0 - 9
DISC-MENU	Disc menu: To show the DVD menu or the index screen
SYSTEM-MENU	System menu: Call up/cancel the main menu (menu bar at the top of the screen)
SELECT	Select: Select function/value
OK	Store/confirm: To store or confirm entry
◀ ▶	Cursor keys: Cursor left, right
CH+ ▲	Cursor buttons/Plus: Cursor up/ Next programme number
CH- ▼	Cursor buttons/Minus: Cursor down / Previous programme number
TIMER	TIMER: To make a TIMER programming with ShowView® without ShowView® or to alter or clear a programmed TIMER
FSS ✕	EDIT: For displaying the edit menu for DVD+R(W) discs, for setting chapter markers
RETURN	Back: Return to previous menu on a video CD (VCD). This also works with some DVDs.
CLEAR	Delete: To delete last entry or clear programmed recording (TIMER)
PLAY▶	Playback: To play a recorded disc.



Front of the device



- STANDBY/ON** **Switch on or off:** To switch off or on, interrupt a function, interrupt a programmed recording (TIMER)
- OPEN/CLOSE** **Open/close disc tray:** Open/close disc tray
- RECORD** **Record:** Record the current TV channel
- Play** **Playback:** To play a recorded disc
- Previous** **Select previous title/search backwards**
- Next** **Select next title/search forwards**
- Stop** **Stop:** Interrupt playback/recording


Behind the flap at the right-hand corner on the front

- S-VIDEO** **S-Video socket:** Connection of SVHS/H8 camcorders or SVHS/H8 video recorders (programme number **PH**)
- Yellow socket VIDEO** **Video input socket:** Connection of camcorders or video recorders (programme number **PH**)
- White/red socket left AUDIO right** **Audio input socket left/right:** Connection of camcorders or video recorders (programme number **PH**)

Switching between the **S-VIDEO** and **VIDEO** sockets takes place automatically. If both sockets are in use, the signal at the **S-VIDEO** socket has priority.

- DV IN** **i-Link/DV socket (digital video input, IEEE 1394, FireWire):** Connecting a digital camcorder or other suitable device (programme number **PH**).

Back of the unit



- ~ MAINS** **Mains socket:** Connection to the mains supply (230V/50Hz)
- ANTENNA IN** **Aerial input:** Connection of the aerial
- TV OUT** **Aerial output:** Connection of the TV set
- EXT 2 AUX-IO** **Start socket 2:** Connection of an additional device (satellite receiver, set-top box, video recorder, camcorder, etc.)
- EXT 1 TO TV-IO** **Start socket 1:** Connection of a TV set, RGB output

Output sockets (AUDIO/VIDEO OUT)

- OUT S-VIDEO (V/C)** **S-Video output:** Connection of an S-Video-compatible TV set
- OUT VIDEO (CVBS)** **Video output (yellow socket):** Connecting a TV set with a video input (CVBS, Composite Video)
- OUT L AUDIO R** **Analogue audio output (white/red socket):** Connection of a TV set with audio input sockets or connection of an additional device

Output socket (DIGITAL AUDIO OUT)

- DIGITAL AUDIO OUT** **Digital audio output:** Connection of a digital audio device (amplifier/receiver)

The symbols on your DVD recorder display

These symbols can light up on your DVD recorder display:

- Multi-function display/text line**
 - Clock**
 - Disc/title playing time**
 - OTR switch-off time**
 - Title name**
 - Display of the programme number of the TV channel/playing time/channel name/function.**
 - Display of information and alerts**




<div>RECORDING</div>		ENGLISH	
<div> </div> <div>Disc bar: Displays the current position on the disc (disc pointer). Play/Record: Single flashing segment at the current position. Pause: Flashing segment on both sides of the current position. Stop: Illuminated segment at the current position.</div>			
SAT	A satellite recording has been programmed.		
TIMER	A recording (timer) has been programmed		
o(((A remote control signal has been received		
VPS/PDC	Video programming system / programme delivery control: A VPS or PDC code will be transmitted for the selected TV program		
LANG II	During playback a HiFi/2 channel tone was detected or a HiFi/2 channel tone was received. 'I' or 'II' lights up depending on which sound channel has been selected		
<div>Messages in the DVD recorder display</div>			
The following messages may appear in your DVD recorder display			
IS TV ON?	The DVD recorder is in initial installation mode. Switch the TV on, then read the paragraph on 'Initial installation' in 'Installing your DVD recorder'.		
NO SIGNAL	No input signal available (signal inadequate or unstable)		
MENU	The menu on the screen is active		
OPENING	Disc tray opening		
TRAY OPEN	Disc tray open		
CLOSING	Disc tray closing		
READING	Disc being read		
MENU UP/DN	Once recording has been successfully completed the table of contents is created.		
INIT MENU	The menu structure is created after the first recording has been made on a new disc		
COPY PROT	You have tried to copy a copy-protected DVD/video cassette.		
WAIT	Please wait until this message disappears. The DVD recorder is busy performing a task.		
NO DISC	A disc has not been inserted for recording. If a disc has been inserted, it cannot be read.		
INFO BUSY	Information about the inserted DVD is displayed on the screen The DVD recorder is processing the changes to make them DVD compatible		
ERASE DISC	The entire disc is erased		

EMPTY DISC	The disc inserted is either new or has been completely erased (no recordings).
PROTECTED	The disc is protected against recording.
MAX TITLE	The maximum number of titles per disc has been reached. The maximum number of titles per disc is 48.
MAX CHAP	The maximum number of chapters per title/disc has been reached. The maximum number of chapters per title is 124.
DISC FULL	The disc is full. There is no space for new recordings
PAL DISC	A disc with PAL recordings has been inserted. The machine is trying to record an NTSC signal. Insert a new disc or one that contains NTSC recordings.
NTSC DISC	A disc with NTSC recordings has been inserted. The machine is trying to record a PAL signal. Insert a new disc or one that contains PAL recordings.
RECORDING	An illegal action (e.g. OPEN/CLOSE button) was attempted during recording.
FREE TITLE	Playback was started for an empty title or the following title is empty.
DISC LOCK	An attempt has been made to record during playback of a protected disc. This message appears if an attempt is made to insert a chapter marker (FSS < button).
DISC ERR	An error occurred when writing the title. If this error keeps occurring, please clean the disc or use a new one. For instructions on how to clean a disc see the section on 'Cleaning the discs' in the next chapter.
DISC WARN	An error occurred when writing the title. Recording was continued; the error was skipped
SETUP	After the automatic search the menu for setting the date/time will appear on the screen.
WAIT 01	During the automatic search the TV channels found are counted
BLOCKED	The disc tray cannot be closed/opened.
SAFE REC	The new recording will be added at the end of all the other recordings (SAFE RECORD).
EASYLINK	Data is being transferred from the 'EasyLink' TV.
POST-FORMAT	Post format

2 Connecting the DVD recorder

Preparing the remote control for operation



The remote control and its batteries are packed separately in the original DVD recorder packaging. You must install the batteries in the remote control before use - described in the following section.

- 1 Take the remote control and the enclosed batteries (2 batteries).
- 2 Open the battery compartment, insert the batteries as shown and then close the battery compartment.

The remote control is now ready to use.
Its range is approximately 5 to 10 meters.



'Aim' correctly

In the following sections, you will need the remote control for the first time.
Aim the remote control at the DVD recorder and not at the TV set.

Tip

Connecting your DVD recorder to the TV set

The necessary cable connections must be made before you can record or playback TV programmes using your DVD recorder.

Connect the DVD recorder **directly** to your TV set. If there is a video recorder in between the picture quality may be poor.
We recommend that you use a scart cable to connect your TV set and DVD recorder.



What is a scart cable?


The scart or Euro AV cable serves as the universal connector for picture, sound and control signals. With this type of connection, there is practically no loss of quality in picture or sound transmission.



ENGLISH

Connecting with a scart cable and 'Easy Link'

Your DVD recorder can exchange information with your TV set using 'Easy Link'. Your TV channels can also be transferred in the same order from your TV set to your DVD recorder using 'Easy Link'.
Please see your TV's operating instructions.



Have the following cables ready:
an aerial cable (1, supplied), a mains cable (2, supplied), a special scart cable (3, suitable for Easylink).

- 1 Switch off your TV set.
- 2 Remove the aerial cable plug from your TV set. Insert it into the **ANTENNA IN** socket at the back of the DVD recorder.
- 3 Insert one end of the supplied aerial cable into the **TV OUT** socket at the back of the DVD recorder and the other end into the aerial input socket at the back of the TV set.
- 4 Plug in a special scart cable (for Easylink) into the scart socket **EXT 1 TO TV-IO** at the back of the DVD recorder and the corresponding scart socket at the back of the TV set (see TV set operating instructions).

When you install your DVD recorder for the first time, select one of the following options:

'Connecting with a scart cable and Easy Link'

If your TV set is equipped with 'Easy Link', Cinema Link, NextView Link, Q-Link, Smart Link, Megalogic, Datalogic, ... and you wish to use a scart cable.

'Connecting with a scart cable without Easy Link'

If your TV set is not equipped with 'Easy Link', Cinema Link, NextView Link, Q-Link, Smart Link, Megalogic, Datalogic, ... and you wish to use a scart cable.

'Connecting with an S-Video(Y/C) cable'

If your TV set is equipped with an S-Video(SVHS) socket.


'Connecting with video(CVBS) cable'

If your TV set is equipped only with an video(CVBS) socket.



Connecting with a scart cable without 'Easy Link'

Have the following cables ready:
an aerial cable (1. supplied), a mains cable (2. supplied), a scart cable (3).



- 1

Remove the aerial cable plug from your TV set. Insert it into the **ANTENNA IN** socket at the back of the DVD recorder.
- 2

Insert one end of the supplied aerial cable into the **TV OUT** socket at the back of the DVD recorder and the other end into the aerial input socket at the back of the TV set.
- 3

Plug a scart cable into the scart socket **EXT 1 TO TV-IO** at the back of the DVD recorder and the scart socket for the DVD recorder at the back of the TV set (see TV set operating instructions).

My TV set has several scart sockets. Which one should I use?
Select the scart socket that is suitable for both video output and for video input.

My TV set shows me a selection menu for the scart socket.
Select 'VCR' as the source for this scart socket.
- 4

Switch on the TV set.
- 5

Insert one end of the supplied mains cable into the mains socket **~MAINS** at the back of the DVD recorder and the other end into the wall socket.

The most important features of the DVD recorder will appear in scrolling text on the display. After the first installation is completed this function will be switched off. How you switch on this function again, read in the chapter 'User preferences' in the section 'standby'.
- 6

Switch on the DVD recorder using **STANDBY/ON**. '15 TV CH' will appear on the display.
- 7

If the connection was properly made and your TV was **automatically switched** to the programme number for the scart socket, e.g. 'EXT', '0', 'AV', you will see the following picture:

ENGLISH

- 5


Switch on the TV set.
- 6

Insert one end of the supplied mains cable into the mains socket **~MAINS** at the back of the DVD recorder and the other end into the wall socket.
- 7

A message appears on the screen announcing that the transfer has started. **~~~~~** appears on the display during transfer.

The TV set transfers all saved TV channels in the same order, to the DVD recorder.

This may take several minutes.



EasyLink:
loading data from TV;
please wait

Problem

***'Time', 'Year', 'Month', 'Date' appears on the TV screen**
Normally the date and time are taken from the data sent by the TV channel stored on programme P01. If the aerial signal is too weak or there is excessive interference, you should set the date and time manually:


- Check if the time in **'Time'** is correct.
- If required, change the time with the number buttons **0-9** on your remote control.
- Select the next line with **CH+▲** or **CH-▼**.
- Check if the displayed settings for **'Year', 'Month'** and **'Date'** are correct.
- When all information is correct, save by pressing **OK**.

Problem

***I can see more installation menus on my TV set**
Not all the necessary data has been transferred. Please enter the settings by hand as follows. For more information on the various functions see 'Initial installation' in 'Installing your DVD recorder'.

- Select the desired audio language using **CH-▼** or **CH+▲** and confirm with **OK**.
- Select the desired subtitle language with **CH-▼** or **CH+▲** and confirm with **OK**.
- Select the desired screen format position using **CH-▼** or **CH+▲**.
- '4:3 letterbox'** For a 4:3 TV set: cinema format (black bars above and below the picture)
- '4:3 panscan'** For a 4:3 TV set: full height format with the sides cut off
- '16:9'** For a 16:9 TV set
- Confirm with **OK**.
- Select the country of your residence with **CH-▼** or **CH+▲**.
- If your country does not appear, select **'Other'**.
- Confirm with **OK**.

Initial installation is now complete.



Problem

✖ **My screen is empty.**


- ✓ Many TV sets are switched by the DVD recorder to the programme number for the start socket by way of a control signal sent through the start cable.
- ✓ If the TV set does not automatically switch to the start socket programme number, manually change to the corresponding programme number on your TV set (see your TV's operating instructions).
- ✓ Check that the start cable is connected from the TV set to the **EXT 1 TO TV/IO** socket on the DVD recorder. The **EXT 2 AUX/IO** socket is intended only for additional devices.

ENGLISH

Then, read the paragraph on 'Initial Installation' in 'Installing your DVD recorder'.


Connecting with an S-Video(Y/C) cable

This connecting cable, also known as the SVHS cable, is used to transmit the brightness signal (Y signal) and colour signal (C signal) separately. This mini DIN socket/plug is also called a Hosiden socket/plug.




Have the following cables ready:
an aerial cable (1, supplied), a mains cable (2, supplied), an S-Video(SVHS) cable (3), an audio cable (4, supplied, red/white plug).



1 Remove the aerial cable plug from your TV set. Insert it into the **ANTENNA IN** socket at the back of the DVD recorder.




2 Insert one end of the supplied aerial cable into the **TV OUT** socket at the back of the DVD recorder and the other end into the aerial input socket at the back of the TV set.



3 Insert one end of an S-Video(SVHS) cable into the **OUT S-VIDEO** (YC) socket at the back of the DVD recorder and the other end into the S-Video (SVHS) input socket on the TV set (usually labelled 'S-Video in' or 'SVHS in'. See TV operating instructions).



4 Insert one end of the supplied audio (Cinch) cable into the red/white Cinch socket. **OUT L AUDIO R** at the back of the DVD recorder and the other end into the audio input socket (usually red/white) on the TV set (usually labelled 'Audio in' or 'AV in'. See TV operating instructions).



5 Switch on the TV set. Switch the TV set over to the SVHS input socket or select the relevant programme number. Please see your TV's operating instructions for the programme number you need.

6 Insert one end of the supplied mains cable into the mains socket and the other end into the wall socket.


7 The most important features of the DVD recorder will appear in scrolling text on the display. After the first installation is completed this function will be switched off. How you switch on this function again, read in the chapter 'User preferences' in the section 'standby'.

8 Switch on the DVD recorder using **STANDBY/ON** . 15 TV ^{EN} will appear on the display.


Then, read the paragraph on 'Initial installation' in 'Installing your DVD recorder'.

Connecting with video(CVBS) cable


This cable, usually with yellow Cinch connectors, is used for transmitting the Composite Video signal (FBAS, CVBS). In this method of transmission the colour signal and the brightness signal are transmitted on the same cable. In certain circumstances, this can lead to problems with the picture, such as 'Moiré' patterns.



Have the following cables ready:
an aerial cable (1, supplied), a mains cable (2, supplied), a video (CVBS) cable (3, supplied, yellow plug), an audio cable (4, supplied, red/white plug).




1 Remove the aerial cable plug from your TV set. Insert it into the **ANTENNA IN** socket at the back of the DVD recorder.




2 Insert one end of the supplied aerial cable into the **TV OUT** socket at the back of the DVD recorder and the other end into the aerial input socket at the back of the TV set.

3

Connecting additional devices


- 

3 Insert one end of the supplied video (CVBS) cable into the yellow Cinch socket **OUT VIDEO (CVBS)** at the back of the DVD recorder and the other end into the video input socket (usually yellow) on the TV set (usually labelled 'Video in' or 'AV in'. See TV operating instructions).



4 Insert one end of the supplied audio (Cinch) cable into the red/white Cinch socket **OUT L AUDIO R** at the back of the DVD recorder and the other end into the audio input socket (usually red/white) on the TV set (usually labelled 'Audio in' or 'AV in'. See TV operating instructions).

5 Switch on the TV set. Switch the TV set over to the Video/Audio input socket or select the relevant programme number. Please see your TV's operating instructions for the programme number you need.



6 Insert one end of the supplied mains cable into the mains socket **~ MAINS** at the back of the DVD recorder and the other end into the wall socket.
The most important features of the DVD recorder will appear in scrolling text on the display. After the first installation is completed this function will be switched off. How you switch on this function again, read in the chapter 'User preferences' in the section 'standby'.


7 Switch on the DVD recorder using **STANDBY ON**. '15 TV OFF' will appear on the display.

Then, read the paragraph on 'Initial Installation' in 'Installing your DVD recorder'.

Connecting the DVD recorder

17

Connecting additional devices to the second scart socket



You can connect additional devices such as decoders, satellite receivers, camcorders, etc. to the **EXT 2 AUX-IO** socket. When playback is started on this additional device the DVD recorder automatically connects the **EXT 2 AUX-IO** scart socket with the **EXT 1 TO TV-IO** scart socket. You will then see the picture from the additional device on your TV set, even if the DVD recorder is switched off.
The **TV/DVD** button on the remote control allows you to switch between playback through the **EXT 2 AUX-IO** scart socket and playback from the DVD recorder.

Connecting additional video recorders

You can connect a video recorder to the **EXT 2 AUX-IO** socket.
If you have an SVHS video recorder you can also use the **OUT S-VIDEO (V/S)** socket and the **OUT L AUDIO R** sockets.

Please note:


Most prerecorded video cassettes and DVDs are copy-protected. If you try to copy them you will see the message "COPY PROTECT" on the DVD recorder's display.

✖ **When copying video cassettes the display on the DVD recorder shows "COPY PROTECT".**

 - ✓ Check that the cable is plugged in firmly.
 - ✓ If a recording is made from a video recorder, change the tracking on the video recorder.
 - ✓ The DVD recorder may not be able to recognise the video input signal if this signal is poor or does not comply with relevant standards.

✖ **When I copy DVD video discs or prerecorded video cassettes the picture is fuzzy and the brightness varies**

 - ✓ This happens if you try to copy DVDs or video cassettes that have been copy-protected. Even though the picture on the TV is fine the recording on a DVD-R(W) is faulty. This interference is unavoidable with copy-protected DVDs or video cassettes.



Problem


Connecting additional devices

18

Connect camcorder to the front sockets

To copy camcorder recordings, you can use the front sockets. These sockets are located behind the flap on the left hand side.

Best picture quality

If you have a DV or Digital 8 camcorder, connect the **DV IN** input of the DVD recorder to the appropriate DV output on the camcorder.
When films are transferred the original recording data and time are stored as DVD subtitles. On playback, this data can be displayed on the TV screen by using the  function (Subtitle).


Very good picture quality

If you have a Hi8 or S-VHS(C) camcorder, connect the **S-VIDEO** input of the DVD recorder to the appropriate S-VHS output on the camcorder.
You must also connect the audio input **left AUDIO right** on the DVD recorder to the audio output on the camcorder.

Good picture quality

If you have a camcorder that only has a single video output (Composite Video, CVBS), connect the **VIDEO** input on the DVD recorder to the appropriate output on the camcorder.
You must also connect the audio input **left AUDIO right** on the DVD recorder to the audio output on the camcorder.

Connecting audio devices to the analogue audio sockets



Two audio output sockets **OUT L AUDIO R** are located on the back of the DVD recorder (audio signal output left/right)

These can be used to connect the following:
• a receiver with **Dolby Surround Pro Logic**
• a receiver with **two-channel analogue stereo**

Can I use the 'Phono' input on my amplifier?

This socket (input) on the amplifier is designed only for record players without preamplifiers. Do **not** use this input for connecting the DVD recorder.
The DVD recorder or the amplifier may be damaged as a result.



At the back of the DVD recorder there is a digital audio output socket **DIGITAL AUDIO OUT** for an coaxial cable.

These can be used to connect the following:
• an **AV receiver or an AV amplifier with a digital multi-channel sound decoder**
• a receiver with **two-channel digital stereo (PCM)**


Digital multi-channel sound

Digital multi-channel sound offers the best possible sound quality. You will need a multi-channel AV receiver or amplifier that supports at least one of the audio formats of the DVD recorder (MPEG2, Dolby Digital and DTS). Consult the operating instructions for your receiver to find out which audio formats it supports.

* All I can hear from my loudspeakers is a loud distorted noise

✓ The receiver is not compatible with the digital audio format of the DVD recorder. The audio format of the DVD disc is displayed in the status window when you switch to another language. Playback in six-channel digital surround sound is only possible if the receiver has a digital multi-channel sound decoder.

Initial installation



After successfully connecting your DVD recorder to the TV set and other additional devices as described in the previous chapters, this chapter will show you how to start the initial installation. The DVD recorder automatically seeks out and stores all available TV channels.

ENGLISH

Connecting additional devices

If you have connected additional devices such as a satellite receiver to the aerial cable, switch them on. The automatic channel search will recognise it and save it.

No aerial connected

Even if you want to use the DVD recorder to play back or have only connected a satellite receiver, you must still complete the initial installation. This is necessary so that the basic settings are stored correctly. Once initial installation is complete you can use the DVD recorder as normal.

Tip

Virgin mode

Menu Language

English
Español
Français
Italiano
Deutsch

Press OK to continue

1 Select the desired language for the on-screen menu by pressing **CH-▼** or **CH+▲**.

What is an on-screen menu?

The multi-language on-screen menu takes the mystery out of using your new DVD recorder. All settings and/or functions are displayed on your TV screen in the relevant language.

2 Confirm with **OK**.

Virgin mode

Audio Language

English
Español
Français
Italiano
Deutsch

Press OK to continue

3 Select the desired audio language using **CH-▼** or **CH+▲**.

What is an audio language?

The DVD will play the sound in the language you select, provided this language is available on the disc. If it is not available on the disc the first language on the DVD will be used instead. The DVD Video Disc menu, if available, will also be displayed in the language you select.

4 Confirm with **OK**.

Virgin mode

Subtitle Language

English
Español
Français
Italiano
Deutsch

Press OK to continue

5 Select the desired language for the subtitles by pressing **CH-▼** or **CH+▲**.

What is the subtitle language?

The subtitles will be displayed in the language you select, provided this language is available on the disc. If it is not available on the disc the first language on the DVD will be used instead.

6 Confirm with **OK**.

7

Virgin mode

TV Shape

4:3 letterbox
4:3 panscan
16:9

Press OK to continue

Select the desired screen format position using **CH-▼** or **CH+▲**. These settings will only be used if you insert a DVD that contains this information.

Which screen formats can I select?

for a 'wide-screen' (cinema format) picture with black bars at the top and bottom.

for a full-height picture with the sides trimmed.

for a wide-screen TV set (screen edge ratio 16:9)

8 Confirm with **OK**.

9

Virgin mode

Country

Austria
Belgium
Denmark
Finland
France

Press OK to continue

Select the country of your residence with **CH-▼** or **CH+▲**. If your country does not appear, select **Other**.

Why do I have to select a country?

To call up the specific settings for the respective country, you must first install the country.

10 Confirm with **OK**.

11

After you connect the aerial (or cable TV, satellite receiver, etc.) to the DVD recorder, press **OK**. The automatic TV channel search starts. 'HFI 1' will appear on the display.

Installation

Autom. search

Searching for TV channels

00 Channels found

Please wait

*The DVD recorder cannot find any TV stations

✓ Select channel 1 on the TV set. Can you see the stored TV channel on the TV set?

If not, check the cable connection from the aerial (aerial socket) to the DVD recorder and to the TV set.

✓ Please have patience.

The DVD recorder searches the entire frequency range in order to find and save the largest possible number of TV channels.

✓ If you have not connected an aerial, go through all the basic settings right to the end and then, if you wish, start the automatic search (see Automatic TV station search).

Problem

12

When the automatic TV channel search is complete, **Autom. search complete** will appear on the TV screen. **'Time', 'Year', 'Month', 'Date'** will then appear on the TV screen.

13

Check if the time in **'Time'** is correct

14

If required, change the time with the number buttons **0..9** on your remote control.

15

Select the next line with **CH+▲** or **CH-▼**.

Autom. search

Autom. search complete

00 Channels found

Time 2001
Year 01
Month 01
Date 01

To continue
Press OK

- 16
- Check if the displayed settings for 'Year', 'Month' and 'Date' are correct.
- 17
- When all information is correct, save by pressing **OK**.

The initial installation is now complete.

ENGLISH

Satellite receiver

If you are connecting a satellite receiver, please read the section on 'Using a satellite receiver'.

Decoder

If you are connecting a decoder, you must install it as described in the next section.

Tip

x Sound may be distorted on some TV channels.
✓ If the sound is distorted on any of the stored TV channels or if there is no sound at all, the wrong TV system may have been stored for the TV channel. Read 'Manual TV channel search' for information on how to change the TV system.

Using a satellite receiver


TV channels from a satellite receiver (connected to start socket **EXT 2 AUX/IO**) are received on the DVD recorder on programme number **EXT2**.

If necessary, use the **MONITOR** button to switch to the internal tuner. Select programme number **EXT1** with **0** on the remote control and then select programme number **EXT2** with **CH-▼**.

You should select the TV channels to be received by the satellite receiver directly on the receiver itself.

Allocating a decoder

Some TV channels send coded TV signals that can only be viewed properly with a purchased or rented decoder. You can connect such a decoder (descrambler) to your DVD recorder. The following function automatically activates the connected decoder for the TV channel you want to watch.



How do I allocate the decoder for Easy Link?

If your TC-V set supports 'Easy Link' the decoder must be assigned to the relevant TV channel on the TV set (see the operating instructions for your TV set). Settings cannot then be made in this menu.

- 1
- Switch on the TV set. If required, select the programme number for the DVD recorder.
- 2
- Switch on the DVD recorder using **STANDBY/ON**.
- 3
- Use the **CH+▲** and **CH-▼** buttons or the number buttons **0-9** on the remote control to select the TV channel for which you want to use the decoder. If necessary, use the **MONITOR** button to switch to the internal tuner.
- 4
- Press the **SYSTEM-MENU** button on the remote control. The menu bar appears.
- 5
- Select **T1** symbol with **◀** or **▶**.
- 6
- Select **'Installation'** using **CH-▼** or **CH+▲** and confirm with **▶**.
- 7
- Select **'Manual search'** using **CH-▼** or **CH+▲** and confirm with **▶**.
- 8
- Select **'Decoder'** using **CH-▼** or **CH+▲**.
- 9
- Select **'On'** with **◀** or **▶**.
- 10
- Confirm with **OK**.
- 11
- To end, press **SYSTEM-MENU**.

How do I switch the decoder off again?

Use **▶** to select **'Off'** in the **'Decoder'** line on the screen (Decoder off).




Installation	Manual search
Channel/freq.	CH
Entry/search	01
Programme number	BBC1
TV channel name	Off
Decoder	PAL-BG
TV system	On
NICAM	0
Fine tuning	To store Press OK

Your decoder has now been allocated to this TV channel.

Manual TV channel search

In some cases, not all of the available TV channels may have been found and stored during initial installation. In this case, you will need to search for and store the missing or coded TV channels manually.



Tip
With 'Easy Link', the DVD recorder will automatically download the TV channels stored on the TV set. This is why some lines have no function. To store new TV channels, they must first be stored on the TV set. The information will then be transferred to the DVD recorder automatically.

- 1 Switch on the TV set. If required, select the programme number for the DVD recorder.
- 2 Switch on the DVD recorder using **STANDBY/ON**.
- 3 Press **SYSTEM-MENU** on the remote control. The menu bar appears.
- 4 Select **TV** symbol with **◀** or **▶**.
- 5 Select **'Installation'** using **CH-▼** or **CH+▲** and confirm with **▶**.
- 6 Select **'Manual search'** using **CH-▼** or **CH+▲** and confirm with **▶**.

Installation	
Manual search	
Channel/freq.	CH
Entry/search	01
TV channel number	BBC1
TV channel name	01
Decoder	01
TV system	PAL-BG
NICAM	0n
Fine tuning	0
	To store Press OK



Problem

x I don't know the channel for my TV station
✓ In this case, press **▶** to start the automatic search. A changing channel number/frequency number will appear on the TV screen. Continue the automatic search until you have found the TV channel you are looking for.

- 7 In **'Channel/freq.'**, select the desired display using **▶**.
'Freq.'(Frequency), **'CH'**(Channel), **'S-CH'**(Specialhyperband channel)
- 8 In **'Entry/search'**, enter the frequency or channel of the TV station using the number buttons **0-9**.
- 9 Using **◀** or **▶** in **'Programme number'**, select the programme number you want to use for the TV channel, e.g. **01**.

How can I change the symbol of a TV channel?

- 1 In **'TV channel name'**, press **▶**.
- 2 Select the desired symbol position using **◀** or **▶**.
- 3 Change the symbol at the symbol position with **CH-▼** or **CH+▲**.
- 4 Select the next symbol position in the same way.
- 5 Keep pressing **▶** until the cursor disappears.



Tip

How can I change the TV system of the TV channel?

In **'TV system'**, use **◀** or **▶** to select the TV system that produces the least distortion of picture and sound.

What is NICAM?

NICAM is a digital sound transmission system. Using NICAM, you can transmit either 1 stereo channel or 2 separate mono channels. However, if reception is poor and the sound distorted you can turn off NICAM. In **'NICAM'**, select **'Off'** using **◀** or **▶**.

How can I improve the automatic process for storing channels?

To change the automatic process for storing channels (fine tuning), select **'Fine tuning'**. Using **◀** or **▶** you can try to fine-tune the TV channel manually.



Tip

- 10 Press **OK** to store the TV channel.
- 11 To search for other TV channels, begin again at **8**.
- 12 To end, press **SYSTEM-MENU**.

Sorting TV channels automatically (Follow TV)

When the automatic channel search function is activated, the TV channels are stored in a specific order. This may differ from the order in which the TV channels appear on your TV set. This function changes the order of the TV channels stored in your DVD recorder to match the order on the TV set.

This only works if the DVD recorder (**EXT 1 TO TV/IO** socket) and the TV set are connected with a **scart** cable.




What does EasyLink do?

If your TV set supports 'EasyLink', TV channels will be stored during initial installation in the same order as they appear on the TV set. To store the TV channels in a different order, you'll need to change the order on the TV set. When you start the Follow TV function the information is transferred again from the TV set.

- 1 Switch on the TV set. If required, select the programme number for the DVD recorder.

Automatic TV channel search

During installation, all available TV channels are searched for and stored. If the channel assignments of your cable or satellite TV provider change or if you are reinstalling the DVD recorder, e.g. after moving house, you can start this procedure again. This will replace the stored TV channels with the new ones.




What does Easy Link do?

With Easylink, you can search for and store TV channels only on the TV set. These settings are accepted by the DVD recorder. Use this function to start the transfer of TV channels from the TV set.



- 1 Switch on the TV set. If required, select the programme number for the DVD recorder.
- 2 Switch on the DVD recorder using **STANDBY/ON**.
- 3 Press **SYSTEM-MENU** on the remote control. The menu bar appears.
- 4 Select **TV** symbol with **◀** or **▶**.
- 5 Select **Installation** using **CH- ▼** or **CH+ ▲** and confirm with **▶**.
- 6 Select **Autom. search** using **CH- ▼** or **CH+ ▲**.
- 7 Press **▶**.
- 8 The automatic TV channel search starts. This allows the DVD recorder to save all available TV channels. This procedure may take several minutes.
- 9 When all the TV channels have been found, **'Autom. search complete'** will appear on the TV screen.
- 10 To end, press **SYSTEM-MENU**.



You can read about how to search for a TV channel manually in 'Manual TV channel search'.

- 2 Switch on the DVD recorder using **STANDBY/ON**.
- 3 Press the **SYSTEM-MENU** button on the remote control. The menu bar appears.
- 4 Select **TV** symbol with **◀** or **▶**.
- 5 Select **Installation** using **CH- ▼** or **CH+ ▲** and confirm with **▶**.
- 6 Select line **'Follow TV with CH- ▼ or CH+ ▲'** and confirm with the **▶** button.
- 7 Confirm the message on the screen with **OK**. **'TV' □ f** will appear in the DVD recorder display.
- 8 Select programme number **'1'** on the TV set.

TV □ f

Problem
x I cannot switch my TV set to programme number '1'.
✓ If you have connected additional devices to the **EXT 2 AUX/IO** socket, please disconnect these devices. Other connected devices may have switched the TV set to the programme number of the start socket.



ENGLISH

- 9 Confirm with **OK** on the DVD recorder remote control. **'Hfl 1'** will appear in the display. The DVD recorder compares the TV channels on the TV set and the DVD recorder. If the DVD recorder finds the same TV channel as on the TV set it stores it at **'P01'**.

Problem
x **'Hfl 1'** will appear in the display. The DVD recorder is not receiving a video signal from the TV set.
✓ Check the connectors at both ends of the start cable.
✓ Check your TV's operating instructions to see which start socket is used for video signals.
✓ If the problem persists, you won't be able to use this feature. Please read 'Adding and clearing TV channels manually'.



Problem

- 10 Wait until for example **'TV □ f'** appears in the display.
- 11 Select the next programme number on the TV set, e.g. **'2'**.
- 12 Confirm with **OK** on the DVD recorder remote control.

TV □ f


Deleting sorting
You can delete incorrect TV channel sorting by pressing **◀**.



Tip

- 13 Repeat steps **10** to **12** until you have assigned all the TV channels.
- 14 To end, press **SYSTEM-MENU**.


Adding and clearing TV channels manually



After you have performed the automatic channel search you may not agree with the sequence in which the individual TV channels have been allocated to the programme positions (programme numbers). You can use this function to rearrange the TV channels already stored or to delete TV channels you don't want or those with poor reception.

EasyLink
With EasyLink, you can search for and store TV channels only on the TV set. These settings are then accepted by the DVD recorder.
That is why you cannot select this function manually.


The teletext clock resets automatically
If you store a TV channel which transmits TXT/PGC on programme number 'P01', the date and time will automatically be transmitted and constantly updated. As a result, the changes from summer time to winter time and back again will be made automatically.

**Tip**

- 1 Switch on the TV set. If required, select the programme number for the DVD recorder.
- 2 Switch on the DVD recorder. Press the **SYSTEM-MENU** button on the remote control. The menu bar appears.
- 3 Select **TV** symbol with **◀** or **▶**.
- 4 Select **'Installation'** using **CH-▼** or **CH+▲** and confirm with **▶**.
- 5 Select **'Sort TV channels'** using **CH-▼** or **CH+▲** and confirm with **▶**.


- 6 Using **CH-▼** or **CH+▲** select the TV channel that you want to delete or whose order you want to change.
- 7 Confirm with **▶**.

Deleting TV channels
Unwanted channels or those with poor reception can be deleted using **CLEAR**. Proceed at step 6.

**Tip**


- 8 Using **CH-▼** or **CH+▲**, shift the TV channel to the desired position and press the **◀** button. The DVD recorder will insert the TV channel.
- 9 Repeat steps 6 to 8 until you have resorted/deleted all the TV channels you want.
- 10 To store, press **OK**.
- 11 To end, press **SYSTEM-MENU**.

Setting the language/country



You can select the country and, for DVD playback, the language for the subtitles and the audio language. Please note that with some DVDs the audio language and/or subtitle language can be changed only via the DVD menu.
For bilingual shows you can also select the sound channel of the TV station for recording. You also have the option of setting one of the displayed languages for the on-screen menu (OSD). However, the DVD recorder display will only display English text regardless of this setting.

- 1 Switch on the TV set. If required, select the programme number for the DVD recorder.
- 2 Switch on the DVD recorder using **STANDBY/ON**.
- 3 Press **SYSTEM-MENU** on the remote control. The menu bar appears.
- 4 Select **TV** symbol with **◀** or **▶**.
- 5 Select line **'Language'** with **CH-▼** or **CH+▲**, and confirm with the **▶** button.
- 6 Select the appropriate line and confirm with **▶**.


**Tip**

Which settings can I choose?
'Audio Language': Playback language (audio language)
'Recording audio': Type of audio recording **'Language 1'** or **'Language 2'**
'Subtitle': Subtitle language
'Menu': Language of the OSD menu
'Country': Location (country)

- 7 Select the appropriate setting using **CH-▼** or **CH+▲** and confirm with **OK**.
- 8 To end, press **SYSTEM-MENU**.

Switching over audio recording (2-channel sound)

Some TV programmes transmit an extra audio signal in stereo in addition to the normal audio signal (2-channel sound). In most cases this means that an additional language is available. If a TV programme is available in, say, English and German, German may be available as the second language.
To record TV programmes in stereo or 2-channel sound you can select Stereo or the language you want as the default setting. This setting does not become active until the sound of a TV programme is transmitted in 2-channel sound.
When you play back the recording you can play back the sound only in the language you used for the recording.



5 On-screen information

You can check or change many of the functions and settings of your DVD recorder via the system menu bar. The menu bar cannot be displayed during recording.

Symbols in the menu bar

Press **SYSTEM-MENU** to open and close the menu bar (main menu). Use **◀** and **▶** to select the relevant function. Use **CH-▼** to confirm the function and go either to another menu or execute the function directly. Some functions may not be available, depending on the disc inserted.

Menu bar 1



	User preferences
	Title track
	Chapter/index
	Audio language
	Subtitle language
	Camera angle
	Zoom

Menu bar 2




While menu bar 1 is being displayed you can go to menu bar 2 by pressing **▶** again.

	Sound
	Frame advance
	Slow motion
	Fast forward
	Search by time


ENGLISH

- 1 Switch on the TV set. If required, select the programme number for the DVD recorder.
- 2 Switch on the DVD recorder using **STANDBY/ON**.
- 3 Press **SYSTEM-MENU** on the remote control. The menu bar appears.
- 4 Select **▶** symbol with **◀** or **▶**.
- 5 Select line **'Language'** with **CH-▼** or **CH+▲**, and confirm with the **▶** button.
- 6 Select line **'Recording audio'** and confirm with **▶**.
- 7 Select **'Language 1'** or **'Language 2'** with **CH-▼** or **CH+▲** and confirm with **OK**.
- 8 To end, press **SYSTEM-MENU**.




Setting the time and date

If the display shows an incorrect time or "----", the time and date must be reset manually. If a TV channel which transmits TXTPDC (teletextPDC) is stored under programme number 'P01', the time and date will automatically be taken from the TXTPDC information.















- 1 Press **SYSTEM-MENU** on the remote control. The menu bar appears.
- 2 Select **▶** symbol with **◀** or **▶**.
- 3 Select **'Installation'** using **CH-▼** or **CH+▲** and confirm with **▶**.
- 4 Select **'Time/Date'** using **CH-▼** or **CH+▲** and confirm with **▶**.
- 5 Check if the time in **'Time'** is correct. If required, change the time with the number buttons **0...9** on your remote control.
- 6 Check **'Year'**, **'Month'** and **'Date'** in the same way. To move between the fields, use **CH-▼** or **CH+▲**.
- 7 Check the displayed settings and confirm with **OK**. **'Stored'** will appear briefly on the screen.
- 8 To end, press **SYSTEM-MENU**.



Field for temporary messages







The top left corner of the menu line contains a field for temporary messages relating to the various operating modes. This information appears briefly on the screen when certain disc functions have been activated:

	Shuffle
	Scan
	Repeat entire disc
	Repeat title
	Repeat track
	Repeat chapter
	Repeat from A to the end
	Repeat from A to B
	Camera angle
	Child lock enabled
	Resume playback
	Illegal action









Status field

The status field shows the current operating mode (status) of the DVD recorder and the type of disc inserted. This display can be disabled.

Disc type symbols




	DVD-RW
	DVD-R
	DVD-Video
	Video-CD
	No disc
	Error

Operating mode symbols

	Recording
	Stop
	Playback
	Playback-Pause
	Record-Pause
	Search forwards (8x speed)
	Search backwards (8x speed)
	Slow motion

Tuner information box




This field is located in the bottom left-hand corner of the screen. The aerial signal, the TV channel and the TV channel name for the selected programme are displayed.

	Current channel/selected input socket
	No signal The TV channel is not available/the additional device is not connected or it is switched off
	Copy-protected signal


Timer information box

This box appears above the tuner information box. When a timer recording is set, it shows the timer icon and the start time or date of the first programme to be recorded. If no timer recording is scheduled, the current time is displayed.

This box disappears during playback of a disc or after a recording starts.

	Timer starts on the day shown
	OTR recording runs until the stop time displayed
	Current time No timer event programmed

6 playback



General notes on playback

With this DVD recorder you can play back the following systems:

- DVD Video
- (Super)Video CD Disc
- DVD+RW Disc
- DVD-R Disc
- DVD-RW (video mode, finalised)
- DVD-R
- CD-R
- CD-RW
- Audio CD
- MP3 CD

You can operate the video recorder using the remote control or the buttons on the front of the DVD recorder.

ENGLISH

* The display will read "!"

- ✓ The child lock has been activated for the inserted disc. Read the sections on 'Child lock' and 'Releasing a disc' in the chapter on 'Access control (child lock)'.
* The menu on the screen is showing an 'X'


- ✓ Some DVD discs can be manufactured so that certain steps are required before the disc can be played, or so that only limited operation is possible during playback. When an 'X' appears on the screen the selected feature is not possible.

* The screen is showing regional code information

- ✓ Since DVD films are not normally released in all parts of the world at the same time, all DVD players have a specific regional code. Discs can be given a regional code. If the regional codes differ between the player and the disc, playback is not possible.
- ✓ The regional code is shown on the label on the back of the machine.
- ✓ The regional code does not apply to recordable DVD discs.

Problem

Inserting a disc



- 1 Press the **OPEN/CLOSE** button on the front. The disc tray will open. While the disc tray is opening, **OPENING** and then **TRAY OPEN** when the tray is fully open.

- 2 Carefully place the disc in the tray with the label facing up and press **PLAY** or **OPEN/CLOSE**. **OPENING** and then **TRAY OPEN** will appear in the display. The information on the disc will be read.

How do I insert a double-sided DVD?

Double-sided discs do not have labelling over the whole surface. The labelling for each side is in the centre of the disc. To play a side its label must be facing up.



Opening/closing the tray using the remote control

You can open and close the disc tray using the remote control. Press and hold the **STOP** button on the remote control until the dialog box shows **OPENING** or **CLOSING**.

Tip

- 3 Playback starts automatically.




A menu may appear when a DVD is played back. If the titles and chapters are numbered, press a number button on the remote control. You can also use the **CH+▲**, **CH-▼** buttons or number buttons **0-9** to select a menu item and confirm with **OK**. You can also access the menu using **DISC-MENU** on the remote control. For further information see 'Playing a DVD video disc'.

When a DVD+RW is played back the index overview appears. Using **CH+▼**, **CH+▲**, **◀▶**, select the title you want to play back. Confirm with **OK**. For further information see 'Playing back a DVD+RW/+R Disc'.

If playback does not start automatically, press **PLAY ▶**. For further information see 'Playing an audio CD'.

If the **■** symbol appears in the display, start playback by pressing **PLAY ▶**. If a menu appears on the screen, use the remote control buttons indicated on the screen to select the menu option you want (**PREV=◀▶**, **NEXT=▶▶**) or with the number buttons **0-9**. For further information see 'Playing a (Super) Video CD'.

Playing a DVD video disc



- 1 If playback does not start automatically, press **PLAY ▶**. This will appear on the display: title, chapter, elapsed time.
- 2 To stop playback, press **STOP ■** on the remote control or **■** on the DVD recorder.
- 3 To eject the disc, press **OPEN/CLOSE ▲** on the front of the DVD recorder.

Playing an MP3 CD

MP3 (MPEG1 Audio Layer-3) files are highly compressed music files. Using this technology the data volume can be compressed by a factor of 10. This means it is possible to record 10 hours of music in CD quality on a single CD-ROM.

When creating MP3 CDs please note the following:

- File system: ISO%60
- Directory structure: maximum of 8 levels
- Formats: *.mp3
- Filenames: maximum of 12 characters (8+3)
- Maximum of 32 albums, 999 titles
- Supported sampling frequencies: 32, 44.1, 48 (kHz). Music with sampling frequencies other than these will be skipped.
- Supported bit rates: 32, 64, 96, 128, 192, 256 (kb/s)
- ID3 Tag: Version 1, 1.1. In later versions the directory name is displayed as the album and the filename as the title.

Important notes for playback:
Only the first session of a multi-session CD will play back.

- 1 Insert an MP3 CD. Playback starts automatically.

MP3 CD display

If the TV is on, the MP3 CD screen appears automatically.

During playback, the current track number and its elapsed playing time will show on the TV screen and on the recorder display.

During stopped playback (**STOP** button) the numbers of the albums will show on the TV screen and on the display.

Further information on the album, track and artist will also be displayed if included in the ID tag.

Tip

- 2 Stop playback using **STOP** button . The number of albums is displayed in the display.

Additional playback features

Using **◀◀** or **▶▶** select the next or previous title.


You can also use the **T/C** button to select titles and albums.

- 1 Press the **T/C** button and use the **▶** or **◀** button to select the **T** symbol for title or **C** for chapter.
- 2 Use the **CH- ▶** or **CH+ ▲** buttons or the number buttons **0-9** on the remote control to select the number of the title/chapter.

You can also use the repeat functions (**PLAY MODE** button).

Tip

Playing a DVD+RW/ +R disc



- 1 If the disc is write-protected or a finalised DVD+R disc, playback starts automatically.
- 2 If playback does not start automatically, use the **CH- ▶** or **CH+ ▲** button to select the title you want to play on the index screen.
You can also use the **◀◀** or **▶▶** button on the front.
- 3 Press the **PLAY ▶** button.
This will appear on the display:
title number, recording quality.

**1 I can see the message "EP1/5/15C"*
✓ The disc does not contain any recordings.

Problem

- 4 To stop playback, press **STOP** button on the remote control or **■** on the DVD recorder.
- 5 To eject the disc, press **OPEN/CLOSE ▲** on the front of the DVD recorder.

What should I note when playing back different recording types (qualities)?

The correct recording quality **M1, M2, M2x, M3, M4, M6** will automatically be selected during playback.

For more information see the section on 'Selecting the recording type (quality)' in the chapter on 'Manual recording'.

Tip

Playing an audio CD

You can also use the DVD recorder to play audio CDs

- 1 Insert an audio CD. Playback starts automatically.

Audio CD display

If the TV is on, the audio CD screen appears automatically.






During playback, the current track number and its elapsed playing time will show on the TV screen and on the recorder display.

Tip

- 2 Stop playback using **STOP** button . The number of tracks and the total time are displayed.

Playing a (Super) Video CD

(Super) Video CDs may be equipped with PBC (Play Back Control). This means that special playback functions (menus) can be directly selected. The video CD must be PBC compatible (see CD case).
*PBC is active in the default settings.

- 1 Insert a (Super) Video CD.
If the  symbol appears in the display, start playback by pressing **PLAY** .
- 2 If a menu appears on the screen, use the remote control buttons indicated on the screen to select the menu option you want (PREV=  , NEXT= ) or with the number buttons **0..9**.
If a PBC menu consists of a list of titles, you can select a title directly.
- 3 Use **RETURN** to go back to the previous menu
- 4 Stop playback using **STOP** .

ENGLISH

Changing to another title/chapter

If there is more than one title or chapter on a disc you can change to another title or chapter as follows. However if there are several chapters within a title, these will be selected. The title can then still be selected via the menu bar.

- 1 During playback, press **▶▶** to go to the next title/chapter. Press **◀◀** to return to the start of the current title/chapter. Press **◀◀** twice to return to the start of the previous title/chapter.




Use the **T/C** (title/chapter) button

- 1 Press **T/C** (title/chapter) and then use **CH+▲** or **CH-▼** to select the appropriate title.
Make sure the symbol **T** (title) is selected in the menu bar.
- 2 Use **T/C** to select chapters within a title. Press **T/C** and use **▶** to select the **C** symbol (chapter).
Now select the appropriate chapter with **CH+▲** or **CH-▼**.

Tip

Searching a disc

You can search the disc for a recording at 4x, 8x or 32x playback speed. Other speeds can only be selected via the menu bar (**▶▶**).

- 1 During playback, press and hold **◀◀** (reverse) or **▶▶** (forwards) to switch to the search feature. You can switch between the playback speeds using **◀◀** / **▶▶**.
- 2 To continue playback, press **PLAY**  twice at your chosen location.




*No sound

✓ The sound is switched off in search mode. This is not a fault in your machine.

Problem


Search feature via menu bar

- 1 During playback press **SYSTEM-MENU** on the remote control. The menu bar will appear at the top of the screen.
- 2 Select the **▶▶▶** symbol using **▶** or **◀** and confirm with **CH-▼**.
- 3 You can now use the **◀** or **▶** button to select different forward and backward search speeds.
- 4 If necessary, switch the menu bar off with the **SYSTEM-MENU** button.
- 5 To continue playback, press **PLAY**  twice.



Tip

Still picture



- 1 During playback, press **PAUSE II** to stop playback and display a still picture.

Frame advance via menu bar

- 1 During a still picture press **SYSTEM-MENU** on the remote control. The menu bar will appear at the top of the screen.
- 2 Select the **[]** symbol using **▶** or **◀** and confirm with **CH-▼**.
- 3 You can now use the **◀** or **▶** button to go forwards or backwards one frame at a time.
- 4 If necessary, switch the menu bar off with the **SYSTEM-MENU** button.



Tip

- 2 To continue playback, press **PLAY▶**.

Slow motion

- 1 During playback press **PAUSE II** on the remote control. Now hold down **◀◀** or **▶▶** to switch to slow motion.
- 2 You can switch between different speeds using **◀◀** or **▶▶**.

Slow motion via menu bar

- 1 During playback, press **PAUSE II** and then **SYSTEM-MENU** on the remote control. The menu bar will appear at the top of the screen.
- 2 Select the **▷** symbol using **▶** or **◀** and confirm with **CH-▼**.
- 3 You can now use the **◀** or **▶** button to select different forward and backward slow motion speeds.
- 4 If necessary, switch the menu bar off with the **SYSTEM-MENU** button.



Tip

- 3 To continue playback, press **PLAY▶** twice.

Search by time

Using this feature you can select where playback should start (select elapsed time).

- 1 During playback press **SYSTEM-MENU** on the remote control. The menu bar will appear at the top of the screen.
- 2 Select the **⌚** symbol using **▶** or **◀** and confirm with **CH-▼**. Playback is stopped and a box appears on the screen showing the elapsed time.

- 3 Enter the start time with the digit keys **0-9** from where playback should start.
- 4 Confirm with **OK**.



* The time entered will flash on the screen

✓ The selected title is shorter than the time entered. Enter a new time or cancel the function by pressing **SYSTEM-MENU**.

Problem

- 5 Playback starts at the time you entered.

Repeat/Shuffle play

You can mark entire sections or the whole disc for endless playback. Depending on the type of disc (DVD video, DVD+RW, video CD) you can select a chapter, title or the entire disc.

- 1 Select the desired chapter, title or the entire disc and start playback.
- 2 During playback, press **PLAY MODE**. By pressing **PLAY MODE** again you can choose from the following options:
 - ▶ **▶▶▶▶▶** : repeat chapter (DVD only)
 - ▶ **▶▶▶▶** : repeat track/title
 - ▶ **▶▶▶▶▶▶** : repeat entire disc (Video CD, Audio CD only)
 - ▶ **▶▶▶▶▶▶▶** : Shuffle
 - ▶ Display disappears: no repeat
- 3 To end the repeat, press the **STOP ■** button. You can also keep pressing the **PLAY MODE** button until the displays disappear.

Repeating a passage (A-B)

You can repeat a particular passage within a title/chapter. You need to indicate the start and end of the passage.

- 1 During playback press **PAUSE II** at the start point. You will see a still picture.
- 2 Keep pressing **PLAY MODE** until **▶▶▶▶▶** appears on the screen. The start point is now saved. Press **PLAY▶** to start playback.
- 3 When the end point is reached press **OK**. **▶▶▶▶▶** appears on the TV screen. Playback now takes place within these points.
- 4 To end the repeat, press the **STOP ■** button. You can also keep pressing the **PLAY MODE** button until the displays disappear.

- 6 Confirm with **OK**.
- 7 To stop the feature, press **PLAY▶** and then **SYSTEM-MENU**.


Select the audio language

Many pre-recorded DVD discs have more than one audio language. The language initially selected for playback will be the one you selected when you first set up the DVD recorder. However you can change the audio language of the inserted disc at any time. You can change the audio language either using the menu of the inserted disc (**DISC-MENU** button) or the **AUDIO** button. The audio languages for DVD playback in the two menus may be different. Please note that with some DVDs the audio language and/or subtitle language can be changed only via the DVD menu.

- 1 During playback press **AUDIO**.
- 2 Select the required audio language using **CH-▼** or **CH+▲**. You can also enter the number directly using the number buttons **0-9**.
- 3 Play continues in the new audio language.


Subtitles

Many pre-recorded DVD discs have more than one subtitle language. The language initially selected for playback will be the one you selected when you first set up the DVD recorder. However you can change the subtitle language of the inserted disc at any time. You can change the subtitle language either using the menu of the inserted disc (**DISC-MENU** button) or the menu bar (**SYSTEM-MENU** button). The subtitle languages in the menus may differ.

- 1 During playback press **SYSTEM-MENU** and select the  icon using **▶**.
- 2 Select the required subtitle language using **CH-▼** or **CH+▲**. You can also enter the number directly using the number buttons **0-9**. You can switch off subtitles again with **0** or by pressing **off**.
- 3 Playback continues in the new subtitle language.

Scan feature

This feature plays back the first 10 seconds of each chapter (DVD) or track (CD).

- 1 During playback, press **PLAY MODE**. Select  using **PLAY MODE**.
- 2 After 10 seconds the DVD recorder switches to the next chapter/index. To start playback at the relevant chapter/index press **STOP■** and then **PLAY▶**.


ENGLISH

Camera angle


If a DVD contains scenes that have been shot from different camera angles you can select these camera angles for playback.

- 1 During playback, press **PAUSE II**. You will see a still picture.
- 2 Press **SYSTEM-MENU** and select the  icon using **▶**.




*The  symbol will be hidden
✓ The selected scene has been shot from only one camera angle. This feature is therefore not available. For more information please read the cover of your DVD disc.


Problem

- 3 Select the required camera angle with **CH-▼** or **CH+▲**. You can also directly enter the number with the number buttons **0-9**.
- 4 After a short time, playback will resume from the new camera angle. The  symbol will remain visible until a scene starts for which there is only one camera angle.

Zoom feature

The Zoom feature allows you to enlarge the video image and pan through the enlarged image.

- 1 During playback, press **PAUSE II**. The DVD recorder switches to 'PAUSE'. You will see a still picture.
- 2 Press **SYSTEM-MENU** and select the  icon using **▶**.
- 3 Select the required zoom factor using **CH-▼** or **CH+▲**.
- 4 When 'press **OK to pan**' appears on the screen, the zoom process is complete.
- 5 Press **OK**. Using **CH+▲**, **CH-▼**, **▶**, **◀** select the part of the image you wish to view.



General

Which discs can I use for recording?

DVD+RW
With this DVD recorder, you can record on two types of DVD:
This disc can be written to and then the contents deleted.

DVD+R

This type of disc can only be recorded once.
If you want to play this DVD in a DVD player, it must be finalised using the **'Finalise disc'** function. It is not possible to make further recordings using this disc.
If this disc is to be played in a DVD recorder, it must not be finalised. Recordings can be added and deleted. The disc space (playback time) from the deleted recording cannot be recovered for further recordings



ENGLISH

Use the 'Manual recording' function to spontaneously start recording (e.g. to record a TV show already in progress).
In the Index display select the title to be overwritten or **'Empty title'** with **CH- ▾** , **CH+ ▴** .
If you insert recordings between existing recordings, check the lengths of the old and new recordings. If the new recording is too long the subsequent recording (title/chapter) will be overwritten.

Insert new recordings at the end of all existing recordings (Safe Record)

To add a new recording at the end of the last recording on the disc, hold down the **REC/OTR** button until the message **'SAFE REC'** appears on the display.
For DVD+R discs each new recording is always added at the end of all previous recordings as existing recordings cannot be overwritten.

End of disc is reached

If the end of a disc is reached during recording, recording will stop and the Recorder will turn itself off automatically.



Tip

Please refer to section **'Recording without automatic switch-off'**, if you want to manually start and stop your own recording.

If you want to start a recording manually but have it stopped automatically, read the section **'Recording with automatic switch-off'** (e.g. not to record to the end of the disc)

Read the section **'Automatic recording from a satellite receiver'**, if you want a recording to be controlled automatically by a satellite receiver.

Read the section **'Direct record'** if you want to record a programme currently being shown.

Recording without automatic switch-off

1 Switch on the TV set and select the programme number for the DVD recorder.

2 Insert a disc on which the recording is to be made. This disc is then checked for content and system. **'REC/OTR'** will appear on the display.

*Index display

✓ A DVD+RW disc has been inserted that already contains recordings. Use the **CH+ ▴** or **CH- ▾** button to select the point where the recording is to start.

x The message **'EMPTY DISC'** appears in the display
✓ The disc inserted is a blank DVD disc.

*A dialog box appears asking you whether you want to delete the contents or eject the disc

✓ The disc inserted is a DVD+RW but its contents are not DVD video-compatible (e.g. a data disc). Recordings on this disc can only be made if the entire disc is first deleted with the **REC/OTR** button.

x The message **'Title limit'** appears on the screen if a recording is to be made

✓ A disc may contain a maximum of 48 titles (including blank titles). Delete titles or change the disc.



Problem

3 If necessary, use the **MONITOR** button on the remote control to switch to the internal tuner in the DVD recorder.

4 Use **CH+ ▴** or **CH- ▾** to select the programme number (station name) you want to record. This will appear on the display.

1 FREETITLE P01

Programme numbers of the external inputs:

'EXT 1' Start socket at the back **EXT 1 TO TV-40**

'EXT 2' Start socket at the back **EXT 2 AUX-40**

'FRONT 1' Front S-VIDEO/audio sockets **S-VIDEO / left AUDIO right**

'FRONT 2' Front video/audio sockets **AV S-VIDEO / left AUDIO right**

Switching between the **S-VIDEO** and **VIDEO** sockets takes place automatically. If both sockets are in use, the signal at the **S-VIDEO** socket has priority.

'FRONT 2' Digital Video (i-Link) front socket **DV IN**


Tip

To start recording, press **REC/OTR** on the remote control or **RECORD** on the DVD recorder.

If you want to start the recording at the end of the existing recordings, hold down the **REC/OTR** button until the message **'SAFE REC'** appears on the display.

For DVD+R discs each new recording is always added at the end of all previous recordings as existing recordings cannot be overwritten. This will, for example, appear in the display:

5 To start recording, press **REC/OTR** on the remote control or **RECORD** on the DVD recorder.



Insert chapter markers

During recording you can mark scenes so you can find them or hide them later.
During recording, press **FSS** < at the start point. 'Inserting marker' appears on the TV screen. In the display, the number of the 'CHAPTER' increases by one.
For further information on titles and chapters, see the section on 'Changing to another title/chapter' in 'Playback'.

Tip

6

Use the **STOP** ■ button on the remote control or ■ on the machine to stop the recording. "RECORDING" will appear on the display. The DVD recorder is writing the list of contents. Wait until the message disappears from the display. The recording is then complete.

***The display will read "DISC ERROR"**

✓ Recording could not be completed correctly because of a disc error. Check the disc and clean it, if necessary.

Problem

Making recordings on DVD-R discs compatible

If you want to play back the recording on a DVD player, you need to finalise the disc in the DVD recorder. You can prepare your DVD for use in a DVD player using the 'Finalising' feature. See 'Finalising DVD-R discs' in 'Managing the disc contents'.

Tip

Interrupt recording (Pause)

1

During recording press **PAUSE** ■, for example to avoid recording the commercials.

2

To continue recording, press **REC/OTR** ●.

End recording

To end the recording, press the **STOP** ■ button. Wait until "RECORDING" disappears from the display.

Tip

Recording with automatic switch-off (OTR one-touch-recording)

1

Insert a disc.

2

If necessary, use the **MONITOR** button on the remote control to switch to the internal tuner in the DVD recorder.

3

Use **CH+▲** or **CH-▼** to select the programme number (channel name) you want to record.

4

Press **REC/OTR** ● on the remote control.

5

Each time you press **REC/OTR** ● you will add 30 minutes to the recording time.

How can I cancel the recording time I have just entered?

To delete an entry, press **CLEAR** while the display shows the recording time.

Preventing accidental erasing of discs

To ensure you don't accidentally delete a recording you can protect the entire disc. You can only ever protect the entire disc. You cannot protect individual recordings.

What happens with DVD-R discs?

As long as these discs are not finalised, they can be protected against accidental erasure in the same way as DVD+RW discs.

1

Insert the disc to be protected.

2

While the index screen is displayed, press **STOP** ■ on the remote control. The first title is highlighted.

3

Press **CH+▲**. This takes you to the disc info screen.

4

Press the **▶** button.
Select the 'Protection' line.
Confirm with **▶**.

5

Select 'Protected' with the **CH-▼** button and confirm with **OK**.

6

Press **◀** and then **DISC-MENU** to terminate.

Selecting the recording type (Quality)

You can select the picture quality of the recording using the recording quality feature and hence the maximum recording time per disc.
You can check the quality by changing the recording mode and then watching the picture from the built-in tuner (MONITOR button).
During playback, the correct picture quality will automatically be selected.

1

Switch on the TV set. If required, select the programme number for the DVD recorder.

Select the record mode with the button **REC MODE** on the remote control.

Which recording types can I choose?

'M1': High Quality offers the best picture quality and a recording time of 1 hour.

'M2': Standard Play (pre-recorded DVD quality) offers standard picture quality and a recording time of 2 hours.

'M2X': Standard Play plus (better than S-VHS quality) offers standard picture quality and a recording time of 2.5 hours.

'M3': Long Play (S-VHS picture quality). Recording time of 3 hours.

'M4': Extended Play (better than VHS picture quality). Recording time of 4 hours.

'M6': Super Long Play (VHS picture quality). Recording time of 6 hours.

Can I select the recording type via a menu as well?

1 Press the **SYSTEM-MENU** button.

2 Select **1** symbol with **◀** or **▶**.

3 Select **'Record settings'** using **CH ▼** or **CH+▲** and confirm with **▶**.

4 In the line **'Record mode'** select the recording type with **◀** or **▶**.

5 Confirm using **OK** and **SYSTEM-MENU**.

6 If you have selected the recording mode **'M3'**, **'M4'** or **'M6'** you can select the settings **'Stand'** (Standard) or **'Sport'** (for rapid movements) in the **'Filter mode'** line.

Tip

Manual recording

Lining up recordings within a title (assemble cut)

The entire disc is now protected.
If an attempt is made to record on a protected disc, **'DISC LOCKED'** will appear on the display and **'Disc locked'** will appear on the screen.

ENGLISH

On a recorded DVD+RW disc you can add another recording to an existing title. This recording is added to the title as a 'chapter'. The existing information will be overwritten starting from this point. Titles will also be overwritten that follow the current title depending on the length of the new recording. The recording type (Quality) will be taken from the current title.
To play back this recording, press **SYSTEM-MENU** and use the **▶** button to select the 'C' (Chapter) symbol. You can also use the **TIC** key.

For further information, see 'Changing to another title/chapter' in 'Playback'.

What happens with DVD+R discs?

New recordings on 'DVD+R' discs can only be added after existing recordings.
It is not possible to overwrite existing recordings on 'DVD+R' discs.

1

In the index display, find the title to which the new recording is to be added.

2

Look at the last minute of the old recording (playback)

3

Press **PAUSE||** on the remote control at the position where the new recording is to go. **'||'** will appear on the screen.

4

To monitor the recording you can press **MONITOR** to switch to the internal tuner.

5

Now start recording as usual by pressing **REC/OTR ●** on the remote control.
The new recording will be inserted.

6

Stop recording with **STOP ■**.


Manual recording

49

50


Direct Record

Can you record the right TV channel in seconds when the DVD recorder is switched off? No problem. If recording is started manually, the **switched-off** DVD recorder takes the current TV channel from the TV set via the scart cable. You will find more information on how to switch 'Direct record' on or off in the next section 'Direct record'.



How does Direct Record work?
The DVD recorder compares the TV channel selected on the TV set with its stored TV channels via the scart cable. If the same TV channel is found, it switches the DVD recorder to the corresponding programme number and starts recording.
Please do not change channel on the TV during the search. This could affect the tuning of the DVD recorder.

- 1 On the TV set, select the programme number you want make the recording from.
- 2 Press **REC/OTR** with the DVD recorder **switched off**.



*** The display will read "NOT!" ***
✓ The DVD recorder is comparing its saved TV channels with those of the TV set. Please do not change the TV channel on the TV set while "NOT!" is shown in the display.
*** "NOT!" appears in the display ***
✓ This TV channel could not be found in the DVD recorder's memory. Check that all TV channels saved on the TV set are available on the DVD recorder. If required, save any missing channels. Please read 'Manual TV channel search' in 'Installing your DVD recorder'.
✓ Check the connectors at both ends of the scart cable.
✓ Check your TV's operating instructions to see which scart socket is used for video signals.
✓ If the problem persists, you won't be able to use this feature.

Problem

- 3 Stop recording with **STOP**.

Automatic recording from a satellite receiver (Sat recording)

You can use this function if you own a satellite receiver that can control other devices via a scart cable and a programming function (timer). For more information, please see the operating instructions for the satellite receiver.

- 1 Switch on the TV set. If required, select the programme number for the DVD recorder.
- 2 Press **SYSTEM-MENU** on the remote control. The menu bar appears.
- 3 Select **T_H** symbol with **◀** or **▶**.
- 4 Select **'Record settings'** using **CH-▼** or **CH+▲** and confirm with **▶**.
- 5 Select **'Sat record'** using **CH-▼** or **CH+▲**.
- 6 Select **'EXT2'** with **◀** or **▶**.



Switching off 'Sat Recording'
To switch off the function, select **Off** using **▶** or **◀**.

Tip
Confirm with **OK**.

- 7 Confirm with **OK**.
- 8 Use a scart cable to connect scart socket **EXT 2 AUX-IO** on the DVD recorder to the corresponding scart socket on the satellite receiver.
- 9 To end, press **SYSTEM-MENU**.
- 10 Insert a disc you want to use for recording.
- 11 Programme the satellite receiver with the required information (programme number of the TV channel, start time, end time). If necessary, please see the operating instructions for your satellite receiver.
- 12 Switch off the DVD recorder using **STANDBY ⏻**. 'SAT' also appears in the display to indicate that the function is active.

The DVD recorder is now ready to record. The start and end of the recording is controlled via scart cable **EXT 2 AUX-IO**.

9

Managing the disc contents

Switching 'Direct Record' on or off

- 1

Switch on the TV set. If required, select the programme number for the DVD recorder.
- 2

Press **SYSTEM-MENU** on the remote control. The menu bar appears.
- 3

Select **PAUSE** symbol with **◀** or **▶**.
- 4

Select **'Record settings'** using **CH-▼** or **CH+▲** and confirm with **▶**.
- 5

Select **'Direct Record'** using **CH-▼** or **CH+▲**.
- 6


Select **'On'** (Direct Record on) or **'Off'** (Direct Record off) using **◀** or **▶**.
- 7

Confirm with **OK**.
- 8

To end, press **SYSTEM-MENU**.
- 9

Switch off with **STANDBY**.

ENGLISH



General

When a recording is made to disc, the following additional information is also stored at the beginning of the recording:

- Name of the recording
- If the TV station does not transmit a name, only the channel number and time will be stored as the name
- Length of the recording
- Record type (Quality)
- Date of the recording
- Index picture of the recording

A marker will be set every 5-6 minutes if the **'Auto chapters'** function is activated in the **'Record settings'** menu. This marker is known as a 'chapter'. These markers can be changed when the recording has finished.



Can markers be set on a DVD-R disc?

Markers can be set on these discs if they have not been finalised.

It is also possible to add 'chapters' later. This means that scenes you do not want to see during playback, such as commercials, can be hidden or skipped. During playback you can watch your recording as a continuous sequence without the hidden chapters.

Select from the following chapters:

'Favorite Scene Selection',
to divide the title into chapters or to manage the chapters.

'Editing recording titles (name)',
to change the recording names.

'Play complete title',
to play the entire title including the hidden chapters.

'Delete recording/title' to delete the relevant title and therefore also the recording.

'Disc settings' to change the general settings of the disc.

3

Using **▶** select **'hidden'**. The picture is shown darker.

Tip

Switching quickly

You can switch between show chapters (**Visible**) and hide chapters (**hidden**) quickly and easily using **SELECT**.

4

To end, press **FSS** **×**.

During playback this chapter will be skipped.
If the chapter is not visible, select **'Visible'** in step 3 with **▶**.

Deleting chapter markers

Within a title you can delete either all markers or individual markers.

1

While the relevant chapter is playing, press **FSS** **×** on the remote control. The **'Favorite Scene Selection'** menu appears on the TV screen.

Tip

How can I select different chapters?

1 Press the **T/C** button on the remote control. Titles and chapters are displayed at the top of the screen.
2 Select title (T) or chapter (C) with **▶** or **◀**.
3 Use **CH+▲** or **CH-▼** to select the title/chapter channel you want to edit.

2

Use **CH-▼** to select either **'Delete marker'** for this chapter or **'Delete all markers'** for all chapters within the selected title.

3

Confirm with **OK**.

4

To end, press **FSS** **×**.

56

Managing the disc contents

Favorite Scene Selection

In this menu you can adapt a title to suit your particular needs.
You can insert/delete chapter markers, hide chapters, select a new index, or split up a title.
Press **FSS** **×** on the remote control during recording to open this menu.

ENGLISH

Insert chapter markers

During recording, you can set or delete chapter markers within a title.
The maximum number of chapters per disc is 124 and 99 per title. If one of these limits is reached the following message will appear on the screen: **'Chapter limit'**. You need to delete some markers before you can insert new ones or make recordings.

1

During playback, press **FSS** **×** on the remote control at the appropriate point. The **'Favorite Scene Selection'** menu appears on the TV screen.

2

Confirm **'Insert marker'** by pressing **OK**. **'Inserting marker'** appears on the TV screen.

Tip

'X' will appear on the screen:

This DVD is write-protected or the disc is a finalised DVD-R. Subsequent changes cannot be made.

3

To stop this function, press **FSS** **×**.

Hiding chapters

Initially, all the chapters are visible. You can hide chapters for playback (e.g. advertisements) or make them visible again. In editing mode, hidden chapters are shown as dimmed.

1

While the relevant chapter is playing, press **FSS** **×** on the remote control. The **'Favorite Scene Selection'** menu appears on the TV screen.

Tip

How can I select different chapters?

1 Press the **T/C** button on the remote control. Titles and chapters are displayed at the top of the screen.
2 Select title (T) or chapter (C) with **▶** or **◀**.
3 Use **CH+▲** or **CH-▼** to select the title/chapter channel you want to edit.

2

Select **'Current chapter'** using **CH-▼**.


Managing the disc contents

55

Changing the index picture

Normally the first picture of a recording is used as the index picture. You can however choose any picture from the recording as the index picture.

- 1 During playback, search for location of the new index picture. Press the **PAUSE II** button.
- 2 Press the **FSS** >< button. The **'Favorite Scene Selection'** menu appears on the TV screen.
- 3 Select line **'New index picture'** and confirm with **OK**.
- 4 Start the change with **OK**. **'Updating menu'** appears on the TV screen.




Once the revision has been completed successfully the DVD recorder reverts to the index overview.

Splitting titles


You can split a title into several sections (titles) of any size. Each of these sections (titles) is identified by its own index.

Note: This split cannot be undone.



Can I split titles on DVD+R discs?
As recordings on DVD+R discs cannot be overwritten, it is not possible to split titles.

- 1 While the relevant title is playing, press **FSS** >< on the remote control. The **'Favorite Scene Selection'** menu appears on the TV screen.
- 2 Select **'Divide title'** and confirm with the **OK** button.
- 3 If you are sure, press **OK** to start the process. **'Dividing title'** appears on the TV screen.
- 4 Wait until the new title is displayed with an index picture in the index picture overview.




The process of splitting the title is now complete.

Editing recording titles (name)

Some TV stations transmit the title (name) of a programme. In this case, the name will be included automatically (e.g. 'ROCKY'). Otherwise, the only the programme number (programme name) and the time are stored as the name of the recording. The name of the recording can only be changed after the recording has been completed.


- 1 Press the **STOP** ■ button or during playback press **DISC-MENU**.
- 2 Using **CH+▲** or **CH-▼** select the title whose name you want to edit and confirm with **▶**. The menu for editing names appears.
- 3 Select **'Name'** using **CH+▲** or **CH-▼** and confirm with **▶**.
- 4 Using **▶** or **◀** select the position where the letter/number/icon is to be changed/re-entered.
- 5 Change the icon using **CH+▲** or **CH-▼**. You can switch between upper and lowercase using **SELECT**. You can delete the character using **CLEAR**.
- 6 Repeat **4** and **5** until you have made the changes you want.
- 7 Save the new name with **OK**. **'Storing name'** appears on the TV screen for confirmation.
- 8 To end, press **◀**.



Playing the entire title


If you have hidden certain sections (chapters) of a title, this setting lets you watch the entire title including the hidden sections. To do this, proceed as follows:

- 1 Press the **STOP** ■ button or during playback press **DISC-MENU**.
- 2 Using **CH+▲** or **CH-▼** select the title you want to play all of and confirm with **▶**. The title editing menu will appear.
- 3 Select **'Play full title'** using **CH+▲** or **CH-▼** and confirm with **OK**.
- 4 Playback starts automatically. The title is played in its entirety - including the hidden chapters.



Changing the disc name

- 1 In the 'Disc info display' press **▶** . The **'Settings for'** menu appears on the TV screen.
- 2 Select **'Disc name'** using **CH+▲** or **CH-▼** and confirm with **▶** .
- 3 Using **▶** or **◀** select the position where the letter/number/icon is to be changed/re-entered.
- 4 Change the icon using **CH+▲** or **CH-▼** . You can switch between upper and lowercase using **SELECT** . You can delete the character using **CLEAR** .
- 5 Repeat **3** and **4** until you have made the changes you want.
- 6 Save the new title with **OK** . **'Storing name'** appears on the TV screen for confirmation.
- 7 To end, press **◀** .



Finishing editing

If one or more titles have been edited a DVD player may still display the original titles. You can prepare your disc in such a way that a DVD player will be able to play the edited version.

- 1 In the 'Disc info display' press **▶** . The **'Settings for'** menu appears on the TV screen.
- 2 Select **'Make edits compatible'** using **CH+▲** or **CH-▼** and confirm with **OK** .



x'Make edits compatible' does not appear
✓ Your disc is already compatible. There is no need for conversion.
To end, press **SYSTEM-MENU**.


Problem

- 3 The screen displays **'This will take'** to show how long the process will last.
- 4 To confirm press **OK** . **'Working'** appears on the TV screen. A bar will move from left to right indicating progress.

Deleting recordings/titles

You can delete specific recordings from a disc. To do this, proceed as follows:

- 1 Press the **STOP ■** button or during playback press **DISC-MENU** .
- 2 Using **CH+▲** or **CH-▼** select the title you want to delete and confirm with **▶** . The title editing menu will appear.
- 3 Select **'Erase this title'** using **CH+▲** or **CH-▼** and confirm with **OK** . **'This will completely erase this title'** appears on the TV screen.. **'Press OK to confirm'** .
- 4 If you want to delete this title, press **OK** to confirm. Otherwise press **◀** .
- 5 **'Erasing title'** appears on the TV screen.
- 6 At this point **'Empty title'** appears in the 'index picture display'. A new recording can now be made here. If the deleted title was very short (less than 1 minute) **'Empty title'** will not appear at this point.



Can titles be deleted from a DVD+R disc?

Titles on DVD+R discs are only marked as deleted. **'Deleted title'** will appear in the display instead of **'Empty title'**. During playback the 'deleted' title is skipped. The space used for this title cannot be used again as the title has not been physically deleted. Once the disc has been finalised no further changes can be made.

Disc settings


This screen appears before the first title and contains general information about the current disc.

You can:

- change the name of the disc
- activate or deactivate write protection on the disc
- Finish editing (make the disc DVD compatible)
- finalise a DVD+R
- delete a DVD+RW

To get to this display, proceed as follows:

- 1 Press the **STOP ■** button or during playback press **DISC-MENU** .
- 2 Select the first title with **CH+▲** or press **STOP ■** .
- 3 Press the **CH+▲** button. The disc info display will appear.



10

Programming a recording (TIMER)

STANDBY

General

Use Programming a recording (TIMER)¹⁾ to automatically start and stop a recording at a later date.

The DVD recorder will switch to the right programme number and begin recording at the correct time.

With this DVD recorder, you can pre-programme up to six recordings within a period of one month.

To make a programmed recording, your DVD recorder needs to know:

- * the date you want to make the recording
- * the programme number of the TV channel
- * the start and stop time of the recording
- * VPS or PDC on or off
- * the recording mode (M1/M2/M3/M4/M6)

This information is saved in a 'TIMER block'.

What is VPS/PDC?

'VPS' (Video Programming System)/PDC (Programme Delivery Control) are used to control the start and duration of TV channel recordings. If a TV programme starts earlier or ends later than was scheduled, the DVD recorder will then turn on and off at the correct time.

What do I need to know about VPS/PDC?

- * Usually the start time is the same as the VPS or PDC time. If a different VPS/PDC time is indicated, eg.: 20.15 (VPS/PDC 20.14), the **VPS/PDC time 20.14** must be entered **exactly to the minute** during programming.
- If you want to programme a time that is different from the VPS or PDC time, you must switch off VPS or PDC.
- * Only one TV program of a TV channel can be controlled using VPS/PDC at a time. If you want to record two or more TV programmes on a TV channel using VPS/PDC, you will need to programme these as two separate recordings.
- * Since the DVD recorder requires a certain lead time (for getting the disc up to speed and positioning the laser) before recording can start, it is possible that the recorder will miss the first few seconds of a TV show recorded with VPS/PDC.

In this case, disable VPS/PDC and enter a start time one minute earlier.

Programming a recording (TIMER)

62

Finalising DVD+R discs

This feature is required to play back a DVD+R disc in a DVD player. Once the disc has been finalised no further recordings or changes can be made.

1

In the 'Disc info display' press **►**. The '**Settings for**' menu appears on the TV screen.

2

Select '**Finalise disc**' using **CH+▲** or **CH-▼** and confirm with **OK**.

* 'Finalise disc' does not appear

✓ Either there is no DVD+R disc inserted or the disc is already finalised.

To end, press **SYSTEM-MENU**.

* The 'Settings for' menu does not appear

✓ The menu may not appear if the disc has been recorded on another DVD recorder. In this case, use the '**Finalise disc**' feature in the **TM** menu, under '**Features**'.

Problem

3

The screen displays '**This will take...**' to show how long the process will take.

4

To confirm press **OK**. '**Working**' appears on the TV screen. A bar will move from left to right indicating progress.

Delete DVD+RW discs

1

In the 'Disc info display' press **►**. The '**Settings for**' menu appears on the TV screen.

2

Select '**Erase disc**' using **CH+▲** or **CH-▼** and confirm with **OK**. '**This will erase all titles**' appears on the TV screen. Press **OK to confirm**.

3

If you want to delete all the titles, press **OK** to confirm. Otherwise press **◀**.

4

'**Erasing disc**' appears on the TV screen.

5

After deletion, the index picture display shows the free space on the disc.

Managing the disc contents

61

SHOWVIEW®

Programming recordings with the ShowView® System

Thanks to this programming system, you no longer need to tediously enter the date, programme number, start and end times. All the information needed by the DVD recorder for programming is contained in the ShowView® programming number. This 9-digit ShowView® number is found in most TV listings magazine.

- Switch on the TV set. If required, select the programme number for the DVD recorder.
- Press **TIMER** on the remote control.
The programming method selected last is marked.
- Select **'ShowView system'** using **CH-▼** or **CH+▲** and confirm with **►**.
- Enter the entire ShowView number. This number is up to 9 digits long and can be found next to the start time of the TV programme in your TV listings magazine.
e.g. 53124 or 53124
Enter 53124 for the ShowView-number.
If you make a mistake, you can clear your instructions with **CLEAR**.

Timer
ShowView system

Prog	Start	End	Rec
01	BBC1 20:15	21:30	M2

Mo-Fri/Weekly
Press SELECT

To store
Press OK

6

The decoded data appears after confirmation. You can go back and change the data. Select the appropriate input field with **►** or **◄**. If required, make changes using **CH+▲**, **CH-▼** or the number buttons **0..9**.

Tip

'Switching on 'VPS/PDC' in the 'Start' input field
Select the 'Start' input field using **►**. Using **SELECT** switch on 'VPS/PDC' (* lights up). If you press **SELECT** again, you will switch 'VPS/PDC' off (* goes out).

Changing the recording mode in input field 'End'
Select the 'End' input field using **►**.
Use **SELECT** to select the recording mode **M1, M2, M2x, M3, M4, M6**.

- 7

If all information is correct, press the **OK** button. The programming information is stored in a **TIMER** block.
- 8

To end, press **TIMER**.
- 9

Insert a recordable disc (one without write protection).
The disk you have inserted will be checked.
- 10

Switch the DVD recorder off with **STANDBY**.
The programmed recording will only function properly if the DVD recorder has been **switched off** using the **STANDBY** button.

If any of the **TIMER** blocks are in use, **TIMER** will light up on the recorder display.

Timer
ShowView system

ShowView number
.....

Mo-Fri/Weekly
Press SELECT

To store
Press OK

Selecting daily/weekly recordings
Using **SELECT**, select from the following options:
'Mo-Fr': Repeated daily recordings (Monday to Friday)
'Weekly': Repeated weekly recordings (every week on the same day).

Tip

5 Confirm with **OK**.

x The following message appears on the screen: 'Please enter programme number'

- ✓ The programme number of the TV channel has not yet been assigned to the ShowView number. Use **►**, **◄** or the number buttons **0..9** on the remote control to select the appropriate programme number (name) of the TV channel and confirm with **OK**.

x The following message appears on the screen: 'ShowView number wrong'

- ✓ The entered ShowView number is incorrect. Correct your entry or cancel using the **SYSTEM-MENU** button.
- ✓ Check the time/date (see 'Setting the time & date' in 'Installing your DVD recorder').

x The following message appears on the screen: 'Weekend programming not possible'

- ✓ A daily recording was entered for the wrong day. Daily programming can only be used for recordings to be made from Monday to Friday.

Problem

Programming recordings without the ShowView® System

- 1

Switch on the TV set. If required, select the programme number for the DVD recorder.
- 2

Press **TIMER** on the remote control.
The programming method selected last is marked.

Timer programming					Rec
Date	Prog	Start	PDC	End	Mode
01	BBCT	2015	*	21:30	M1
Mo-FriWeekly					Press OK

- 3

Select line **'Timer programming'** with **CH-▼** or **CH+▲** . and confirm with the **►** button.
The information will appear on the screen.
- 4

Select the input field with **◀** or **▶** .
- 5

Enter information with **CH-▼** or **CH+▲** or with the number buttons **0..9** .

Tip

Selecting daily/weekly recordings
In **'Date'** use **SELECT** to select from the following options:
'Mo-Fri': Repeated daily recordings from Monday to Friday
'Mon': Repeated weekly recordings (every week on the same day, e.g. Monday).

Programme numbers of the 'EXT1' and 'EXT2' start socket
You can also programme recordings from external sources via start socket **EXT 1 TO TV-IO (EXT1)** or **EXT 2 AUX-IO (EXT2)**.
'Switching on 'VPS/PDC' in the **'Start'** input field
Select the **'Start'** input field using **TIMER** . Using **SELECT** switch on VPS/PDC (* lights up). If you press **SELECT** again, you will switch VPS/PDC off (* goes out).

Changing the recording quality in input field 'End'
Select the **'End'** input field using **►** .
Use **SELECT** to select the recording mode.

- 6

If all information is correct, press the **OK** button. The programming information is stored in a **TIMER** block.
- 7

To end, press **TIMER** .
- 8

Insert a DVD (one without write protection).
The disk you have inserted will be checked.
- 9

Switch off with **STANDBY** ⏻ .
The programmed recording will only function properly if the DVD recorder has been **switched off** using the **STANDBY** ⏻ button.

If any of the **TIMER** blocks are in use, **'TIMER'** will light up on the recorder display.

How to change or delete a programmed recording (TIMER)

- 1

Switch on the TV set. If required, select the programme number for the DVD recorder.
- 2

Press **TIMER** on the remote control.
The programming mode selected last is marked.
- 3

Select **'Timer List'** using **CH-▼** or **CH+▲** and confirm with **►** .
- 4

Select the programmed recording (**TIMER**) you want to check, change or delete with **CH-▼** or **CH+▲** .

Timer List					Rec
Date	Prog	Start	PDC	End	Mode
01	BBCT	2015	*	21:30	M2
Total record time 01:15					To exit Press TIMER

Tip

Delete programmed recording
1 Press the **CLEAR** button.
2 Confirm with **OK** . **'Timer Cleared'** will briefly appear on the TV screen.
3 To end, press **TIMER** .

... appears rather than the displayed values

- 5

Press **►** .
Select the input field with **◀** or **▶** .
If required, change the information with **CH+▲** , **CH-▼** or the number buttons **0..9** .
- 6

Confirm with **OK** .
- 7

To end, press **TIMER** .
- 8

Switch off with **STANDBY** ⏻ .

'NexTVView Link'

This DVD recorder is equipped with the 'NexTVView Link' feature. If your television is also equipped with this function, you can mark TV programmes on the television for programming. These TV programmes will automatically be transmitted to a **TIMER** block on the DVD recorder. If you clear the marking of the TV programme on the television, the corresponding **TIMER** block on the DVD recorder will also be cleared.
For more information, read the instruction manual of your TV set.


In this section you will learn how to set your user preferences on the DVD recorder. The symbols have the following meanings:

	Picture setting
	Sound setting
	Language setting
	Additional settings
	Remote control settings
	Disc settings
	Recording settings
	Installation

- 1 Switch on the TV set. If required, select the programme number for the DVD recorder.
- 2 Press **SYSTEM-MENU** on the remote control. The menu bar appears.
- 3 Select **TA** using **◀** or **▶** and confirm with **CH-▼**.
- 4 Select the appropriate function with **CH-▼** or **CH+▲** and confirm with **▶**.
- 5 Select the appropriate line using **CH-▼** or **CH+▲** and confirm with **▶**.
- 6 Select the appropriate function using **CH-▼** or **CH+▲** or the setting with **◀** or **▶**.
- 7 Confirm the new setting by pressing **OK**.
- 8 To close the menu item, press **◀**.

Picture settings

You can choose the following features in this menu:



'TV shape'

The picture signal from your DVD Recorder can be set to match your TV screen.
 '4:3 letterbox': for a 'wide-screen' picture with black bars at the top and bottom
 '4:3 panscan': for a full-height picture with the sides trimmed.
 '16:9': for a wide-screen TV set (screen edge ratio 16:9)

'Black level shift'

Adapts the colour dynamics for NTSC playback

Problem solving for programmed recordings

PROBLEM	SOLUTION
The DVD recorder is not responding	✓While a programmed recording is being made, you cannot operate your DVD recorder manually. If you want to cancel the programmed recording, press STANDBY
'Switch off, timer recording' flashes on the TV screen.	✓The DVD recorder was switched on several minutes before the start of a programmed recording. Switch off the DVD recorder using STANDBY . A programmed recording (timer) will only function if the DVD recorder is switched off (STANDBY button).
Error message: 'Insert recordable disc'	✓Either a disc has not been inserted or the disc cannot be used for recording. Insert a disc on which recordings can be made. Switch off the DVD recorder using STANDBY .
The error message 'Disc locked' appears briefly on the screen.	✓A write-protected disc has been inserted. Undo the write protection (see 'Preventing accidental erasing of discs' in 'Manual recording') or insert a different disc.
Error message: 'Memory full'	✓If this error message appears after pressing TIMER , then all TIMER blocks are already programmed. No more recordings can be programmed. Press the ▶ button. If you want to clear or check a programmed recording (TIMER block), select it with CH+▲ or CH-▼ .
The 'Data error' message appears on the screen.	✓The data for the recording could not be transferred. Please check date, start time and end time of the programmed recording.
The 'Collision' message appears on the screen.	✓Two programmed recordings overlap. ✓If you ignore this error message the show with the earlier start time will be recorded first. The start of the second show will not be recorded. ✓Change the setting for either of the two recordings. ✓Clear either of the two recordings

'Vertical video shift'

Use this feature to adjust the position of the picture on your TV left or right using ◀, ▶ to suit your TV set.

'SCART video'

By default the recorder is set to 'RGB'. Select 'S-Video' if you want to connect an S-VHS recorder.

ENGLISH

Sound settings

Depending on which audio outputs are used, you can select the settings in this menu. If you only use the analogue audio output (OUT L AUDIO R), select the settings 'Off' in the 'Digital output' menu.

'Digital output'

For devices connected to the DIGITAL AUDIO OUT socket, you can select from the following settings.

'All': Dolby Digital and DTS signals are fed unaltered to the digital output. MPEG-2 multi-channel signals are converted to PCM (Pulse Code Modulation).

For receivers/amplifiers with digital multi-channel sound decoders.

'PCM only': Dolby Digital and MPEG-2 multi-channel signals are converted to PCM (Pulse Code Modulation).

For receivers/amplifiers without digital multi-channel sound decoders.

'Off': Digital output switched off.

For devices with analogue audio input.

'Analogue output'

For devices connected to the analogue audio output (OUT L AUDIO R), you can select from the following settings.

'Stereo': For devices without DolbySurround or TruSurround. Use this setting if the DVD recorder is only connected to a stereo TV set.


'Surround': Dolby Digital and MPEG-2 multi-channel are mixed down to a DOLBY surround-compatible two-channel output signal. For devices with Dolby Surround Pro Logic decoder.

'Night mode'

Night mode optimises the sound for playback at low volume. You are therefore less likely to disturb your neighbours. This only works for Dolby Digital audio on DVD video discs.

Language settings

You can choose the following settings in this menu:



'Audio Language'

Playback audio language

'Recording audio'

Audio recording

'Subtitle'

Subtitle language

'Menu'


Screen menu language

'Country'

'Country'

Additional settings

You can select the following functions in this menu:



'Status box'


Along with the on screen menu, the OSD (On Screen Display) also displays information on the current operating status (counter, playback, recording, TV channel, etc.) on the TV screen. You can switch off the information about the operating status so that the on screen display (OSD) is not recorded during copying.

'On': The OSD information appears in every selected mode for a few seconds and disappears again.

'Off': The OSD information is switched off. It is no longer displayed on the screen.

Disk feature menu

In this menu you can make the changes that relate to the disc:



'Access control'

Please read the next chapter on 'Access control (child lock)'.

'Auto resume'

If playback of a pre-recorded DVD video disc or video CD is interrupted (button **STOP** ■ or **OPEN/CLOSE** ▴) when the disc is reloaded (disc is started) playback starts at the precise location where it stopped. This applies not only to the current disc but to the last 20 discs played.

This feature can be switched off if not required.

'PBC'

This line appears only if a VCD is loaded.
This function lets you activate or deactivate the PBC menu (Playback Control) for video CDs.
See 'Playing a (Super) Video CD'.

'Finalise disc'

This feature allows you to finalise DVD+R discs. If the disc has already been finalised this line will appear darker.

'Adapt disc format'

If a DVD+RW has been recorded in a computer drive or in another DVD recorder the index screen may not be displayed correctly.
This feature allows you to change the format of the disc.
It is therefore only visible if the disc format is different.

'Standby'

To save power, you can switch off the clock display on the DVD recorder. Programmed (TIMER) recordings will still take place.
In addition, you can present the most important features of the DVD recorder in scrolling text in the display (demo).

'Low power': If the DVD-Recorder is switched off (button **STANDBY** ⏻), the clock display is also switched off.

'Off': If the DVD-Recorder is switched off (button **STANDBY** ⏻), the clock display is visible.

'Demo mode': If the DVD recorder is switched off with the **STANDBY** ⏻ button, a list of the most important features is shown in the display.

'Display'

You can change the brightness of the display on the DVD recorder. This setting only affects the DVD recorder when it is switched on.

'Bright': The display appear with normal brightness. The disc tray light is switched on.

'Dimmed': The display appears less bright. The disc tray light is switched off.

'Off': The display and the disc tray light are switched off.


Remote Control settings

In this menu you can set the remote control type to which your DVD recorder should respond.

'DVD player': The DVD recorder responds to a DVD player remote control.

The DVD recorder also responds to the remote control of a DVD player (remote control code RC-6). Choose this setting if your Philips TV remote supports DVD functions.

'DVD recorder': The DVD recorder only responds to the supplied remote control.



Child lock (DVD and VCD)

This feature enables discs to be locked for children. When Child Lock is on, a 4-digit code (PIN) needs to be entered before a disc can be played. You can also decide whether the inserted disc should always be played or should be played only once, despite the child lock.

•)Play always:

This disc is stored in a memory with space for 50 child-safe discs. If more than 50 discs are stored, the last disc in the list is removed and the new disc is added. The screen shows 'Child safe' at the start of playback.

•)Play once:

This disc is only authorised for single playback. If the recorder is switched off, the PIN code must be re-entered.

Activating/deactivating child lock

- 1 Switch on the TV set. If required, select the programme number for the DVD recorder.
- 2 Switch on the DVD recorder using **STANDBY/ON**.
- 3 Press **SYSTEM-MENU**. The menu bar appears.
- 4 Select the **Child lock** icon using **◀** or **▶**.
- 5 Select **(Disc features)** using **CH+▼** or **CH+▲** and confirm with **▶**.
- 6 Confirm **Access control** using **▶**.
- 7 Enter a 4-digit code of your choice. If the code is new, you may have to enter the code a second time as confirmation.
- 8 Select **Child lock** using **CH+▲** or **CH+▼** and confirm with **▶**.
- 9 Select the **Child lock** icon using **CH+▼** or **CH+▲**.
- 10 Confirm with **OK**.
- 11 Quit the feature using **◀** and **SYSTEM-MENU**.

Unauthorised discs can only be played by entering the four-digit PIN code. To deactivate the child lock, select the **Child lock** icon in **9**.

Authorising a disc

- 1 Insert a disc. The access control box will appear after a short delay.
- 2 Using **CH+▲** or **CH+▼** select **Play once** or **Play always**.
- 3 Enter your PIN code using the number buttons **0..9**.

Double-sided DVDs may have a different ID for each side. For these discs, each side must be authorised. Multi-volume video CDs may have a different ID for each volume. For these CDs, each volume must be authorised.

Locking unlocked discs

To lock a disc that was formerly authorised follow the instructions below

- 1 Insert a disc. Playback starts automatically. If the playback does not start automatically, press **PLAY▶**.
- 2 Press the **STOP■** button while the **Child lock** icon is visible. The icon changes to **Child lock**. The disc is now locked.

Parental level control (DVD video only)

Films on pre-recorded DVD discs may contain scenes not suitable for children. Therefore, some discs may contain 'Parental Control' rating information that applies to the entire disc or to certain scenes on the disc. The appropriate scenes have filter values that range from 1-8. If such a scene is detected during playback, the filter value set on the DVD recorder is compared to the scene. If the filter value is higher than the setting, an alternative scene will be played (if available). Most DVDs apply the rating to an entire DVD. Therefore, if certain scenes exceed the rating you select, the entire disc will be blocked from viewing.

Activating/deactivating parental level control

- 1

Switch on the TV set. If required, select the programme number for the DVD recorder.
- 2

Switch on the DVD recorder using **STANDBY/ON** .
- 3

Press **SYSTEM-MENU** . The menu bar appears
- 4

Select the **TH** icon using **◀** or **▶** .
- 5


Select **(Disc features)** using **CH-▼** or **CH+▲** and confirm with **▶** .
- 6


Confirm **'Access control'** using **▶** .
- 7

Enter a 4-digit code of your choice. If the code is new, you may have to enter the code a second time as confirmation.
- 8

Select the **'Parental level'** using **CH+▲** or **CH-▼** and confirm with **▶** . A bar appears to select the parental level.
- 9

Select the appropriate rating using **CH-▼** , **CH+▲** or the number buttons **0-9** .





Tip

What do the ratings mean?
Rating 0 (displayed as '-') parental control not active.
Rating 1 (suitable for children)
Rating 8 (only suitable for adults)
What happens if a DVD scene contains a higher level than the rating set?
If the recorder does not find a suitable alternative, playback will stop and you must enter the four-digit code.

- 10

Confirm with **OK** . Quit using **◀** and **SYSTEM-MENU** .

Changing the country

The set filter values depend on the respective country. It is therefore necessary to enter the country to which these filter values apply.

- 1

Switch on the TV set. If required, select the programme number for the DVD recorder.
- 2

Switch on the DVD recorder using **STANDBY/ON** .
- 3

Press **SYSTEM-MENU** . The menu bar appears
- 4

Select the **TH** icon using **◀** or **▶** .
- 5

Select line **(Disc features)** using **CH-▼** or **CH+▲** and confirm with **▶** .
- 6


Confirm the line **'Access control'** using **▶** .
- 7

Enter your four-digit code. If the code is new, you may have to enter the code a second time as confirmation.
- 8

Select **'Change country'** using **CH-▼** or **CH+▲** and confirm with **▶** .
- 9

Select the corresponding country using **CH+▲** or **CH-▼** and confirm with **OK** .
- 10

To end, press **◀** and then **SYSTEM-MENU** .



Changing the PIN code

ENGLISH

1

Switch on the TV set. If required, select the programme number for the DVD recorder.

2

Switch on the DVD recorder using **STANDBY/ON** .

3

Press **SYSTEM-MENU** . The menu bar appears

4

Select the **"1"** icon using **◀** or **▶** .

5

Select **Disc features** using **CH- ▼** or **CH+ ▲** and confirm with **▶** .

6

Confirm **'Access control'** using **▶** .

7

Enter your four-digit PIN code. If the code is new, you may have to enter the code a second time as confirmation.

8

Select **'Change code'** using **CH+ ▲** or **CH- ▼** and confirm with **▶** .

9

Enter the new code using the number buttons **0..9** . Enter the same code again as confirmation.

10

Quit using **◀** and **SYSTEM-MENU** .

1

2

3

4

5

6

7

8

9

0

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

270

271

272

273

274

275

276

277

278

279

280

281

282

283

284

285

286

287

288

289

290

291

292

293

294

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

318

319

320

321

322

323

324

325

326

327

328

329

330

331

332

333

334

335

336

337

338

339

340

341

342

343

344

345

346

347

348

349

350

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365

366

367

368

369

370

371

372

373

374

375

376

377

378

379

380

381

382

383

384

385

386

387

388

389

390

391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

441

442

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477

478

479

480

481

482

483

484

485

486

487

488

489

490

491

492

493

494

495

496

497

498

499

500

501

502

503

504

505

506

507

508

509

510

511

512

513

514

515

516

517

518

519

520

521

522

523

524

525

526

527

528

529

530

531

532

533

534

535

536

537

538

539

540

541

542

543

544

545

546

547

548

549

550

551

552

553

554

555

556

557

558

559

560

561

562

563

564

565

566

567

568

569

570

571

572

573

574

575

576

577

578

579

580

581

582

583

584

585

586

587

588

589

590

591

592

593

594

595

596

597

598

599

600

601

602

603

604

605

606

607

608

609

610

611

612

613

614

615

616

617

618

619

620

621

622

623

624

625

626

627

628

629

630

631

632

633

634

635

636

637

638

639

640

641

642

643

644

645

646

647

648

649

650

651

652

653

654

655

656

657

658

659

660

661

662

663

664

665

666

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

683

684

685

686

687

688

689

690

691

692

693

694

695

696

697

698

699

700

701

702

703

704

705

706

707

708

709

710

711

712

713

714

715

716

717

718

719

720

721

722

723

724

725

726

727

728

729

730

731

732

733

734

735

736

737

738

739

740

741

742

743

744

745

746

747

748

749

750

751

752

753

754

755

756

757

758

759

760

761

762

763

764

765

766

767

768

769

770

771

772

773

774

775

776

777

778

779

780

781

782

783

784

785

786

787

788

789

790

791

792

793

794

795

796

797

798

799

800

801

802

803

804

805

806

807

808

809

810

811

812

813

814

815

816

817

818

819

820

821

822

823

824

825

826

827

828

829

830

831

832

833

834

835

836

837

838

839

840

841

842

843

844

845

846

847

848

849

850

851

852

853

854

855

856

857

858

859

860

861

862

863

864

865

866

867

868

869

870

871

872

873

874

875

876

877

878

879

880

881

882

883

884

885

886

887

888

889

890

891

892

893

894

895

896

897

898

899

900

901

902

903

904

905

906

907

908

909

910

911

912

913

914

915

916

917

918

919

920

921

922

923

924

925

926

927

928

929

930

931

932

933

934

935

936

937

938

939

940

941

942

943

944

945

946

947

948

949

950

951

952

953

954

955

956

957

958

959

960

961

962

963

964

965

966

967

968

969

970

971

972

973

974

975

976

977

978

979

980

981

982

983

984

985

986

987

988

989

990

991

992

993

994

995

996

997

998

999

1000

Disc features

Enter code...

0h

Access control

Auto resume

I have forgotten my code

Press **STOP** ■ four times (step 7) , then press **OK** . Access control is now switched off. You can now enter a new code as described above.

Tip

Access control (Child Lock)

77

4. Mechanical Instructions

4.1 Dismantling and Assembly of the Set

For item numbers please see the exploded views in chapter 10.

4.1.1 Manually opening the tray

- In case the loader is defective or cannot be opened electrically you can open the tray manually.
- Through a slot at the underside of the cabinet a slider that unlocks the tray can be accessed.
However in sets with drive VAD8031 (AV3) the slot is covered by an adhesive tape on the cabinet of the drive. Push through this adhesive tape by means of a thin screwdriver and move the slider to the left, see picture 4-1.
- **Make sure that an adhesive tape has been reapplied to the AV3 drive when repair is finished!**




Figure 4-1

4.1.2 Front

- After removing the top cover, remove tray front (1), see picture 4-2
- Remove the three screws (2) that fix the front panel
- Release the two snap hooks on the sides (3) and remove the front (4)
- Remove the 9 screws (5) to remove the front plate (6), see picture 4-3




Figure 4-2




Figure 4-3

4.1.3 DVIO Board, only for sets with DV input and Digital Board 1.5

To put the DVIO board in a service position, an extender board must be used. This extender board can be ordered with codenumber 3104 128 07770.

- After removal of the EPG board (if present) the DVIO board can be reached
- Remove the two screws (1), see picture 4-4
- Release the snaps of the two board spacers 125
- Put the DVIO board in the service position with the extender board 3104 128 07770.





Figure 4-4

4.1.4 Digital Board

- After removal of EPG board (if present) and DVIO board (if present) the digital board can be reached
- Remove screws (1)
- Turn the PCB in the service position





Figure 4-5

4.1.5 Basic Engine

- Remove the tray (1)
- Remove the four screws that fix the drive, see figure 4-6 or 4-7





Figure 4-6




Figure 4-7

4.1.6 Analog Board

- Remove the 3 screws (1) that fix the back plate to the bottom plate, see picture 4-8
- Remove the 4 screws (2) that fix the Analog Board to the bottom plate
- In sets with fan remove the Fan assy by releasing the fixing screw (3)
- Remove screw safety holder (4)
- Unlock the two snaps hooks at the left and right (5), see picture 4-9, and pull the board and backplate out gently (6)
- Turn the PCB in the service position (7), see picture 4-10




Figure 4-8




Figure 4-9




Figure 4-10

4.2 Dismantling Instructions

DISMANTLING INSTRUCTIONS
See exploded view for item numbers




Figure 4-11

5. Diagnostic Software

Due to the complexity of the DVD recorder, the time to find a defect in the recorder can become long. To reduce this time, the recorder has been equipped with Diagnostic and Service software (DS). The DS offers functionality to diagnose the DVDR hardware and tests the following:

- Interconnections between components
- Accessibility of components
- Functionality of the audio and video paths

This functionality can be accessed via several interfaces:

1. End user/Dealer script interface
2. Command Interface
3. Player script interface for sets with Digital Board 1.5, Empress
4. Menu interface for sets with Digital Board 1.5, Empress

5.1 End User/Dealer Script Interface

5.1.1 Description

The End user/Dealer script interface gives a diagnosis on a stand alone DVD recorder. During this mode, a number of hardware tests (nuclei) are automatically executed to check if the recorder is faulty. The diagnosis is simply a "fail" or "pass" message. If the message "FAIL" appears on the display, there is apparently a failure in the recorder. If the message "PASS" appears, the nuclei in this mode have been executed successfully. There can be still a failure in the recorder because the nuclei in this mode don't cover the complete functionality of the recorder.

5.1.2 Structure




Figure 5-1

The End use/Dealer script executes all diagnostic nuclei that do not need any user interaction and are meaningful on a standalone DVD recorder.

5.1.3 Contents for sets with Digital Board 1.5, Empress

The nuclei called in the End user/Dealer script are the following:

Counter	Nucleus	Name	Description
22	104	HostdSdramWrR	checks all memory locations of the 4MB SDRAM
21	106	HostdDramWrR	checks all the DRAM connected to the microprocessor of the digital board
20	123	Hostdl2cNvram	checks the data line (SDA) and the clock line (SCL) of the I2C bus between the host decoder and NVRAM
19	202	SAA7118I2c	checks the interface between the Host I2C controller and the AVENC SAA7118 Video Input Processor
18	200	VideoEncl2c	checks the interface between the host I2C controller and Empress SAA6752
17	207	AudioEncl2c	checks the I2C connection between the host decoder and Empress SAA6752
16	204	AudioEncAccess	tests the HIO8 interface lines between the host decoder and the audio encoder
15	203	AudioEncSramAccess	checks the access of the SRAM by the audio encoder (address and data lines).
14	205	AudioEncSramWrR	tests the SRAM connected to the audio encoder
13	206	AudioEncInterrupt	tests the interrupt line between the host decoder and the audio encoder
12	300	VsmAccess	checks whether the VSM interrupt controllers and DRAM are accessible
11	303	VsmInterrupt	checks both interrupt lines between the VSM and the host decoder
10	302	VsmSdramWrR	tests the entire SDRAM of the VSM
9	1400	Clock11_289MHz	switches the A_CLK of the micro clock to 11.2896 MHz
8	1401	Clock12_288MHz	switches the A_CLK of the micro clock to 12.288 MHz
7	601	BeS2Bengine	checks the S2B interface with the Basic Engine by sending an echo command
6	500	DisplayEcho	checks the interface between the host processor and the slave processor on the display board
5	700	AnalogueEcho	checks the interface between the host processor and the microprocessor on the analogue board
4	711	AnalogueNvram	checks the NVRAM on the analogue board
3	706	AnalogueTuner	checks whether the tuner on the analogue board is accessible

Counter	Nucleus	Name	Description
2	901	LoopAudioUserDealer	This nucleus tests the components on the audio signal path The host decoder - The analogue board - The audio encoder - The VSM Attention: the rear cinch audio out has to be connected to the front cinch audio in.
1	906	LoopVideoUserDealer	Nucleus for testing the components on the video signal system path: - The VIP - The video encoder - The VSM - The host decoder - The analogue board Attention: the rear cinch video out has to be connected to the front cinch video in.

5.1.4 Contents for sets with Digital Board Chrysalis

Included tests:	1.DS_ANAB_COMMUNICATIONECHO_NUC 2.DS_DCB_COMMUNICATIONECHO_NUC 3. DS_BROM_COMMUNICATION_NUC 4. DS_SYS_SETTINGSDISPLAY_NUC 5. DS_CHR_DEVTYPEGET_NUC 6. DS_CHR_INT_PIC_NUC 7. DS_CHR_DMA_NUC 8. DS_BROM_WRITEREAD_NUC 9. DS_NVRAM_COMMUNICATION_NUC 10. DS_NVRAM_WRITEREAD_NUC 11. DS_SDRAM_WRITEREADFAST_NUC 12. DS_FLASH_WRITEREAD_NUC 13.DS_FLASH_CHECKSUMPROGRAM_NUC 14.DS_SYS_HARDWAREVERSIONGET_NUC 15. DS_VIP_DEVTYPEGET_NUC 16. DS_VIP_COMMUNICATION_NUC 17. DS_DVIO_LINKDEVTYPEGET_NUC 18. DS_DVIO_PHYDEVTYPEGET_NUC 19. DS_DVIO_LINKCOMMUNICATION_NUC 20. DS_DVIO_PHYCOMMUNICATION_NUC 21.DS_PSCAN_COMMUNICATIONDENC_NUC 22.DS_PSCAN_COMMUNICATIONDEINTERLACER_NUC 23. DS_BE_COMMUNICATIONECHO_NUC 24.DS_ANAB_COMMUNICATIONIICNVRAM_NUC 25.DS_ANAB_COMMUNICATIONIICTUNER_NUC 26.DS_ANAB_COMMUNICATIONIICSOUNDPROCESSOR_NUC 27.DS_ANAB_COMMUNICATIONIICAVSELECTOR_NUC 28. DS_ANAB_CHECKSUMPROGRAM_NUC
-----------------	---

5.2 Player Script Interface only for sets with Digital Board 1.5 Empress

5.2.1 Description

The Player script will give the opportunity to perform a test that will determine which of the DVD recorder's modules are faulty, to read the error log and to perform an endurance loop test. To successfully perform the tests, the DVD recorder must be connected to a TV set.

To be able to check results of certain nuclei, the player script expects some interaction of the user (i.e. to approve a test picture or a test sound). Some nuclei (e.g. nuclei that test functionality of the DVDR module) require that a DVD+RW disc is inserted.

Only tests within the scope of the diagnostic software will be executed hence only faults within this scope can be detected.

5.2.2 Structure of the Player Script

The player script consists of a set of nuclei testing the hardware modules in the DVD recorder: the Display PWB, the Digital PWB, the Analogue In/Out PWB and the DVDR module. Nuclei run by the player test need some user interaction; in the next table this interaction is described. The player test is done in two phases:

- Interactive tests: this part of the player test depends strongly on user interaction and input to determine nucleus results and to progress through the full test. Reading the error log information can be useful to determine any errors that occurred recently during normal operation of the DVD player.
- The loop test will perform the same nuclei as the dealer test, but it will loop through the list of nuclei indefinitely.

STEP	DESCRIPTION	NUCLEUS
1	Press OPEN/CLOSE and PLAY at the same time and POWER ON the recorder to start the playerscript	2
2	The local display shows FPSEGMENTS . Press PLAY to start the test. First the <i>starburst pattern</i> is lit, then the <i>horizontal segments</i> are lit, followed by the <i>vertical segments</i> and the last test is <i>light all segments</i> test. After each of the 4 tests the user has to confirm that the correct pattern was lit. Press PLAY to confirm that the correct pattern was lit (four times if the FPSEGMENTS test was successful). Press RECORD to indicate that the correct pattern was not successfully lit. Press STOP to skip this nucleus.	502

STEP	DESCRIPTION	NUCLEUS
3	The local display shows FPLABELS . Press PLAY to start the test. Press PLAY to confirm that all labels are lit. Press RECORD to indicate that not all labels are lit. Press STOP to skip this nucleus.	503
4	The local display shows FPLIGHT ALL . Press PLAY to start the test. Press PLAY to confirm that everything was lit. Press RECORD to indicate that not all patterns are lit. Press STOP to skip this nucleus.	520
5	The local display shows FPLED . Press PLAY to start the test. Press PLAY to confirm that the led is lit. Press RECORD to indicate that the led is not lit. Press STOP to skip this nucleus.	504
6	The local display shows FPKEYBOARD . Press PLAY to start the test. Attention all keys have to be pressed to get a positive result! Press PLAY for more than one second to confirm that all the keys were pressed and shown on the local display. If not all the keys were pressed, a FAIL message will appear on the local display. Press RECORD for more than one second to indicate that not all keys were pressed and shown on the local display. Press STOP for more than one second to skip this nucleus.	505
7	The local display shows FPREMOTE CONTROL . Press PLAY to start the test. Press PLAY to confirm that a key on the remote control was pressed and shown on the local display. Only one key has to be pressed to get a successful result. Press RECORD to indicate that the key on the remote control was pressed but not shown on the local display. Press STOP to skip this nucleus.	506
8	The local display shows FPDIMMER . Press PLAY to start the test. Press PLAY to confirm that the text on the local display was dimmed. Press RECORD to indicate that the text on the local display was not dimmed. Press STOP to skip this nucleus.	518
9	The local display shows ROUTE VIDEO . Press PLAY to start the test. Press STOP to skip this nucleus.	712
10	The local display shows ROUTE AUDIO . Press PLAY to start the test. Press STOP to skip this nucleus.	713
11	The local display shows COLOUR-BAR ON . Press PLAY to start the test. Press STOP to skip this nucleus.	120
12	The local display shows PINK NOISE ON . Press PLAY to start the test. Press STOP to skip this nucleus.	115
13	The local display shows PINK NOISE OFF . Press PLAY to start the test. Press STOP to skip this nucleus.	116
14	The local display shows SINE ON . Press PLAY to start the test. Press STOP to stop the sine. Press STOP to skip this nucleus.	117
15	The local display shows COLOUR-BAR OFF . Press PLAY to start the test. Press STOP to skip this nucleus.	121
16	The local display shows BERESET . Press PLAY to start the test. Press STOP to skip this nucleus.	603
17	The local display shows BETRAY OPEN . Press PLAY to start the test. Press STOP to skip this nucleus.	616
18	The local display shows BETRAY CLOSE . Press PLAY to start the test. Press STOP to skip this nucleus.	615
19	The local display shows BEWRITE READ . Press PLAY to start the test. Press STOP to skip this nucleus.	617
20	The local display shows BETRAY OPEN . Press PLAY to start the test. Press STOP to skip this nucleus.	616
21	The local display shows BETRAY CLOSE . Press PLAY to start the test. Press STOP to skip this nucleus.	615
22	The local display shows READ ERRORLOG . Press PLAY to start the test. Press STOP to skip this nucleus. If the player test succeeded, the user/dealer script will start in an endless loop. If the player test failed, the local display will display FAIL and the error code	633

Remark

In case of failure, the display shows " FAIL XXXXXX ". The description of the shown error code can be retrieved in the survey of Nuclei Error Codes (paragraph 5.4). Once an error occurs, it is not possible to continue the player script. Unplug the set and restart the player script. By pressing the STOP key, it is possible to jump over the failure and to continue the player script.




Figure 5-2




Figure 5-3

5.2.3 Error Log

Explanation:

The application errors will be logged in the NVRAM. The maximum number of error bytes that will be visible is 19. The last reported error is shown as DN D0000000, the oldest visible error as D0000000 UP and the errors in between as DN D0000000 UP. DN stands for DOWN, UP stands for UPWARDS. The shown error codes are identical to the Nuclei Error Codes (paragraph 5.4).

5.2.4 Trade Mode

TRADE MODE

When the recorder is in Trade Mode, the recorder cannot be controlled by means of the front key buttons, but only by means of the remote control.




Figure 5-4

5.2.5 Virgin mode

If you want that the recorder starts up in Virgin mode, follow this procedure:

- Unplug the recorder
- plug the recorder again while you keep the STAND BY/ON key pressed
- the set starts up in Virgin mode.

5.3 Menu and Command Mode Interface

5.3.1 Nuclei Numeration

Each nucleus has a unique number of four digits. This number is the input of the command mode.




Figure 5-5

The following groups are defined for Digital Board 1.5, Empress:

Group number	Group name
0	Basic / Scripts
1	Host decoder (Sti5505 and memory)
2	Audio / video encoder (DVDR only)
3	VSM (DVDR only)
4	NVRAM
5	Front Panel

Group number	Group name
6	Basic Engine
7	Analogue board (DVDR only)
8	DVIO (DVDR only)
9	Loop nuclei (DVDR only)
10	Library sub nuclei (I2C nuclei)
11	User interface
12	Furore (SACD only)
13	DAC (SACD only)

The following groups are defined for Digital Board Chrysalis:

Group number	Group name
0	Basic / Scripts
1	Chrysalis
2	Boot EEPROM
3	NVRAM
4	SDRAM
5	Flash
6	Video Input Processor
7	DVIO
8	Progressive Scan
9	Basic Engine
10	Display and Control Board
11	Analogue Board
12	System

5.3.2 Error Handling

Each nucleus returns an error code. This code contains six numerals, which means:




Figure 5-6

The nucleus group numbers and nucleus numbers are the same as above.

5.3.3 Command Mode Interface

Set-Up Physical Interface Components

Hardware required:

- Service PC
- one free COM port on the Service PC
- special cable to connect DVD recorder to Service PC

The service PC must have a terminal emulation program (e.g. Hyperterminal) installed and must have a free COM port (e.g. COM1). Activate the terminal emulation program and check that the port settings for the free COM port are: 19200 bps, 8 data bits, no parity, 1 stop bit and no flow control. The free COM port must be connected via a special cable to the RS232 port of the DVD recorder. This special cable will also connect the test pin, which is available on the connector, to ground (i.e. activate test pin).

Code number of PC interface cable: 3122 785 90017

Activation Digital Board 1.5 Empress

Plug the recorder to the mains and the following text will appear on the screen of the terminal (program):

```

DVD Video Recorder Diagnostic Software version 48
Basic SDRAM Data bus test passed
Basic SDRAM Address bus test passed
Basic SDRAM Device test passed

(M) enu, (C) omand or (S) 2B-interface? [M] : @ c
DD:>

```

CL 16532095_073.aps
150801

Figure 5-7

The first line indicates that the Diagnostic software has been activated and contains the version number. The next lines are the successful result of the SDRAM interconnection test and the basic SDRAM test. The last line allows the user to choose between the three possible interface forms. If pressing C has made a choice for Command Interface, the prompt ("DD>") will appear. The diagnostic software is now ready to receive commands. The commands that can be given are the numbers of the nuclei.

Activation Digital Board Chrysalis

1. Pull the mains cord from the recorder and reconnect it again (reboot).
2. The next welcome message will appear on the PC:

Welcome screen D&S program

```

D&S - HyperTerminal
File Edit View Call Transfer Help

Factory Diagnostics and Service Software
DVD Video Recorder
Version 6 (Jan 9 2003, 11:11:15)

DS:>

```

Connected 0:01:10 Auto detect 19200 8-N-1 SCROLL CAPS NUM Capture Print echo

Figure 5-8

Now, the prompt 'DS:>' will appear. The diagnostic software is now ready to receive commands. The commands that can be given are the numbers of the nuclei. If you see above shown screen, continue with paragraph 'Nuclei Codes'.

3. It is possible that the next messages will appear when starting the DVD+RW for the first time

Error messages D&S program

```

D&S - HyperTerminal
File Edit View Call Transfer Help

[MIS_DIV.WARNING,Digital Board Hardware Information is corrupt,]
Factory Diagnostics and Service Software
DVD Video Recorder
Version 6 (Jan 9 2003, 11:11:15)

WARNING,Digital Board Hardware Information is corrupt
DS:>

```

Connected 0:01:10 Auto detect 19200 8-N-1 SCROLL CAPS NUM Capture Print echo

Figure 5-9a

Error messages D&S program

```

D&S - HyperTerminal
File Edit View Call Transfer Help

DS:> *****
System error: Diversity string UnAccessible!! Eeprom problem! *****

*****

Factory Diagnostics and Service Software
DVD Video Recorder
Version 8 (May 12 2003, 16:44:35)

WARNING,Digital Board Hardware Information is corrupt
DS:>

```

Figure 5-9b

In these cases, the boot EEPROM of the Chrysalis Digital Board does not contain the required string with the hardware information. To update the Digital Board with the correct string, nucleus 1226 must be executed.

See next section 'Diversity String Input'.

There can also be the next error message.

```

D&S - HyperTerminal
File Edit View Call Transfer Help

DS:> *****
* System error: Due to a setting in the Digital Board Diversity *
* Settings, the Recorder is unable to function properly.      *
* Please change the hardware diversity settings by using the  *
* proper nuclei BEFORE proceeding to the application!!        *
*****

The next Hardware Settings can be safely programmed:
Board name: FAILSAFE
Hardware ID: 21

Codec IC: PNK7100_MF3
Video Input Processor IC: SAA7118
Progressive Scan Deinterlacer IC: None
Progressive Scan Denc IC: ADV7196
I-Link physical layer circuit IC: PDI1394P25
I-Link link layer circuit IC: PDI1394P40
Audio clock: Clock scheme 1
Bit engine connector: available
IDE connector 1: available
IDE connector 2: not available
PCI connector: not available
RAM size: 32MByte
ROM size (NOR FLASH bank 1): 8MByte
ROM size (NOR FLASH bank 2): Not available
ROM size (NAND FLASH): Not available
Settings ID: 4641494C5341464521030300010101020101000020080000
Program these settings? [Y/N]
Programming the settings values...

Factory Diagnostics and Service Software
DVD Video Recorder
Version 8 (May 1 2003, 18:38:27)

DS:>_

```

Connected 00:02:31 Auto detect Auto detect SCROLL CAPS NUM Capture Print echo

Figure 5-9c

Enter "Y" to program a safe string. With this automatically generated string the board will work in principle but it has to be checked if all board settings were detected correctly.

Diversity String Input

4. Execute nucleus 1226 to enter the string. Please see chapter 8.5 for details

Nucleus 1226 execution with string




Figure 5-10

5. To check if the hardware info is filled correctly, you can execute nucleus 1228.

Nucleus 1228 info example




Figure 5-11

6. Exit the 'Terminal' program.
7. Reboot the DVD recorder to allow the software to start.

Command Overview Digital Board 1.5 Empress

We provide an overview of the nuclei and their numbers. This overview is preliminary and subject to modifications.

Host Decoder [01]

[xx yy] Number	Nuclei
100	Checksum Flash
101	Flash Write Access 1
102	Flash Write Access 2
103	Flash Write Read
104	SdRam Write Read
105	SdRam Write Read Fast
106	Dram Write Read
107	Dram Write Read Fast
108	Hardware Version
109	Mute On
110	Mute Off
115	Pink Noise On
116	Pink Noise Off
117	Sine On
118	Sine Burst 1kHz
119	Sine Burst 12kHz
120	Colour-bar On Note: Use nucleus 712 with parameter 07 to route the signals to the analogue board output
121	Colour-bar Off
122	NvramWrR
123	NvramI2c
130	Boot Version
131	Application Version
132	Diagnostics Version
133	Download Version
134	Write / read I2C message to / from digital board
135	Video Test Signal OnNote: Use nucleus 712 with parameter 07 to route the signals to the analogue board output. Input: 135 [a] [b] a: Number of test image, 0. Horizontal colour-bar 1. White 2. Yellow 3. Light blue 4. Green 5. Magenta 6. Red 7. Blue 8. Black 9. Colour triangle (execution time is 12 seconds) 10. Test image for progressive scan (execution time is 6 seconds) b: Video standard, 0. PAL BDGHI 1. NTSC
136	Video Test Signal Off
137	Macrovision Off

Audio Video Decoder [02]

[xx yy] Number	Nuclei
200	Video Encoder I2C
202	SAA7118 I2C
203	Audio Encoder SRAM Access
204	Audio Encoder Access
205	Audio Encoder SRAM Write Read
206	Audio Encoder Interrupts

[xx yy] Number	Nuclei
207	Audio Encoder I2C
208	SAA7118 select input
209	Empress Version

VSM [03]

[xx yy] Number	Nuclei
300	Register Access
301	SDRAM Access
302	SDRAM Write Read
303	Interrupt lines
304	VSM Interconnection
305	UART

NVRAM [04]

[xx yy] Number	Nuclei
400	Reset
401	Read
402	Modify
403	UniqueNr Read
404	Read Error Log
407	Reset Error Log
409	Line2 Region-Code Reset
410	UniqueNr Store

Front Panel [05]

[xx yy] Number	Nuclei
500	Echo
501	Version
502	Segment
503	Label
504	Led
505	Keyboard
506	Remote-Control
507	Segment Starburst
508	Segment Vertical
509	Segment Horizontal
514	Beeper
515	Disbar
516	Disbar Dots
517	Vu / Grid
518	Dimmer
519	Blinking
520	Light All Segments
522	Flap Open
523	Flap Close

Basic Engine [06]

[xx yy] Number	Nuclei
600	S2B Pass
601	S2B Echo
602	Version
603	Reset
604	Focus On
605	Focus Off
606	Disc Motor On
607	Disc Motor Off
608	Radial On

[xx yy] Number	Nuclei
609	Radial Off
615	Tray In
616	Tray Out
617	Write Read
618	Write Read Endless Loop
619	Selftest
620	BE Test
621	Laser Test
622	Spindle (Disc) Motor Test
623	Focus Test
624	Sledge Motor Test
625	Sledge Motor Slow
626	Tilt
627	EEPROM Read
628	EEPROM Write
629	Optimise Jitter
630	Radial ATLS Calibration
631	Get Statistics Information
632	Reset Statistics Information
633	BE Read Error Log
634	BE Reset Error Log
638	Get Self Test Result
639	Radial Initialisation
640	Get OPU info

Analog Board [07]

[xx yy] Number	Nuclei
700	Echo
703	Boot Version
704	Hardware Version
705	Clock Adjust
706	Tuner
707	Frequency Download
708	Data Slicer
709	Sound Processor
710	AV Selector
711	Nvram
712	Route Video
713	Route Audio
715	Set Slash Version
716	Application Version
717	Diagnostics Version
718	Download Version
720	Bargraph Level Adjustment
721	Clock correction
722	Clock reference
723	Re-virginise Recorder
724	Flash Checksum
725	Tuner frequency selection Europe: To make video and audio signals from the tuner available on Scart2, send command "712 08". For Nafta/Apac: To make the black/white Video available on Y/C Rear Out connector, send command "712 08" Input: 725 [frequency in MHz*16] [system] System: NTSC=16, PAL BG=16, PAL I=32, PAL DK=48, SEC L=64, SEC LS=80, SEC BG=96, SEC DK=112
727	Set virgin bit
728	Clear Virgin Bit
729	Write / read I2C message to / from analogue board

[xx yy] Number	Nuclei
730	Store external presets
731	Get slash version
732	AFC Reference Voltage Tuner
736	Get EPG Version
737	Get operating hours in Tuner Mode

DVIO [08]

[xx yy] Number	Nuclei
800	Check DVIO board presence
801	Reset DVIO
802	DVIO Access
803	Get DVIO error codes
804	Get DVIO module Ids
805	Execute DVIO module SelfTestInput: 805 [a] [b]Parameters: a=1/0...full Ram test, b=1/0...cable connected
806	Set DVIO led on.
807	Set DVIO led off.

Loop Nuclei [09]

[xx yy] Number	Nuclei
900	Digital Audio Loop(no function in Gen. 1.5 and Lead)
901	User / Dealer Audio Loop
902	Digital Video Loop
903	Digital Video VBI Loop
904	System Video Loop
905	System Video VBI Loop
906	User / Dealer Video Loop
907	User / Dealer Video VBI Loop
908	System Audio Loop SCART
909	System Audio Loop CINCH
910	Digital DVIO Video Loop
911	System Video Vip

Miscellaneous [14]

[xx yy] Number	Nuclei
1400	Clock 11.289 MHz
1401	Clock 12.288 MHz
1412	Progressive Scan I2C
1413	Progressive Scan test image on
1414	Progressive Scan test image off
1415	Progressive Scan Route Enable
1416	Progressive Scan Route Disable

Scripts [00]

[xx yy] Number	Nuclei
1	UserDealer Script
2	Player Script

Routing Audio and Video*Route Video*

Nucleus Number: 712

Description

This nucleus routes the video signals on the analogue board to the destination determined by the input parameters

The paths that are available for video routing and their description (Euro region):

Path ID	Description
00	Input signal is VIDEO(CVBS) from digital board and will be re-routed back to the digital board.
01	Input signal is from FRONT VIDEO(CVBS) IN and will be routed to the digital board.
02	No Routing.
03	Input signal is from FRONT S-VIDEO(Y/C) and will be routed to the digital board.
04	No Routing.
05	Input signal is CVBS from SCART1 and will be routed to the digital board.
06	Input signal is CVBS from SCART2 and will be routed to the digital board.
07	Input Signal is CVBS from Digital Board and it will be routed to Scart1 and Scart2.
08	Input signal is VIDEO(CVBS) from ANTENNA IN and will be routed to SCART2.
09	Input signal is VIDEO(CVBS) from SCART1 and will be routed to SCART2.
10	Input signal is VIDEO(CVBS) from SCART2 and will be routed to SCART1.
11	Signal path is routed Fast Blank from Scart2 pin16 and will be routed Scart1 pin16
12	Input Signal is YC from Digital Board and it will be routed to Scart1.
13	
14	No Routing.
15	Input Signal is CVBS from TUNER and it will be routed to Digital .
16	No Routing.
17	Input Signal is routed from digital board YC to REAR S-VIDEO(YC) OUT
18	Signal path is routed from digital board RGB to RGB SCART1 and from digital board CVBS to digital board CVBS.
19	No Routing.
20	Input RGB Signal is routed from Digital Board to SCART1(RGB),Input CVBS Signal from Digital Board to Digital Board and Fast Blanking Signal from Scart 2 to Scart1.
21	Input Y/C Signal from Digital Board is routed to Rear Y/C Connector and Input Y/c Signal from Front Y/C connector is routed to Digital Board.

Example

DD:> 712 01

71200: Video routing on the Analogue Board OK.

Test OK @

Route Audio

Nucleus Number: 713

Description

This nucleus routes the audio on the analogue board to the destination determined by the input parameters

The paths that are available for audio routing and their description (Europe version)

Path ID	Description
00	Input signal is from FRONT AUDIO IN and will be routed to the digital board.(This is done so that nucleus 901 works)
01	Input signal is from FRONT AUDIO IN and will be routed to the digital board.
02	No Routing.
03	Input signal is AUDIO from SCART1 and will be routed to the digital board.
04	Input signal is AUDIO from SCART2 and will be routed to the digital board.
05	No routing.
06	No routing.
07	Input Audio signal is from the digital Board and it will be routed to the Scart 1 and Scart2
08	Input AUDIO signal from TUNER and will be routed to SCART2.
09	Input signal is AUDIO from SCART1 and will be routed to SCART2.
10	Input audio signal from Scart2 is routed to Scart1.
11	Input Audio signal is routed from DVIO to Scart2.
12	
13	No Routing.
14	Input is Audio Signal from DVIO and it will be routed to Digital Board.
15	Input is Audio Signal from TUNER and it will be routed to Digital Board..
16	No routing.
17	No Routing.
18	Input signal is from FRONT AUDIO IN and will be routed to SCART2.
21	Input signal is from FRONT AUDIO IN and will be routed to the digital board.(This is done so that nucleus 909.1 works)

EXAMPLE

DD:> 713 00

71300: Audio routing on the Analogue Board OK.

Test OK @

Below you will find an overview of the nuclei, their numbers, and their error codes. This overview is preliminary and subject to modifications.

Command overview Digital Board Chrysalis*Chrysalis (CHR)*

Nucleus Name	DS_CHR_DevTypeGet
Nucleus Number	100
Description	Sends the device ID and the module ids and revisions of the PN7100 (Chrysalis) to the stdout port.
User Input	None
Example	<pre>DS:> 100 Device ID 7100 Codec ID PN7100_MF2 F-BCU (0x0102) 1.0 INTC (0x011d) 1.0 PCI-XIO(0x0113) 1.0 SIF(0x013b) 1.0 EJTAG (0x0104) 0.0 S-BCU (0x0102) 1.0 BOOT (0x010a) 1.0 CONFIG (0x013f) 1.0 RESET (0x0123) 1.0 DEBUG (0x0116) 0.0 UART0 (0x0107) 0.1 UART1 (0x0107) 0.1 UART2 (0x0107) 0.1 UART3 (0x0107) 0.1 I2C0 (0x0105) 0.1 I2C1 (0x0105) 0.1 GPIO (0x013c) 1.0 SYNC (0x013a) 1.0 DISP0 (0xa015) 0.1 DISP1 (0xa00f) 0.0 OSD (0x0136) 0.1 SPU (0xa00e) 0.0 MIXER (0x0137) 1.0 DENC (0x0138) 0.1 CCIR (0x0139) 1.0 VDEC (0x0133) 0.1 PARSER (0xa00d) 0.0 DV (0xa00c) 0.0 BEI (0xa00a) 0.0 IDE (0xa009) 0.0 SGDX (0xa008) 0.0 BYTE (0xa00b) 0.0 OUTPUT (0xa003) 0.0 ACOMP (0xa000) 0.0 VFE (0xa001) 0.0 VCOMP (0xa002) 0.0 SCR (0x0000) 0.0 SIFF (0xa011) 0.0 WMD (0xa010) 0.0 AUDIO0 (0xa015) 0.1 AUDIO1 (0xa00f) 0.0 PSCAN (0xa018) 0.0 010000: Test OK @</pre>

Nucleus Name	DS_CHR_TestImageOn
Nucleus Number	101
Description	Generates a test-image of a selected video standard on selected video output on the digital board. When no input is given, the default values will be used. Use nucleus DS_ANAB_VideoRouting to route the video signal on the analogue board output
User Input	<p>The user has to decide which test image, video standard and video output must be used:</p> <p>Test image id:</p> <ul style="list-style-type: none"> 0 VERTICAL_COLOURBAR (default) 1 HORIZONTAL_COLOURBAR 2 WHITE 3 YELLOW 4 CYAN 5 GREEN 6 MAGENTA 7 RED 8 BLUE 9 BLACK 10 GRAY <p>Video standard:</p> <ul style="list-style-type: none"> PAL (default) NTSC <p>Video output:</p> <ul style="list-style-type: none"> ALL CVBS and YC and RGB (default) CVBS YC RGB YUV PSCAN progressive scan
Example	<pre>DS:> 101 010100: Test OK @ DS:> 101 0 pal cvbs 010100: Test OK @ DS:> 101 4 ntsc yc 010100: Test OK @</pre>

Nucleus Name	DS_CHR_TestImageOff
Nucleus Number	102
Description	Switches the test-image off.
User Input	None
Example	DS:> 102 010200: Test OK @

Nucleus Name	DS_CHR_SineOn
Nucleus Number	103
Description	Generate an audio sine signal on the audio output of the digital board. Note: Left channel 6kHz, right channel 12 kHz sine. Make sure to route the signal first.
User Input	None
Example	DS:> 103 010300: Test OK @

Nucleus Name	DS_CHR_SineOff
Nucleus Number	104
Description	Stop generating the audio sine signal
User Input	None
Example	DS:> 104 010400: Test OK @

Nucleus Name	DS_CHR_SineBurst
Nucleus Number	105
Description	Generate an audio sine signal on the audio output of the digital board for 4 seconds. Note: Left channel 6kHz, right channel 12 kHz sine with some known hick-ups
User Input	None
Example	DS:> 105 010500: Test OK @

Nucleus Name	DS_CHR_MuteOn
Nucleus Number	106
Description	Mute the audio outputs of the digital board
User Input	None
Example	DS:> 106 010600: Test OK @

Nucleus Name	DS_CHR_MuteOff
Nucleus Number	107
Description	De-mute the audio outputs of the digital board
User Input	None
Example	DS:> 107 010700: Test OK @

Nucleus Name	DS_CHR_DvLedOn
Nucleus Number	108
Description	Check the connection to the DV-LED on the digital board by switching it on
User Input	None
Example	DS:> 108 010800: Test OK @

Nucleus Name	DS_CHR_DvLedOff
Nucleus Number	109
Description	Switch off the DV-LED on the digital board
User Input	None

Example	DS:> 109 010900: Test OK @
---------	----------------------------------

Nucleus Name	DS_CHR_MacroVisionOn	
Nucleus Number	110	
Description	Turn on MacroVision.	
User Input	None	
Example	DS:> 110 011000: Test OK @	

Nucleus Name	DS_CHR_MacroVisionOff	
Nucleus Number	111	
Description	Turn off MacroVision.	
User Input	None	
Example	DS:> 111 011100: Test OK @	

Nucleus Name	DS_CHR_Peek	
Nucleus Number	112	
Description	Peek a value on a specified address	
User Input	The address to peek on	
Example	DS:> 112 0xa0700000 011200: Value read = 0x000001BD Test OK @	

Nucleus Name	DS_CHR_Poke	
Nucleus Number	113	
Description	Poke a value on a specified address	
User Input	The address to poke and the value: <address><value>	
Example	DS:> 113 0xa0700000 0xaabccdd 011300: Test OK @	

Nucleus Name	DS_CHR_INT_PICInterrupts	
Nucleus Number	114	
Description	Test all interrupts of the priority interrupt controller	
User Input	-	
Example	DS:> 114 011400: Test OK @	

Nucleus Name	DS_CHR_DMA_TestDMA	
Nucleus Number	115	
Description	Test the memory to memory DMA transfer	
User Input	-	
Example	DS:> 115 011500: Test OK @	

Boot EEPROM (BROM)

Nucleus Name	DS_BROM_Communication	
Nucleus Number	200	
Description	Check the communication between the IIC controller of the Chrysalis and the boot EEPROM	
User Input	None	
Example	DS:> 200 020000: Test OK @	

Nucleus Name	DS_BROM_WriteRead	
Nucleus Number	201	

Description	Check whether the Boot EEPROM can be written to and read from
User Input	None
Example	DS:> 201 020100: Test OK @

NVRAM

Nucleus Name	DS_NVRAM_Communication
Nucleus Number	300
Description	Check the communication between the IIC controller of the Chrysalis and the EEPROM
User Input	None
Example	DS:> 300 030000: Test OK @

Nucleus Name	DS_NVRAM_WriteRead
Nucleus Number	301
Description	Check whether the EEPROM can be written to and read from
User Input	None
Example	DS:> 301 030100: Test OK @

Nucleus Name	DS_NVRAM_Clear
Nucleus Number	302
Description	Make the EEPROM empty, containing all zeroes.
User Input	None
Example	DS:> 302 030200: Test OK @

Nucleus Name	DS_NVRAM_Modify
Nucleus Number	303
Description	Modifies one or more locations in NVRAM and updates the checksum of the section modified
User Input	1. The location that must be modified i.e. "ALL" "BOOT" "DIAGNOSTICS" "DOWNLOAD" "CONFIG" "RECORDER" or no string if an offset from the base address of the NVRAM is required 2. The offset and data which to put on the selected location <offset> <length> <data>
Example	DS:> 303 DIAGNOSTICS 5 1 0x5a 030300: Section is modified successfully Test OK @

Nucleus Name	DS_NVRAM_Read
Nucleus Number	304
Description	Read out one or more locations in the NVRAM
User Input	1. The location which must be read i.e. "ALL" "BOOT" "DIAGNOSTICS" "DOWN LOAD" "CONFIG" "RECORDER" or no string if an offset from the base address of the NVRAM is required 2. The offset and number of bytes to read <offset> <length>
Example	304 DIAGNOSTICS 0 6 030400: Value read = 0x00 0x00 0x00 0x00 0x00 0x5A Test OK @

SDRAM

Nucleus Name	DS_SDRAM_WriteRead
Nucleus Number	400
Description	Check all data lines, address lines and memory locations of the SDRAM
User Input	None
Example	DS:> 400 040000: Test OK @

Nucleus Name	DS_SDRAM_WriteReadFast
Nucleus Number	401
Description	Check all data lines and address lines of the SDRAM
User Input	None
Example	DS:> 401 040100: Test OK @

Nucleus Name	DS_SDRAM_Write
Nucleus Number	402
Description	Write to a specific memory address
User Input	1. The location that must be modified (SDRAM starts at address 0xA0000000) 2. The value to put on the selected location
Example	DS:> 402 0xa1000010 0xad112222 040200: Test OK @

Nucleus Name	DS_SDRAM_Read
Nucleus Number	403
Description	Read from a specific memory address
User Input	The location from which the data must be read (SDRAM starts at address 0xA0000000)
Example	DS:> 403 0xa1000010 040300: Value read = 0xAD112222 Test OK @

FLASH

Nucleus Name	DS_FLASH_DevTypeGet
Nucleus Number	500
Description	Get the device (revision) type information of the FLASH IC. (manufacturer and device ID)
User Input	None
Example	DS:> 500 050000: Found FLASH memory: Manufacturer ID: 0x01 Device ID : 0x01 Test OK @

Nucleus Name	DS_FLASH_WriteRead
Nucleus Number	501
Description	Check whether the FLASH can be written to and read from
User Input	None
Example	DS:> 501 050100: Test OK @

Nucleus Name	DS_FLASH_Read
Nucleus Number	502
Description	Read from a specific memory address in FLASH
User Input	The location from which data must be read (FLASH starts at address 0xB8000000)
Example	DS:> 502 0xb8000000 050200: Value read = 0x3C08A000 Test OK @

Nucleus Name	DS_FLASH_ChecksumProgram
Nucleus Number	503
Description	Check the checksum of the application partitions by recalculating and comparing partition checksums
User Input	None

Example	DS:> 503 050300: BootCode checksum is: 0xBABE5B6F, which is correct Diagnostics checksum is : 0xBABEBAFF, which is correct Download checksum is: 0xBABEEDBF, which is correct Application checksum is : 0xBABE8EEC, which is correct Test OK @
---------	--

Nucleus Name	DS_FLASH_CalculateChecksum
Nucleus Number	504
Description	Calculate the checksum over all memory addresses. Used to check entire FLASH contents
User Input	None
Example	DS:> 504 050400: The Checksum = 0xBABE30A4 Test OK @

Nucleus Name	DS_FLASH_CalculateChecksumFast
Nucleus Number	505
Description	Calculate a checksum over a selected number of address locations
User Input	None
Example	DS:> 505 050500: The Checksum = 0xBABEB064 Test OK @

Video Input Processor (VIP)

Nucleus Name	DS_VIP_DevTypeGet
Nucleus Number	600
Description	Get the device (revision) type information of the VIP IC
User Input	None
Example	DS:> 600 060000: Found SAA7118 Test OK @

Nucleus Name	DS_VIP_Communication
Nucleus Number	601
Description	Check the communication between the IIC controller of the chrysalis and the VIP IC
User Input	None
Example	DS:> 601 060100: Test OK @

Nucleus Name	DS_VIP_ClockOutputOn
Nucleus Number	602
Description	Switch the clock output on
User Input	None
Example	DS:> 602 060200: Test OK @

Nucleus Name	DS_VIP_ClockOutputOff
Nucleus Number	603
Description	Switch the clock output off
User Input	None
Example	DS:> 603 060300: Test OK @

Nucleus Name	DS_VIP_SelectInput
Nucleus Number	604
Description	Select an input video path to be switched to the analogue output pin (AOUT) of the VIP

User Input	The input to select, see table below. 1 CVBS_Y_IN_A 2 CVBS_OUT_B 3 CVBS_Y_IN_B 4 CVBS_Y_IN_C 6 C_IN 8 G_IN 9 Y_IN 13 B_IN 14 U_IN 18 R_IN 19 V_IN
Example	DS:> 604 1 060400: Test OK @

Digital Video Input Output (DVIO)

Nucleus Name	DS_DVIO_LinkDevTypeGet
Nucleus Number	700
Description	Get the device (revision) type information of the 1394 Link layer IC
User Input	None
Example	DS:> 700 070000: Device type of the link layer IC: ffc00301 Test OK @

Nucleus Name	DS_DVIO_PhyDevTypeGet
Nucleus Number	701
Description	Get the device (revision) type information of the 1394 Physical layer IC
User Input	None
Example	DS:> 701 070100: Device type of the phy layer IC: 0 Test OK @

Nucleus Name	DS_DVIO_LinkCommunication
Nucleus Number	702
Description	Check the accessibility of the 1394 Link layer IC by writing to and reading from a specific address
User Input	None
Example	DS:> 702 070200: Test OK @

Nucleus Name	DS_DVIO_PhyCommunication
Nucleus Number	703
Description	Check the accessibility of the 1394 Physical layer IC by writing to and reading from a specific address
User Input	None
Example	DS:> 703 070300: Test OK @

Nucleus Name	DS_DVIO_Routing
Nucleus Number	704
Description	Route a DV stream containing an audio and video signal through the physical and link layer ICs to the Chrysalis
User Input	None, test works for both NTSC and PAL
Example	DS:> 704 070400: Test OK @

Nucleus Name	DS_DVIO_DetectNode
Nucleus Number	705
Description	Check whether a DV node can be detected by the hardware
User Input	None, test works for both NTSC and PAL

Example	DS:> 705 070500: Test OK @
---------	----------------------------------

Nucleus Name	DS_DVIO_DetectStream
Nucleus Number	706
Description	Check whether a DV stream can be detected by the hardware
User Input	None, test works for both NTSC and PAL
Example	DS:> 706 070600: Test OK @

Progressive Scan (PSCAN)

Nucleus Name	DS_PSCAN_CommunicationDenc
Nucleus Number	801
Description	Check the communication between the IIC controller of the chrysalis and the progressive scan DENC-IC
User Input	None
Example	DS:> 801 080100: Test OK @

Nucleus Name	DS_PSCAN_TestImageOn
Nucleus Number	802
Description	Generate the test images that are present on the progressive scan IC.
User Input	In case of ADV7196: When no input is given "HATCH" is the default - "HATCH" - "FRAME" Remark: "HATCH" is a crosshatch test pattern (horizontal and vertical white lines are displayed against a black background) "FRAME" is a uniform coloured frame/field test pattern (default white). In case of FLI2300: Nothing.
Example	DS:> 802 HATCH 080200: Test OK @

Nucleus Name	DS_PSCAN_TestImageOff
Nucleus Number	803
Description	Switch off the generated test image
User Input	None
Example	DS:> 803 080300: Test OK @

Nucleus Name	DS_PSCAN_TestImageColourSettingsSet
Nucleus Number	804
Description	Set the colour of the hatch- or the frame- field to a different value than the default white
User Input	A colour string of one of the next non-case sensitive strings (WHITE, BLACK, RED, GREEN, BLUE, YELLOW, CYAN, MAGENTA) or Y Cr Cb (hexa-) decimal values.
Example	DS:> 804 yellow 080400: Test OK @ DS:> 804 0x6a 0xde 0xca 080400: Test OK @

Nucleus Name	DS_PSCAN_TestImageColourSettingsGet
Nucleus Number	805
Description	Get the colour settings of the hatch- or the frame- field.
User Input	None
Example	DS:> 805 080500: Colour Y Cr Cb values: 0xD2 0x92 0x10 Test OK @

Nucleus Name	DS_PSCAN_Routing	
Nucleus Number	806	
Description	Route a video signal from the host processor through the progressive scan ICs to the progressive scan output of the set. Note: to route the progressive scan to the output of the set, first call nucleus 1112 with parameter 0 (video routing on analogue board).	
User Input	None	
Example	DS:> 806 080600: Test OK @	

Nucleus Name	DS_PSCAN_DevTypeGetDeinterlacer	
Nucleus Number	807	
Description	Get the device (revision) type information of the progressive scan deinterlacer.	
User Input	None	
Example	DS:> 807 080700: Chip name : 2300 Chip version : 1 Test OK @	

Nucleus Name	DS_PSCAN_CommunicationDeinterlacer	
Nucleus Number	808	
Description	Check the communication between the IIC controller of the chrysalis and the progressive scan Deinterlacer-IC	
User Input	None	
Example	DS:> 808 080800: Test OK @	

Basic Engine (BE)

Nucleus Name	DS_BE_CommunicationEcho	
Nucleus Number	900	
Description	Check the communication between the digital board and the basic engine by issuing an echo command over the S2B interface	
User Input	None	
Example	DS:> 900 090000: Test OK @	

Nucleus Name	DS_BE_Reset	
Nucleus Number	901	
Description	Reset the basic engine	
User Input	None	
Example	DS:> 901 090100: Test OK @	

Nucleus Name	DS_BE_VersionGet	
Nucleus Number	903	
Description	Get the version of the basic engine and that of the optical unit	
User Input	None	
Example	DS:> 903 090300: BE version = 20.09.18 Optical unit version = 3C.00.09.41.08 Test OK @	

Nucleus Name	DS_BE_GetSelftestResult	
Nucleus Number	902	
Description	Return the self-test results through the service port	
User Input	None	
Example	DS:> 902 090200: Test OK @	

Nucleus Name	DS_BE_TrayOut
Nucleus Number	904
Description	Open the tray of the basic engine
User Input	None
Example	DS:> 904 090400: Test OK @

Nucleus Name	DS_BE_TrayIn
Nucleus Number	905
Description	Close the tray of the basic engine
User Input	None
Example	DS:> 905 090500: Test OK @

Nucleus Name	DS_BE_WriteReadDvdRw
Nucleus Number	906
Description	Write data to and read data from a DVD+RW disc through the basic engine for verification of the writing
User Input	None
Example	DS:> 906 090600: Testing on sector 0x5dbe0: OK Test OK @

Nucleus Name	DS_BE_WriteReadDvdR
Nucleus Number	907
Description	Write data to and read data from a DVD+R disc through the basic engine for verification of the writing
User Input	None
Example	DS:> 907 090700: Testing on sector 0x36210: OK Test OK @

Nucleus Name	DS_BE_StatisticalInformationGet
Nucleus Number	908
Description	Retrieve the statistical information from the basic engine
User Input	None
Example	DS:> 908 Number of times Tray went Open/Closed : 4 Total minutes the CD laser was on : 0 Total minutes the DVD laser was on : 0 Total minutes the write laser was on : 0 090800: Test OK @

Nucleus Name	DS_BE_StatisticalInformationReSet
Nucleus Number	909
Description	Reset the statistical information in the basic engine
User Input	None
Example	DS:> 909 090900: Test OK @

Nucleus Name	DS_BE_ErrorLogGet
Nucleus Number	910
Description	Get the error log from the basic engine
User Input	None
Example	DS:> 910 Momentary errors (0-9): 0x21 0x00 0x00 0x20 0x00 0x00 0x00 0x00 0x00 0x00 Cumulative errors (1-9): 0x00 0x80 0x20 0x00 0x00 0x00 0x00 0x00 0x00 0x00 Software fatal assert : 256 cpowermanager.cpp 091000: Test OK @

Nucleus Name	DS_BE_ErrorLogReset
Nucleus Number	911
Description	Reset the error log in the basic engine
User Input	None
Example	DS:> 911 091100: Test OK @

Nucleus Name	DS_BE_JitterOptimise
Nucleus Number	912
Description	Perform jitter optimisation: A formatted DVD must be loaded into the engine before executing this nucleus
User Input	none
Example	DS:> 912 Test OK @

Nucleus Name	DS_BE_FocusOn
Nucleus Number	913
Description	Put the laser of the BE into focus
User Input	None
Example	DS:> 913 091300: Test OK @

Nucleus Name	DS_BE_FocusOff
Nucleus Number	914
Description	Turn off putting the laser of the BE into focus
User Input	None
Example	DS:> 914 091400: Test OK @

Nucleus Name	DS_BE_MotorOn
Nucleus Number	915
Description	Turn on the turntable motor
User Input	None
Example	DS:> 915 091500: Test OK @

Nucleus Name	DS_BE_MotorOff
Nucleus Number	916
Description	Turn off the turntable motor
User Input	None
Example	DS:> 916 091600: Test OK @

Nucleus Name	DS_BE_RadialOn
Nucleus Number	917
Description	Close the radial loop
User Input	A formatted DVD must be loaded into the engine before executing this nucleus
Example	DS:> 917 091700: Test OK @

Nucleus Name	DS_BE_RadialOff
Nucleus Number	918
Description	Open the radial loop
User Input	None
Example	DS:> 918 091800: Test OK @

Nucleus Name	DS_BE_RadialCalibration
Nucleus Number	919
Description	Calibrate the radial loop
User Input	A formatted DVD must be loaded into the engine before executing this nucleus
Example	DS:> 919 091900: Test OK @

Nucleus Name	DS_BE_Tilt
Nucleus Number	920
Description	Test the tilt mechanism control loop, or allow its proper functioning to be measured. Before executing this nucleus a disc must be loaded into the recorder
User Input	None
Example	DS:> 920 092000: Tilt sensor bathtub: (71,-12,145)(68,-12,135)(62,-10,120)(56,-92,97)(50,-75,86) (44,-59,80)(41,-52,80)(35,-37,86)(29,-22,86) (23,-7,92)(17,8,111)(11,23,135)(8,31,138)(5,39,158) Test OK @

Nucleus Name	DS_BE_CheckDisc
Nucleus Number	921
Description	Check whether there is a disc inside the BE
User Input	None
Example	DS:> 921 092100: A DVD+Rewritable is loaded (disc is empty or partially recorded) Test OK @ DS:> 921 092100: No Disc is loaded Test OK @

Nucleus Name	DS_BE_SledgeMotor
Nucleus Number	922
Description	Send the sledge to its home position, then to the middle of the disc, and then to the end.
User Input	None
Example	DS:> 922 092200: Test OK @

Nucleus Name	DS_BE_ReadTocInfo
Nucleus Number	924
Description	Read the TOC from the disc. This gives a good indication if the BE works properly..
User Input	None
Example	DS:> 924 092400: TOC info [hex] = 91 3A 0C Test OK@ DS:> 924 092403: The BE returned: 0x10 #{no_disc_error} No disc is detected Error@ DS:> 924 092403: The BE returned: 0x1e #{illegal_medium_error} Engine unable to handle current disc. Probably illegal medium. Error @

Nucleus Name	DS_BE_DiscErase
Nucleus Number	925
Description	Perform a DC-erase on a DVD+RW disc.
User Input	None

Example	DS:> 925 The entire disc will be erased. Are you sure you want this?[y/n] 092500: Test OK @
---------	---

Nucleus Name	DS_BE_RegionCodeSet
Nucleus Number	928
Description	Set the region code in the AV3.
User Input	Region code
Example	DS:> 928 1 092800: Test OK @ DS:> 928 This nucleus is not supported by the engine 092800: Test OK @

Nucleus Name	DS_BE_RegionCodeGet
Nucleus Number	929
Description	Read the region code from the AV3.
User Input	None
Example	DS:> 929 092900: DVD region 1 Test OK @ DS:> 929 This nucleus is not supported by the engine 092900: Test OK @

Nucleus Name	DS_BE_RegionCounterReset
Nucleus Number	930
Description	Reset the region counter in the AV3.
User Input	None
Example	DS:> 930 093000: Test OK @ DS:> 930 This nucleus is not supported by the engine 093000: Test OK @

Display and Control Board (DCB)

Nucleus Name	DS_DCB_CommunicationEcho
Nucleus Number	1000
Description	Check the communication between the digital board and the DCB by issuing an echo command
User Input	None
Example	DS:> 1000 100000: Test OK @

Nucleus Name	DS_DCB_VersionGet
Nucleus Number	1001
Description	Get the version of the DCB
User Input	None
Example	DS:> 1001 100100: DCB version: 13 Test OK @

Nucleus Name	DS_DCB_LightDisplay
Nucleus Number	1002
Description	Light the entire display of the DCB, and clear the display after confirmation. User confirmation is necessary.
User Input	None

Example	DS:> 1002 100200: Test OK @
---------	-----------------------------------

Nucleus Name	DS_DCB_Keyboard	
Nucleus Number	1004	
Description	Check all keys of the keyboard by confirming the key-code displayed of each key.	
User Input	None	
Example	DS:> 1004 100400: Test OK @	

Nucleus Name	DS_DCB_RemoteControl	
Nucleus Number	1005	
Description	Check the interface between the remote control and the DCB by checking the key-code displayed	
User Input	None	
Example	DS:> 1005 100500: Test OK @	

Nucleus Name	DS_DCB_Led	
Nucleus Number	1006	
Description	Switch the record LED on, and after confirmation off. The user confirms by pressing the REC key, STOP key, or the PLAY key on the local keyboard. The PLAY key confirms that the LED is on and the REC key	
User Input	None	
Example	DS:> 1006 100600: Test OK @	

Analogue Board (ANAB)

Nucleus Name	DS_ANAB_CommunicationEcho	
Nucleus Number	1100	
Description	Check the communication between the digital board and the analogue board by issuing some echo string.	
User Input	None	
Example	DS:> 1100 110000: Hello Analogue Board Test OK @	

Nucleus Name	DS_ANAB_CommunicationIICNvram	
Nucleus Number	1101	
Description	Check the communication between the digital board and the NVRAM on the analogue board.	
User Input	None	
Example	DS:> 1101 110100: Test OK @	

Nucleus Name	DS_ANAB_CommunicationIICTuner	
Nucleus Number	1102	
Description	Check the communication between the digital board and the tuner on the analogue board	
User Input	None	
Example	DS:> 1102 110200: Test OK @	

Nucleus Name	DS_ANAB_CommunicationIICDataSlicer	
Nucleus Number	1103	
Description	Check the communication between the digital board and the data slicer on the analogue board	
User Input	None	

Example	DS:> 1103 110300: Test OK @
---------	-----------------------------------

Nucleus Name	DS_ANAB_CommunicationIcSoundProcessor
Nucleus Number	1104
Description	Check the communication between the digital board and the sound processor on the analogue board
User Input	None
Example	DS:> 1104 110400: Test OK @

Nucleus Name	DS_ANAB_CommunicationIcAVSelector
Nucleus Number	1105
Description	Check the communication between the digital board and the A/V-selector on the analogue board
User Input	None
Example	DS:> 1105 110500: Test OK @

Nucleus Name	DS_ANAB_HardwareVersionGet
Nucleus Number	1106
Description	Get the hardware version of the analogue board
User Input	None
Example	DS:> 1106 110600: Analogue hardware version : 11 Test OK @

Nucleus Name	DS_ANAB_SoftwareVersionBootGet
Nucleus Number	1107
Description	Get the software version of the boot software of the analogue board
User Input	None
Example	DS:> 1107 110700: Bootcode application version : 11.00.11 Test OK @

Nucleus Name	DS_ANAB_SoftwareVersionDownloadGet
Nucleus Number	1108
Description	Get the software version of the download software of the analogue board
User Input	None
Example	DS:> 1108 110800: Download application version : 11.00.06 Test OK @

Nucleus Name	DS_ANAB_SoftwareVersionApplGet
Nucleus Number	1109
Description	Get the software version of the application software of the analogue board
User Input	None
Example	DS:> 1109 110900: Recorder application version : 11.00.23 Test OK @

Nucleus Name	DS_ANAB_SoftwareVersionDiagnosticsGet
Nucleus Number	1110
Description	Get the software version of the diagnostic software of the analogue board
User Input	None
Example	DS:> 1110 111000: Diagnostics application version : 11.00.13 Test OK @

Nucleus Name	DS_ANAB_ChecksumProgram
Nucleus Number	1111

Description	Check the checksum of the several partitions by recalculating and comparing partition checksums
User Input	None
Example	DS:> 1111 BootCode checksum is: 0xBABE6240, which is correct Diagnostics checksum is : 0xBABEBEAD, which is correct Download checksum is: 0xBABEA6B7, which is correct Application checksum is : 0xBABEB277, which is correct 111100: Test OK @

Nucleus Name	DS_ANAB_VideoRouting
Nucleus Number	1112
Description	Perform the routing of the video paths on the analogue board
User Input	The user has to input the correct parameter for the routing (see table 'video routing' below).
Example	DS:> 1112 00 111200: Test OK @

Video routing paths (Europe)

Path ID	Description
0	Input signal is VIDEO(CVBS) from digital board and will be re-routed back to the digital board.
1	Input signal is from FRONT VIDEO(CVBS) IN and will be routed to the digital board.
2	No Routing.
3	Input signal is from FRONT S-VIDEO(Y/C) and will be routed to the digital board.
4	No Routing.
5	Input signal is CVBS from SCART1 and will be routed to the digital board.
6	Input signal is CVBS from SCART2 and will be routed to the digital board.
7	Input Signal is CVBS from Digital Board and it will be routed to Scart1 and Scart2.
8	Input signal is VIDEO(CVBS) from ANTENNA IN and will be routed to SCART2.
9	Input signal is VIDEO(CVBS) from SCART1 and will be routed to SCART2.
10	Input signal is VIDEO(CVBS) from SCART2 and will be routed to SCART1.
11	Signal path is routed Fast Blank from Scart2 pin16 and will be routed SCART1 pin16
12	Input Signal is YC from Digital Board and it will be routed to SCART1.
13	
14	No Routing.
15	Input Signal is CVBS from TUNER and it will be routed to Digital .
16	No Routing.
17	Input Signal is routed from digital board YC to REAR S-VIDEO(YC) OUT
18	Signal path is routed from digital board RGB to RGB SCART1 and from digital board CVBS to digital board CVBS.
19	No Routing.
20	Input RGB Signal is routed from Digital Board to SCART1(RGB), Input CVBS Signal from Digital Board to Digital Board and Fast Blanking Signal from SCART2 to SCART1.
21	Input Y/C Signal from Digital Board is routed to Rear Y/C Connector and Input Y/C Signal from Front Y/C connector is routed to Digital Board.

Video routing paths (NAFTA)

Path ID	Description
0	No Routing.
1	Input signal is from FRONT VIDEO(CVBS) IN and will be routed to the digital board. This routing is same as the above path id.
2	Input signal is from REAR VIDEO(CVBS) IN and will be routed to the digital board.
3	Input signal is from FRONT S-VIDEO(Y/C) IN and the signal received will be routed to the digital board.
4	Input signal is from REAR S-VIDEO(Y/C) IN and will be routed to the digital board.
5	No Routing.
6	No routing.
7	No routing.
8	Input signal is VIDEO(CVBS) from TUNER and will be routed to Y Pin of Rear Y/C Connector. This will give only black/White Picture .
9	Input signal is from YUV IN and will be routed to YUV OUT. This is possible only if Digital Board routes back YUV signal received back to the Analogue board(DENC)

10	No routing.
11	No routing.
12	No Routing.
13	No Routing.
14	No Routing.
15	Input CVBS Signal from Tuner is routed to Digital Board..
16	No Routing.
17	No Routing.
18	Input Signal from CVBS Rear In is routed to Digital Board. This is the same as path ID 02.
19	Input Y/C signal from Digital Board is routed to Y/C Rear Out Connector and Input signal from Y/C Front In Connector is routed to Y/C Digital Board.
20	Y/C signal from Digital Board is routed to Y/C Rear Out Connector and Input signal from Y/C Rear In Connector is routed to Y/C Digital Board.
23	The Video signal received from the Digital board will be output on Modulator channel 3.
24	The Video signal received from the Digital board will be output on Modulator channel 4.

Nucleus Name	DS_ANAB_AudioRouting
Nucleus Number	1113
Description	Perform the routing of the audio paths on the analogue board
User Input	The user has to input the correct parameter for the routing (see table 'audio routing' below)
Example	DS:> 1113 00 111300: Test OK @

Audio routing paths (Europe)

Path ID	Description
0	Input signal is from FRONT AUDIO IN and will be routed to the digital board.
1	Input signal is from FRONT AUDIO IN and will be routed to the digital board.
2	No Routing.
3	Input signal is AUDIO from SCART1 and will be routed to the digital board.
4	Input signal is AUDIO from SCART2 and will be routed to the digital board.
5	No routing.
6	No routing.
7	Input Audio signal is from the digital Board and it will be routed to the SCART1 and SCART2
8	Input AUDIO signal from TUNER and will be routed to SCART2.
9	Input signal is AUDIO from SCART1 and will be routed to SCART2.
10	Input audio signal from SCART2 is routed to SCART1.
11	Input Audio signal is routed from DVIO to SCART2.
12	
13	No Routing.
14	Input is Audio Signal from DVIO and it will be routed to Digital Board.
15	Input is Audio Signal from TUNER and it will be routed to Digital Board..
16	No routing.
17	No Routing.
18	Input signal is from FRONT AUDIO IN and will be routed to SCART2.
21	Input signal is from FRONT AUDIO IN and will be routed to the digital board.

Audio routing paths (NAFTA)

Path ID	Description
0	No Routing.
1	Input signal is from FRONT AUDIO IN and will be routed to the digital board.
2	Input signal is from REAR AUDIO IN 2 and will be routed to the digital board.
3	Input Audio Signal is routed from FRONT Cinch In to Digital Board.(This is same as path ID 01)
4	Input Signal is from Rear Cinch In1 and it will be routed to Digital Board..
5	No routing.
6	No routing.
7	No routing.
8	No Routing.
9	No routing.
10	No Routing.
11	No Routing.
12	No Routing.

13	Input Signal is from Digital Board and it will be routed to the digital board.
14	No routing.
15	Input is Audio Signal from TUNER and it will be routed to Digital Board.
16	Input signal is AUDIO from dvio board and will be routed to Digital Board.
17	No routing.
18	No routing.
19	No routing.
20	Input signal is from REAR AUDIO IN 2 and will be routed to the digital board.
21	Input signal is from REAR AUDIO IN 1 and will be routed to the digital board.
22	Input signal is from REAR AUDIO IN 1 and will be routed to the digital board.
23	The Audio signal received from the Digital board will be outputted on Modulator channel 3.
24	The Audio signal received from the Digital board will be outputted on Modulator channel 4.

Nucleus Name	DS_ANAB_SelectTunerChannel																									
Nucleus Number	1114																									
Description	Set the tuner to receive a valid audio and video signal																									
User Input	<p><Frequency*16> <video standard id> Tuner frequency: to tune the tuner to e.g. 216 MHz, this parameter must be 3456. (Since $216 \times 16 = 3456$. This is to avoid the decimal points to the parameter list.) Video standard id: The table below shows which video standards are possible</p> <table> <tr> <th>Video standard id</th><th>Europe</th><th>NAFTA</th></tr> <tr> <td>16</td><td>PAL_BG</td><td>NTSC</td></tr> <tr> <td>32</td><td>PAL_I</td><td>Invalid</td></tr> <tr> <td>48</td><td>PAL_DK</td><td>Invalid</td></tr> <tr> <td>64</td><td>SEC_L</td><td>Invalid</td></tr> <tr> <td>80</td><td>SEC_LS</td><td>Invalid</td></tr> <tr> <td>96</td><td>SEC_BG</td><td>Invalid</td></tr> <tr> <td>112</td><td>SEC_DK</td><td>Invalid</td></tr> </table>		Video standard id	Europe	NAFTA	16	PAL_BG	NTSC	32	PAL_I	Invalid	48	PAL_DK	Invalid	64	SEC_L	Invalid	80	SEC_LS	Invalid	96	SEC_BG	Invalid	112	SEC_DK	Invalid
Video standard id	Europe	NAFTA																								
16	PAL_BG	NTSC																								
32	PAL_I	Invalid																								
48	PAL_DK	Invalid																								
64	SEC_L	Invalid																								
80	SEC_LS	Invalid																								
96	SEC_BG	Invalid																								
112	SEC_DK	Invalid																								
Example	DS:> 1114 3456 16 111400: Test OK @																									

Nucleus Name	DS_ANAB_IICWriteRead	
Nucleus Number	1115	
Description	Perform an IIC write and read action on the analogue board	
User Input	Writing: [<W> <w>] [I2C address] [number of data bytes to write] with <data[0]...data[n]> Max 16 data bytes (n < 16). Reading: [<R> <r>] [I2C address] [number of data bytes to read] Max 16 data bytes (n < 16).	
Example	DS:> 1115 w 0x94 2 0x06 0x02 111500: Test OK @	

Nucleus Name	DS_ANAB_ClockAdjust	
Nucleus Number	1116	
Description	Set the clock to the value passed through in the YYYY MM DD HH MM SS format	
User Input	<YYYY> <MM> <DD> <HH> <MM> <SS>	
Example	DS:> 1116 2002 11 11 11 11 111600: Test OK @	

Nucleus Name	DS_ANAB_ClockReference	
Nucleus Number	1117	
Description	Generate a 1 kHz signal on pin 7 (INT) of the clock IC	
User Input	None	
Example	DS:> 1117 111700: Test OK @	

Nucleus Name	DS_ANAB_ClockCorrection	
Nucleus Number	1118	

Description	Store the clock IC correction value in NVRAM
User Input	The correction value for the clock
Example	DS:> 1118 1000023 111800: Test OK @

Nucleus Name	DS_ANAB_TunerAFCReferenceVoltage
Nucleus Number	1119
Description	Store the reference voltage for the tuner in NVRAM
User Input	The reference voltage, between 0 and 255
Example	DS:> 1119 5 111900: Test OK @

Nucleus Name	DS_ANAB_TunerFrequencyDownload
Nucleus Number	1120
Description	Store the frequency table in NVRAM. The frequency table is passed through the error-string provided to the nucleus.
User Input	See frequency table
Example	DS:> 1120 2233 00 02 4E45442031 112000: Test OK @

Frequency download string format

Format	description	remarks
X(XXX)	Preset number	
VVWW	VV: Channel number WW : Channel offset	
ZZ	Byte containing 8 bit fields for TRUE/FALSE : BIT 0: Decoder BIT 1: Modulation BIT 2: NICAM SAP BIT 3: Satpreset BIT 4: Presetdefined Channelpreferred BIT 5: ExtPreset BIT 6: NameManuallyChanged BIT 7: ChannelPreset	NICAM/stereo bit for Europe SAP/stereo bit for NAFTA Preset defined bit is only used for Europe. For NAFTA, it is renamed as channelpreferred to indicate if a channel is preferred or not. TRUE if preset is defined from P50 as extern [TGA]
HH	HfSystemFineTuning	HfS: 4 bit, FT: -4,...,4
IJJKKLLMM	Netname	Range: A,...,Z,0,...,9,... Netname length exists for Europe only. 'II' is the HEX-value for the first character, 'JJ' for the second, Ö

The message string of (DS_MessageDef *msgString) should be in the format:

"X(XXX)_VVWW_ZZ_HH_IJJKKLLMM".

Here will be 'X(XXX)' a decimal value in the range of 0 to 255.

V, W, Z, H, I, J, K, L, M are hex values with out the prefix '0x' (in the range 0... 9,A ... F)

"_" Denotes a space character.

Remarks:

CHANNEL_SYSTEM is for NAFTA.

PRESET_SYSTEM is for Europe.

Nucleus Name	DS_ANAB_StoreExternalPresets
Nucleus Number	1121
Description	Store the external presets in NVRAM
User Input	None
Example	DS:> 1121 112100: Test OK @

Nucleus Name	DS_ANAB_BargraphLevelAdjust
Nucleus Number	1122
Description	Measure the audio signal corresponding to 0dB per channel and store it as correction value in NVRAM

User Input	none
Example	DS:> 1122 112200: Test OK @

System (SYS)

Nucleus Name	DS_SYS_HardwareVersionGet	
Nucleus Number	1200	
Description	Get the hardware version and type of the digital board	
User Input	None	
Example	DS:> 1200 120000: Hardware ID = 00 The (PIO-pins) Digital Board ID = 2 Test OK @ DS:>	

Nucleus Name	DS_SYS_SoftwareVersionBootGet	
Nucleus Number	1201	
Description	Get the version of the boot software on the digital board	
User Input	None	
Example	DS:> 1201 120100: Software Boot Version = 0001 Test OK @	

Nucleus Name	DS_SYS_SoftwareVersionDownloadGet	
Nucleus Number	1202	
Description	Get the version of the download software on the digital board	
User Input	None	
Example	DS:> 1202 120200: Software Download Version = 0001 Test OK @	

Nucleus Name	DS_SYS_SoftwareVersionApplGet	
Nucleus Number	1203	
Description	Get the version of the application software on the digital board	
User Input	None	
Example	DS:> 1203 120300: Software Application Version = 0001 Test OK @	

Nucleus Name	DS_SYS_SoftwareVersionDiagnosticsGet	
Nucleus Number	1204	
Description	Get the version of the diagnostics software on the digital board	
User Input	None	
Example	DS:> 1204 120400: Software Diagnostics Version = 0001 Test OK @	
	120503	Something went wrong while transferring the data.
	120504	User cancelled the upload.
Example	DS:> 1205 1 120500: Test OK @	

Nucleus Name	DS_SYS_EepromUpload	
Nucleus Number	1205	
Description	Upload the contents of the NVRAM on the analogue board or the digital board to the service PC, by using the X-modem protocol	
User Input	Choose one of the following parameters for the nucleus: 1. Upload the contents of the NVRAM of the digital board 2. Upload the contents of the NVRAM of the analogue board Choose in the terminal on the control PC -> transfer -> receive file. Select X-modem protocol. Then click receive in the dialogue and fill in the file name in which you want to store the data.	

Nucleus Name	DS_SYS_EepromDownload
Nucleus Number	1206
Description	Download a file with the contents of the NVRAM for the analogue board or the digital board from the service PC to the recorder, by using the X-modem protocol
User Input	Choose one of the following parameters for the nucleus: 1. Download the contents of the NVRAM of the digital board 2. Download the contents of the NVRAM of the analogue board Choose in the terminal of the control PC -> transfer -> send file. Select X-modem protocol. Then choose a file with the Browse button in the dialogue and click on send.
Example	DS:> 1206 1 120600: Test OK @

Nucleus Name	DS_SYS_DvIdNumberGet
Nucleus Number	1208
Description	Get the IEEE1394 ID
User Input	None
Example	DS:> 1208 120800: The DvIdNumber is: 0x0C22384E5A Test OK @

Nucleus Name	DS_SYS_licWrite
Nucleus Number	1209
Description	Perform an IIC write action on the digital board
User Input	The user input the number of bytes to write followed by these bytes: <BusID><Slave address to write to><number of bytes to write><d1><d2><...><dx> Where the bus ID is either 0 (normally used) or 1
Example	DS:> 1209 0 0xa0 1 0x6 120900: 1 Bytes written Test OK @

Nucleus Name	DS_SYS_licRead
Nucleus Number	1210
Description	Perform an IIC read action on the digital board
User Input	The user inputs the number of bytes to read and the address to read them from: <BusID><Slave address to read from><Number of bytes to read> Where the bus ID is either 0 (normally used) or 1
Example	DS:> 1210 0 0xa0 1 121000: Value read =0x06 Test OK @

Nucleus Name	DS_SYS_UartWrite
Nucleus Number	1211
Description	Perform an UART write action on the digital board on a specified UART
User Input	The user inputs the UART to write to, the number of bytes and the bytes to be written to the UART. 1=UART port 1 : not used 2=UART port 2 : Bit Engine 3=UART port 3 : Analogue board <UartNr><Number of bytes to write><d1><d2><...><dx>
Example	DS:> 1211 2 2 0xd1 0x01 121100: Test OK @

Nucleus Name	DS_SYS_UartRead
Nucleus Number	1212
Description	Perform an UART read action on the digital board on a specified UART
User Input	The user inputs the UART to read from. 1=UART port 1 : not used 2=UART port 2 : Bit Engine 3=UART port 3 : Analogue board <UartNr >
Example	DS:> 1212 2 121200: The value that was read is: 0x50 0xD1 0x00 Test OK @

Nucleus Name	DS_SYS_VideoLoopThroughStart
Nucleus Number	1213
Description	The video signal, which is confirm the user input, is routed from the input to the output. Input is set with the routing nucleus 1112. All outputs are enabled.
User Input	<viplInput> <VideoOutput> <VideoStandard> 1. viplInput (CVBS, YC, YUV, RGB). 2. VideoOutput (YUV, RGB). 3. VideoStandard (PAL, NTSC).
Example	DS:> 1213 CVBS RGB PAL 121300: Test OK @

Nucleus Name	DS_SYS_VideoLoopThroughStop
Nucleus Number	1214
Description	Stop routing the video input to all the outputs.
User Input	-
Example	DS:> 1214 121400: Test OK @

Nucleus Name	DS_SYS_VideoLoop
Nucleus Number	1215
Description	Note: Before executing this nucleus the user must route the video signal on the analog board with nucleus DS_ANAB_VideoRouting(1112).
User Input	Video input of the digital board: - CVBS - YC - YUV - RGB - TEST (The video output will be routed to the video input on the digital board.) Video standard: - PAL - NTSC When no input is given, the nucleus will take TEST for video input and PAL for video standard.
Example	DS:> 1215 cvbs ntsc 121500: Test OK @ DS:> 1215 cvbs pal 121508: The VideoInputProcessor cannot detect a sync-signal. Error @ DS:> 1215 yuv ntsc 121511: Error in luminance signal(Y) Error in chrominance signal(U) Error in chrominance signal(V) Error @

Nucleus Name	DS_SYS_SlashVersionSet
Nucleus Number	1217
Description	Set the slash version of the system
User Input	The slash version
Example	DS:> 1217 82 121700: Test OK @

Nucleus Name	DS_SYS_SlashVersionGet
Nucleus Number	1218
Description	Get the slash version of the system
User Input	None
Example	DS:> 1218 121800: The slash version is: 82 Test OK @

Nucleus Name	DS_SYS_Virginize
Nucleus Number	1219

Description	(Re-) Virginize the recorder. User data in the NVRAM of the analogue board is cleared
Example	DS:> 1219 121900: Test OK @

Nucleus Name	DS_SYS_VirginModeOn
Nucleus Number	1220
Description	Turn on the virgin mode functionality (e.g. the auto channel search upon start-up)
User Input	None
Example	DS:> 1220 122000: Test OK @

Nucleus Name	DS_SYS_VirginModeOff
Nucleus Number	1221
Description	Turn off the virgin mode functionality (e.g. the auto channel search upon start-up)
User Input	None
Example	DS:> 1221 122100: Test OK @

Nucleus Name	DS_SYS_DisplayFatalOn
Nucleus Number	1223
Description	Turn on the display-fatal functionality which displays debug-information on the display when encountering a fatal error condition from which could not be recovered automatically
User Input	None
Example	DS:> 1223 122300: Test OK @

Nucleus Name	DS_SYS_DisplayFatalOff
Nucleus Number	1224
Description	Turn off the display-fatal functionality which displays debug-information on the display when encountering a fatal error condition from which could not be recovered automatically
User Input	None
Example	DS:> 1224 122400: Test OK @

Nucleus Name	DS_SYS_DisplayFatalGet
Nucleus Number	1225
Description	Get the display-fatal flag of the recorder
User Input	None
Example	DS:> 1225 122500: Test OK @

Nucleus Name	DS_SYS_SettingsSet
Nucleus Number	1226
Description	Programs the digital board settings into the boot EEPROM on the digital board.
User Input	A large hexadecimal value that represents the digital board settings obtained from the DbString.exe program or from a reference set.
Example	DS:> 1226 6469616774737462010102000101010101000020080000 122600: Test OK @

Nucleus Name	DS_SYS_SettingsDisplay
Nucleus Number	1228
Description	Show the settings that are programmed in the BROM on the digital board.
User Input	None.

Example	DS:> 1228 Settings ID: 6D7920626F61726400020300010101020101000020080000 Board name: my board Hardware ID: 0 Codec IC: PNX7100_MF2 Video Input Processor IC: SAA7118 Progressive Scan Deinterlacer IC: None Progressive Scan Denc IC: ADV7196 I-Link physical layer circuit IC: PDI1394P25 I-Link link layer circuit IC: PDI1394P40 Audio clock: Clock scheme 1 Bit engine connector: available IDE connector 1: available IDE connector 2: not available PCI connector: not available RAM size 32MByte ROM size (NOR FLASH bank 1) 8MByte ROM size (NOR FLASH bank 2) Not available ROM size (NAND FLASH) Not available Bit Engine: AV 2.0 122800: Test OK @
---------	---

Nucleus Name	DS_SYS_SettingsGet
Nucleus Number	1229
Description	Get the digital board diversity settings string that is programmed in the BROM on the digital board.
User Input	None.
Example	DS:> 1229 122900: 6D7920626F61726400020300010101020101000020080000 Test OK @

Nucleus Name	DS_SYS_AudioLoopThroughStart
Nucleus Number	1230
Description	Description: The audio input is routed from the an input to all outputs. Input is set with the routing nucleus 1113. All outputs are enabled.
User Input	None.
Example	DS:> 1230 123000: Test OK @

Nucleus Name	DS_SYS_AudioLoopThroughStop
Nucleus Number	1231
Description	Stop routing the audio input to all the outputs
User Input	-
Example	DS:> 1231 123100: Test OK @

Electronic Program Guide Board (EPGB)

Nucleus Name	DS_EPGB_VersionGet
Nucleus Number	1300
Description	Returns the version of the EPG board.
User Input	None
Example	DS:> 1300 130000: Version : 6.1.9 Test OK @

PCMCIA INTERFACE (PCMCIA)

Nucleus Name	DS_PCMCIA_Reset
Nucleus Number	1400
Description	Reset the PCMCIA device by sending a reset command through IDE
Example	DS:> 1400 140000: Test OK @

Nucleus Name	DS_PCMCIA_Inquiry
Nucleus Number	1401
Description	Get the vendor- and product identification and the product revision level of the media in the slot.
Example	DS:> 1401 140100: Test OK @

Nucleus Name	DS_PCMCIA_WriteRead
Nucleus Number	1402
Description	Perform a Write Read test to a random sector on the inserted medium in the PCMCIA device and check if the data read is equal to the data written.
Example	DS:> 1402 140200: Test OK @

Nucleus Name	DS_PCMCIA_Diagnostics
Nucleus Number	1403
Description	Shall perform the internal diagnostic tests implemented by the media in the slot.
Example	DS:> 1403 140300: Test OK @

Script

Nucleus Name	DS_IH_ScriptHandler
Nucleus Number	Script
Description	
Included tests:	<ol style="list-style-type: none"> 1. DS_ANAB_COMMUNICATIONECHO_NUC 2. DS_DCB_COMMUNICATIONECHO_NUC 3. DS_BROM_COMMUNICATION_NUC 4. DS_SYS_SETTINGSDISPLAY_NUC 5. DS_CHR_DEVTYPEGET_NUC 6. DS_CHR_INT_PIC_NUC 7. DS_CHR_DMA_NUC 8. DS_BROM_WRITEREAD_NUC 9. DS_NVRAM_COMMUNICATION_NUC 10. DS_NVRAM_WRITEREAD_NUC 11. DS_SDRAM_WRITEREADFAST_NUC 12. DS_FLASH_WRITEREAD_NUC 13. DS_FLASH_CHECKSUMPROGRAM_NUC 14. DS_SYS_HARDWAREVERSIONGET_NUC 15. DS_VIP_DEVTYPEGET_NUC 16. DS_VIP_COMMUNICATION_NUC 17. DS_DVIO_LINKDEVTYPEGET_NUC 18. DS_DVIO_PHYDEVTYPEGET_NUC 19. DS_DVIO_LINKCOMMUNICATION_NUC 20. DS_DVIO_PHYCOMMUNICATION_NUC 21. DS_PSCAN_COMMUNICATIONDENC_NUC 22. DS_PSCAN_COMMUNICATIONDEINTERLACER_NUC 23. DS_BE_COMMUNICATIONECHO_NUC 24. DS_ANAB_COMMUNICATIONIICNVRAM_NUC 25. DS_ANAB_COMMUNICATIONIICTUNER_NUC 26. DS_ANAB_COMMUNICATIONIICSOUNDPROCESSOR_NUC 27. DS_ANAB_COMMUNICATIONIICAVSELECTOR_NUC 28. DS_ANAB_CHECKSUMPROGRAM_NUC
User Input	None

Example	<pre> DS:> script Executing User/Dealer script. Busy executing NUC1100 1-28 Hello Analogue Board Busy executing NUC1000 2-28 Busy executing NUC200 3-28 Busy executing NUC1228 4-28 Settings ID: 4C4541440D00000000030300010101020101000020080000 Board name: LEAD Hardware ID: 0 Codec IC: PNX7100_MF3 Video Input Processor IC: SAA7118 Progressive Scan Deinterlacer IC: None Progressive Scan Denc IC: ADV7196 I-Link physical layer circuit IC: PDI1394P25 I-Link link layer circuit IC: PDI1394P40 Audio clock: Clock scheme 1 Bit engine connector: available IDE connector 1: available IDE connector 2: not available PCI connector: not available RAM size 32MByte ROM size (NOR FLASH bank 1) 8MByte ROM size (NOR FLASH bank 2) Not available ROM size (NAND FLASH) Not available Bit Engine: AV 2.0 Busy executing NUC100 5-28 Device ID 7100 Codec ID PNX7100_MF3 F-BCU (0x0102) 1.0 INTC (0x011d) 1.0 PCI-XIO(0x0113) 1.0 SIF (0x013b) 1.0 EJTAG (0x0104) 0.0 S-BCU (0x0102) 1.0 BOOT (0x010a) 1.0 CONFIG (0x013f) 1.0 RESET (0x0123) 1.0 DEBUG (0x0116) 0.0 UART0 (0x0107) 0.1 UART1 (0x0107) 0.1 UART2 (0x0107) 0.1 UART3 (0x0107) 0.1 I2C0 (0x0105) 0.1 I2C1 (0x0105) 0.1 GPIO (0x013c) 1.0 SYNC (0x013a) 1.0 DISP0 (0xa015) 0.2 DISP1 (0xa00f) 0.0 OSD (0x0136) 0.1 SPU (0xa00e) 0.0 MIXER (0x0137) 1.0 DENC (0x0138) 0.1 CCIR (0x0139) 1.0 VDEC (0x0133) 0.1 PARSER (0xa00d) 0.0 DV (0xa00c) 0.0 BEI (0xa00a) 0.0 IDE (0xa009) 0.0 SGDX (0xa008) 0.0 BYTE (0xa00b) 0.0 OUTPUT (0xa003) 0.0 ACOMP (0xa000) 0.0 VFE (0xa001) 0.0 VCOMP (0xa002) 0.0 SCR (0x0000) 0.0 SIFF (0xa011) 0.0 WMD (0xa010) 0.0 AUDIO0 (0xa015) 0.2 AUDIO1 (0xa00f) 0.0 PSCAN (0xa018) 0.0 Busy executing NUC114 6-28 Busy executing NUC115 7-28 Busy executing NUC201 8-28 Busy executing NUC300 9-28 Busy executing NUC301 10-28 Busy executing NUC401 11-28 Busy executing NUC501 12-28 Busy executing NUC503 13-28 BootCode checksum is: 0xBABEB432, which is correct Diagnostics checksum is: 0xBABED22B, which is correct Download checksum is: 0xBABE025F, which is correct Application checksum is: 0xBABE2825, which is correct Busy executing NUC1200 14-28 Hardware ID = 00 Busy executing NUC600 15-28 Found SAA7118 </pre>
---------	--

Example	Busy executing NUC601 16-28 Busy executing NUC700 17-28 Device type of the link layer IC: ffc00301 Busy executing NUC701 18-28 Device type of the phy layer IC: 0 Busy executing NUC702 19-28 Busy executing NUC703 20-28 Busy executing NUC801 21-28 Busy executing NUC808 22-28 The IIC acknowledge was not received, which is correct Busy executing NUC900 23-28 Busy executing NUC1101 24-28 Busy executing NUC1102 25-28 Busy executing NUC1104 26-28 Busy executing NUC1105 27-28 Busy executing NUC1111 28-28 BootCode checksum is: 0xBABE6240, which is correct Diagnostics checksum is: 0xBABEDC9A, which is correct Download checksum is: 0xBABEA6B7, which is correct Application checksum is: 0xBABE5968, which is correct PASS DS:>
---------	--

5.3.4 Menu Mode Interface Digital Board 1.5, Empress

Activation

Plug the recorder to the mains and the following text will appear on the screen of the terminal (program):

```

DVD Video Recorder Diagnostic Software version 48
Basic SDRAM Data bus test passed
Basic SDRAM Address bus test passed
Basic SDRAM Device test passed

(M) enu, (C) ommand or (S) 2B-interface? [M] : @ M ↵

Main Menu

1. Digital Board      ->
2. Analogue Board    ->
3. Front Panel       ->
4. Basic Engine      ->
5. DVIO              ->
6. Progressive Scan Board ->
7. Loop tests        ->
8. Log               ->
9. Scripts           ->

Select>
  
```

Figure 5-12

The first line indicates that the Diagnostic software has been activated and contains the version number. The next lines are the successful result of the SDRAM interconnection test and the basic SDRAM test. The last line allows the user to choose between the three possible interface forms. If pressing M has made a choice for Menu Interface, the Main Menu will appear.


5.4 Nuclei Error Codes

DVIO 1.8 Error Codes



Error Code	Id	Description	Hardware
0	0x00	DVIOC_ERR_DDS_OK	No Error
6	0x06	DVIOC_ERR_DDS_UNKNOWN	Unknown Error(including UART communication error)
17	0x11	DVIOC_ERR_DDS_TNF_1	Link chip incorrect responding
18	0x12	DVIOC_ERR_DDS_TNF_2	No link register access or link reset failed
23	0x17	DVIOC_ERR_DDS_TNF_7	Link reset failed
38	0x26	DVIOC_ERR_DDS_TNF_16	Expecting no 1394 node with GUID connectivity, while detecting connection
39	0x27	DVIOC_ERR_DDS_TNF_17	Expecting 1394 node with GUID connectivity, while not detecting connection
48	0x30	DVIOC_ERR_DDS_UPINTRAM A	Internal ram problem in address lines
50	0x32	DVIOC_ERR_DDS_UPEXTRA MA	External ram problem in address lines
51	0x33	DVIOC_ERR_DDS_UPEXTRA MD	External ram problem in data lines
58	0x3A	DVIOC_ERR_DDS_ROMCHK	Checksum of codespace 0x0000-0x1f80, 0x2000-0xeffd is not correct
244	0xF4	DVIOC_ERR_LINK_HWPHY	PHY chip not responding(PHY down report received)
245	0xF5	DVIOC_ERR_LINK_HWLINK	LINK chip not responding

6. Block Diagrams, Waveforms, Wiring Diagram.


Overall Block Diagram Digital Board 1.5 Empress




Overall Block Diagram Digital Board 2.1 Chrysalis



Control Block Diagram Analog Board, uP Board




Wiring Diagram




Waveforms

Waveforms Analog Board

Waveforms Display Board




Waveforms Digital Board 1.5




CL 16532145_053.eps
031201

Waveforms Digital Board 1.5




CL 16532145_054.eps
031201


Waveforms Digital Board 1.5




Waveforms DVIO



Waveforms Digital Board Chrysalis 2.1



Test points overview Analog Board




[illegible]

TR 06058_001
250203

F8001 C3	F831 C1	F8610 C3	I808 A3
F8002 C3	F832 A2	F8701 A1	I809 C1
F8003 C3	F833 C1	F8702 A3	I810 B3
F8004 C3	F834 A1	F8703 A3	I811 A3
F8005 C3	F835 C1	F8704 A3	I812 A2
F8006 C3	F836 C1	F8705 A3	I813 A1
F8007 C2	F837 A2	F8706 A3	I814 B3
F8008 C2	F838 A2	F8707 A3	I815 A3
F801 A3	F839 C2	F8708 A3	I816 A1
F802 A2	F840 A2	F8802 C2	I817 C1
F803 A1	F8401 A2	F8803 C2	I818 B1
F804 B3	F8402 A2	F8804 C2	I819 C1
F805 B3	F8403 A2	F8805 C2	I820 C1
F807 B3	F8406 A2	F8806 C2	I821 B3
F812 C2	F8407 A1	F8807 C2	I822 B3
F813 C2	F841 C2	F8808 C1	I823 A2
F814 C2	F842 C2	F901 A1	I824 A2
F815 C2	F843 B1	F902 A3	I825 C2
F816 C2	F844 A2	F903 A1	I903 B1
F817 C1	F845 A2	F904 A1	I904 B1
F818 C1	F846 A1	F905 A2	I905 B1
F819 A3	F847 B1	F906 A1	I906 B1
F820 B3	F848 A3	F907 B1	I907 C1
F821 A3	F849 A3	F908 A1	I908 B1
F822 B3	F850 B3	F909 B1	
F823 A3	F851 B3	F910 B1	
F824 B3	F852 C2	I801 C2	
F825 A3	F8603 C1	I802 C3	
F826 A3	F8604 A3	I803 C2	
F827 A2	F8606 C3	I804 B2	
F828 A2	F8607 C3	I805 A3	
F829 A2	F8608 C3	I806 A3	
F830 A2	F8609 C3	I807 A3	


Test points overview DIVIO Board



F0101 B5	F503 B1	F565 C2
F0102 B5	F504 B2	F566 C3
F0103 B5	F505 B1	F567 C2
F0104 B5	F506 B2	F601 F4
F0106 B5	F507 B1	F603 C4
F0201 E6	F508 B2	F604 F4
F0202 D2	F509 C1	F605 F3
F0203 C2	F510 B2	F606 F3
F0204 C2	F511 B1	F609 E3
F0205 E3	F512 B1	F610 E3
F0301 A2	F513 B1	F611 F3
F0302 A1	F514 B1	F614 F3
F0401 F3	F515 B1	F615 F3
F0402 F1	F516 B1	F616 F3
F0403 F1	F517 C3	F617 G3
F0404 F1	F518 D2	F618 E5
F0405 F1	F519 B2	F619 F2
F0406 F1	F520 B2	F620 G3
F122 B5	F521 C1	F621 F2
F400 C5	F522 B2	F622 F2
F401 C5	F523 C2	F623 F2
F402 B5	F524 C2	F624 F4
F403 C5	F525 B3	F800 F2
F404 C5	F526 B2	F801 F2
F405 C5	F527 B2	F802 B1
F406 C5	F528 C2	F803 B1
F407 C5	F529 B2	F804 E2
F408 C5	F530 C2	F805 F2
F409 B6	F531 C2	F806 D2
F410 B5	F532 C2	F808 F2
F411 B5	F533 C2	F809 E2
F412 A6	F534 C1	F810 G1
F413 C5	F535 C1	F811 E2
F414 C5	F536 B3	F812 F2
F415 C6	F537 C2	F815 D2
F416 C6	F538 E2	F816 E2
F417 C6	F539 C1	F817 E3
F418 C6	F540 A3	F818 E3
F419 C6	F541 A3	F819 E2
F420 C5	F542 A3	F820 E2
F421 B5	F543 A3	F822 E2
F422 B5	F544 B3	F823 E3
F423 B5	F545 B3	F824 E2
F424 B6	F547 C1	F825 E3
F425 B6	F548 B3	F826 E3
F430 D5	F549 C1	F827 E1
F431 E5	F550 C1	F829 E1
F432 E5	F551 B2	F830 E1
F433 D4	F552 B3	F831 F1
F434 C4	F553 A3	F832 F2
F435 D5	F554 B2	F833 G2
F436 B4	F555 B2	F834 G2
F437 G5	F556 B1	F835 G1
F438 E3	F557 C1	F836 E1
F439 C5	F558 B1	F837 F1
F440 D5	F559 C1	F838 F2
F441 C4	F560 D3	F839 G1
F442 E3	F561 C3	
F443 D5	F562 G1	
F501 B2	F563 C2	
F502 B2	F564 C2	

TR03021_001
090802

Test points overview Digital Board 1.5




Layout Digital Board (Mapping Testlands)

F214	A3	I175	A3	I300	A2	I610	A5	I720	B3	I880	C3
F247	A2	I176	A3	I301	A2	I611	B5	I721	B2	I881	C3
F248	A2	I177	A3	I302	A2	I612	A5	I722	B3	I882	C3
F249	A2	I178	A3	I303	B2	I613	B5	I723	B2	I883	C2
F250	A2	I179	A3	I304	B3	I614	A5	I724	B2	I884	C2
F264	A2	I180	A3	I305	B3	I615	B5	I725	B3	I900	B4
F265	A3	I181	A3	I306	A3	I616	A5	I726	B2	I901	B4
F931	A4	I182	B3	I307	B3	I617	A5	I727	B2	I902	B4
F932	A4	I183	A2	I308	A3	I618	C4	I728	A1	I903	B4
F933	A5	I184	A3	I309	B3	I619	A5	I729	A1	I904	B2
F934	A4	I186	A3	I400	A4	I621	A1	I730	A1	I905	A4
F935	A4	I187	A3	I401	A4	I622	A1	I731	A1	I906	A4
I100	A4	I188	A3	I402	B4	I623	A1	I732	B2	I907	A4
I101	C5	I200	A2	I403	A4	I624	A1	I733	B2	I908	A5
I102	C5	I201	B3	I404	B4	I625	A1	I734	B1	I909	B4
I103	B4	I202	A5	I405	B4	I626	A1	I735	B1	I911	B3
I104	B4	I203	A3	I406	B4	I627	B4	I800	C4	I912	A3
I105	B3	I204	C3	I407	A4	I628	C4	I801	C3	I913	B3
I106	B3	I205	A2	I408	A5	I629	A5	I802	C3	I915	B3
I107	B3	I206	A4	I409	A4	I630	C4	I803	C3	I916	B3
I108	B3	I207	A2	I410	A4	I631	C4	I805	C3	I917	B3
I109	B4	I208	B3	I412	B4	I632	C4	I806	C3	I918	A5
I110	B3	I209	B4	I413	A4	I633	B4	I807	C3	I919	B3
I111	A2	I210	A2	I414	B4	I634	C4	I808	C2	I920	B3
I112	B5	I211	A2	I415	B4	I635	C5	I809	C2	I921	A5
I113	B5	I212	A2	I416	B4	I636	C4	I810	C3	I922	A5
I114	B5	I213	A2	I500	C5	I637	C5	I811	C3	I923	B3
I115	B5	I215	B5	I501	C5	I638	C5	I812	C2	I924	A4
I116	C3	I216	A1	I502	C5	I639	C5	I813	C2	I925	B3
I117	C3	I217	A2	I503	C5	I640	C5	I814	C1	I926	A5
I118	C4	I218	A2	I504	C5	I641	B5	I815	B2	I927	A5
I119	C4	I219	A1	I505	C5	I642	A5	I816	B2	I928	A5
I120	A4	I220	A1	I506	C5	I643	A5	I817	B2	I930	B3
I121	A3	I221	B2	I507	C5	I644	A5	I818	C2	I931	A5
I122	B3	I222	B2	I508	C5	I645	B5	I819	C3	I932	B2
I123	A2	I223	A2	I509	C5	I646	C4	I820	C3	I933	B3
I124	B4	I224	A1	I510	B5	I647	A5	I821	C3		
I125	A2	I225	A2	I511	C4	I649	C5	I822	C3		
I126	A3	I226	A2	I512	C5	I650	B4	I823	C3		
I127	A2	I227	A2	I513	B5	I651	B5	I824	B2		
I128	A4	I228	A2	I514	B4	I652	B5	I825	B2		
I129	A2	I229	B5	I515	C5	I653	B5	I826	C3		
I130	B3	I230	A2	I516	C5	I654	B4	I827	C3		
I131	A3	I231	A2	I517	C5	I655	B4	I828	C3		
I132	B1	I232	A2	I518	C4	I656	B5	I829	C3		
I133	A3	I233	A2	I519	C5	I657	C4	I830	C3		
I134	A3	I234	A4	I520	C4	I658	C4	I831	C3		
I136	A3	I235	A4	I521	C4	I659	C3	I832	C3		
I137	A2	I236	B4	I522	C4	I660	B5	I833	C3		
I138	A3	I237	A2	I523	C4	I661	B5	I834	B3		
I140	A3	I238	A2	I524	C4	I662	C5	I835	B3		
I141	A4	I239	B5	I525	C5	I663	B4	I836	B2		
I142	A3	I240	A4	I526	C5	I664	B5	I837	C3		
I143	B4	I241	B2	I527	C5	I665	C4	I838	C3		
I145	A3	I242	B1	I528	C4	I666	C5	I839	C3		
I147	B4	I243	B1	I529	C5	I667	B5	I840	C3		
I149	B3	I244	A2	I530	C5	I668	B4	I841	C3		
I152	B3	I245	A1	I531	C5	I669	B4	I842	C3		
I153	B5	I246	A2	I532	C5	I670	A5	I843	C2		
I154	B3	I251	A1	I533	C4	I671	B5	I844	C2		
I155	B3	I252	A2	I535	C5	I700	B2	I845	C2		
I156	A3	I253	A2	I536	C4	I701	B1	I846	B3		
I157	A3	I254	A1	I537	C5	I702	B1	I847	B2		
I158	B4	I255	A1	I538	C4	I703	C2	I848	B2		
I159	A5	I256	A2	I540	C5	I704	C2	I849	B2		
I160	B3	I257	C5	I543	C5	I705	C2	I850	B2		
I161	B3	I258	A2	I551	C5	I706	C2	I851	B1		
I162	C4	I259	A2	I552	C4	I707	C2	I852	B1		
I163	A3	I260	A1	I553	C4	I708	C2	I868	C2		
I164	B4	I261	A1	I555	C4	I709	C1	I869	C2		
I165	A3	I262	A1	I600	A5	I710	B3	I870	B2		
I166	B4	I263	A1	I601	A5	I711	C2	I871	C3		
I167	A3	I264	A2	I602	A5	I712	C2	I872	C3		
I168	C5	I265	B5	I603	C5	I713	A1	I873	B2		
I169	A3	I266	A2	I604	A5	I714	C2	I874	C2		
I170	A3	I267	A2	I605	A5	I715	C2	I875	C2		
I171	A3	I268	B2	I606	A5	I716	B3	I876	C3		
I172	A3	I269	B2	I607	A5	I717	B3	I877	C2		
I173	A3	I270	A2	I608	A5	I718	B3	I878	C3		
I174	A3	I271	B1	I609	B5	I719	B3	I879	C3		


7. Circuit Diagrams and PWB Layouts

Display Panel




0005 A4	7100 A5
0206 C11	7101 B13
0210 I1	7102 D13
0211 C11	7103 E11
1110 D9	7104 F4
1111 A1	7105 C3
1160 I7	7106 E7
1161 B8	7107 F9
1162 I5	7108 F7
1163 I3	7109 E8
1164 I2	7110 E2
1165 I6	7112 C4
1166 I3	9101 F5
1167 I6	F102 G3
1168 I4	F103 F2
1169 I6	F104 G3
1170 I4	F105 F1
1910 G1	F1402 F2
1911 H1	F1403 F3
2000 I8	F1404 G2
2101 D10	F1405 G1
2102 D10	F1407 G2
2103 I9	F1408 G3
2104 D11	F1409 G2
2105 G3	F1410 G3
2106 G9	F1501 H1
2109 C9	F1502 H1
2110 E6	F1503 H1
2111 E7	F1504 H1
2112 E9	I100 E12
2113 F7	I101 E12
2114 F9	I102 E12
2115 F5	I103 E12
2116 G9	I1401 F1
2117 F6	I105 I12
2118 E13	I106 H12
2119 F13	I107 H12
2120 F13	I108 H12
2121 F13	I109 H12
2122 F13	I110 H12
2123 C13	I111 H12
2124 D13	I112 H12
2125 D13	I113 H12
2126 G13	I114 H12
3100 C13	I115 H12
3101 D13	I116 H12
3102 H8	I117 G12
3103 I6	I118 G12
3104 I7	I119 G12
3105 I7	I120 G12
3106 I7	I121 G12
3107 H9	I122 G12
3108 I4	I123 G12
3109 I2	I124 G12
3110 I4	I125 G12
3111 F3	I126 G12
3112 G10	I127 G12
3113 E6	I128 F12
3114 G4	I129 F12
3115 G3	I130 F12
3116 E7	I131 F12
3117 E9	I132 F12
3118 E8	I133 F12
3119 F6	I134 F12
3120 F9	I135 F12
3121 F9	I136 F12
3122 F1	I137 H10
3123 F6	I142 F10
3124 F8	I143 F10
3125 E8	I144 F10
3126 E9	I147 E8
3127 C14	I150 D9
3128 D14	I151 D9
3129 I8	I155 E10
3130 I3	I156 D7
3131 I3	I157 F5
3132 H10	I158 F6
3133 H10	I159 F7
3134 F1	I160 E8
3135 I5	I161 E8
3136 D2	I162 F8
3137 B3	I163 F8
3138 E2	I165 F10
3139 C3	I166 I4
3140 G8	I167 I4
3141 C3	I168 C3
3142 D6	I169 I8
3143 C5	I170 I7
3144 E3	I172 I6
3146 E2	I173 G4
3147 E14	I174 G4
3148 F14	I175 D13
3149 F14	I176 B13
3151 G14	I177 E5
3152 G14	I178 A12
3153 G14	I179 I6
3154 H5	I180 I3
4100 B13	I181 I2
4101 D13	I182 A3
4102 D2	I184 E4
4103 D2	I185 E4
5101 F2	I189 D2
5103 G2	I190 B3
6100 F6	I191 D2
6101 A3	I192 C3
6102 B3	I193 E2
6103 B3	I194 C3
6105 B14	
6106 C14	
6107 C2	
6109 G8	
6110 D5	
6111 E4	
6112 E3	

2



Layouts Display Panel



2100	A2	3207	A2
2101	A5	3208	A1
2103	A6	3209	A6
2104	A4	4100	A6
2105	A4	4101	A6
2108	A4	4102	A4
2109	A6	4122	A4
2111	A6	4123	A5
2112	A4	4124	A3
2114	A6	4125	A5
2115	A6	4126	A4
2118	A6	4127	A6
2119	A6	4128	A6
2200	A5	4129	A1
2201	A6	4130	A5
2202	A5	4131	A4
2203	A5	4132	A4
2204	A5	4133	A4
2205	A5	4134	A4
2206	A1	4135	A4
2207	A1	4136	A4
2208	A2	4137	A1
2209	A2	4138	A2
2210	A2	4139	A2
2211	A2	4140	A2
2212	A2	4141	A2
2213	A2	4142	A2
2214	A2	4143	A2
2215	A2	4144	A2
2216	A2	4145	A2
2217	A2	4146	A2
2218	A2	4147	A2
2219	A2	4148	A2
2220	A2	4149	A2
2221	A2	4150	A2
2222	A2	4151	A2
2223	A2	4152	A2
2224	A2	4153	A2
2225	A2	4154	A2
2226	A2	4155	A2
2227	A2	4156	A2
2228	A2	4157	A2
2229	A2	4158	A2
2230	A2	4159	A2
2231	A2	4160	A2
2232	A2	4161	A2
2233	A2	4162	A2
2234	A2	4163	A2
2235	A2	4164	A2
2236	A2	4165	A2
2237	A2	4166	A2
2238	A2	4167	A2
2239	A2	4168	A2
2240	A2	4169	A2
2241	A2	4170	A2
2242	A2	4171	A2
2243	A2	4172	A2
2244	A2	4173	A2
2245	A2	4174	A2
2246	A2	4175	A2
2247	A2	4176	A2
2248	A2	4177	A2
2249	A2	4178	A2
2250	A2	4179	A2
2251	A2	4180	A2
2252	A2	4181	A2
2253	A2	4182	A2
2254	A2	4183	A2
2255	A2	4184	A2
2256	A2	4185	A2
2257	A2	4186	A2
2258	A2	4187	A2
2259	A2	4188	A2
2260	A2	4189	A2
2261	A2	4190	A2
2262	A2	4191	A2
2263	A2	4192	A2
2264	A2	4193	A2
2265	A2	4194	A2
2266	A2	4195	A2
2267	A2	4196	A2
2268	A2	4197	A2
2269	A2	4198	A2
2270	A2	4199	A2
2271	A2	4200	A2
2272	A2	4201	A2
2273	A2	4202	A2
2274	A2	4203	A2
2275	A2	4204	A2
2276	A2	4205	A2
2277	A2	4206	A2
2278	A2	4207	A2
2279	A2	4208	A2
2280	A2	4209	A2
2281	A2	4210	A2
2282	A2	4211	A2
2283	A2	4212	A2
2284	A2	4213	A2
2285	A2	4214	A2
2286	A2	4215	A2
2287	A2	4216	A2
2288	A2	4217	A2
2289	A2	4218	A2
2290	A2	4219	A2
2291	A2	4220	A2
2292	A2	4221	A2
2293	A2	4222	A2
2294	A2	4223	A2
2295	A2	4224	A2
2296	A2	4225	A2
2297	A2	4226	A2
2298	A2	4227	A2
2299	A2	4228	A2
2300	A2	4229	A2
2301	A2	4230	A2
2302	A2	4231	A2
2303	A2	4232	A2
2304	A2	4233	A2
2305	A2	4234	A2
2306	A2	4235	A2
2307	A2	4236	A2
2308	A2	4237	A2
2309	A2	4238	A2
2310	A2	4239	A2
2311	A2	4240	A2
2312	A2	4241	A2
2313	A2	4242	A2
2314	A2	4243	A2
2315	A2	4244	A2
2316	A2	4245	A2
2317	A2	4246	A2
2318	A2	4247	A2
2319	A2	4248	A2
2320	A2	4249	A2
2321	A2	4250	A2
2322	A2	4251	A2
2323	A2	4252	A2
2324	A2	4253	A2
2325	A2	4254	A2
2326	A2	4255	A2
2327	A2	4256	A2
2328	A2	4257	A2
2329	A2	4258	A2
2330	A2	4259	A2
2331	A2	4260	A2
2332	A2	4261	A2
2333	A2	4262	A2
2334	A2	4263	A2
2335	A2	4264	A2
2336	A2	4265	A2
2337	A2	4266	A2
2338	A2	4267	A2
2339	A2	4268	A2
2340	A2	4269	A2
2341	A2	4270	A2
2342	A2	4271	A2
2343	A2	4272	A2
2344	A2	4273	A2
2345	A2	4274	A2
2346	A2	4275	A2
2347	A2	4276	A2
2348	A2	4277	A2
2349	A2	4278	A2
2350	A2	4279	A2
2351	A2	4280	A2
2352	A2	4281	A2
2353	A2	4282	A2
2354	A2	4283	A2
2355	A2	4284	A2
2356	A2	4285	A2
2357	A2	4286	A2
2358	A2	4287	A2
2359	A2	4288	A2
2360	A2	4289	A2
2361	A2	4290	A2
2362	A2	4291	A2
2363	A2	4292	A2
2364	A2	4293	A2
2365	A2	4294	A2
2366	A2	4295	A2
2367	A2	4296	A2
2368	A2	4297	A2
2369	A2	4298	A2
2370	A2	4299	A2
2371	A2	4300	A2
2372	A2	4301	A2
2373	A2	4302	A2
2374	A2	4303	A2
2375	A2	4304	A2
2376	A2	4305	A2
2377	A2	4306	A2
2378	A2	4307	A2
2379	A2	4308	A2
2380	A2	4309	A2
2381	A2	4310	A2
2382	A2	4311	A2
2383	A2	4312	A2
2384	A2	4313	A2
2385	A2	4314	A2
2386	A2	4315	A2
2387	A2	4316	A2
2388	A2	4317	A2
2389	A2	4318	A2
2390	A2	4319	A2
2391	A2	4320	A2
2392	A2	4321	A2
2393	A2	4322	A2
2394	A2	4323	A2
2395	A2	4324	A2
2396	A2	4325	A2
2397	A2	4326	A2
2398	A2	4327	A2
2399	A2	4328	A2
2400	A2	4329	A2
2401	A2	4330	A2
2402	A2	4331	A2
2403	A2	4332	A2
2404	A2	4333	A2
2405	A2	4334	A2
2406	A2	4335	A2
2407	A2	4336	A2
2408	A2	4337	A2
2409	A2	4338	A2
2410	A2	4339	A2
2411	A2	4340	A2
2412	A2	4341	A2
2413	A2	4342	A2
2414	A2	4343	A2
2415	A2	4344	A2
2416	A2	4345	A2
2417	A2	4346	A2
2418	A2	4347	A2
2419	A2	4348	A2
2420	A2	4349	A2
2421	A2	4350	A2
2422	A2	4351	A2
2423	A2	4352	A2
2424	A2	4353	A2
2425	A2	4354	A2
2426	A2	4355	A2
2427	A2	4356	A2
2428	A2	4357	A2
2429	A2	4358	A2
2430	A2	4359	A2
2431	A2	4360	A2
2432	A2	4361	A2
2433	A2	4362	A2
2434	A2	4363	A2
2435	A2	4364	A2
2436	A2	4365	A2
2437	A2	4366	A2
2438	A2	4367	A2
2439	A2	4368	A2
2440	A2	4369	A2
2441	A2	4370	A2
2442	A2	4371	A2
2443	A2	4372	A2
2444	A2	4373	A2
2445	A2	4374	A2
2446	A2	4375	A2
2447	A2	4376	A2
2448	A2	4377	A2
2449	A2	4378	A2
2450	A2	4379	A2
2451	A2	4380	A2
2452	A2	4381	A2
2453	A2	4382	A2
2454	A2	4383	A2
2455	A2	4384	A2
2456	A2	4385	A2
2457	A2	4386	A2
2458	A2	4387	A2
2459	A2	4388	A2
2460	A2	4389	A2
2461	A2	4390	A2
2462	A2	4391	A2
2463	A2	4392	A2
2464	A2	4393	A2
2465	A2	4394	A2
2466	A2	4395	A2
2467	A2	4396	A2
2468	A2	4397	A2
2469	A2	4398	A2
2470	A2	4399	A2
2471	A2	4400	A2
2472	A2	4401	A2
2473	A2	4402	A2
2474	A2	4403	A2
2475	A2	4404	A2
2476	A2	4405	A2
2477	A2	4406	A2
2478	A2	4407	A2
2479	A2	4408	A2
2480	A2	4409	A2
2481	A2	4410	A2
2482	A2	4411	A2
2483	A2	4412	A2
2484	A2	4413	A2
2485	A2	4414	A2
2486	A2	4415	A2
2487	A2	4416	A2
2488	A2	4417	A2
2489	A2	4418	A2
2490	A2	4419	A2
2491	A2	4420	A2
2492	A2	4421	A2
2493	A2	4422	A2
2494	A2	4423	A2
2495	A2	4424	A2
2496	A2	4425	A2
2497	A2	4426	A2
2498	A2	4427	A2
2499	A2	4428	A2
2500	A2	4429	A2
2501	A2	4430	A2
2502	A2	4431	A2
2503	A2	4432	A2
2504	A2	4433	A2
2505	A2	4434	A2
2506	A2	4435	A2
2507	A2	4436	A2
2508	A2	4437	A2
2509	A2	4438	A2
2510	A2	4439	A2
2511	A2	4440	A2
2512	A2	4441	A2
2513	A2	4442	A2
2514	A2	4443	A2
2515	A2	4444	A2
2516	A2	4445	A2
2517	A2	4446	A2
2518	A2	4447	A2
2519	A2	4448	A2
2520	A2	4449	A2
2521	A2	4450	A2
2522	A2	4451	A2
2523	A2	4452	A2
2524	A2	4453	A2
2525	A2	4454	A2
2526	A2	4455	A2
2527	A2	4456	A2
2528	A2	4457	A2
2529	A2	4458	A2
2530	A2	4459	A2
2531	A2	4460	A2
2532	A2	4461	A2
2533	A2	4462	A2
2534	A2	4463	A2
2535	A2	4464	A2
2536	A2	4465	A2
2537	A2	4466	A2
2538	A2	4467	A2
2539	A2	4468	A2
2540	A2	4469	A2



TR 06006a_001
240203

[illegible]

TR 06006b_001
240203


Standby Panel (STBY)

Layout Standby Panel




Tray Left Panel (TRL)

Layout Tray Left Panel




TR 06021_001
030203




TR06008_001
030203

Tray Right Panel (TRR)


Layout Tray Right Panel





TR 06022_001
030203



Analog Board: Frontend Video (FV)



Analog Board: In/Out Video (IOV)





TR07005_001
110303

Analog Board: IN/Out Audio (IOA)




2501 A5	I503 B1
2502 A6	I504 D1
2503 A2	I505 B2
2504 A1	I506 B2
2505 A1	I507 C3
2506 A4	I508 E4
2507 A6	I509 D3
2508 A6	I510 D3
2509 B4	I511 C3
2510 A3	I513 C6
2511 E4	I514 C6
2512 D7	I515 B6
2513 F4	I516 B6
2514 C4	I517 B8
2515 F5	I518 C8
2516 E3	I519 D6
2517 F4	I520 D7
2518 E2	I521 D6
2519 A4	
2520 F3	I523 D9
2521 C9	I524 E9
2522 E8	I525 B8
2523 E9	I526 C8
2524 F1	I527 F1
2525 F1	I528 F1
2526 F8	I529 E6
2527 F9	I530 E7
2530 C9	I531 E3
2531 B8	I532 E4
2532 C8	I533 E3
2535 D5	I534 E8
2536 F5	I535 E8
3501 B8	I539 F8
3502 B8	I540 F8
3503 A5	
3504 A5	
3505 C6	
3506 B5	
3507 C1	
3508 C3	
3509 C8	
3510 D1	
3511 D1	
3512 D8	
3513 D3	
3514 E1	
3515 D7	
3516 E1	
3517 D8	
3518 E7	
3519 E8	
3520 F3	
3521 F4	
3522 E9	
3523 E7	
3524 E9	
3525 F9	
3526 F7	
3527 F9	
3528 F2	
3529 F3	
3530 F2	
3531 F4	
3532 C3	
3533 D3	
3534 C1	
3535 C3	
3536 D3	
3537 F7	
3538 E7	
7501 A7	
7502-A C4	
7502-B D4	
7502-C E7	
7502-D D7	
7503 B2	
7504 D5	
7505-A B9	
7505-B C8	
7506 D9	
7508 E9	
7509 F2	
7511 F4	
F501 E2	
F502 F2	
F504 D2	
I501 C1	
I502 C1	

Analog Board for VAE8020: Power Supply (PS)




1300.01	3364.68	F351 H1
1301 B1	3365.73	F352 H1
1302 A3	3366.65	F353 I1
1303 E8	3367.65	F354 I1
1304 C9	3368.01	F355 I1
1305 B1	3371.10	F356 C9
1307 A12	3372.10	F357 I1
1308 D13	3373.10	F358 I1
1309 A13	3374.12	F359 I8
1931 B1	3375.12	F360 I1
1932 E1	3376.14	F361 I6
1933 H1	3377.13	F362 G11
1934 D1	4301 G12	F363 G11
2302 B2	5300 A6	F364 I2
2302 B2	5302 B3	F366 E8
2303 B4	5304 D6	F367 E8
2304 B8	5305 G9	F368 E9
2305 H8	5306 C8	F369 E9
2306 B9	5307 E9	F371 G2
2307 C4	5308 A8	F372 G12
2308 C5	5309 D9	F373 A12
2309 A1	5300 A7	F374 I2
2310 A10	6301 B4	F381 F1
2311 B10	6302 B4	F382 E13
2312 C8	6303 B7	F383 G1
2313 C9	6304 B13	F384 G1
2314 D5	6305 C4	I300 A6
2315 E4	6306 C4	I301 A11
2316 A7	6307 C7	I302 A6
2317 B3	6308 C7	I303 A8
2318 D3	6309 D5	I304 A10
2319 D8	6310 D7	I305 A10
2320 D9	6311 E5	I306 A3
2321 E10	6312 F7	I307 G4
2322 E9	6313 E8	I308 B8
2323 E9	6314 I10	I309 B12
2324 H4	6315 E7	I310 B8
2325 H4	6316 H4	I311 B9
2326 H1	6317 F10	I312 B4
2327 G11	6318 H11	I313 B10
2328 G9	6319 G9	I314 B3
2329 I6	6320 I10	I315 B10
2330 C10	6321 G4	I316 B5
2331 I3	6322 F12	I317 C3
2332 H13	6324 H12	I318 C11
2333 A8	6325 I10	I319 C10
2334 B1	7301 A11	I320 C10
2335 D9	7302 B10	I321 D5
2336 I8	7303 C10	I322 D6
2337 H3	7304 B11	I323 D11
2338 H11	7305 C11	I324 E5
2339 B10	7306 D12	I325 E3
2340 A2	7307 E3	I326 E9
2341 B9	7308 H13	I327 F10
2342 E1	7309 A11	I329 D10
3300 A5	7310 H7	I330 F3
3301 A6	7311 H8	I331 F3
3302 F10	7312 F11	I332 F7
3303 F11	7313 G2	I333 F11
3304 F10	7314 H5	I334 F11
3305 B2	7315 I6	I335 F6
3306 A3	7317 A10	I336 F7
3307 A10	7318 I10	I337 F10
3308 C4	7319 I10	I338 F11
3309 C5	7320 H13	I339 G7
3310 C5	7321 I9	I340 G4
3311 C9	7322 G12	I341 H5
3312 C10	9301 E10	I342 I5
3313 D11	9304 F9	I344 H6
3314 C11	9305 H11	I345 H8
3315 C11	9306 B13	I346 H8
3316 H6	9307 B13	I347 H10
3317 H6	F300 A11	I348 I3
3318 E3	F301 A12	I349 H10
3319 A7	F302 A12	I350 I5
3320 E4	F304 A7	I351 I6
3322 F9	F305 A7	I352 I10
3323 E11	F306 A5	I353 I3
3324 G4	F307 A5	I354 I12
3325 E10	F308 B1	I355 I7
3326 G11	F309 B1	I356 H12
3327 H13	F310 B2	I357 H11
3328 H8	F311 B2	I361 I8
3329 I3	F312 B7	
3330 I6	F313 B1	
3331 I6	F314 B1	
3332 I7	F315 C7	
3333 I7	F316 C8	
3334 I7	F317 C9	
3335 A9	F318 C8	
3336 A10	F319 C8	
3337 B9	F320 C7	
3338 B10	F321 D12	
3339 A11	F322 D13	
3340 A11	F323 D7	
3341 A12	F324 D12	
3342 B11	F325 D13	
3343 B11	F326 D8	
3344 B12	F328 E3	
3345 I7	F329 E7	
3346 F7	F331 F13	
3347 I3	F333 F13	
3348 H10	F334 F9	
3349 I10	F335 F9	
3350 F10	F336 G9	
3351 G3	F337 G6	
3352 E4	F338 E6	
3353 H11	F339 E8	
3354 H11	F340 G11	
3355 I9	F341 G13	
3356 G4	F342 G3	
3357 I10	F343 G12	
3358 H8	F344 G11	
3359 B9	F346 I3	
3360 G4	F347 I3	
3361 F11	F348 H1	
3362 H10	F349 H1	
3363 G7		


Analog Board for VAD8031: Power Supply (PS)



130020	3361 F12	F346 E1 3
1301 B2	3362 H1 0	F347 E1 3
1302 A3	3363 G8	F348 G2
1303 E9	3364 G8	F349 A13
1304 B9	3365 F4	F350 G1
1306 G1 3	3366 G5	F351 A14
1307 B2	3367 G5	F352 G2
1308 D1 3	3368 D1 1	F353 G1
1309 A1 3	3371 H1 1	F354 E1 2
1931 B1	3372 H1 1	F355 E1 2
1932 C1	3373 H1 1	F356 C9
1933 G1	3374 A1 1	F357 H2
1934 E1	3375 A1 3	F358 G2
1935 F1	3376 A1 3	F359 F9
1936 F1	3377 A1 1	F360 H1 1
2001 A7	3378 D1 1	F361 I6
2002 B2	4501 G1 2	F362 G1 1
2003 B4	4504 F2	F363 G1 1
2004 F9	5300 A6	F364 A12
2005 B8	5301 B1 3	F366 E8
2006 B9	5302 B4	F367 F9
2007 C5	5304 D6	F368 F9
2008 C5	5305 F9	F369 F9
2009 D4	5306 C8	F371 G1 3
2101 A1 1	5307 E1 0	F372 G1 3
2111 B1 1	5308 A9	F373 A12
2112 C8	5309 D9	F374 A13
2113 C9	6300 A8	F381 D1
214 D6	6301 B4	F382 E14
2153 E4	6302 B5	F383 D1
2161 B3	6303 A4	F384 D1
217 F4	6305 C4	A006 A6
2181 G6	6306 C5	I001 A1 2
219 D9	6307 C8	I002 A7
220 D9	6308 C8	I003 A8
2321 E1	6309 D5	I004 A10
2322 E9	6310 D8	I005 A13
2323 E1	6311 E5	I006 A1
2324 H4	6312 F8	I007 G4
2325 H5	6313 E8	I008 B8
2326 J1	6314 I0	I009 B12
2327 G1 2	6315 E8	I010 B8
2328 G1 0	6316 H5	I111 B9
2329 I6	6317 F10	I12 B5
2330 C1 1	6318 G12	I13 B10
2331 H4	6319 F9	I14 B4
2332 I4	6520 I0	I15 B11
2333 H1	6521 G4	I16 B5
2334 I0	6522 F12	I17 C4
2335 D1 0	6524 H1 2	I18 C12
2336 B8	6525 E1 0	I19 C10
2337 H3	7301 A1 1	I20 C11
2338 H1 2	7302 B1 1	I21 D6
2339 B1 0	7303 C1 1	I22 D6
2340 A3	7304 B1 1	I23 D12
2341 C1 0	7305 C1 1	I24 B3
2342 F3	7306 D1 2	I25 E5
2343 E1	7307 F4	I26 I0
2344 B1	7308 H1 3	I27 F1 1
3001 A6	7309 E1 1	I29 F1 1
3002 F1 1	7310 H8	I30 F3
3003 F1 1	7311 H8	I31 F4
3004 F1 1	7312 F1 2	I32 F8
3005 F1 1	7313 G3	I33 F1 1
3006 A4	7314 H5	I34 F1 2
3007 F1 1	7315 I6	I35 F6
3008 C5	7317 A1 1	I36 F8
3009 C5	7318 D1 0	I37 F1 0
3101 C5	7319 I11	I38 F1 1
3111 C1 0	7320 H1 4	I39 G8
3121 C1 0	7521 I0	I40 G5
3131 C1 0	7522 G12	I41 I2
3141 C1 2	9201 I0	I43 H6
3151 C1 2	9202 G2	I44 H6
3161 C1 2	9304 F10	I45 H8
3171 H6	9305 H1 2	I46 H13
3181 E3	C300 B8	I47 H11
3191 A7	F300 A12	I48 I3
3221 E4	F301 A1 3	I49 H10
3222 F1 0	G02 A13	I50 I6
3223 F4	F004 A8	I51 I2
3224 G4	F005 A7	I52 I11
3225 E1	F306 A6	I53 I14
3226 G1 2	F307 A6	I54 I13
3227 H1 3	F308 B1	I55 I7
3228 H8	F309 B2	I56 H12
3229 I3	F310 B3	I57 H11
3303 I6	F311 B2	I61 I8
3311 F7	F312 B7	
3321 F7	F313 B1	
3331 F7	F314 B3	
3335 A1 0	F315 C9	
3336 A10	F317 C9	
3337 B10	F318 C9	
3338 B1 1	F319 C8	
3340 A1 0	F320 C7	
3341 A12	F321 D12	
3342 B12	F323 D7	
3343 B12	F324 D13	
3344 B1 2	F325 D13	
3345 F7	F326 D8	
3346 F8	F28 E3	
3347 I3	F29 E8	
3348 H1 0	F331 F1 3	
3349 G1 1	F333 F1 3	
3350 F1 1	F334 F1 0	
3351 G4	F335 F1 0	
3352 E5	F336 F9	
3353 H1 1	F337 F9	
3354 H1 2	F338 G6	
3355 I10	F339 G9	
3356 G5	F402 G12	
3357 H7	F431 G13	
3358 H8	F432 G3	
3359 H9	F433 G12	
360 G5	F444 G14	




Analog Board: Multi Sound Processing (MSP)




Analog Board: VPS

1990 D1	2934 B1	2937 D1	3932 C4	3935 E1	5932 A3	1988 B2	1991 C1	1994 C1	1997 D1
2932 B4	2935 C1	2938 B3	3933 C4	3936 E3	7931 B2	1989 C1	1992 C4	1995 D1	1998 E1
2933 B4	2936 C1	3931 B2	3934 D1	5931 A4	1987 B4	1990 C4	1993 C1	1996 D1	1999 E3




Analog Board: Follow Me (FOME)


2940 A2	2944 D4	3937 C1	3941 D3	3945 E3	3950 A3	3954 C2	7934-B B4	1951 B3	1956 D2
2941 B3	2945 D2	3938 C1	3942 E1	3946 E2	3951 B2	7932 B2	7934-C C2	1952 B3	1957 D2
2942 D2	2946 E1	3939 C3	3943 E2	3947 E4	3952 B3	7933 B3	7934-D C3	1954 C3	1958 D3
2943 D4	2947 E3	3940 D1	3944 E3	3948 A2	3953 B2	7934-A A2	F950 A2	1955 C1	1959 D3



1951 A4	2585 C3	2590 A3	3582 D2	5580 A2	7580-A C2	7580-D D3	F4102 A4	I488 C2	I491 D2
2580 A3	2586 D3	3580 A3	3584 C1	5581 A1	7580-B C3	7580-E C3	F4103 A4	I489 C3	I492 C3
2581 A1	2587 D2	3581 C2	3585 C3	6580 C4	7580-C C3	7580-F D3	I487 A3	I490 C1	I493 B4




Analog Board 603 3033: Audio Converter (DAC_ADC)




1001 A7	4003 F1
1900 B1	4004 F1
2001 A4	4006 A8
2002 A4	5001 A8
2003 A6	6001 A1
2004 A9	6002 B1
2005 A9	6003 F3
2006 A2	7001 A6
2007 B6	7002-A C9
2008 B7	7002-B E9
2009 C5	7003 B4
2010 C6	7005 D5
2011 C6	7006 E1
2012 E9	7008 C2
2013 D6	7009 C3
2014 D6	7010 C4
2015 D5	7011 F7
2016 D5	F0001 E1
2018 D9	F0002 E1
2019 E6	F0003 D1
2020 E7	F0005 D1
2022 B4	F0007 D1
2023 F1	F0009 D1
2024 B8	F0011 C1
2025 D7	F0012 C1
2026 D8	F0014 C1
2029 F1	F0016 C1
2031 D2	F0021 A1
2032 F8	F006 A8
2033 B7	F007 A7
2034 D7	F008 A7
2035 B8	F009 A7
2036 D8	F010 C9
2037 B7	F011 E9
2038 B8	I002 A5
2039 D8	I003 A4
2040 D7	I006 A4
3001 A4	I008 B8
3002 A4	I011 C5
3003 A3	I012 C7
3004 B2	I013 D6
3005 B1	I014 E2
3006 B2	I015 D4
3007 B6	I018 E7
3008 A2	I020 E1
3009 A7	I021 F1
3010 A8	I022 E2
3011 B8	I028 F2
3012 B8	I030 F1
3013 B2	I032 E2
3014 C4	I033 B6
3015 D6	I036 E1
3017 D6	
3018 D4	
3019 D3	
3020 E2	
3024 C6	
3026 E2	
3027 C7	
3029 D8	
3030 D8	
3034 E2	
3035 E1	
3039 F2	
3041 F2	
3043 F5	
3044 C3	
3045 C3	
3046 C2	
3047 D3	
3048 C2	
3049 F6	
3050 F7	
3051 F8	
3052 A9	
3053 C8	
3054 C9	


TR 07012_001
120303

Analog Board 603 3028: Audio Converter (DAC_ADC)







Layout Analog Board 603 3033 (Part 1 Bottom View)




Layout Analog Board 603 3033 (Part 2 Bottom View)




Layout Analog Board 603 3028 (Top View)




Layout Analog Board 603 3028 (Overview Bottom View)



Layout Analog Board 603 3028 (Part 1 Bottom View)




Layout Analog Board 603 3028 (Part 2 Bottom View)



UP Sub Board: Fan Control (FACO)


1301 B4	3915 B3	3922 C1	3929 A4	4902 D3	7902-3 C4	7908 B1	F905 A1	I904 C2
1901 A4	3916 D1	3923 E1	3930 A4	4903 D3	7902-4 D4	7909 B4	F906 A2	I905 C2
2911 D1	3917 C1	3924 A2	3931 A4	6901 E3	7903 A1	7910 B3	F907 A2	I906 E2
2912 B3	3918 B2	3925 D1	3932 B4	6902 A1	7904 A3	F901 A4	F908 B4	I907 E4
2913 B4	3919 C1	3926 A2	3933 B4	6903 C3	7905 A3	F902 A4	F909 C3	I908 D1
3913 B2	3920 E1	3927 D2	3934 A4	7902-1 C2	7906 A1	F903 B4	F910 E3	
3914 C4	3921 E4	3928 C3	4901 A1	7902-2 D2	7907 A2	F904 B4	I903 C2	




TR 06032_001
030203

[illegible]

Layout UP Sub Board (Bottom View)




1394 INTERFACE



LINK + CODEC


TR03015_001
090702

DVIO Board: uP-Part




TR03016_001
090702

DVIO Board: Interface+DAC



0003 I4	F542 G14
0004 I5	F543 G14
0005 I5	F544 G13
0006 I6	F545 G11
0007 I7	F547 G9
1500 C7	F548 G13
1501 H14	F549 H7
1502 E9	F550 G7
1503 F9	F551 F11
1906 I8	F552 F11
1907 I9	F553 G10
1908 I9	F554 E5
1909 I9	F555 F5
2500 A6	F556 F5
2501 C3	F557 F6
2502 C3	F558 F6
2503 C3	F559 E6
2504 C3	F560 G10
2505 C3	F561 F11
2506 E12	F562 F7
2507 E12	F563 A10
2508 E12	F564 B12
2509 C5	F565 B10
2510 C6	F566 B12
2511 C6	F567 A10
2512 E12	
2513 E7	
2514 G11	
2515 C6	
2516 D5	
2517 D6	
2518 D6	
2519 D6	
2520 F9	
2521 F9	
2522 G13	
2523 G10	
2524 G14	
2525 H12	
2526 H13	
2527 A11	
2528 C12	
2529 F9	
2530 F9	
2531 F5	
2532 F6	
2533 F6	
2534 E10	
3500 B5	
3501 B3	
3502 B5	
3503 B5	
3504 C5	
3505 C5	
3506 D5	
3507 D5	
3508 D5	
3509 D5	
3510 E5	
3511 B3	
3512 B2	
3514 E5	
3515 F5	
3516 F5	
3517 G10	
3518 G13	
3519 G11	
3520 G13	
4500 A3	
4501 B2	
4502 F9	
4503 G9	
4504 G10	
4507 A12	
5500 A5	
5501 C4	
5503 E12	
5504 E12	
5505 A10	
7500-A A1	
7500-B A2	
7500-C A2	
7500-D A4	
7500-E A3	
7500-F I1	
7501 F10	
7505 D4	
7506 E11	
7507-A B11	
7507-B B13	
7508 C11	
F501 A5	
F502 A2	
F503 A2	
F504 C5	
F505 C7	
F506 C5	
F507 B7	
F508 B5	
F509 B7	
F510 B5	
F511 D7	
F512 D7	
F513 D7	
F514 D7	
F515 E7	
F516 E6	
F517 F10	
F518 D7	
F519 D5	
F520 D5	
F521 E7	
F522 D5	
F523 F8	
F524 D5	
F525 E12	
F526 E12	
F527 E3	
F528 F8	
F529 E5	
F530 E7	
F531 E7	
F532 E9	
F533 E9	
F534 F7	
F535 F7	
F536 F11	
F537 F9	
F538 G7	
F539 G9	
F540 G11	
F541 G13	

DVIO Board: Clock




TR03018_002
040203


2600 B4
2601 C5
2602 D3
2603 D5
2604 E3
2605 E2
2606 F8
2607 A8
2608 B7
2609 A8
2610 B9
2611 A5
2612 C3
2613 E9
2614 D3
2615 F3
2616 A2
2617 B4
2618 E3
2619 B1
3600 D3
3601 A1
3602 D5
3603 B3
3604 F8
3605 F7
3606 E2
3607 F3
3608 D4
3609 F6
3610 F7
3612 E2
3613 F8
3614 E9
3616 C9
3617 A6
3618 E1
4602 F3
4603 F7
4604 A4
4605 A5
4606 B2
4608 B2
4609 C2
5600 C5
5601 A8
5602 A4
5603 A8
7600 A2
7601 A3
7602 C2
7604 D4
7605 B8
7606-A B5
7606-B D1
7608 F8
F601 D4
F603 A1
F604 F3
F605 D2
F606 F9
F609 D2
F610 B3
F611 D3
F614 D4
F615 F6
F616 F8
F617 F8
F618 B9
F619 B7
F620 B9
F621 B6
F622 C6
F623 B9
F624 F2

1500	B2	2503	B5	2810	E5	3450	C3	3511	B5	3800	B6	5501	B5
1500	C6	2504	B5	2811	F5	345	F2	3512	B5	3801	F5	5503	B4
1501	A4	2505	B5	2812	D4	3452	G3	3514	C5	3802	E6	5504	B4
1502	C5	2506	B5	2813	E6	3453	C2	3515	C6	3803	E4	5505	C5
1503	C5	2507	B4	2814	E6	3454	E2	3516	C6	3804	E4	5600	G4
1800	F5	2508	A5	2816	E4	3455	E2	3517	A4	3805	E4	5601	F4
1901	A2	2509	B6	2817	E4	3456	E2	3518	A4	3806	E4	5602	C3
1902	C5	2510	B6	2818	D4	3457	D2	3519	A4	3807	E4	5603	F5
1903	A6	2511	B6	2819	C6	3458	D2	3520	A4	3808	F5	5800	B6
1904	F6	2512	B4	2820	F5	3459	D2	3530	G3	3809	G6	5801	D5
1905	F4	2513	C6	2821	F5	3460	D2	3531	F2	3810	E4	5802	D6
1906	G5	2514	A4	2822	D6	3461	C2	3532	F2	3811	E4	6801	G5
1907	A3	2515	C6	3400	B1	3462	E2	3533	F2	3812	E4	6802	G5
1908	D1	2516	B6	3401	B2	3463	E2	3534	G3	3813	E4	6803	F6
1909	B4	2517	B6	3402	B2	3464	E2	3535	F2	3814	F5	6804	E6
2400	B1	2518	B6	3403	C1	3465	D2	3536	G3	3815	G5	7400	B2
2401	B2	2519	B6	3404	B2	3466	D2	3537	F2	3816	G5	7430	F2
2402	A2	2520	C5	3405	A2	3467	D2	3538	G3	3817	E6	7431	D3
2403	B1	2521	C5	3406	B2	3468	D2	3539	F2	3818	E6	7432	C4
2404	B2	2522	A5	3407	B2	3469	D2	3540	G3	3819	E6	7433	D1
2405	B2	2523	A4	3408	B2	3470	E4	3541	F2	3820	E6	7500	B5
2406	B1	2524	A4	3409	B2	3471	E2	3542	F3	3821	G5	7501	B4
2407	B1	2525	B4	3410	C1	3472	D4	3543	F2	3822	E5	7505	B5
2408	B2	2526	B4	3411	C1	3473	D4	3544	E3	3823	G5	7506	B4
2412	C2	2527	C4	3413	C1	3474	D4	3545	F2	3824	G5	7507	C4
2413	B2	2528	C4	3414	C1	3475	D4	3546	F3	3825	E4	7508	C4
2415	C3	2529	C5	3415	C2	3476	D4	3547	F2	3826	D5	7600	C3
2416	B1	2530	C6	3416	C2	3477	D4	3548	E3	3827	D4	7601	C2
2417	C2	2531	B6	3417	C2	3478	D4	3549	F2	3828	F5	7602	F4
2418	C2	2532	C6	3418	C2	3479	C4	3550	F3	3829	D5	7604	F4
2419	C1	2533	B6	3419	C2	3480	C4	3551	F3	3831	E5	7605	F4
2420	C2	2534	B4	3420	C2	3481	B4	3552	E3	3832	E5	7606	F4
2431	C2	2600	C2	3421	C2	3482	B4	3553	F3	3833	E4	7608	F4
2432	E2	2601	G3	3422	C2	3483	B3	3554	G3	3834	E4	7800	B6
2433	D3	2602	F3	3423	C2	3484	C3	3555	F3	3835	F6	7801	G5
2434	E4	2603	F4	3424	C2	3485	B4	3556	F3	3836	G6	7802	E5
2435	D4	2604	F4	3425	E4	3486	B4	3557	E3	3837	D5	7803	E6
2436	G2	2605	F4	3426	E3	3487	C3	3558	F3	3838	D6	7804	E6
2437	E2	2606	F4	3427	B4	3488	C3	3559	G3	3839	F6	7805	E6
2438	D2	2607	F4	3428	E3	3489	C4	3560	G3	4401	C2	7806	G6
2439	G3	2608	F5	3429	E4	3490	B4	3561	G2	4402	B2	7807	D4
2440	E3	2609	F4	3430	F2	3491	B4	3562	E2	4500	B5	7808	D5
2441	F2	2610	F4	3431	F2	3492	C3	3563	C3	4501	B5	7809	F5
2442	E3	2611	F4	3432	F2	3493	C4	3564	E4	4502	C5	7810	F6
2443	E3	2612	F4	3433	F2	3494	B4	3600	F3	4503	C5	7811	F6
2444	F2	2613	F4	3434	F2	3495	B3	3601	C3	4504	B4		
2445	D3	2614	F3	3435	F2	3496	C3	3602	F4	4507	B5		
2446	G2	2615	F3	3436	F2	3497	D4	3603	F5	4602	F3		
2447	G2	2616	C3	3437	F2	3498	D4	3604	F4	4603	F4		
2448	B4	2617	C3	3438	F2	3499	D4	3605	F4	4604	C3		
2449	D2	2618	F4	3439	F2	3500	B5	3606	F4	4605	C3		
2450	D1	2619	C3	3440	F2	3501	B5	3607	F3	4606	C3		
2451	E3	2801	F5	3441	F3	3502	C5	3608	F3	4608	E4		
2452	E4	2802	F5	3442	F3	3503	B5	3609	F4	4609	E4		
2453	D2	2803	A6	3443	F3	3504	B5	3610	F4	5400	B1		
2454	D3	2804	A6	3444	F3	3505	B5	3612	F4	5401	C2		
2455	D2	2805	F5	3445	F3	3506	B5	3613	F4	5431	D2		
2456	C3	2806	C6	3446	C2	3507	B6	3614	F4	5432	D2		
2500	A5	2807	D5	3447	F3	3508	B6	3616	F5	5433	G2		
2501	B5	2808	D5	3448	G2	3509	B6	3617	F5	5434	B3		
2502	B5	2809	F5	3449	C3	3510	B5	3618	F4	5500	A5		


Layout DVIO Board (Part 1 Top View)





Layout DVIO Board (Part 2 Top View)




Digital Board 1.5: VSM, Buffer Memory and Bit Engine Interface




Digital Board 1.5: AV Decoder STI5519




Digital Board 1.5: AV Decoder Memory





Digital Board 1.5: Video Encoder, Empress




1500 H4	2504 E2	2509 E2	2514 A5	2519 B3	2524 B7	2529 B7	2534 A6	2539 A7	2544 C11	3502 C3	3507 F4	4500 C2	5503 B3	5508 C5	7501-B B2	7503 H2	1503 C7	1508 A5	1515 A5	1518 C5	1523 E3	1528 E3	1533 F4	1540 B1	1555 H4
2500 C4	2505 E2	2510 H3	2515 C4	2520 B5	2525 C8	2530 C5	2535 C7	2540 B8	2545 G3	3503 C2	3508 G5	4501 C8	5504 F11	5509 G2	7501-C H7	7504 B2	1504 C7	1509 A6	1514 B4	1519 E3	1524 C3	1529 H7	1534 F4	1543 C1	
2501 D2	2506 E2	2511 H4	2516 B5	2521 C8	2526 B7	2531 A6	2536 B7	2541 C8	2545 C2	3504 A2	3509 G4	5500 A5	5505 B8	6500 B1	7501-D H6	1500 C8	1505 F4	1510 A4	1515 B7	1520 E3	1525 E8	1530 E8	1536 F4	1551 E8	
2502 D2	2507 E2	2512 F11	2517 A5	2522 B7	2527 A6	2532 C8	2537 B7	2542 C5	3500 C7	3505 E9	3513 C2	5501 A3	5506 A8	7500 C3	7502-A C10	1501 C8	1506 C2	1511 A7	1516 D3	1521 E3	1526 E11	1531 E8	1537 F4	1552 G4	
2503 D2	2508 E2	2513 B4	2518 B3	2523 C8	2528 C8	2533 B7	2538 A6	2543 A6	3501 C7	3506 H7	3515 H3	5502 B5	5507 A7	7501-A F11	7502-B D11	1502 C3	1507 C7	1512 D2	1517 D3	1522 E3	1527 E8	1532 F2	1538 G5	1553 H3	



Digital Board 1.5: Analog Board Cons. Video In / Output




Digital Board 1.5: Progressive Scan




2700 B9	I708 E11
2701 B8	I709 A2
2702 B9	I710 B6
2703 B9	I711 A4
2704 B8	I712 A3
2705 B8	I713 G10
2706 B8	I714 F4
2707 G3	I715 F3
2708 B8	I716 G11
2709 B8	I717 F11
2710 B8	I718 F11
2711 B8	I719 F11
2712 B8	I720 F11
2713 B8	I721 F11
2714 F13	I722 F11
2715 B6	I723 F11
2716 B7	I724 G11
2717 B8	I725 F11
2718 B7	I726 H11
2719 B8	I727 H11
2720 B11	I728 C6
2721 E2	I729 D6
2722 D3	I730 D6
2723 B3	I731 D6
2724 B2	I732 D6
2725 B2	I733 D6
2726 B3	I734 D6
2727 B8	I735 D6
3700 G11	
3701-A F11	
3701-B F11	
3701-C F11	
3701-D F11	
3702-A G11	
3702-B F11	
3702-C F11	
3702-D F11	
3703-A F6	
3703-B F6	
3703-C F6	
3703-D F6	
3704-A F6	
3704-B F6	
3704-C F6	
3704-D F6	
3705 F11	
3706 G11	
3707 H11	
3708 H11	
3709-A E6	
3709-B E6	
3709-C E6	
3709-D F6	
3710-A G6	
3710-B F6	
3710-C E6	
3710-D E6	
3711-A G6	
3711-B G6	
3711-C G6	
3711-D G6	
3712 F3	
3713-A G6	
3713-B G6	
3713-C G6	
3713-D G6	
3714 G11	
3715-A H7	
3715-B H7	
3715-C H7	
3715-D H7	
3716-A H8	
3716-B H8	
3716-C H8	
3716-D H8	
3717-A H8	
3717-B H8	
3717-C H8	
3717-D H8	
3718-A H8	
3718-B H8	
3718-C H8	
3718-D H8	
3719-A H8	
3719-B H8	
3719-C H8	
3719-D H8	
3720 F6	
4700 A1	
4701 B1	
4702 E2	
5700 B11	
5701 A3	
5702 B6	
7700 B7	
7701-A E1	
7701-B C1	
7702-A E3	
7703 A2	
I701 E3	
I702 E2	
I703 E11	
I704 B9	
I705 B9	
I706 B9	
I707 F11	

TR 06044_001
050203




Digital Board 1.5: Power, Clock, and Reset Audio Clock




[illegible]


Layout Digital Board 1.5 (Part 1 Top View)



Layout Digital Board 1.5 (Part 2 Top View)




Layout Digital Board 1.5 (Overview Bottom View)




7101	7102	7103	7104	7105	7106	7107	7108	7109	7110	7111	7112	7113	7114	7115	7116	7117	7118	7119	7120	7121	7122	7123	7124	7125	7126	7127	7128	7129	7130	7131	7132	7133	7134	7135	7136	7137	7138	7139	7140	7141	7142	7143	7144	7145	7146	7147	7148	7149	7150	7151	7152	7153	7154	7155	7156	7157	7158	7159	7160	7161	7162	7163	7164	7165	7166	7167	7168	7169	7170	7171	7172	7173	7174	7175	7176	7177	7178	7179	7180	7181	7182	7183	7184	7185	7186	7187	7188	7189	7190	7191	7192	7193	7194	7195	7196	7197	7198	7199	7200	7201	7202	7203	7204	7205	7206	7207	7208	7209	7210	7211	7212	7213	7214	7215	7216	7217	7218	7219	7220	7221	7222	7223	7224	7225	7226	7227	7228	7229	7230	7231	7232	7233	7234	7235	7236	7237	7238	7239	7240	7241	7242	7243	7244	7245	7246	7247	7248	7249	7250	7251	7252	7253	7254	7255	7256	7257	7258	7259	7260	7261	7262	7263	7264	7265	7266	7267	7268	7269	7270	7271	7272	7273	7274	7275	7276	7277	7278	7279	7280	7281	7282	7283	7284	7285	7286	7287	7288	7289	7290	7291	7292	7293	7294	7295	7296	7297	7298	7299	7300	7301	7302	7303	7304	7305	7306	7307	7308	7309	7310	7311	7312	7313	7314	7315	7316	7317	7318	7319	7320	7321	7322	7323	7324	7325	7326	7327	7328	7329	7330	7331	7332	7333	7334	7335	7336	7337	7338	7339	7340	7341	7342	7343	7344	7345	7346	7347	7348	7349	7350	7351	7352	7353	7354	7355	7356	7357	7358	7359	7360	7361	7362	7363	7364	7365	7366	7367	7368	7369	7370	7371	7372	7373	7374	7375	7376	7377	7378	7379	7380	7381	7382	7383	7384	7385	7386	7387	7388	7389	7390	7391	7392	7393	7394	7395	7396	7397	7398	7399	7400	7401	7402	7403	7404	7405	7406	7407	7408	7409	7410	7411	7412	7413	7414	7415	7416	7417	7418	7419	7420	7421	7422	7423	7424	7425	7426	7427	7428	7429	7430	7431	7432	7433	7434	7435	7436	7437	7438	7439	7440	7441	7442	7443	7444	7445	7446	7447	7448	7449	7450	7451	7452	7453	7454	7455	7456	7457	7458	7459	7460	7461	7462	7463	7464	7465	7466	7467	7468	7469	7470	7471	7472	7473	7474	7475	7476	7477	7478	7479	7480	7481	7482	7483	7484	7485	7486	7487	7488	7489	7490	7491	7492	7493	7494	7495	7496	7497	7498	7499	7500	7501	7502	7503	7504	7505	7506	7507	7508	7509	7510	7511	7512	7513	7514	7515	7516	7517	7518	7519	7520	7521	7522	7523	7524	7525	7526	7527	7528	7529	7530	7531	7532	7533	7534	7535	7536	7537	7538	7539	7540	7541	7542	7543	7544	7545	7546	7547	7548	7549	7550	7551	7552	7553	7554	7555	7556	7557	7558	7559	7560	7561	7562	7563	7564	7565	7566	7567	7568	7569	7570	7571	7572	7573	7574	7575	7576	7577	7578	7579	7580	7581	7582	7583	7584	7585	7586	7587	7588	7589	7590	7591	7592	7593	7594	7595	7596	7597	7598	7599	7600	7601	7602	7603	7604	7605	7606	7607	7608	7609	7610	7611	7612	7613	7614	7615	7616	7617	7618	7619	7620	7621	7622	7623	7624	7625	7626	7627	7628	7629	7630	7631	7632	7633	7634	7635	7636	7637	7638	7639	7640	7641	7642	7643	7644	7645	7646	7647	7648	7649	7650	7651	7652	7653	7654	7655	7656	7657	7658	7659	7660	7661	7662	7663	7664	7665	7666	7667	7668	7669	7670	7671	7672	7673	7674	7675	7676	7677	7678	7679	7680	7681	7682	7683	7684	7685	7686	7687	7688	7689	7690	7691	7692	7693	7694	7695	7696	7697	7698	7699	7700	7701	7702	7703	7704	7705	7706	7707	7708	7709	7710	7711	7712	7713	7714	7715	7716	7717	7718	7719	7720	7721	7722	7723	7724	7725	7726	7727	7728	7729	7730	7731	7732	7733	7734	7735	7736	7737	7738	7739	7740	7741	7742	7743	7744	7745	7746	7747	7748	7749	7750	7751	7752	7753	7754	7755	7756	7757	7758	7759	7760	7761	7762	7763	7764	7765	7766	7767	7768	7769	7770	7771	7772	7773	7774	7775	7776	7777	7778	7779	7780	7781	7782	7783	7784	7785	7786	7787	7788	7789	7790	7791	7792	7793	7794	7795	7796	7797	7798	7799	7800	7801	7802	7803	7804	7805	7806	7807	7808	7809	7810	7811	7812	7813	7814	7815	7816	7817	7818	7819	7820	7821	7822	7823	7824	7825	7826	7827	7828	7829	7830	7831	7832	7833	7834	7835	7836	7837	7838	7839	7840	7841	7842	7843	7844	7845	7846	7847	7848	7849	7850	7851	7852	7853	7854	7855	7856	7857	7858	7859	7860	7861	7862	7863	7864	7865	7866	7867	7868	7869	7870	7871	7872	7873	7874	7875	7876	7877	7878	7879	7880	7881	7882	7883	7884	7885	7886	7887	7888	7889	7890	7891	7892	7893	7894	7895	7896	7897	7898	7899	7900	7901	7902	7903	7904	7905	7906	7907	7908	7909	7910	7911	7912	7913	7914	7915	7916	7917	7918	7919	7920	7921	7922	7923	7924	7925	7926	7927	7928	7929	7930	7931	7932	7933	7934	7935	7936	7937	7938	7939	7940	7941	7942	7943	7944	7945	7946	7947	7948	7949	7950	7951	7952	7953	7954	7955	7956	7957	7958	7959	7960	7961	7962	7963	7964	7965	7966	7967	7968	7969	7970	7971	7972	7973	7974	7975	7976	7977	7978	7979	7980	7981	7982	7983	7984	7985	7986	7987	7988	7989	7990	7991	7992	7993	7994	7995	7996	7997	7998	7999	8000
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Layout Digital Board 1.5 (Part 1 Bottom View)


TR 06015a_001
250203



TR 06015b_001
180203




Digital Board Chrysalis 2.1: IDE, UARTS, RESET, BE




1100 A10
1102 B14
1103 G14
1104 G9
1105 C10
1106 I5
2100 A8
2101 E4
2102 D7
2103 D3
2104 D8
2105 D8
2106 D8
2107 D8
2108 A7
2109 E9
2110 E9
2111 E9
2112 G12
2113 E6
2116 F11
2119 I12
2120 I8
2124 I5
2125 D3
2127 A3
2128 D11
3080 H7
3081 H7
3082 F10
3085 C7
3086 C7
3088 I6
3091 H2
3092 I12
3093 I12
3094 E8
3095 C2
3096 H5
3097 I8
3098 I7
3099 I8
3100 A12
3101 A12
3102 B9
3103 A12
3104 B8
3105 B8
3106 A12
3107 B9
3108 A12
3109 B8
3110 A12
3111 B9
3112 A12
3113 B6
3114 D5
3115 B8
3116 B12
3117 I2
3118 B12
3119 A9
3120 B12
3121 F6
3122 D12
3123 F7
3124 B12
3125 G6
3126 B12
3127 G7
3128 B12
3129 G4
3130 C12
3131 C7
3132 F5
3133 C12
3134 H4
3135 C12
3136 C7
3137 G6
3138 C12
3139 C7
3140 C7
3141 C7
3142 G7
3143 C12
3144 G7
3145 C12
3147 D12
3149 D12
3150 I6
3152 D8
3154 D12
3156 D12
3157 D8
3159 D12
3161 D12
3162 E2
3163 D2
3164 D12
3165 D2
3167 E12
3168 E12
3170 E12
3172 E12
3173 F2
3175 E12
3176 B3
3178 E12
3180 D12
3184 F2
3185 G12
3186 G11
3187 G2
3189 H12
3191 H11
3192 H12
3195 H10
3197 H12
3199 I12
4101 A8
4110 F8
4111 H7
4113 F8
4115 D1
4116 G5
4117 E6

4118 F8
4119 F8
4121 H6
4122 B5
4123 B5
5100 C4
5102 E1
5103 H13
5104 I8
5108 A5
6100 E5
6101 E6
6106 D8
6107 D8
7101 F6
7102-1 A4
7102-2 A5
7102-3 B4
7102-4 B5
7104-1 H2
7104-2 I3
7104-3 D2
7104-4 E2
7105 D3
7106 E5
7107-1 F2
7107-2 F2
7107-3 G2
7107-4 H5
7108 G6
7111-1 F12
7111-2 H11
7111-3 G11
7111-4 H11
7111-5 H6
7111-6 H7
7111-7 H7
7111-8 H7
7111-9 H7
7111-10 H7
7111-11 H7
7111-12 H7
7111-13 H7
7111-14 H7
7111-15 H7
7111-16 H7
7111-17 H7
7111-18 H7
7111-19 H7
7111-20 H7
7111-21 H7
7111-22 H7
7111-23 H7
7111-24 H7
7111-25 H7
7111-26 H7
7111-27 H7
7111-28 H7
7111-29 H7
7111-30 H7
7111-31 H7
7111-32 H7
7111-33 H7
7111-34 H7
7111-35 H7
7111-36 H7
7111-37 H7
7111-38 H7
7111-39 H7
7111-40 H7
7111-41 H7
7111-42 H7
7111-43 H7
7111-44 H7
7111-45 H7
7111-46 H7
7111-47 H7
7111-48 H7
7111-49 H7
7111-50 H7
7111-51 H7
7111-52 H7
7111-53 H7
7111-54 H7
7111-55 H7
7111-56 H7
7111-57 H7
7111-58 H7
7111-59 H7
7111-60 H7
7111-61 H7
7111-62 H7
7111-63 H7
7111-64 H7
7111-65 H7
7111-66 H7
7111-67 H7
7111-68 H7
7111-69 H7
7111-70 H7
7111-71 H7
7111-72 H7
7111-73 H7
7111-74 H7
7111-75 H7
7111-76 H7
7111-77 H7
7111-78 H7
7111-79 H7
7111-80 H7
7111-81 H7
7111-82 H7
7111-83 H7
7111-84 H7
7111-85 H7
7111-86 H7
7111-87 H7
7111-88 H7
7111-89 H7
7111-90 H7
7111-91 H7
7111-92 H7
7111-93 H7
7111-94 H7
7111-95 H7
7111-96 H7
7111-97 H7
7111-98 H7
7111-99 H7
7111-100 H7


Digital Board Chrysalis 2.1: 1394




Digital Board Chrysalis 2.1: Audio PLL



1400	D14	3447	B11	5400	B13
1401	I5	3448	B10	5401	H12
2400	A9	3449	B11	5402	H12
2401	A9	3450	B10	5403	H1
2402	A9	3451	B11	5404	J6
2403	B12	3452	B10	5405	I12
2404	H12	3453	B11	5406	J12
2405	H13	3454	C10	7400	B2
2406	H13	3455	C11	7401	I1
2407	H13	3456	C10	7402	J6
2408	I12	3457	C11	F1401	D14
2409	I12	3458	C10	F1402	D14
2410	I13	3459	C11	F1403	D14
2411	I13	3460	C10	F1405	D14
2412	I13	3461	C11	F1407	D14
2413	I13	3462	C10	F1409	E14
2414	I13	3463	C11	F1411	E14
2415	I14	3464	C10	F1413	E14
2416	I14	3465	C11	F1415	F14
2417	I14	3466	C10	F1417	F14
2418	I12	3467	D11	F1419	F14
2419	I13	3468	D10	F1421	F14
2420	J12	3469	D11	F1423	G14
2421	J12	3470	D10	F1425	G14
2422	J13	3471	D11	F1427	G14
2423	J13	3472	D10	F400	A12
2424	J13	3473	D11	F401	A12
2425	J13	3474	D10	F402	A8
2426	J13	3475	D11	F403	C1
2427	J14	3476	D10	F404	D1
2428	J14	3477	D11	F405	I5
2429	J14	3478	D10	F406	I5
2430	I5	3479	D11	I400	I3
2431	I6	3480	D10	I401	J3
2432	I1	3481	E11	I402	I1
2433	J6	3482	E10	I403	J4
2435	A9	3483	E11	I404	E10
3021	I1	3484	E10	I405	F10
3400	A14	3485	E11	I406	F10
3401	A14	3486	E10	I407	J6
3402	A14	3487	E11	I408	J6
3403	A14	3488	E10	I409	J6
3404	A14	3489	E10	I410	J7
3405	A12	3490	E11	I411	J7
3406	A12	3491	E10	I412	J7
3407	A12	3492	E11	I413	B12
3408	A12	3493	F10	I414	H12
3409	A14	3494	F11	I415	H12
3410	B14	3495	F11	I416	I12
3411	B14	3496	F10	I417	J12
3412	B14	3497	J4	I418	A14
3413	B14	3498	G1	I419	A14
3414	B14	3499	G1	I420	A14
3415	B14	3820	D1	I421	A14
3416	B14	3821	D1	I422	A14
3417	C14	3822	D1	I423	A14
3418	C14	3823	D1	I424	B14
3419	C14	3824	D1	I425	B14
3420	C14	3825	D1	I426	B14
3421	C14	3826	D1	I427	B14
3422	C14	3827	E1	I428	B14
3423	C14	3828	B1	I429	B14
3424	D13	3829	B1	I430	B14
3425	C13	3830	B1	I431	C14
3426	C13	3831	B1	I432	C14
3427	C13	3832	B1	I433	C14
3428	C13	3833	C1	I434	C14
3429	D13	3834	C1	I435	C14
3430	E13	3835	C1	I436	C14
3431	F13	3837	J1	I437	C14
3432	F13	3838	J1	I438	A12
3433	F1	3839	J1	I439	A12
3434	F1	3840	H1	I440	F11
3435	F1	3850	H1		
3436	F13	3851	H2		
3437	G13	3852	I2		
3438	G13	3853	G2		
3439	G13	4401	I5		
3440	G13	4402	J4		
3442	B10	4403	I2		
3443	B11	4404	J2		
3444	B10	4405	J2		
3445	B11				




Digital Board Chrysalis 2.1: 1.8V Power






- 1500 C1
- 1501 E4
- 1502 E4
- 1503 E4
- 1504 E4
- 1505 C2
- 1506 A3
- 1507 D2
- 2512 A5
- 2514 A3
- 2515 B2
- 2516 B5
- 2518 C3
- 2519 C2
- 2521 D2
- 2524 D2
- 2525 E2
- 2526 E2
- 2527 B3
- 3503 C4
- 3504 C4
- 4500 D2
- 5501 A4
- 5502 A3
- 5503 B5
- 7500-1 A4
- 7500-2 B4
- 7501 A2
- F1501 C1
- F1502 C1
- F1505 D1
- F1506 D1
- F1509 D1
- F1510 E1
- F1512 E1
- F500 A4
- F501 A4
- F502 D1
- I500 B2
- I501 B3
- I502 A3
- I503 B3
- I504 C4
- I505 A4
- I506 B5
- I507 B5
- I508 C2
- I509 C2
- I510 C2
- I511 D2
- I512 D2

Digital Board Chrysalis 2.1: Prog. scan DAC




Digital Board Chrysalis 2.1: Flash SDRAM EEPROM





Layout Digital Board Chrysalis 2.1 (Top View)



0605 D1	2707 A3	3164 D3	3403 C2	3719 A2	4407 B2
0609 D3	2711 A2	3167 D3	3404 C2	3727 A3	4702 A3
1001 A3	2717 A2	3168 D3	3405 D2	3805 C2	4703 A3
1100 C3	2722 A2	3170 D3	3406 D2	3806 D2	4728 A2
1102 C3	2723 A2	3172 D3	3407 C2	3807 D2	4729 A2
1103 A3	2724 A2	3175 D3	3408 C2	3820 B1	4730 A2
1104 A2	2725 A2	3176 D3	3410 C2	3821 B1	4804 C3
1105 C3	2728 A2	3178 D3	3411 C2	3822 B1	4812 C3
1106 B3	2729 A2	3180 D3	3413 C2	3823 B1	4813 C2
1200 A1	2832 D2	3204 B1	3416 C2	3824 B2	4814 C2
1203 A1	2833 D2	3206 A1	3417 C2	3825 B2	4905 A3
1400 C1	2900 A3	3208 B1	3419 C2	3826 B2	4907 A3
1500 B3	2901 A3	3209 A1	3420 C2	3827 B2	4908 A2
1505 B3	2903 A3	3210 B1	3421 C2	3828 C1	4909 A2
1704 A2	2904 A3	3211 B1	3423 C2	3829 C1	5002 B3
1900 A1	2905 A3	3212 A1	3424 C1	3830 C1	5005 B3
1901 A2	2906 A3	3213 A1	3425 C1	3831 C1	5008 B3
1904 A3	2907 A3	3214 B1	3426 C1	3832 C2	5009 B3
2000 B3	2908 A3	3215 B1	3427 C1	3833 C2	5011 B3
2001 B3	2909 A3	3216 A1	3428 C1	3834 C2	5102 D3
2002 B3	2910 A2	3217 B1	3429 C1	3835 C2	5108 D2
2003 B3	2912 A3	3218 B1	3430 C1	3836 C2	5200 A1
2014 B3	2914 A3	3220 B1	3431 C1	3840 C1	5201 B2
2015 A3	2915 A3	3221 B1	3432 C1	3850 C1	5202 A1
2023 B3	2918 A2	3223 A1	3436 C1	3853 C1	5203 A1
2026 A3	2919 A1	3225 B1	3437 C1	3854 A3	5204 B1
2033 B3	2920 A2	3228 B1	3438 C1	3855 D2	5300 B1
2035 A3	2922 A2	3229 B1	3439 C1	3902 C1	5301 B1
2037 A3	2924 A3	3230 A1	3440 C1	3905 A3	5302 B1
2044 B3	2926 A3	3231 B1	3442 D2	3906 A3	5400 D2
2046 A1	2927 A3	3232 A1	3443 D1	3907 A3	5404 C1
2049 B3	2930 A1	3233 A1	3444 D1	3908 A3	5700 B2
2050 B3	2931 D3	3234 A1	3445 D1	3909 A1	5710 A3
2054 A3	2933 A3	3235 B1	3446 D1	3910 A1	5802 D1
2056 A3	2935 A3	3236 B1	3447 D2	3911 A3	5804 D2
2058 A3	2936 A3	3237 B2	3448 D2	3912 A3	5808 D2
2059 A3	2938 D3	3238 B1	3449 D2	3913 A1	5809 D2
2060 B3	2939 A3	3239 B2	3450 D2	3914 A1	5902 A3
2062 B3	2940 A3	3240 A1	3451 D2	3916 A1	5903 A3
2064 A3	3005 B3	3241 B2	3452 D1	3917 A2	5904 A2
2065 A3	3008 B3	3242 B1	3453 D2	3918 A3	5905 A1
2071 A3	3010 B3	3243 B2	3454 D2	3919 A3	5906 A1
2100 D3	3013 A3	3244 B2	3455 D2	3922 A2	5908 A3
2102 C3	3015 B3	3245 B1	3456 D2	3924 A3	5909 A1
2104 C3	3016 B3	3246 B2	3457 D2	3926 A3	5910 A3
2105 C3	3017 B3	3247 B2	3458 D2	3929 A2	5912 A3
2106 C3	3018 B2	3248 A1	3459 D2	3930 A3	5914 A2
2107 C3	3019 B3	3249 B2	3460 D2	3931 A3	5915 A2
2109 C3	3023 A3	3251 B2	3461 D2	3934 A3	6103 D3
2110 C3	3026 A3	3252 B2	3462 D2	3936 A3	6200 B2
2111 C3	3085 C1	3254 B2	3463 D2	3938 A3	7001 B3
2116 D3	3086 C1	3255 B2	3464 D2	3941 A3	7004 B3
2127 D2	3087 A1	3256 B2	3465 D2	3942 A3	7008 C3
2128 D3	3088 C1	3257 B1	3466 D2	3943 A3	7102 D3
2200 A1	3094 C3	3258 B2	3467 D2	3944 A3	7200 A1
2201 A1	3101 C3	3259 B2	3468 D2	3945 A3	7201 A2
2204 A1	3103 C3	3260 A2	3469 D2	3946 A3	7202 B2
2205 A1	3104 D3	3261 A1	3470 D2	3947 A3	7300 B1
2212 B1	3106 C3	3270 A2	3471 D2	3950 A3	7301 B1
2235 A1	3108 C3	3271 A2	3472 D2	3951 A3	7303 C1
2236 A1	3110 C3	3272 A2	3473 D2	3952 A3	7304 C1
2238 B1	3112 C3	3273 A2	3474 D1	3953 A3	7305 B1
2300 B1	3113 D2	3275 B2	3475 D1	3954 A3	7400 C2
2301 B1	3116 C3	3276 A2	3476 D1	4001 B3	7402 C1
2302 B2	3118 C3	3278 A2	3477 D1	4002 B3	7703 A2
2303 B1	3120 C3	3284 A1	3478 D1	4005 B3	7809 C3
2304 B1	3122 C3	3294 A2	3479 D1	4119 C1	7810 D3
2305 B1	3124 C3	3295 A2	3480 D1	4122 D3	7900 A1
2306 B1	3126 C3	3296 A2	3481 D1	4123 D2	7901 A2
2307 B1	3128 C3	3297 A2	3482 D1	4201 B1	7903 A2
2308 B1	3130 C3	3298 A2	3483 D1	4202 A1	7904 A3
2309 B1	3131 C3	3299 B2	3484 D1	4205 A1	7907 A3
2310 B1	3133 C3	3300 B1	3485 D1	4300 B1	7908 A3
2311 C1	3135 C3	3301 B1	3486 D1	4301 B1	7911 A3
2312 B1	3136 C3	3302 B1	3487 D2	4302 B1	
2400 D2	3138 C3	3303 B1	3488 D2	4303 B1	
2401 D2	3139 C3	3304 B1	3489 D2	4304 C1	
2402 C2	3140 C3	3305 B1	3490 D2	4306 B1	
2403 D2	3141 C3	3306 B1	3491 D2	4307 C1	
2408 D1	3143 C3	3307 B1	3492 D2	4308 B1	
2433 C1	3145 C3	3308 B1	3493 D1	4309 B1	
2435 C2	3147 C3	3309 B1	3494 D2	4311 B1	
2525 B3	3149 D3	3310 B1	3495 D2	4312 B1	
2526 B3	3152 C3	3311 B1	3496 D2	4313 B1	
2700 B3	3154 D3	3316 B2	3497 C1	4315 B1	
2703 A2	3156 D3	3317 B2	3498 C1	4316 C1	
2704 B2	3157 C3	3318 B2	3499 C1	4404 B2	
2705 B2	3159 D3	3319 B2	3702 B2	4405 B2	
2706 A2	3161 D3	3402 D2	3715 A2	4406 B2	

1000 B1	2409 C2	3007 B1	3291 B2	3956 A2	7107 B3
1201 A3	2410 C2	3009 A1	3292 B3	4003 B1	7108 A2
1401 C3	2411 C2	3011 B1	3293 B3	4004 B1	7111 B1
1506 C1	2412 C2	3012 B1	3315 A2	4007 A1	7112 B1
1507 C1	2413 C2	3014 B1	3320 A2	4101 D1	7302 B3
2004 B1	2414 C3	3020 B1	3400 D2	4110 B3	7401 B2
2005 B1	2415 C3	3021 A2	3401 D2	4111 B1	7500 C1
2006 B1	2416 C2	3022 B1	3409 C2	4113 B2	7501 C1
2007 C1	2417 C2	3024 A1	3412 C2	4115 B3	7701 A1
2008 C1	2418 C3	3025 A1	3414 C2	4116 C3	7702 A2
2009 B1	2419 C3	3080 B1	3415 C2	4117 B2	7801 C1
2010 B1	2420 C2	3081 A2	3418 C2	4118 C3	7802 D1
2011 B1	2421 C2	3082 B1	3422 C2	4121 B2	7803 C1
2012 C1	2422 C3	3090 B3	3433 C2	4203 A2	7804 D3
2013 C1	2423 C2	3091 B3	3434 C2	4204 A2	7805 C2
2016 A1	2424 C3	3092 B1	3435 C3	4305 B3	7806 D1
2017 A1	2425 C3	3093 B1	3503 C1	4310 B3	7807 C1
2018 A1	2426 C3	3095 B3	3504 D1	4314 B3	7808 D2
2019 B1	2427 C2	3096 C3	3700 A2	4401 C3	7811 C2
2020 B1	2428 C2	3097 B1	3701 A2	4402 C3	7812 D3
2021 B1	2429 C3	3098 B1	3703 A1	4403 C3	7813 D2
2022 A1	2430 C3	3099 B1	3704 A1	4500 C1	7814 D1
2024 B1	2431 C3	3100 B1	3705 A1	4701 A1	7902 A2
2025 B1	2432 B2	3102 D1	3706 A1	4800 C1	7905 A2
2027 B1	2512 C1	3105 C1	3707 A1	4801 C1	7906 A1
2028 B1	2514 C1	3107 C1	3708 A2	4802 C2	7909 A1
2029 B1	2515 D1	3109 D1	3709 A2	4803 D1	7910 A1
2030 B1	2516 C1	3111 C1	3710 A2	4805 D1	7912 A1
2031 B1	2518 D1	3114 B2	3711 A2	4806 D1	
2032 B1	2519 B1	3115 C1	3712 A2	4807 D1	
2034 B1	2521 B1	3117 B2	3713 A2	4808 C2	
2036 A1	2524 B1	3119 C1	3714 A2	4809 C1	
2038 B1	2527 D1	3121 A2	3716 A2	4815 D3	
2039 B1	2701 A2	3123 A2	3717 A2	4816 D2	
2040 B1	2708 A2	3125 A2	3718 A2	4817 D2	
2041 B1	2709 A2	3127 A2	3720 A2	4818 D2	
2042 B1	2710 A1	3129 A3	3721 A2	4819 D1	
2043 B1	2712 A2	3132 C3	3722 A2	4822 C1	
2045 B1	2714 A2	3134 A2	3723 A2	4900 A2	
2047 B1	2715 A2	3137 A2	3724 A2	4901 A2	
2048 A1	2716 A2	3142 C3	3725 A2	4902 A2	
2051 B1	2719 A2	3144 A2	3726 A2	4903 A1	
2052 B1	2720 A2	3150 B1	3801 C1	4904 A1	
2053 B1	2721 A2	3162 B3	3802 D1	4906 A1	
2055 B1	2726 A1	3163 B3	3804 D2	4910 A2	
2057 B1	2727 A1	3165 B3	3808 D1	4911 A3	
2061 A1	2806 D2	3173 B3	3809 D1	5001 A1	
2063 A1	2807 D2	3184 B3	3810 D1	5003 B1	
2066 B1	2808 D2	3185 A1	3811 D1	5010 A1	
2067 B1	2809 D3	3186 B1	3812 D1	5100 B3	
2101 B2	2810 D2	3187 B3	3813 D1	5103 B1	
2103 B3	2811 D3	3189 B1	3814 D1	5104 B1	
2108 D1	2812 D2	3191 B1	3815 D1	5401 C3	
2112 A1	2814 D3	3192 B1	3816 C1	5402 D3	
2113 B2	2818 D1	3195 B1	3817 C1	5403 B2	
2119 B1	2819 D1	3197 B1	3818 C2	5405 C3	
2120 B1	2820 D2	3199 B1	3819 C2	5406 C2	
2124 B1	2821 D2	3200 A2	3837 B2	5501 C1	
2125 B3	2822 D2	3202 A2	3838 B2	5502 C1	
2202 A3	2823 D2	3203 B3	3839 B2	5503 C1	
2203 B3	2824 D2	3205 A3	3841 D2	5701 A2	
2206 A3	2825 D2	3207 A3	3842 D2	5702 A2</	


8. Alignments

8.1 Alignment Instructions Analog Board

Test equipment:

1. Dual-trace oscilloscope
Voltage range : 0.001 ~ 50 V/div
Frequency : DC ~ 50 MHz
Probe : 10:1, 1:1
2. DVM (Digital voltmeter)
3. Frequency counter
4. Sinus generator
Sinus : 0 ~ 50 MHz
5. Test pattern generator

How to read the adjustment procedures:



Front End (FV)

Service tasks after replacement of IC 7710, coil L5710 and L5711:

1 AFC Adjustment:

Purpose: Correct adjustment of demodulator AFC - circuit

Symptom, if incorrectly set:

Bad or disturbed TV channel reception.

PAL - AFC adjustment [5711]:

TP	ADJ.	MODE	INPUT
IC 7710 Pin 17 (F708)	L5711	TUNER	38,9MHz 500mV _{pp} at Tuner 1705, Pin 11 (F710, IF-out)
DISC		MEAS.EQ.	SPEC.
		DC Voltmeter Frequ. Generator	2,5V ±0,1V

Storage in NVRAM via command mode interface of DSW:

After adjustment, the AFC reference value has to be stored in the NVRAM.

This reference value is 256 * measured voltage/Ucc. Ucc is 5.0V.

Store the reference value via command 732 , followed by the ref. value.

Example: DD:> 732 128

2 HF - AGC adjustment [3724]:

Service tasks after replacement of IC 7710:

Purpose: Set amplifier control.

Symptom, if incorrectly set:

Picture jitter if input level is too low and picture distortion if input level is too high.

TP	ADJ.	MODE	INPUT
Tuner 1705 Pin 11 (F710, IF-out)	R3707	Set tuned to channel 25 503.25 MHz	5mV(74dBμV) on aerial input PAL white picture, audio IF on, no modulation
DISC		MEAS.EQ.	SPEC.
		Oscilloscope Video Pattern Generator	500mV _{pp} +/-0.5dB (use a 10:1 probe)

3 Attenuating the 40.4 MHz [5710]: (SECAM only)

Service tasks after replacement of coil 5710:

Purpose: To attenuate the band I carrier rests.

Symptom, if incorrectly set:

Bad picture quality when the filter attenuates the picture carrier (38.9MHz).

TP	ADJ.	MODE	INPUT
OFW 1701 Pin 1 (F709)	L5710	TUNER	40.4 MHz, 200mV _{rms} at Tuner 1705, Pin 11 (F710, IF-out)
DISC		MEAS.EQ.	SPEC.
		Oscilloscope, Sinus Generator, Counter	adjust minimum amplitude

If the adjustment is correct the signal at pin 1 of OFW [1701] must be smaller than the input signal amplitude by at least 6 dB.

Figure 8-1

8.2 Reprogramming Procedure of NVM on the Microprocessor Sub PCB

The NVM, item 7808, on the Microprocessor Sub board contains the following factory settings:

1. Clock correction factor
2. AFC reference value
3. Slash version

The settings 1,2 and 3 are stored in the NVM during the production of the analogue board.

The slash version is stored at the end of the production line of the set.

In case of failure, the NVM must be replaced by an empty device. By way of commands via the Diagnostic Software or via ComPair, the factory settings must be restored in the NVM.

8.2.1 Clock Correction Adjustment

To guarantee an exact function of the real time clock, an adjustment of the clock frequency is possible. The adjustment value is stored in the NVM.

Procedure:

- put the set in service command mode
- execute command 722 for Digital Board 1.5 Empress or 1117 for Chrysalis to initiate that a signal with 32768 Hz is available on pin 3 of connector 1988
example:
DD:>722 or DD:>1117
- measure the frequency fmeas of the Clock Crystal with an accuracy of 0.1 Hz.
- Calculate the parameter to be entered: $32768/fmeas * 106$
- Normally the parameter must be between 999902 and 1000097. If the parameter and therefore the frequency of the crystal is outside this range, the crystal must be replaced.
- Execute command 721 for Empress or 1118 for Chrysalis with the parameter as input
example:
DD:>721 1000023 (Empress)
or DD:>1118 1000023 (Chrysalis)

8.2.2 AFC Reference Voltage Tuner

This function stores the reference voltage for the tuner in the NVM. Before this value can be stored, the AFC adjustment, described in the adjustment instructions of the analogue board, must be carried out.

Procedure:

- Adjust AFC circuit
- Calculate the reference value
- Execute command 732 for Empress or 1119 for Chrysalis and use the calculated reference value as parameter
example: DD:>732 128 (Empress)
or DD:>1119 128 (Chrysalis)

8.2.3 Slash Version

The slash version is stored with command 715 for Empress or 1217 for Chrysalis, followed by the slash version as parameter. The slash versions used in DVDR75 and DVDR80 are the following:

- DVDR80/00x/02x: SV 65
- DVDR80/05x: SV 66
- DVDR75/00x/02x: SV 67
- DVDR75/05x: SV 68
- DVDR70/00x/02x: SV 69
- DVDR70/05x: SV 70

Example:

DD:>715 65 (Empress)

or DD:>1217 65 (Chrysalis)

Reset of Slash Version

Use command 729 for Empress or 1115 for Chrysalis to reset the analogue board to the default setting.

Procedure:

- Put the set in DSW command mode
- Execute command 729 (Empress) or 1115 (Chrysalis) with the following parameters:
DD:> 729 w 0xAE 2 0xD0 0x00 (Empress)
DD:> 1115 w 0xAE 2 0xD0 0x00 (Chrysalis)
- Leave the DSW command mode and start up the set in application mode
No background is visible on the TV screen. The analogue board is ready to accept the appropriate slash version

8.3 Rework Procedure IEEE Unique Number

8.3.1 Scope:

The procedure describes how to upgrade sets with a unique number after repair. This unique number is stored in the NVRAM (item 7201) of the digital board at the end of the production line.

This procedure is only valid or necessary when:

- The digital board is replaced
- NVRAM on the digital board is replaced
- NVRAM is cleared

In all other cases the repaired set retains its unique number.

The procedure defines several means to re-assure the unique number depending on the possibilities of repair or the state the faulty set is in.

8.3.2 Handling:

State of original (defective) board:

1. The digital board starts up in Diagnostics Mode: follow procedure A to retrieve the valid unique number
2. The digital board does NOT start up in Diagnostics Mode: follow procedure B.

8.3.3 Procedure A

1. Connect defective digital board to PC via serial cable (3122 785 90017)
2. start up hyper terminal or any other serial terminal via the correct settings (DSW command mode interface)
3. read out existing unique number via nucleus 403 (Empress) or 1208 (Chrysalis)
example:
DD:> 403 40300: DV Unique ID = 00D7A1FC6C Test OK @
4. note read out
5. program new digital board via nucleus 410 (Empress) or 1207 (Chrysalis)
example:
DD:> 410 00D7A1FC6C 41000: Test OK @

The set has now the original unique number

8.3.4 Procedure B

- Note the serial number of the set example:
VN050136130156
 - VN = production centre (VN....Szekesfehervar).
 - According to UAW-500: V=22 and N=14
 - 05 = change code (this is not used for this calculation)
 - 01 = YEAR
 - 36 = Production WEEK
 - 130156 = Lot and SERIAL number
- Calculate the unique number: this number always exists out of 10 hexadecimal numbers.
- First 5 numbers: First we calculate a decimal number according to the formula below: $35828 \times \text{YEAR} + 676 \times \text{WEEK} + 26 \times A + H + 8788$ The figures are fixed, YEAR + WEEK + factory code (A + H) are variable Example: $35828 \times 01 + 676 \times 36 + 26 \times 1 + 8 + 8788 = 68986$ (decimal) Then we translate the decimal number to a hexadecimal number. example: 68986 (decimal) = 10D7A (hex)
- Last 5 numbers: The last 5 numbers exist out of the Lot and SERIAL number.
We have to translate the decimal number to the next 5 hexadecimal numbers: Example: 130156 (decimal) = 1FC6C (hex)
- Program new digital board via nucleus 410 (Empress) or 1207 (Chrysalis). Therefore we use the 10 hexadecimal numbers we calculated above:
example:
DD:> 410 10D7A1FC6C
or DD:> 1207 10D7A1FC6C
41000: Test OK @

The set has now its original unique number

8.4 Adjustment DVIO 1.8 PCB

This adjustment sets the free running frequency of the VCO of the audio PLL. It should be carried out after replacement of IC 7604.

- Disconnect DVD+RW set from the mains.
- Plug DVIO1.8 board via edge-connector onto Digital Board (DVIO board is vertically oriented, so that both sides of the PCB are accessible for measurements).
- Connect DVD+RW set to the mains.
- Turn DVD+RW set on and select any video input source except the DV input.
- Check the signal at test point F611 with an oscilloscope. The signal should be 5V digital with 50% duty-cycle.
- Measure the frequency of the signal at test point F610 and adjust the potentiometer 3605 to get a frequency of 12.288MHz 50kHz (after removing the screwdriver from the potentiometer).
 - In case the frequency can not be increased sufficiently, replace capacitor 2618 by NP0-type capacitor with 18pF. Adjust afterwards again the frequency with the potentiometer.
 - In case the frequency can not be decreased sufficiently, add (3pF-10pF) trim-capacitor in parallel to capacitor 2618 or replace capacitor 2618 by NP0-type capacitor with 27pF. Adjust afterwards again the frequency with the potentiometer (and/or trim-capacitor).
- Switch DVD+RW set to Stand-by mode.
- Disconnect the DVD+RW set from the mains.
- Plug DVIO1.8 board directly (without edge connector) onto Digital Board.
- Connect DVD+RW set to the mains.
- Connect a DV-source that transmits DV-video data with audio to the DVD+RW set.
- Turn DVD+RW set on, select DV input, and switch DVD+RW set appropriately to output the decoded signal. Audio should be output without distortion.

8.5 Alignments after replacing the Boot EEPROM 7810 in sets with Digital Board Chrysalis

The NVM, item 7810, on the Digital Board Chrysalis contains the "Diversity String" that tells the software during startup which hardware version is present.

The setting is stored in the NVM during the production of the Digital Board Chrysalis

In case of a fault the NVM must be replaced by a programmed device containing the boot script.

Via the Diagnostic Software the Diversity String is stored with command 1226, followed by the Diversity String as parameter.

The diversity strings used in DVDR70/0x1 and DVDR75/0x1 are the following:

Chrysalis Board Type	String
E1	44424849A8E9200145310000000000002303030000101020100000020040000
E1_AV3	444248492721200145315F41563300003203030000101020001000020040000
E2	44424849BAE920014532000000000000024030300000000020100000020040000
E2_AV3	444248493921200145325F41563300003303030000000020001000020040000

Example:

DD:> 1226 44424849A8E92001453100000000000023030300000101020100000020040000
122600
Test OK @

E1 ...Digital Board Chrysalis version Euro 1 (with DV input) for DVDR75/0x1 with Basic Engine VAE8020.

E1_AV3...Digital Board Chrysalis version Euro 1 (with DV input) for DVDR75/0x1 with Basic Engine VAD8031.

E2 ...Digital Board Chrysalis version Euro 2 (without DV input) for DVDR70/0x1 with Basic Engine VAE8020.

E2_AV3...Digital Board Chrysalis version Euro 2 (without DV input) for DVDR70/0x1 with Basic Engine VAD8031.

With command 1228 the settings can be displayed.

9. Circuit-, IC descriptions and list of abbreviations

9.1 Display Board

9.1.1 Microcontroller

The core element of the Display Control unit is the microcontroller TMP87CH74AF [7110]. The TMP87CH74AF is an 8 bit microcontroller fitted with 32kB ROM and 1kB RAM. It requires 5V supply and is responsible for the following functions:

- Interface to Central Controller-P
- Evaluation of the keyboard matrix
- Decoding the remote control commands from the infra-red receiver
- Activation and control of the local display
- Heater voltage generation

The 8 MHz resonator (Pos. 1111) generates the system clock. The reset is generated by the CC-P via "POR_DC"-signal where the transistor [7106] is used as a level-shifter from 3V3 to 5V.

9.1.2 Interface to the Central Control μ P

The communication to the main microcontroller (CC) on the P-Sub-PCB is done via I2C-Interface, where the TMP87CH74AF acts in slave-mode.

An additional wire ("INT"-line) is used to signal the Central controller that data are ready, e.g. when a key has been pressed.

9.1.3 Evaluation of the keyboard matrix

There are 12 different keys on the display board. A resistor network is used to generate a specific direct voltage value, depending on the pressed key. Via the resistors 3107 and 3102 on the analog/digital (A/D) ports (7103 pin 37 and 38) the evaluation is done.

9.1.4 IR receiver and signal evaluation

The IR receiver [7107] contains a selectively controlled amplifier as well as a photo-diode. The photo-diode changes the received infra red transmission (approx. 940nm) to electrical pulses, which are then amplified and demodulated. On the output of the IR receiver [7107], a pulse sequence with TTL-level, which corresponds to the envelope curve of the received IR remote control command, can be measured. This pulse sequence is fed into the controller for further processing via port TC1 [7103, pin20].

9.1.5 Vacuum Fluorescence Display

The VFD "BJ900GNK" [POS 7100] is fully controlled by the microcontroller. The μ C also includes the driving stages. Only two additional drivers [POS 7101 and 7102] are necessary for the grids 8 and 9 because of their large size.

9.1.6 VFD Heater Voltage Generator

The circuit around POS [7106, 7108 and 7109] is used to generate a proper AC-Voltage for the filament of the VFD. For this the microcontroller generates an appropriate rectangular signal with 50% duty-cycle and a frequency of 30 kHz at pin 19. Pos. [5104] and [2113] are acting as a resonance-circuit. Via Zener-Diode (POS[6100]) and resistors [3119, 3122 and 3123] the two heater-pins of the VFD ("FIL1" and "FIL2") are clamped so that the grids and segments can be fully switched off.

9.1.7 REC-LED

The REC-LED-ring is made with 3 red LED, controlled via pin 3 (only for flashing) and pin 12 for on/off switching, of the microcontroller. The POS [7105] is used as a driver for the led.

9.1.8 EPG-LED

The EPG led is a white led and controlled from the pin 14 from the microcontroller. The POS [7110] is used as a driver for the led.

9.1.9 TRAY-LED

There are 6 leds (chip) necessary to illuminate the tray, these 6 leds are located on a little sub-pcb connected over a 4 pin connector POS [1911] from the DC-print. The leds are controlled from pin 11 of the microcontroller.

9.2 Microcontroller Sub Board (UP SUB Board)

9.2.1 General

This small PCB is directly soldered in on top of the Analogue-Board.

It is used with no diversity in all three different basic versions (Europe, NAFTA and APAC-Pal). Only the software being loaded into the external Flash-memory is not the same.

9.2.2 Microcontroller

The main part of the Sub-PCB is the central controller (CC) μ P [7804] TMP91CW12AF, which is a 16-bit CPU with 128kBROM and 4kB RAM.

It works with a 3V3 supply and a system clock of 24,576MHz [1801].

The 3V3-supply is made out of the "5VSTBY" by the circuit around [7816].

After connecting the set to the mains (power-up) the IC [7806] generates a reset pulse. This signal ("IPOR") is directly fed to first priority interrupt input (pin 63) for power fail detection and also to the Reset-Input of the CC (Pin30) via [7802], which is necessary to generate a reset only during power-up. In case of power fail pin 30 of the CC must be kept high (3V3).

The internal memory of the CC is too small for all necessary demands. Therefore an external Flash-ROM [7805] with 1MByte in size and a RAM [7803] with 128kByte are necessary. Both parts are connected to the μ P via a parallel address-/data-bus. The lower eight bus-lines (AD0 to AD7) are multiplexed by [7801] and the "ALE"-signal of the CC.

For updating of the software the external Flash-ROM can be reprogrammed by the μ P. During this process [7807] is switched on by the "WE"-signal.

When no mains is connected, the CC is supplied via Gold-Cap [2816] during the power backup period. The diode [6802] prevents unwanted current consumption of other components. The internal ROM of the μ P holds the program code for the Real-Time-Clock. Only the microprocessor is supplied by the backup cell, not the external memories and the μ P operates in a low frequency mode with the clock crystal [1805] only (32.768 kHz). To adjust the clock the frequency can be measured at pin 87 of the μ P in a special test-mode.

9.2.3 Control-Interfaces

The CC is communicating with the digital board via a serial connection, which operates at a speed of 19,4 kbit/s ("D_DATA"-, "A_DATA", "D_RDY"- and "A_RDY"-signal on

[1986]). By generating a high level on pin 16 of the CC the digital PCB can be reset (inverter [7817] in between). Most of the other parts are controlled by the μ P via I2C-bus ("SDA"- and "SCL"-signal). The FETs [7821] and [7822] are used for adaptation of the 3V3-level on CC-side to the components supplied with 5V. The CC can also reset the display-board- μ P by pulling pin 39 to high.

The transistor [7819] acts as a level shifter for the "INT"-signal. In the European sets a bi-directional interface is established between the recording unit and the TV device at pin 10 of the Scart ("P50"-line/Easy Link). The processing is done via pin 14 (output) and pin 38 (input) of the CC and the circuit around [7813], [7814] and [7815].

9.2.4 EEPROM

The EEPROM M24C16 [7808] is an electrical erasable and programmable, non-volatile memory. The EEPROM stores data specific to the device, such as the AFC-reference value of the Europe IF-part, the clock-correction-factor, etc. It is accessed by the μ P via the I2C-bus.

9.2.5 Sync Separator

To detect whether a video signal is available or not a separate IC [7825] is used to extract the sync information out of the video signal that is also routed to the digital board for recording. While on the input a low-pass-filter ([2823] and [3869]) limits the bandwidth an additional filter (circuit around [7818]) on the output avoids distortions. Afterwards the sync-signal is routed to pin11 of the CC.

9.2.6 Fan Control

To avoid unwanted temperatures inside the set (especially the Laser on the OPU of the drive is very sensitive) a fan is located on top of the basic engine. The speed control is dependent on the ambient temp. A NTC resistor [3134] located on the display board measures the temperature. An operational amplifier [7902-B] generates a proper voltage, which is then fed to the engine ("BE_FAN"-line). Below 28°C ambient temp. the fan-voltage is approx. 5V and is increased to 10V when the ambient temperature goes up to approx. 38°C. The second part of the Op-Amp. [7902-A] prevents damage of any temperature-sensitive part in case the NTC or the wire in between is damaged. It acts as a comparator and pulls the "BE_FAN"-signal to 10V. As the fan has to be stopped in case the tray of the drive is open this voltage is "killed" by the CC ("FAN_OFF"-signal). The double-diode [6901] acts for both Op.-Amp.-circuits. The circuit is also prepared for a set-fan (circuit around the Op-Amp. [7902-C]).

9.3 Analog board Europe

9.3.1 General

This PCB consists out of the following parts:

- Power-Supply-Unit
- Frontend (Audio & Video)
- Input/Output-switching
- Audio ADC- & DAC-processing
- VPS/PDC- and Text-Data slicer
- Analog Follow-Me Circuit

All functional groups are either controlled via I2C-bus or via separate signal lines by the Central-Controller on the μ P-Sub-Board. This sub board is directly soldered in onto the analog PCB. During Stand-By mode of the set, several parts are not supplied (Tuner, MSP, ...). The microprocessor is running and maintains the clock of the set.

To avoid bus blockades the I2C-bus ("SCLSW" & "SDASW") to/from these units is decoupled via transistors [7419], [7420] from the general bus ("SCL" & "SDA").

9.3.2 Power Supply Unit

Functional principle:

This power supply works in the way of a flyback converter. In the mains input part [1931 to 2309], the mains voltage is rectified and buffered in the capacitor [2309]. From this direct voltage at [2309] energy is transferred into the transformer [5300, pins 7-5] during the conductive phase of the switching transistor [7307] and is stored there as magnetic energy. This energy is passed to the secondary outputs of the power supply in the blocking phase of the switching transistor [7307]. With the switch-on time of the switching transistor [7307], the energy transferred in every cycle is regulated in such a way that the output voltages remain constant regardless of changes in the load or mains voltage. The power transistor is driven by the integrated circuit [7313].

Mains input part:

The mains input part extends from the mains socket [1931] to the capacitor [2309]. The diodes [6301, 6302, 6305 and 6306] rectify the AC supply voltage, which is then buffered by the capacitor [2309]. The common mode coil [5302] and capacitor [2302] work as a filter to block interference arising in the power supply from the mains. Components [1302], [3306] and [3304] protect the power supply against short-term over voltages in the mains, e.g. caused by indirect lightning.

Start-up with Mains-on:

After connecting the power cord to the mains, the capacitor [2325] is loaded via a current source between pin 8 and pin 1 in the IC [7313]. Once the voltage on [2325] and therefore the supply voltage V_{cc} of the IC [7313] has reached approx. 11V, the IC starts up and provides pulses at its output pin 5. These pulses are used to drive the gate of the power transistor [7307]. The frequency of these pulses is depending on load and mains voltage. The current consumption of the IC is approx. 5 mA at V_{cc} in normal mode.

If V_{cc} drops to below approx. 9V (e.g. with power limitation) or if V_{ac} exceeds approximately 16V (e.g. interruption of the control loop), the output of the IC [7313, pin 5] is blocked and a new start-up cycle begins. (See also "Overload, Power Limitation, Burst Mode" section)

Normal operation:

With the power supply in normal mode, the periodic sequences in the circuit are divided primarily into the conductive and blocking phase of the switching transistor [7307]. During the conductive phase of the switching transistor [7307], current flows from the rectified mains voltage at capacitor [2309] through the primary coil of the transformer [5300, pins 7-5], the transistor [7307] and resistors [3321, 3352] to ground. The positive voltage on pin 7 of the transformer [5300] can be assumed as constant for a switching cycle. The current in the primary coil of the transformer [5300] increases linearly. A magnetic field representing a certain value of the primary current is formed inside the transformer. In this phase, the voltages on the secondary coils are polarized such that the diodes [6300, 6303, 6307, 6308, 6310, 6313, 6317 and 6319] block. From the controller [7315] a current is supplied into the CTRL input on the IC [pin 3, 7313] via optocoupler [7314]. Once the switch on time of the switching transistor [7307] - that corresponds to the current supplied into the CTRL input - has been reached, the switching transistor [7307] is switched off. When the switching transistor has been switched off, the blocking phase begins. No more energy will be transferred into the transformer. The inductivity of the transformer will still attempt to keep the current flowing at a constant level ($U=L \cdot di/dt$). Switching off transistor [7307] interrupts the primary current circuit. The polarity of the voltages on the transformer is reversed, which means that the diodes [6300, 6303, 6307, 6308, 6310, 6313, 6317 and 6319] become conductive and current flows into the capacitors [2305, 2312, 2319, 2322, 2326 and 2328] and the load. This current is also ramp-shaped (di/dt negative, therefore decreasing).

The feedback control for the switched-mode power supply is done by changing the conductive phase of the switching transistor so that either more or less energy is transferred from the rectified mains voltage at [2309] into the transformer. The regulation information is provided by voltage reference [7315]. This element compares the 5V-output voltage via voltage divider [3332, 3333, 3334] with an internal 2.5V reference voltage. The output voltage of [7315] passes via an optocoupler [7314] for insulation of primary and secondary parts as a current value into pin 3 on the IC [7313]. The switch-on time of the transistor [7307] is inversely proportional to the value of this current.

Overload, power limitation, burst mode:

With increasing load on one or more of the power supply outputs, the switch-on time for the power transistor [7307] increases, and thus also the peak value of the delta-shaped current through this power transistor. The equivalent voltage of this current profile is passed from resistors [3321] and [3352] via [3365] to pin 5 of the IC [7313]. If the voltage on pin 2 reaches approx. 0.4V in one switching cycle, the conductive phase of the switching transistor is ended immediately. The check is done in each individual switching cycle. This process ensures that no more than approx. 60W can be taken out from the mains (= power limitation).

If the power supply reaches the power limit, the output voltages and the supply voltage Vcc on pin 1 of the IC [7313] will be reduced following further loading. If Vcc is less than approx. 9V at any point during this process, the output of the IC [7313, pin 6] is blocked. All output voltages and Vcc decrease and a new start-up cycle begins. If the overload status or short-circuit remains, the power limitation will be activated immediately and the voltages will again decrease, followed by another start-up cycle (Burst Mode). The amount of power taken up from the mains in burst mode is low.

Standby modes:

In the 'AV-Standby' operating mode of the set, the 'ION' control line is primarily used to switch off all output voltages for Basic Engine and Digital Board (supplies 3V3, 5V, 12V, 5N and 4V6 at Connectors 1932 and 1933) of the power supply. This reduces the amount of power taken from the mains. In Low Power Standby mode additionally the 'STBY' control line is used to switch off output voltages 5SW and 8SW. This reduces power consumption to less than 3W, if additionally the display is switched off. The power supply will continue operating in Standby mode with a switching frequency of approx. 25 kHz.

9.3.3 Frontend

This unit is designed to support two basic versions, which are distinguished by a different assembly variant only (one for multistandard and the second for Pal-I only) and comprises the following parts:

- Tuner UV1316K [1705]
- IF amplifier & video demodulator IC TDA 9818/9817 [7710]
- Sound processor MSP3415G [7600]

Tuner and IF selection

The Tuner [1705] converts the RF-signal coming from the antenna input to an IF-signal. The tuner is fully controlled via I²C-bus of the CC-μP. [1705] is also equipped with a "passive-loop-through" between antenna-in and -out to save power in stand-by of the set, when the complete part is not supplied. The IF frequency of the video carrier is 38.9 MHz for all systems except SECAM L' (34,0 MHz).

A quasi-split audio system is used. Separate surface-wave filters (SAW) are required. [1701], [1703] for video, [1702] for audio. [1701] is switched into the signal path for DK/I-SECAM L/L' reception, if the signal "SFS_TS" is "high". In this case the switches [7704], [7705] are open and the diode [6703] is conducting. [1703] is switched into the signal path for BG reception ("SFS_TS" is "low"). Then the switch [7712] is open and the diode [6704] is conducting. For DK/I-SECAM L/L'

reception, an additional circuit for suppressing the audio carrier of the adjacent channel is used. This circuitry is adjusted by coil [5710] for maximum suppression at 40.4MHz.

IF demodulator


The signal from the tuner and IF-selection circuit is processed by the demodulator IC TDA 9818/9817 [7710]. The signal "PSS" to pin 3 switches between demodulation of positive (SECAM only) or negative modulated video carriers. A QSS-audio-IF signal SIF1 is generated for demodulation in the sound processor [7600]. The audio-IF carrier is selected in the audio SAW filter [1702]. This filter is switched for SECAM L'. If the signal "SB1" is "high", the switch [7714] is closed and the diode [6705] is not conducting. For all other standards the diode [6705] is conducting and the switch [7714] is open. The output signal of this SAW filter is firstly processed in the TDA 9818. Audio carriers are converted from the tuner IF level to the audio IF position and further processed in the audio demodulator [7600]. The AFC coil [5711] on the TDA 9818/9817 is adjusted so that when a frequency of 38.90 MHz is supplied to the IF output of the tuner, the AFC voltage on pin 17 of [7710] is 2.5V. The setting of the picture carrier frequency for SECAM L in the TDA 9818 is achieved by connecting pin 7 of the IC via a resistor [3710] to ground. The switch [7701] and the signal "SB1" do this. The HF-AGC is set using the potentiometer [3724] so that, with a sufficiently large antenna input signal (74 dBμV), the voltage at the IF output of the tuner [1705] pin 11 is 500 mVpp. This setting must be carried out when the audio carrier is switched off. The demodulated video signal appears on pin 16 of [7710]. The AGC voltage at pin 4 is used to determine the antenna signal strength after a buffer [7717] with the signal "AGC" and an analog input port of the CC-P. The trap [1704] reduces the sound carrier remainders in the video for BG standards. The trap [1706] works in the same way for the Pal-I standard only. For all other standards the switch [7713] is closed via [7706] and "SFS_TS"-line set "high" to bypass this trap. In these cases the selectivity of the SAW filter [1701] is sufficient. The coil [5713] for non-BG standards realizes a frequency response correction. This correction is not desired for SECAM L' and therefore short-circuited by [7716] (signal SB1 is "high" and [7702] has on-status). The demodulated video signal "VFV" is available after the buffer and limiting stage for noise peaks [7711]. The FM-PLL demodulator function of TDA 9818 is not necessary and therefore deactivated by the resistor [3739].

Audio demodulator

The sound demodulation is done by the MSP3415 [7600], which is also fully controlled via I²C-bus by the CC-P (determination of bandwidth, amplitude, standard, ...). The audio signals are available at pin 30 and pin 31 of [7600] and fed as "AFER"- & "AFEL"-line to the audio-I/O for further processing.

9.3.4 Audio routing

Audio IO Europa Overview



11.03.2002 Vers. (

The processing of audio is always done in stereo (e.g. separate left- and right-channel) and the complete switching is realized by using HEF4052, which is a dual four-to-one multiplexer. In principle there are three independent selectors:

a) Scart 1-Output-Path:

Pos [7504] is used to select either Scart 2-Input ("AIN2L"/"AIN2R") or the signal directly from the audio DAC [7004] ("ALDAC"/"ARDAC") as the output source for Scart 1 ("AOUT1L"/"AOUT1R").

The control is done by means of the lines "ASC1S" coming from [7408] (IC [7408] acts as a port expander for the CC-P) and "IASC1M", which is directly coming from the CC. Pos [7412] is used for level adaptation (3V3 to 5V) for the "IASC1M"-signal.

b) Scart 2-Output-Path:

Pos [7503] selects between Scart 1-Input ("AIN1L"/"AIN1R"), signals from the internal frontend ("AFEL"/"AFER") via MSP [7600] or audio directly from the DAC [7004] ("ALDAC"/"ARDAC"). The outputs of this switch are routed to Scart 2 ("AOUT2L"/"AOUT2R"). This switch is controlled via "VSA1"- and "VSA2"-line. These lines come from [7408] that is acting as a port expander for the CC-P.

c) Record-Path:

Pos [7501] selects either signals from Scart 1 ("AIN1L"/"AIN1R") or Scart 2 ("AIN2L"/"AIN2R") or Cinch-Front ("AINFL"/"AINFR") or the MSP [7600] ("AFEL"/"AFER") and routes to the audio ADC [7007] ("ALADC"/"ARADC") for record purposes. The switch is controlled via "RSA1"- and "RSA2"-signals.

These signals come from the MSP [7600], which acts as a port expander of the CC-P. As there can also exist a fifth input in case of DV-In is present the corresponding analog audio signals from the DVIO-board are firstly routed via extra cable and connector [1960] to the MSP. The MSP acts as a preselector between audio from internal frontend or the DV-Input.

Each of these three selectors ([7501], [7503] & [7504]) has a separate Op-Amp on the output for level-adaptation-, performance- and line-driving-reasons. [7505-A & -B] for record, [7502-C & -D] for Scart 1-Output and [7502-A & -B] respectively for Scart 2. Every audio output line on the two Scart connectors can be "killed" (muted) by an extra transistors ([7506], [7508], [7509] & [7511]), which can be activated by the "AKILL"-line. This signal is generated by the circuit around [7404]/[7421] and is a combination of the "KILL"- from the CC-P and the "IPFAIL" of the power-supply-unit.

d) Line-Out-Path:

see chapter 9.3.5

e) Digital Audio Output-Path without IOE-Print:

Additionally to analog audio the set is also equipped with a digital output via cinch plug [1951]. The signal is generated on the dig. board and routed via audio interface cable and connector [1900] to the Ana-PCB. Here the "DAOUT"-line first passes a 6-fold inverter [7580] being used as a driver and for performance reasons (noise reduction, jitter, etc.). Afterwards a transformer [5580] is necessary to achieve the correct level and also to have a floating output with isolated ground before the signal is fed via [3580] to cinch plug [1951]. The capacitor [2580] performs an AC-coupling between connector- and set-ground.

f) Digital Audio Output-Path with IOE-Print:

In case of usage of the IOE-print the digital audio signals (input and output) are directly routed from digital board via interface cable to plug [1920] on the IOE-print. The "DAOUT"-line is splitted into two signals, one for cinch out and one for optical out. The signal to cinch out first passes a 5-fold inverter [7250] being used as a driver and for performance reasons (noise reduction, jitter, etc.). Afterwards a transformer [5250] is necessary to achieve the correct level and also to have a floating output with isolated ground before the signal is fed via [3259] to the cinch plug [1925] (or [1926-B] in case of option

"DIGITAL IN"). The capacitors [2256] and [2266] perform an AC-coupling between connector- and set-ground. The second "DAOUT"-signal is fed directly via [3264] to the optical out transmitter [6255].

g) Digital Audio Input-Path with IOE-Print:

There are two possibilities for a digital audio input signal in case of option "DIGITAL IN". One is the signal from the optical receiver [6259], which is routed via [3269] directly to plug [1920]. The second is the signal from the cinch plug [1926-A]. This signal then passes an inverting amplifier [7250-6] and is then routed via [2253] to the plug [1920].

9.3.5 Audio ADC/DAC

a) PCBs with AD1852 [7004]:

The conversion of analog audio signals from the record-selector [7501] in the I/O ("ALADC"- & "ARADC") is done via UDA1361TS [7007]. This IC can process input signals up to 2Vrms by using external resistors [3047], [3053] in series to the input pins. As the level from the DVIO-Board is only 1Vrms a 6dB step can be performed by setting pin 7 of [7007] to 3,3V via [7008] and the "PWONSW"-line controlled by the CC-P to use the whole dynamic range of the ADC. All required clock signals are generated on the dig. board and only the audio data ("A_DAT"-line) are routed from Ana- to Dig.-PCB for further processing.

The transformation of dig. audio back into the analog domain is done by AD1852 [7004]. All necessary clock signals are coming from the dig. board and dig. audio data ("D_DATA0"-line) are converted into analog signals, which are available at pin 17/16 and pin 12/13 of [7004] as symmetrical signals. Afterwards an Op-Amp. [7003] (line driver & converting to unsymmetrical signal, gain = 1), which is also working as low-pass-filter to increase signal performance (noise, distortions,...), is passed. Then both signals ("ALDAC" & "ARDAC") are directly routed to the rear cinch output and also used in the audio-I/O for further processing. The DAC has also a mute possibility, which can be activated by setting pin 23 to 5V via [7001]. This mute is controlled either by the dig. board ("D_IKLL"-line) or the "IPFAIL"-signal from power-supply-unit (in this case it's the combination of "A_KILL" and "IPFAIL"). If the DAC is muted externally via pin 23 or if there are no audio data available (e.g. "D_DATA0"-line zero), the output pins 8 and 22 of the DAC change to high (+ 5V). These two signals are then combined with diode pos. 6006. After decoupling via [7009] the signal "DAC_MUTE" is used as mute signal for the mute transistors [7415], [7416] for cinch rear out.


b) PCBs with UDA1334BTS [7001]:

The conversion of analog audio signals from the record-selector [7501] in the I/O ("ALADC"- & "ARADC") is done via UDA1361TS [7005]. This IC can process input signals up to 2Vrms by using external resistors [3039], [3041] in series to the input pins. As the level from the DVIO-Board is only 1Vrms a 6dB step can be performed by setting pin 7 of [7005] to 3,3V via [7006] and the "PWONSW"-line controlled by the CC-P to use the whole dynamic range of the ADC. All required clock signals are generated on the dig. board and only the audio data ("A_DAT"-line) are routed from Ana- to Dig.-PCB for further processing.

The transformation of dig. audio back into the analog domain is done by UDA1334BTS [7001]. All necessary clock signals are coming from the dig. board and dig. audio data ("D_DATA0"-line) are converted into analog signals, which are available at pin 14 and pin 16 of [7001]. Afterwards an Op-Amp. [7002] (line driver & level adaptation, gain = 2) which is also working as low-pass-filter to increase signal performance (noise, distortions,...), is passed. Then both signals ("ALDAC" & "ARDAC") are directly routed to the rear cinch output and also used in the audio-I/O for further processing. The DAC has also a mute possibility, which can be activated by setting pin 8 to 3,3V via [7003]. This mute is controlled either by the dig. board

("D_IKLL"-line) or the "IPFAIL"-signal from power-supply-unit (in this case it's the combination of "A_KILL" and "IPFAIL"). In addition to that the DAC [7001] and the cinch outputs can be killed (muted) in case of "digital silence" by the circuit around [7008], [7009] and [7010], when no audio data are available (e.g. "D_DATA0"-line zero). This function can be also activated via the "ION"-line (set to high during any stand-by mode). To avoid signal distortions (clipping) the mute transistors for cinch rear out [7415], [7416] are decoupled via [7011].

Figure 9-1



The Video-I/O-switching is basically realized by the matrix switch STV6618 [7408], which is controlled via I²C-bus by the CC. All used outputs excluding pin 21 (Y/CVBS-REC) have a 6 dB-amplification and a 75 Ohms driver-stage inside. This IC includes also several digital outputs, which are used for switching purposes on the analog board. The record selector inside the switch selects between the CVBS from frontend ("VfV"), the input from Scart 1 ("YCVBSIN1") or the signal from Scart 2 ("YCVBSIN2"). Afterwards the signal passes another switch [7411] in which a selection between signals from the front or the preselected ones are done. The output signals of [7411] are fed as "A_YCVBS"- and "A_C"-line to the digital board for further processing.

To reduce the number of external presets there exists only one preset for CVBS- and Y/C-front. The set automatically detects between the two inputs depending on the presence of a video signal (sync separator-circuit on μ P-sub-board) where Y/C has higher priority.

The R/G/B-inputs and the Fast-Blanking-line from Scart 2 are routed over the optional EPG board to the digital PCB. Also all other video signal from the analog board are routed through the EPG board if present. These signals are also available on the corresponding input-pins of the STV6618 to enable a loop-through in AV-Standby. In this mode the set has to behave like a cable between the two Scart-connectors. AV-Standby is activated either by a "high" level on pin 8 of Scart 2 ("active device is present") or by the "WU"-line (wake up). This signal is generated out of the circuit around [7401], [7402] & [7403] and will become "high" if there is a signal on pin 20 of Scart 1- or Scart 2. The detection of the input level on pin 8 of Scart 2 ("8SC2") is done via an analog input of the CC-P (less than 2V means inactive; 4,5V to 7V determines a source with 16:9 picture-ratio and greater than 9,5V is an active 4:3 source). All signals from the digital board ("D_R", "D_G", "D_B", "D_C", "D_Y" and "D_CVBS") are routed to the proper inputs of the STV6618 for amplification and driving purpose before they can be seen on the appropriate Scart outputs. In case of EPG the signals from the digital board are routed through the EPG board where the selection between digital board video or EPG OSD is taken.

The "D_CVBS"- and the "D_Y"-line are passing a 6 dB-amplifier and driver-IC [7410] and are then routed to the CVBS-Cinch and Y/C-out rear. The chroma signal for this Y/C out is coming from the STV6618 - which makes the 6 dB-amplification - and a driver [7406] in between.

The detection of the picture ratio information on the Y/C-input front is made by measuring the DC-level on the Chroma signal via analog input of the CC-P ("WSFI"-line). In case the level is higher than 3,5V the input signal is a 16:9 source. If the level is lower than 2,4V the picture ratio is 4:3.

For generation of the appropriate DC-voltage on the Y/C-out rear the "WSRO"-line is controlled via pin 18 of [7408] by the CC-P (Pin 18 set to low means 4:3, pin 18 set to high determines 16:9).

The control of the switching voltage (Pin 8 of Scart 1) is done via 3-level-pin (nr.2) of the STV6618 [7408] and the transistors [7405], [7407] & [7409]. A "low" on pin 2 of [7408] causes around 11V on pin 8-Scart 1 (e.g. source with 4:3 picture-ratio active). Medium level (2,5V) on pin 2 of the STV6618 generates medium level (approx. 6V) on pin 8-Scart 1 (e.g. active source with 16:9) and a "high" on pin 2 of the STV6618 pushes pin 8-Scart 1 to "low" (e.g. inactive).

9.3.7 VPS/PDC- and Text-Dataslicer

For extraction of relevant information out of the video signal (time controlled recording, net-name-identification, time- & date- download) the STV5348 [7931] is used. Data transfer to/from the CC is fully done via I²C-bus and the input signal for decoding is the same as the one being routed to the digital board for recording purposes ("A_YCVBS"-line).

9.3.8 Analog Follow-Me

This circuit compares the video signal from the internal frontend ("VfV") of the recorder with that one of the connected TV-set ("CVBS1"). The TV set delivers the signal via Scart-cable. A comparator [7934] and several additional parts ([7932], [7933], ...) are used to compare the two video signals. In case of both input signals are equal the output-line of this circuit ("FOME") is set to low. Detection is made via an input port of the CC-P.

9.4 Analog board NAFTA- & APAC-Pal- version

9.4.1 Frontend NAFTA

[1701] demodulates the video signal from the antenna input. Tuner and IF-demodulator are in one unit. Also a modulator is included in that part. The audio- and video-signal to the modulator are the ones from the selected input or the playback path of the set ("AMCO"- and "D_CVBS"-line). The control of the tuner is fully done via I²C-bus by the CC-P. Via the "MSW"-signal and [7701] the modulator is switched on and off. In opposite to this the antenna loop-through is opened or closed. In the APAC-Pal version POS [1700] is used with the difference that it demodulates only PAL- instead of NTSC-signals and has also no modulator. The "CSW_SSW" line switches the modulator between CH3 or CH4 in the NTSC-version. To achieve optimal tuning the "AFC"-signal is detected by the CC via an analog input; [3701], [3702] and [3703] are used for level adaptation (5V to 3V3). Pos [7700] is a driver for the video signal.

The sound demodulation is realized by the MSP34x5 [7600], which is also fully controlled via I²C-bus by the CC-P (determination of bandwidth, amplitude, standard, ...). The audio signals are available at pin 30 and pin 31 of [7600] and fed as "AFER"- & "AFEL"-line to the audio-I/O for further processing. As this PCB is used for different regions (NAFTA and APAC) either MSP3425 or MSP3415 are assembled.

9.4.2 Audio routing

Audio IO NAFTA / APAC Overview

12.03.2002 Vers. 05




Figure 9-2

TR 01057_001
170502

The sound processing is always done in stereo (that means separate left- and right-channel).

a) Record-Path:

The complete selection of the audio signal for recording is done by a HEF4052 [7501], which is a dual four-to-one multiplexer. The input lines for the selector [7501] are coming either from MSP [7600] ("AFEL"/"AFER") or cinch rear in 1 ("AIN1L"/"AIN1R") or cinch rear in 2 ("AIN2L"/"AIN2R") or the cinch in front ("AINFL"/"AINFR"). The [7501] is controlled via "RSA1"- and "RSA2"-signals coming from the MSP [7600]. The MSP acts as a port expander of the CC-P. The Op-Amp on the output [7504] is necessary for performance reasons and acts also as a driver. The selected signals "ARADC" and "ALADC" are directly fed to the Audio-ADC.

As there can exist also a fifth input in case of DV-In is present the corresponding analog audio signals from the DVIO-board are firstly routed via extra cable and connector [1960] to the MSP, which acts as a preselector between audio from internal frontend or the DV-Input.

b) Line-Out-Path:

see chapter 9.4.3

c) Digital Audio Output-Path without IOE-Print:

Additionally to analog audio the set is also equipped with a digital output via cinch plug [1951]. The signal is generated on the dig. board and routed via audio interface cable and connector [1900] to the Ana-PCB. Here the "DAOUT"-line first passes a 6-fold inverter [7580] being used as a driver and for performance reasons (noise reduction, jitter, etc.). Afterwards a transformer [5580] is necessary to achieve the correct level and also to have a floating output with isolated ground before the signal is fed via [3580] to cinch plug [1951]. The capacitors [2580], [2582] and [2583] perform an AC-coupling between connector- and set-ground.

d) Digital Audio Output-Path with IOE-Print:

see chapter 9.3.4.f

e) Digital Audio Input-Path with IOE-Print:

see chapter 9.3.4.g

9.4.3 Audio ADC/DAC

The conversion of analog audio signals from the record-selector [7501] in the I/O ("ALADC"- & "ARADC") is done via UDA1361TS [7005]. This IC can process input signals up to 2Vrms by using an external resistor [3039], [3041] in series to the input pins. As the level from the DVIO-Board is only 1Vrms a 6dB step can be performed by setting pin 7 of [7005] to 3,3V via [7006] and "PWONSW"-line controlled by the CC-P to use the whole dynamic range of the ADC. All required clock signals are generated on the dig. board and only the audio data ("A_DAT"-line) are routed from Ana- to Dig.-PCB for further processing.

The transformation of dig. audio back to the analog domain is done by UDA1334BTS [7001]. All necessary clock signals are coming from the dig. board and dig. audio data ("D_DATA0"-line) are converted into analog signals, which are available at pin 14 and pin 16 of [7001]. Afterwards an Op-Amp. [7002] (line driver & level adaptation) which also works as a low-pass-filter to increase signal performance (noise, distortions,...) is passed. Then both signals ("ALDAC" & "ARDAC") are directly routed to the rear cinch output. The DAC has also a mute possibility, which can be activated by setting pin 8 to 3,3V via [7003]. This mute is controlled either by the dig. board ("D_IKLL"-line) or the "IPFAIL"-signal from power-supply-unit. In addition to that the DAC [7001] and the cinch outputs can be killed (muted) in case of "digital silence" by the circuit around [7008], [7009] and [7010], when no audio data are available (e.g. "D_DATA0"-line zero).

The signals from the audio DAC part ("ARDAC"/"ALDAC") are directly routed to both cinch rear outputs, which are connected

in parallel. To avoid plops and any other audible noise on the output there is a mute-stage implemented [7509], [7511] for each channel. The activation is done via "AKILL"-line, which is a combination of the "KILL" from CC-P, "DAC_MUTE" from DAC-part and "IPFAIL" from the power-supply-unit. The circuit around [6430], [6431], [7430] and [7404] generates this signal.

9.4.4 Video-routing




Figure 9-3

The Video-I/O-switching is basically realized by the matrix switch STV6618 [7408], which is controlled via I²C-bus by the CC. All used outputs excluding pin 21 (Y/CVBS-REC) have a 6dB-amplification and a 75 Ohms-driver-stage inside. This IC also includes several digital outputs, which are used for switching purposes on the analog board. The record selector inside the switch selects between the CVBS from frontend, the CVBS from Cinch-Rear or Y from the S-Video-input rear. Afterwards the signal passes another switch [7411] in which a selection between signals from the front or the preselected ones is done. The output signals of [7411] are fed as "A_YCVBS"- and "A_C"-line to the digital board for further processing.

To reduce the number of external presets there is only one station for CVBS or Y/C (front and rear). The set automatically detects between the two inputs depending on the presence of a video signal (sync separator-circuit on μ P-sub-board) where Y/C has higher priority.

The Y/U/V-inputs are routed over the optional EPG board to the digital PCB. Only the Y-line has to be present additionally on pin 4 of [7408] for video recognition. Also all other video signal from the analog board are routed through the EPG board if present.

The signals "D_C" and "D_Y" are fed through [7408] (6dB amplification) and via [7406], [7409] used as driver to the S-Video output connector. The "D_CVBS" line is directly routed to the modulator and via the circuit around [7431] and [7432] amplified by 6dB before it is fed to the CVBS output plug. In case of EPG the signals from the digital board are routed through the EPG board where the selection between digital board video or EPG OSD is taken.

The Y/U/V signals from the digital board are also passing [7408] for 6dB amplification and driving purpose.

To achieve optimal picture quality the set is equipped with a simple progressive scan function based on a so-called line doubler. The complete generation of the signal is done on the digital board and via a separate cable and connector [1946] the corresponding Y/U/V lines are routed to the analog PCB. Also the YUVprogressive signals are switchable to EPG OSD on the EPG board if implemented. As there is only one Y/U/V output available a switching between interlaced and progressive output is necessary. While the transistors [7421], [7422], [7424], [7425], [7427] and [7428] are used as driver for Y/U/V progressive, [7423], [7426] and [7429] together with [7405] are necessary for killing these signals via pin 42 of [7408] in case the interlaced is selected ("PSCAN_KILL"-line set to low). If progressive output is active the pins 27, 29 and 31 of [7408] are set to high impedance and "PSCAN_KILL" is also high (e.g. 5V).

The detection of the picture ratio information on the Y/C inputs (rear or front) is done by measuring the DC-level on the Chroma signal via an analog input of the CC-P ("WSRI"- and "WSFI"-line). In case the level is higher than 3,5V the input signal is a 16:9 source, if the level is lower than 2,4V the picture ratio is 4:3.

For generation of the appropriate DC-voltage on the Y/C output the "WSRO"-line is controlled via pin18 of [7408] by the CC-P (Pin 18 set to low means 4:3, pin 18 set to high determines 16:9).

During Stand-By there is also no loop-through of any input to any output performed.

9.5 Digital Board

9.5.1 Record Mode

Video Part

Analog Video input signals CVBS, YC and UV(RGB for EURO and YUV for USA) are routed via the analog board to connector 1601 and sent to IC7500 SAA7118 (Video Input Processor). Digital video input signals (DV_IN_DATA(7:0)) are sent from the DIVIO board through the connector 1603 and further also to IC7500.

IC7500 (VIP) encodes the analog video to digital video and processes the digital video to a digital video stream (CCIR656 format). This output stream (VIP_YUV[7:0]) goes to IC7403 SAA6752H (EMPRESS) and to IC7100 Versatile Stream Manager. The latter uses the data for VBI (vertical blanking interval) extraction.

IC7403 (EMPRESS) encodes the digital video stream into a MPEG2 video stream that is fed to IC7100 (VSM).

Audio Part

I2S audio are sent from the analog board to IC7403 EMPRESS via connector 1602. The EMPRESS compresses I2S audio data into an AC3 audio stream which is fed to IC7100 (VSM).

Front-End I2S

IC7100 (VSM) interfaces directly to the different hardware modules such as Basic Engine, EMPRESS IC7403, MPEG decoder IC7200 (Sti5508) and buffers the data streams that are coming from or going to these hardware modules. In IC7100 (VSM), the video MPEG2 stream and the audio AC3 stream are multiplexed into a I2S packetized stream. The serial data are sent to the Basic Engine to be recorded.

Loop-Through

The multiplexed audio and video stream in the VSM is fed back via the parallel front-end interface to IC7200 (Sti5508). This IC decodes the MPEG stream into analog video and I2S audio. The video and audio signals are routed to the analog board via connectors 1601 and 1602. During recording, the recorded signal is present at the outputs of the analog board.

9.5.2 Playback Mode

During playback, the serial data from the Basic Engine is going directly to the Sti5505 via the serial front-end I2S interface. The Sti5508 is a MPEG & Audio/video decoder and has the following outputs:

- To the analog board:
 - analog video RGB, YC, CVBS
 - I2S audio (PCM format)
 - SPDIF audio (digital audio output)
- To the Progressive scan board:
 - digital video YC(7:0).

9.5.3 S2B Interface

The S2B interface between the VSM (IC7100) and the Servo processor MACE3 controls the Basic Engine during record and playback mode.

9.5.4 System Clock

System clocks(27MHz) of VSM, Sti5508, EMPRESS and Progressive Scan are generated by oscillator 7906

9.5.5 Audio Clock

During record mode, the audio clock ACC_ACLK_OSC is generated by IC7102 (PLL) because then, the audio clock must be synchronized with the incoming video (VIP_FID) from the VIP.

During playback mode, the audio clock ACC_ACLK_PLL is generated by the clock synthesizer IC7900 (MK2703S). Both ACC_ACLK_OSC(also goes to the EMPRESS as ACLK_EMP) and ACC_ACLK_PLL are fed to the VSM. This IC selects the appropriate clock to the Sti5508. The EMPRESS IC derives from the incoming ACLK_EMP the I2S audio encoder clocks AE_BCLK and AE_WCLK which are sent to the VSM.

9.5.6 On/Off

The digital board is not powered in standby mode. Control signal ION, coming from the analog board, will enable the PSU and power the digital board.

- ION = High: the digital board is in powered down standby mode
- ION = Low: the power supply to the digital board is enabled

9.5.7 Reset

Control signal IRESET_DIG, controlled by the microprocessor on the analog board is sent to the RESET LOGIC circuit.

- IRESET_DIG = Low in standby mode
- IRESET_DIG = High: the whole system is reset and the Digital board is waked up.

9.5.8 I2C Bus

Sti5508 is master of the I2C bus. The following IC's are controlled by the I2C bus:

- IC7201 NVRAM
- IC7403 EMPRESS
- IC7500 VIP
- IC7700 FLI2200 Video Deinterlacer Line Doubler
- IC7801 ADV7196 Video Denc

9.5.9 EMI Bus

The following IC's are connected to the External Memory Interface bus (EMI) which functions as system bus:

- IC7301 and 7302: Flash memories which contain the application and diagnostic software
- IC7100: VSM
- IC7200: MPEG AV Decoder

Block Diagram Digital Board




Figure 9-4

9.5.10 Progressive Scan

Description

The progressive scan part is integrated in the Digital Board and built around the SAGE Fli2200 de-interlacer / line doubler (7701). This I2C controlled de-interlacer uses a 64Mbit SDRAM (32bit x 2M) to perform high quality deinterlacing (meshing). The de-interlacer gets his digital YUV input data from the STi5508 (7200). The format of the digital YUV input to the SAGE is CCIR656 with separated Hsync, Vsync and odd/even signal running on 27Mhz. Because the STi5508 doesn't have a Vsync output the odd/even output of this IC has to be translated to a Vsync signal. Some glue logic has been added to extract the vertical sync. The glue logic circuit consists of Flip-Flop IC 74HC74D (7701) and EXOR 74LVC86 (7702). The next diagram shows how the vertical sync is extracted.




Figure 9-5

The output of the de-interlacer (4:4:4 progressive video) is fed to the Analog Devices ADV71967 MacroVision compliant DENC (7801).

The YUV current output of the DENC is fed via a low pass filter to the single supply output opamps AD8061/8062 (7802-7803). The analog video is fed via a 7 poled flex to the analog board where the YUV 2FH cinch connectors are located.

9.6 Divio 1.8 Board

9.6.1 Short Description of the Module:

The DVIO Module is a decoder for DV streams. Input is a stream from a DV-camcorder via IEEE1394. Outputs are CCIR656 Video and Analog audio (L+R). A serial control interface is present.

The following picture shows the location of the DVIO Module inside the DVDR set.

Description DIVIO Module




Figure 9-6

9.6.2 Block Diagram

Block Diagram DVIO1.8


TR03022_001
090802

Figure 9-7

9.6.3 Functional Description

The DVIO module consists of the following blocks (see blockdiagram):

1. IEEE1394 Interface
 - uPD72852 (7400) (Phy)
 - uPD72893 (7431) (Link part)
2. Micro-controller
 - uPD78F0988 (7802)
 - Voltage regulator LM2931 for generation of 10V programming voltage (7801)
3. Reset-circuitry
 - Power-on reset
 - Reset pulse-shortener
4. DV-Decoder
 - uPD72893 (7431) (Codec part)
 - 16MBit SDRAM (7430)
 - optional Flash-Memory M29W800AT for Firmware-Update of uPD72893 (7432)
5. Clocking & Audio PLL
 - Clock oscillator FXO-31FT (7601)
 - Audio-PLL: Voltage controlled oscillator BA7082F (7604), clock generator BU2288FV (7605), and clock divider 74LV74 (7606-A)
6. Audio Format adaption (MSB justified -> I2S), option
 - 74LV74 (7507-A, -B)
7. Audio & Video output
 - Audio DAC UDA1334ATS(7602)
 - Clock delay(7500)
 - Tristate buffer(7505)

IEEE1394 Interface

The 1394 interface consists of a uPD72852 physical layer and a uPD72893 link layer IC (uPD72893 integrated also DV-Decoder).

It has the following features:

- S400 operation (400 megabit per second)
- Two i.Link ports (4 pin), only one used
- AV link port

Micro-Controller

The uPD78F0988 processor has following extra features:

- 60 kilobyte of flash memory as program memory
- 2 kilobyte of internal data memory
- watchdog timer
- On board ISP(In-System-Programming) functionality

ISP

By use of In-System-Programming, it is possible to update the software of the DVIO board that is in the uPD78F0988. ISP can be made active by resetting the processor and keeping the ISPn pin low during reset. During ISP, the ISPn signal on the board has to be kept low. A programming voltage of 10V is activated by the uPD78F0988 itself at the Vpp pin before programming procedure starts. When the ISP mode is active, the new program can be sent to the microprocessor through the serial port.

Reset-circuitry

The reset-circuitry consists of two parts.

First part (around transistor 7803) generates a reset pulse when the board is powered up.

Second part (around transistors 7804 & 7805) acts as a reset-pulse shortener, i.e. a short reset pulse (4ms) is generated from the input signal RESETn which is much longer (usually 100ms). This is required to ensure correct operation of the Micro-controller after booting-up when RESETn is again deactivated

DV-Decoder

The uPD72893 decodes the stream into video data in 656 format and audio data in I2S format.

The microprocessor has the ability to read the status registers of the uPD72893. By reading these registers, extra data from

the DV stream, that is not decoded into audio or video, can be sent to the digital board using pin TXD of the serial interface. This data includes time stamp and some more.

Clocking and Audio PLL

The FXO-31FT generates the free-running 27MHz system clock. Video part of input DV-stream is in the uPD72893 adapted to the local 27MHz clock domain (skip, repeat frame). Because audio clock (11.2896Mz [fs=44.1kHz] or 12.288MHz [fs=32kHz, 48kHz]).

The uPD72893 integrates the phase comparator that drives the VCO BA7082F to a nominal frequency of 27MHz which in turn is converted by BU2288FV and 74LV74 to 11.2896MHz or 12.288Mhz, respectively.

The uPD72893 controls directly the frequency ratio of the BU2288FV.

Audio Format adaptation (MSB justified -> I2S), option

Due to a bug in 1st version of uPD72893 digital audio output is not correct in I2S mode when in 32kHz operation. As a workaround uPD72893 is generally configured in MSB justified mode and conversion to I2S mode is done externally via a 74LV74 device.

Can be disabled with later versions of uPD72893.

Audio & Video Output


The audio I2S data are sent to audio DAC UDA1334. Analog audio left and right signals are connected to the analog board. The tri-state buffer enables the digital video stream to the Video Input Processor on the digital board when the DV source is selected.

The clock delay synchronizes the AV clock with the AV data at the output.

9.7 Digital Board Chrysalis 2.1

9.7.1 Introduction

Block diagram 2nd generation DVD recorder



CL 96532004_001.aps
140203

Figure 9-8

This 2nd generation Digital Board is based on the highly integrated 'Chrysalis' IC. Its predecessors, the 'Empire' and 'Empress' based boards, had two PWBs mounted on top of each other (due to separate DVIO board). For this new generation, all functionality is now available on one PWB in one BGA IC (Ball Grid Array) i.s.o. four VLSI ICs.

The board encodes and multiplexes analogue video and digital uncompressed audio (I2S) into an MPEG2 stream. This MPEG2 stream is formatted, to be recorded by the DVD+RW engine. In playback, the board will decode the MPEG2 stream into analogue and digital audio and into analogue video. In addition, a DV stream can be received via IEEE1394 (i-Link), and transformed to MPEG2 format.


There are versions foreseen, to generate a progressive scan analogue video output. In the standard Chrysalis board, the

progressive video output is generated by the PNX7100. In the Chrysalis 'F' it is generated by the Faroudja FLi2301.

The Chrysalis Digital board is pin compatible with the Empress digital board in terms of A/V IO, BE interface, Power Supply, and Service interface. For functional enhancements, several connectors are added: IDE connector (HDD, AV3, PCMCIA, etc.).

9.7.2 Record Mode

Block diagram Chrysalis Digital Board



CL 36532004_003.eps
140203

Figure 9-9

Video Part

The analogue video input signals CVBS, YC, and YUV/RGB (RGB for EURO and YUV for USA), are routed via the analogue board to connector 1904 and sent to IC7004 (SAA7118, Video Input Processor).

The digital video input signals are routed from the DV-In connector (item 1200) via ICs 7200 (1394 PHY) and 7201 (1394 LINK) to IC7400 (PNX7100, Chrysalis).

The multistandard Video Input Processor (VIP, IC7400) encodes the analogue video to digital video stream (CCIR656 format). It provides filtering of the analogue signals and separation of luminance and chrominance by a comb filter. The output stream, named ITU_IN(7:0), is then routed to the Chrysalis IC (PNX7100). This IC encodes and decodes the digital video stream into/from MPEG2 format.

Audio Part

I2S audio is sent from the analog board to the Chrysalis IC via connector 1900. The Chrysalis compresses the I2S audio data into an MPEG1-L2/AC3 audio stream.

Front-end I2S

IC7400 (Chrysalis) interfaces directly to the Basic Engine (BE) via connectors 1100 (clock and data) and 1105 (control). For future use (with AV3 BE module, HDD, or card reader) it also interfaces to an IDE bus via connector 1102.

It buffers the data streams that are coming from (or going to) these hardware modules.

In the Chrysalis, the video MPEG2 stream and the audio AC3 stream are multiplexed into an I2S stream. The serial data are sent to the Basic Engine for recording.

9.7.3 Playback Mode

During playback, the serial data from the Basic Engine is going directly to the PNX7100 via the serial front-end I2S interface. The PNX7100 is an MPEG CoDec and has the following outputs:

- To the analogue board: analogue video RGB, YC, CVBS on connector 1904.
- I2S audio (PCM format) on connector 1900.
- SPDIF audio (digital audio output) on connector 1904.
- Progressive video on connector 1704.
- Communication gateway (RS232) on connector 1104.

9.7.4 Basic Engine Interfaces

AV2 Basic Engine (VAE8015 and VAE8020)


The UART interface (for the S2B commands) between the Chrysalis and the servo processor (MACE3 on the BE module), controls the AV2 Basic Engine during record and playback mode. For data transport, an I2S bus is used.

For detailed information on the AV2 BE module, see Service Manual 3122 785 12470.

AV3 Basic Engine (VAE8030)

To be prepared for new developments, the Chrysalis Digital Board is equipped with two IDE busses (ATAPI). They can be used for connecting to the new generation Basic Engine (e.g. the AV3), a Hard Disc Drive (HDD), or a Smart Card Reader.

9.7.5 Clock Distribution

Clock distribution on Chrysalis board

CL 36532004_004.eps
140203

Figure 9-10

The PNX7100 has a complex clock system, which is needed to support the processes running at different frequencies such as video decoding, audio decoding or peripheral I/O devices etc. To ensure a synchronous initialisation of all the registers and state machines, all the PLLs are switched to their default frequency and the reset sequence is run at 4 MHz. Then when the booting control unit is correctly initialized and once it has captured all the booting parameters, it sets the PLLs to its functional frequency to allow the modules to run at their nominal frequencies. Thanks to a clock blocking mechanism, the frequency switching is glitch free.

System clocks:

- PNX7100 (IC7400, pins AF9 and AF10) : 4 MHz provided by the xtal oscillator 7402.
- SAA7118 (IC7004, pins A3 and B4): 24.576 MHz provided by xtal 1001.
- ADV7196 (IC7703, pin 25): 27 MHz provided by PNX7100.
- SDRAM (IC7804 and 7808, pin 38): 133 MHz provided by the PNX7100.
- 1394-LINK (IC7201, pin 88): 49.152 MHz provided by 1394-PHY.
- 1394-PHY (IC7200, pins 59 and 60): 24.576 MHz provided by xtal 1201.

9.7.6 Power Supply

The Digital Board is not powered in standby mode. The control signal 'ION' (Inverse On), coming from the analogue board, will enable the PSU, and power the digital board.

- ION = High: the digital board is in powered down standby mode.
- ION = Low: the power supply to the digital board is enabled.

The 3V3, +5V, -5V, and +12V come from the PSU, while the 1V8 core voltage is generated on the board by a low voltage buck controller (item 7501). It provides the control for a DC-DC power solution producing an 1.8V output voltage over a wide current range. The NCP1570-based solution is powered from

12 V with the output derived from the 3V3 supply. It contains all required circuitry for a synchronous NFET (IC7500-1 and -2) buck regulator.

9.7.7 Memory

Several memories are used on the Chrysalis Digital Board:

- EEPROM IC7810: this memory contains all the necessary boot parameters of the board.
- EEPROM IC7809: this memory contains all the necessary parameters for the application.
- FLASH IC7807(05/11): this memory contains the application-, diagnosis-, and service software.

9.7.8 Reset

Reset concept Chrysalis board




Figure 9-11

The voltage detector NCP303LSN29 (IC7600) provides the reset signal PNX7100_RESETh (active 'low') with the correct timing behavior. This circuitry functions as a Power-On Reset (POR) module, which detects the minimum functional voltage that is needed by the device. It also detects any voltage drop. When the power voltage is outside the nominal range, a reset signal is generated by the POR module and fed to the reset module which controls the individual reset of the different peripherals and processing units.

There are two control lines which can overrule this reset signal:

- IRESET_DIG (controlled by the microprocessor on the Analogue Board).
- EJTAG_RESETh (only for production).

They can pull the output of the NCP303LSN29 (item 7106) down via a shottky diode.

So when the output signal PNX7100_RESETh is 'low', the board will reset. When this signal is 'high', the board is up and running.

The PNX7100_SYS_RESETh is a general enabling signal for the different reset lines. All other reset lines are directly driven from Chrysalis port pins (e.g. MPIO13_IDE1_RESETh). All

reset lines are logically connected via 74LVC08D (item 7104) and (item 7107) AND-gates. If both reset signals are low, all other external devices are initialised.

9.7.9 I2C Bus

The PNX7100 is the master of the I2C bus (during reset, external I2C masters are allowed). The following ICs are controlled by the I2C bus:

- IC7809.
- IC7810 NVRAMs.
- IC7004 VIP.
- IC7700 FLI2301 Video De-interlacer Line Doubler (for Chrysalis-F boards).
- IC7703 ADV7196 Video Enc (for progressive scan done by Chrysalis).

9.7.10 I/O Connectors

AIO Connector (item 1900)

The Audio In/Out (AIO) connector is used to interchange digital audio signals between Analog- and Digital Board.

DAIO Connector (item 1901)

The Digital Audio In/Out (DAIO) connector is used to interchange digital audio (SPDIF) signals between the IOE-Board and the Digital Board.

VIO Connector (item 1904)

The Video In/Out (VIO) connector is used to interchange analogue video signals between Analog- and Digital-Board.

9.7.11 Progressive Scan

Introduction

- There are two versions foreseen, to generate a progressive scan analogue video output:
- In the standard Chrysalis board, the 'low end' progressive video output is generated by the PNX7100.
 - In the Chrysalis 'F', the 'high end' progressive output is generated by the Faroudja FLI2301. This IC offers additionally DCDi, upscaling to HDTV, and picture enhancement.

Description

The progressive scan part is integrated in the Digital Board and built around the FLI2301 de-interlace/line doubler (7701). This I2C controlled de-interlace uses a 64Mbit SDRAM (32bit x 2M) to perform high quality de-interlacing (meshing). The de-interlace gets its digital YUV input data from the PNX7100 (7400). The format of the digital YUV input to the FLI2301 is CCIR656 with separated Hsync, Vsync, and odd/even signal running on 27MHz.

9.8 Service UART Interface

Logic IC 74HCT14D (item 7111) is used to make a level conversion from microprocessor (LVTTL) to +/-5V (compatible with most RS232 interfaces) and vice versa. The control line MPIO19_CTL_SERVICE is used to activate service and diagnostic SW at start up procedure. The connectivity is provided via an external service tool.

9.9 EPG Nafta Board

9.9.1 General

Two ASICs from Gemstar, GS501 (item 7100) and GS502 (item 7201), generate the EPG OSD. The host P controls both ICs via the I2C bus (pins 45 and 48). A RAM memory (item 7102) and a Flash memory with the firmware (item 7101) belong also to the periphery of these ASICs. A PIC processor (item 7303) generates the POR_N reset for this system. The POR_DC reset comes from the set, and is active after AC power 'on'. A port expander from the host, controls the EXT_RESET signal. This port expander (item 7200) is also used for switching the video paths on the EPG board.

Either the board works in 'Loop Trough' mode, or (for EPG) the output path is switched to the 'EPG RGB' video.

Blockdiagramm EPG-Modul Nafta




Figure 9-12

9.9.2 Loop trough

For 'Loop Trough' the input video signals (CVBS, YC, YUV, and YUV-progressive) from the Digital board are passing three video switches before going to the Analog board.

- Item 7503 for CVBS and Y/C.
- Item 7502 for YUV-interlaced.
- Item 7501 for YUV-progressive.

9.9.3 EPG RGB Video

A V-sync and H-sync (for progressive = 2H-sync) are necessary for outputting an RGB video. A sync separator (item 7703) generates these syncs. Input for the sync separator is either the 1fh or the 2fh luminance signal from the Digital board. A video switch (item 7700) makes the selection. For progressive video, the signal must be attenuated (item 7701).

The RGB signal goes via emitter followers (items 7202, 7203, and 7204) to an RGB-to-YUV converter and to an RGB-to-CVBS, Y/C converter.

The RGB-to-YUV converter consists of four OpAmp's, which are necessary for RGB/YUV conversion (item 7600-B, -C, and -D) and for adding the C-sync to the Y signal (item 7600-A). The RGB-to-CVBS, Y/C conversion is realized by IC7602. The oscillator (item 7601) is necessary for generating the chroma carrier.

With transistor 7603 the conversion stages can be switched 'off' for power saving.

For the PIP (Picture in Picture) feature, the D_CVBS video signal from the Digital board is used. This signal is fed to Pin 10 of IC7201. For scanning the EPG data, the A_YCVBS signal from the Analog board is fed to pin 8 of IC7201.

9.9.4 Power supply

The supply for the video stages and the EPG digital part, are generated via DC-DC converters (items 7400, 7401, and 7403) out of the 12STBY.

9.10 EPG Europe Board

9.10.1 General

The ARM7 based microprocessor (item U1) and an ASIC (Gemstar GSA03, item U2) generates the EPG OSD data (RGB or YUV-interl./progr.). The host P on the Digital board, controls both ICs via the I2C bus. A RAM memory (item U7)

and two Flash memories (items U8 and U9) with the firmware and EPG data, belong also to the periphery of the ASIC. A resistor and capacitor (items R1 and C6) generate the reset for this system. The IPOR reset comes from the set and is active after main power 'on'. A port expander from the host, controls the nGCLR reset signal. This port expander (item U31) is also used for switching the video paths on the EPG board.




Figure 9-13

Either the board works in 'Loop Trough' mode, or (for EPG) the output path is switched to the 'EPG RGB' video.

9.10.2 Loop Trough

For 'Loop Trough', the input video signals (CVBS, YC, RGB, YUV-interlaced, and YUV-progressive) from the digital board are passing three video switches before going to the Analogue board.

- Item U15 for CVBS and Y/C selection between EPG and Loop trough.
- Items U16, U18, and U19 (and periphery) for RGB selection between EPG and Loop trough.
- Items U42 and U17 for YUV-interlaced and YUV-progressive selection between EPG and Loop trough. These signals are amplified (items U13B, C, and D) for driving a 75-Ohm output.

Note: RGB and YUV-interlaced (VR_DVD, UB_DVD, YG_DVD) are the same signals. It depends on the software, which signal is chosen.

9.10.3 EPG RGB

A V-sync and H-sync (for progressive = 2H-sync) are necessary for outputting an EPG video. A sync separator (item U10) generates these syncs. Input for the sync separator is either the 1fh or the 2fh luminance signal from the Digital board. A video switch (item U50) makes the selection.

The EPG signal goes via a PIP-inserter IC (item U11 and peripherals) that inserts a PIP (Picture In Picture) into the EPG OSD. Source for this PIP is the CVBS signal from the digital board.

When the PIP output is a YUV signal, the Y signal is without a sync. Therefore, this sync must be added with item U13A.

For RGB-to-CVBS, Y/C conversion is realized by a PAL conversion IC (item U14). The oscillator (item Y5) is necessary for generating the chroma carrier.

For scanning EPG data, the A_YCVBS signal from the Analogue board is used. This signal is fed to pin 189 of item U2. There is also a sync from the Analogue board necessary. A discrete circuit (items Q18-Q23 and periphery) generates it.

9.10.4 Power supply

The supply for the video stages and the EPG digital part are generated via DC-DC converters and linear regulators (items U28, U40, and U41) out of the 12VSTBY.

9.11 I/O Extension Board

This board feeds the internal S/PDIF signal from the Digital board to an optical and/or digital out connector. For European players, also an YUV output is present on this board.

9.12 IC Descriptions

9.12.1 Display Board

IC 7103 TMP87CH74F Display Board, Front Microprocessor

Block Diagram




Figure 9-14

Pin Function

Pin Name	Input / Output	Function	
P07 to P03	I/O	Two 8-bit programmable input/output ports (tri-state). Each bit of these ports can be individually configured as an input or an output under software control. When used as a SIO input/output, an External interrupt input, a timer/counter input, the latch must be set to "0". When used as a PPG output or divider output, the latch must be set to "1".	
P02 (SO1)	I/O (Output)		SIO1 serial data Output
P01 (SI1)	I/O (Input)		SIO1 serial data Input
P00 (SCK1)	I/O (I/O)		SIO1 serial clock input/output
P17 (INT4/TC3)	I/O (Input)		External interrupt input 4 or Timer/Counter 3 input
P16 (INT2)			External interrupt input 2
P15 (INT3/TC1)			External interrupt input 3 or Timer/Counter 1 input
P14 (TC4/PDO/PWM)			Timer counter 4 input or 8-bit programmable divider output or 8-bit PWM output
P13 (DVO)	I/O (Output)		Divider output
P12 (TC2/PPG)	I/O (I/O)		Timer counter 2 input or Programmable pulse generator output
P11 (INT1)	I/O (Input)		External interrupt input 1
P10 (INT0)			External interrupt input 0
P22 (XTOUT)	I/O (Output)	3-bit input/output port with latch. When used as input port, or external interrupt input, STOP mode release signal input, the latch must be set to "1".	Resonator connecting pins (32.768 kHz). For inputting external clock, XTIN is used and XTOUT is opened.
P21 (XTIN)	I/O (Input)		External interrupt input 5 or STOP mode release signal input
P20 (INT5/STOP)			
P32 (SCK0)	I/O (I/O)	3-bit programmable input/output ports (Sink open drain).	SIO0 serial clock input/output
P31 (SDA/SO0)	I/O (I/O/Output)	Each bit of these ports can be individually configured as an input or an output under software control. When used as a I2C input/output, the latch must be set to "1".	I2Cbus serial data input/output or SIO0 serial data output
P30 (SCL/SI0)	I/O (I/O/Input)		I2Cbus serial clock input/output or SIO0 serial data Input
P47 (AIN7) to P40 (AIN0)	I/O (Input)	8-bit programmable input/output ports (tri-state). Each bit of these ports can be individually configured as an input or an output under software control. When used as an analog input, the P4CR must be set to "0".	A/D converter analog inputs
P53 (AIN13) to P50 (AIN10)	I/O (Input)	4-bit programmable input/output ports (tri-state). Each bit of these ports can be individually configured as an input or an output under software control. When used as an analog input, the P5CR must be set to "0".	A/D converter analog inputs
P67 (V7) to P60 (V0)	I/O (Output)	Four 8-bit high brackdown voltage output ports with the latch. When used as a VFT driver output, the latch must be cleared to "0".	VFT driver outputs
P77 (V15) to P70 (V8)			
P87 (V23) to P80 (V16)			
P97 (V31) to P90 (V24)			
PD4 (V36) toPD0 (V32)	I/O (Output)	5-bit high breakdown voltage output ports with the latch. When used as a VFT driver output, the latch must be cleared to "0".	

Figure 9-15

Pin Name	Input / Output	Function
XIN, XOUT	Input, Output	Resonator connecting pins for high-frequency clock. For inputting external clock, XIN is used and XOUT is opened.
$\overline{\text{RESET}}$	I/O	Reset signal input or watchdog timer output/address-trap-reset output/system-clock-reset outputted.
TEST	Input	Test pin for out-going test. Be tied to low.
VDD, VSS	Power Supply	+ 5 V, 0 V (GND)
VKK		VFT driver power supply
VAREF, VASS		Analog reference voltage inputs (High, Low)

Figure 9-16

9.12.2IC’s Analog Board

IC7408: STV6618 Analog Board, Video Switch Matrix

1.2 Pin Description

Pin No.	Symbol	Description
1	Y/CVBSIN_TUN	Y/CVBS Input from Tuner
2	DIGOUT3	Digital Output Pin 3
3	GND1	Ground Supply 1 for Video Inputs
4	CVBSIN_ENC	CVBS Input from Encoder
5	DECV	Video decoupling capacitor
6	CIN_ENC	Chroma Input from Encoder
7	YIN_ENC	Y Input from Encoder
8	V _{CC}	+5 V Power Supply for Video Inputs
9	R/PR/CIN_ENC	Red or Pr or Chroma Input from Encoder
10	G/YIN_ENC	Green or Y Input from Encoder
11	B/PBIN_ENC	Blue or Pb Input from Encoder
12	GND2	Ground Supply 2 for Video Inputs
13	B/PBIN_AUX	Blue or Pb Input from Auxiliary (SCART2 or external Cinch)
14	DIGOUT4	Digital Output Pin 4
15	G/YIN_AUX	Green or Y Input from Auxiliary (SCART2 or external Cinch)
16	DIGOUT5	Digital Output Pin 5
17	R/PR/CIN_AUX	Red or Pr or Chroma input from Auxiliary (SCART2 or external Cinch)
18	DIGOUT6	Digital Output Pin 6
19	Y/CVBSIN_AUX	Y/CVBS Input from Auxiliary (SCART2 or external Cinch)
20	VCCB_REC	Video Output Recorder Buffer Supply Pin
21	Y/CVBSOUT_REC	Y/CVBS Output to Recorder
22	GNDB_REC	Ground Supply for Recorder Buffer
23	COUT_AUX	Chroma Output to Auxiliary (SCART2 or external Cinch)
24	VCCB1	Video Output Buffer Supply Pin
25	Y/CVBSOUT_AUX	Y/CVBS Output to Auxiliary (SCART2 or external Cinch)
26	GNDB	Ground Supply for Video Buffer
27	B/PBOUT_TV	Blue or Pb Output to TV (SCART1 or external Cinch)
28	C_GATE	External Transistor Command for Bidirectinnal B/C SCART I/O
29	G/YOUT_TV	Green or Y Output to TV (SCART1 or external Cinch)
30	VCCB2	Video Buffer
31	R/PR/COUT_TV	Red or Pr or Chroma Output to TV (SCART1 or external Cinch)
32	VCCB3	Video Output Buffer Supply Pin
33	Y/CVBSOUT_TV	Y/CVBS Output to TV (SCART1 or external Cinch)
34	FBOUT_TV	Fast Blanking Output to TV (SCART1)
35	FBIN_AUX	Fast Blanking Input from Auxiliary (SCART2)

Pin No.	Symbol	Description
36	VDD	+5 V Digital Power Supply
37	SCL	I ² C Bus Clock
38	SDA	I ² C Bus Data
39	GNDD	Digital Ground Supply
40	CIN_TV	Chroma Input from TV (SCART1 or external Cinch)
41	Y/CVBSIN_TV	Y/CVBS Input from TV (SCART1 or external Cinch)
42	DIGOUT1	Digital Output Pin 1
43	CIN_TUN	Chroma Input from Tuner
44	DIGOUT2	Digital Output Pin 2

Figure 2: STV6618 Input/Output Diagram






Figure 3: STV6618 Block Diagram



IC7411: NJM2285 Analog Board, Video Switch



NJM2285D
NJM2285M
NJM2285V

IC7313 TEA 1507 Analog Board, Power Supply Control

BLOCK DIAGRAM





Fig.2 Block diagram.

IC7404: AD1582 Analog Board, Digital/Analogue Converter**FUNCTIONAL BLOCK DIAGRAM**

AD1852

PIN FUNCTION DESCRIPTIONS

Pin	Input/Output	Pin Name	Description
1	I	DGND	Digital Ground.
2	I	MCLK	Master Clock Input. Connect to an external clock source at either 256 F _S , 384 F _S , 512 F _S , 768 F _S , or 1024 F _S .
3	I	CLATCH	Latch Input for Control Data. This input is rising-edge sensitive.
4	I	CCLK	Control Clock Input for Control Data. Control input data must be valid on the rising edge of CCLK. CCLK may be continuous or gated.
5	I	CDATA	Serial Control Input, MSB first, containing 16 bits of unsigned data per channel. Used for specifying channel-specific attenuation and mute.
6		NC	No Connect.
7	I	192/48	Selects 48 kHz (LO) or 192 kHz Sample Frequency.
8	O	ZEROR	Right Channel Zero Flag Output. This pin goes HI when Right Channel has no signal input for more than 1024 LR Clock Cycles.
9	I	DEEMP	De-Emphasis. Digital de-emphasis is enabled when this input signal is HI. This is used to impose a 50 μs/15 μs response characteristic on the output audio spectrum at an assumed 44.1 kHz sample rate. Curves for 32 kHz and 48 kHz sample rates may be selected via SPI control register.
10	I	96/48	Selects 48 kHz (LO) or 96 kHz Sample Frequency.
11, 15	I	AGND	Analog Ground.
12	O	OUTR+	Right Channel Positive Line Level Analog Output.
13	O	OUTR-	Right Channel Negative Line Level Analog Output.
14	O	FILTR	Voltage Reference Filter Capacitor Connection. Bypass and decouple the voltage reference with parallel 10 μF and 0.1 μF capacitors to the AGND.
16	O	OUTL-	Left Channel Negative Line Level Analog Output.
17	O	OUTL+	Left Channel Positive Line Level Analog Output.
18	I	AVDD	Analog Power Supply. Connect to Analog 5 V Supply.
19		FILTB	Filter Capacitor Connection. Connect 10 μF capacitor to AGND (Pin 15).
20	I	IDPM1	Input Serial Data Port Mode Control One. With IDPM0, defines 1 of 4 serial modes.
21	I	IDPM0	Input Serial Data Port Mode Control Zero. With IDPM1, defines 1 of 4 serial modes.
22	O	ZEROL	Left Channel Zero Flag Output. This pin goes HI when Left Channel has no signal input for more than 1024 LR Clock Cycles.
23	I	MUTE	Mute. Assert HI to mute both stereo analog outputs. Deassert LO for normal operation.
24	I	RESET	Reset. The AD1852 is reset on the rising edge of this signal. The serial control port registers are reset to the default values. Connect HI for normal operation.
25	I	L \overline{R} CLK	Left/Right Clock Input for Input Data. Must run continuously.
26	I	BCLK	Bit Clock Input for Input Data. Need not run continuously; may be gated or used in a burst fashion.
27	I	SDATA	Serial Input, MSB first, containing two channels of 16, 18, 20, and 24 bits of twos complement data per channel.
28	I	DVDD	Digital Power Supply Connect to digital 5 V supply.

Table I. Serial Data Input Mode

IDPM1 (Pin 20)	IDPM0 (Pin 21)	Serial Data Input Format
0	0	Right-Justified
0	1	I ² S-Compatible
1	0	Left-Justified
1	1	DSP

9.12.3IC’s Digital Board 1.5

IC7100: VSM Digital Board 1.5, Versatile Stream Manager




Figure 2.1: VSM Overview

PINNING

OVERVIEW

Name	Pins	Type	Function
System			
RESETn	1	In	
SYSCLK (27MHz)	1	In	
Host Interface			
HO_A(21:1)	21	In	
HO_D(15:0)	16	In/Out	
HO_BEn(1:0)	2	In	
HO_RWn	1	In	
HO_CSLn	1	In	
HO_CSHn	1	In	
HO_A22	1	In	
HO_WAIT	1	Out	
HO_PROCCLK	1	In	
Memory Interface			
M_A(13:0)	14	Out	
M_DQ(15:0)	16	In/Out	
M_RASn	1	Out	
M_CASn	1	Out	
M_WEn	1	Out	
M_LDQM	1	Out	
M_UDQM	1	Out	
M_CLKOUT	1	Out	
M_CLKEN	1	Out	
Basic Engine Interface			
BE_BCLK	1	In	
BE_DATI	1	In	
BE_WCLK	1	In	
BE_SYNC	1	In/Out	
BE_FLAG	1	In	
BE_V4	1	In	
BE_DATO	1	Out	
Video Encoder Interface			
VE_D(15:0)	16	In	
VE_DSn	1	Out	
VE_DTACKn	1	In	
VE_VIP_ERROR	1	In	Signal coming from SAA7114
Audio Encoder Interface			
AE_CSn	1	Out	
AE_BCLK	1	In/Out	(CR151,CR157)
AE_WCLK	1	In/Out	(CR151,CR157)
AE_DATA	1	In	(CR157)

Decoder Interface

D_PAR_D(7:0)	8	Out	
D_PAR_DVALID	1	Out	
D_PAR_STR	1	Out	
D_PAR_REQ	1	In	
D_PAR_SYNC	1	Out	
D_WCLK	1	Out	
D_V4	1	Out	

Audio Clock Control

ACC_FID	1	In	(CR200)
ACC_PWM	1	Out	
ACC_ACLK_OSC	1	In	
ACC_ACLK_DAI	1	In	
ACC_ACLK_PLL	1	In	
ACC_ACLK_DEC	1	Out	

VBI Extractor

VBI_IPD(7:0)	8	In	
VBI_ICLK	1	In	

UART 1

UART1_RX	1	In	
UART1_TX	1	Out (OC)	
UART1_CTSn	1	In	
UART1_RTSn	1	Out (OC)	

UART 2

UART2_RX	1	In	
UART2_TX	1	Out (OC)	
UART2_CTSn	1	In	
UART2_RTSn	1	Out (OC)	

UART 3 (VSM1B)

UART3_RX	1	In	
UART3_TX	1	Out	
UART3_CTSn	1	In	
UART3_RTSn	1	Out	

Interrupt Controller

EXTINT(3:0)	4	In	From: VEnc, AEnc, BE, VSync (STi5505)
CPUINT(1:0)	2	Out (OC)	

JTAG

TCK	1	In	Boundary Scan
TDI	1	In	
TDO	1	Out/Z	
TMS	1	In	
TRSTn	1	In	

Test

TEST0	1	In	Amsal Test
TEST1	1	In	

Power Supply

VDD	20	Power	10% of total pins package
VSS	20	Power	10% of total pins package

Total Pins	208		
------------	-----	--	--

IC7403: SAA6752H (EMPRESS), Digital Board 1.5, MPEG-2 Encoder

5 BLOCK DIAGRAM




Fig.1 Block diagram.

PINNING

SYMBOL	PIN	INPUT/OUTPUT ⁽¹⁾	I _{max} (mA)	DESCRIPTION
V _{SSP}	1	ground	–	pad ground
SDATA1	2	input	–	I ² S-bus serial data input port 1 with internal pull-down resistor
SCLK1	3	input/output	4	I ² S-bus serial clock port 1 with internal pull-down resistor
SWS1	4	input/output	4	I ² S-bus word select port 1 with internal pull-down resistor
V _{DDP}	5	supply	–	pad ring supply voltage (3.3 V)
SDATA2	6	input/output	4	I ² S-bus serial data port 2 with internal pull-down resistor
SCLK2	7	input/output	4	I ² S-bus serial clock port 2 with internal pull-down resistor
SWS2	8	input/output	4	I ² S-bus word select port 2 with internal pull-down resistor
ACLK	9	output	4	audio clock output ($256 \times f_s$ or $384 \times f_s$)
V _{SSP}	10	ground	–	pad ground
IDQ	11	input	–	reserved (recommended connect to pin V _{SSP}) with internal pull-down resistor
YUV0	12	input	–	video input signal bit 0 (LSB)
YUV1	13	input	–	video input signal bit 1
YUV2	14	input	–	video input signal bit 2
YUV3	15	input	–	video input signal bit 3
YUV4	16	input	–	video input signal bit 4
YUV5	17	input	–	video input signal bit 5
YUV6	18	input	–	video input signal bit 6
YUV7	19	input	–	video input signal bit 7 (MSB)
V _{SSP}	20	ground	–	pad ground
HSYNC	21	input	–	horizontal sync input (video) with internal pull-down resistor
VSYNC	22	input	–	vertical sync input (video) with internal pull-down resistor
FID	23	input	–	video field identification input (odd/even field) with internal pull-down resistor
VCLK1	24	input	–	video clock input 1 (27 MHz) with internal pull-down resistor
V _{SSCO}	25	ground	–	core ground
V _{SSCO}	26	ground	–	core ground
V _{DDCO}	27	supply	–	core supply voltage (2.5 V)
V _{DDCO}	28	supply	–	core supply voltage (2.5 V)
V _{DDP}	29	supply	–	pad ring supply voltage (3.3 V)
VCLK2	30	input	–	video clock input 2 (27 MHz) with internal pull-down resistor
PDOAV	31	3-state output	4	parallel stream data output for audio/video identifier
PDIDS	32	input	–	parallel stream data input for data strobe (request for packet in Data Expansion Bus Interface (DEBI) slave mode) with internal pull-up resistor
PDOSYNC	33	3-state output	4	parallel stream data output for packet sync
V _{SSP}	34	ground	–	pad ground
PDOVAL	35	3-state output	4	parallel stream data valid output with internal pull-up resistor
PDO0	36	3-state output	4	parallel stream data output bit 0 (LSB)

SYMBOL	PIN	INPUT/OUTPUT ⁽¹⁾	I _{max} (mA)	DESCRIPTION
PDO1	37	3-state output	4	parallel stream data output bit 1
PDO2	38	3-state output	4	parallel stream data output bit 2
V _{DDP}	39	supply	–	pad ring supply voltage (3.3 V)
PDO3	40	3-state output	4	parallel stream data output bit 3
PDO4	41	3-state output	4	parallel stream data output bit 4
PDO5	42	3-state output	4	parallel stream data output bit 5
PDO6	43	3-state output	4	parallel stream data output bit 6
V _{SSP}	44	ground	–	pad ground
PDO7	45	3-state output	4	parallel stream data output bit 7 (MSB)
PDIOCLK	46	input/output	4	parallel stream clock input/output
I2CADDRSEL	47	input	–	I ² C-bus address select input with internal pull-up resistor
SD_DQ15	48	input/output	8	SDRAM data input/output bit 15 (MSB)
V _{DDP}	49	supply	–	pad ring supply voltage (3.3 V)
SD_DQ0	50	input/output	8	SDRAM data input/output bit 0 (LSB)
SD_DQ14	51	input/output	8	SDRAM data input/output bit 14
SD_DQ1	52	input/output	8	SDRAM data input/output bit 1
V _{SSP}	53	ground	–	pad ground
SD_DQ13	54	input/output	8	SDRAM data input/output bit 13
SD_DQ2	55	input/output	8	SDRAM data input/output bit 2
SD_DQ12	56	input/output	8	SDRAM data input/output bit 12
V _{DDP}	57	supply	–	pad ring supply voltage (3.3 V)
SD_DQ3	58	input/output	8	SDRAM data input/output bit 3
SD_DQ11	59	input/output	8	SDRAM data input/output bit 11
SD_DQ4	60	input/output	8	SDRAM data input/output bit 4
SD_DQ10	61	input/output	8	SDRAM data input/output bit 10
V _{SSP}	62	ground	–	pad ground
SD_DQ5	63	input/output	8	SDRAM data input/output bit 5
SD_DQ9	64	input/output	8	SDRAM data input/output bit 9
SD_DQ6	65	input/output	8	SDRAM data input/output bit 6
SD_DQ8	66	input/output	8	SDRAM data input/output bit 8
V _{DDP}	67	supply	–	pad ring supply voltage (3.3 V)
SD_DQ7	68	input/output	8	SDRAM data input/output bit 7
SD_DQM1	69	output	8	SDRAM data mask enable output bit 1
SD_DQM0	70	output	8	SDRAM data mask enable output bit 0 (LSB)
SD_WE	71	output	8	SDRAM write enable output (active LOW)
V _{SSP}	72	ground	–	pad ground
SD_CAS	73	output	8	SDRAM column address strobe output (active LOW)
SD_CLK	74	output	8	SDRAM clock output
SD_RAS	75	output	8	SDRAM row address strobe output (active LOW)
SD_CKE	76	output	8	SDRAM clock enable output

SYMBOL	PIN	INPUT/OUTPUT ⁽¹⁾	I _{max} (mA)	DESCRIPTION
V _{SSCO}	77	ground	–	core ground
V _{SSCO}	78	ground	–	core and substrate ground
V _{DDCO}	79	supply	–	core supply voltage (2.5 V)
V _{DDCO}	80	supply	–	core supply voltage (2.5 V)
V _{DDP}	81	supply	–	pad ring supply voltage (3.3 V)
SD_CS	82	output	8	SDRAM chip select output (active LOW)
SD_A13	83	output	8	SDRAM address output bit 13 (bank selection for 64 Mbit)
SD_A9	84	output	8	SDRAM address output bit 9
SD_A8	85	output	8	SDRAM address output bit 8
V _{SSP}	86	ground	–	pad ground
SD_A11	87	output	8	SDRAM address output bit 11 (bank selection for 16 Mbit)
SD_A7	88	output	8	SDRAM address output bit 7
SD_A12	89	output	8	SDRAM address output bit 12 (bank selection for 64 Mbit)
SD_A6	90	output	8	SDRAM address output bit 6
V _{DDP}	91	supply	–	pad ring supply voltage (3.3 V)
SD_A10	92	output	8	SDRAM address output bit 10
SD_A5	93	output	8	SDRAM address output bit 5
SD_A0	94	output	8	SDRAM address output bit 0 (LSB)
SD_A4	95	output	8	SDRAM address output bit 4
V _{SSP}	96	ground	–	pad ground
SD_A1	97	output	8	SDRAM address output bit 1
SD_A3	98	output	8	SDRAM address output bit 3
SD_A2	99	output	8	SDRAM address output bit 2
SD_DQM3	100	output	8	reserved (do not connect)
V _{DDP}	101	supply	–	pad ring supply voltage (3.3 V)
SD_DQM2	102	output	8	reserved (do not connect)
SD_DQ31	103	input/output	8	reserved (do not connect)
SD_DQ16	104	input/output	8	reserved (do not connect)
V _{SSP}	105	ground	–	pad ground
SD_DQ30	106	input/output	8	reserved (do not connect)
SD_DQ17	107	input/output	8	reserved (do not connect)
SD_DQ29	108	input/output	8	reserved (do not connect)
V _{DDP}	109	supply	–	pad ring supply voltage (3.3 V)
SD_DQ18	110	input/output	8	reserved (do not connect)
SD_DQ28	111	input/output	8	reserved (do not connect)
SD_DQ19	112	input/output	8	reserved (do not connect)
SD_DQ27	113	input/output	8	reserved (do not connect)
V _{SSP}	114	ground	–	pad ground
SD_DQ20	115	input/output	8	reserved (do not connect)
SD_DQ26	116	input/output	8	reserved (do not connect)

SYMBOL	PIN	INPUT/OUTPUT ⁽¹⁾	I _{max} (mA)	DESCRIPTION
V _{SSCO}	77	ground	–	core ground
V _{SSCO}	78	ground	–	core and substrate ground
V _{DDCO}	79	supply	–	core supply voltage (2.5 V)
V _{DDCO}	80	supply	–	core supply voltage (2.5 V)
V _{DDP}	81	supply	–	pad ring supply voltage (3.3 V)
SD_CS	82	output	8	SDRAM chip select output (active LOW)
SD_A13	83	output	8	SDRAM address output bit 13 (bank selection for 64 Mbit)
SD_A9	84	output	8	SDRAM address output bit 9
SD_A8	85	output	8	SDRAM address output bit 8
V _{SSP}	86	ground	–	pad ground
SD_A11	87	output	8	SDRAM address output bit 11 (bank selection for 16 Mbit)
SD_A7	88	output	8	SDRAM address output bit 7
SD_A12	89	output	8	SDRAM address output bit 12 (bank selection for 64 Mbit)
SD_A6	90	output	8	SDRAM address output bit 6
V _{DDP}	91	supply	–	pad ring supply voltage (3.3 V)
SD_A10	92	output	8	SDRAM address output bit 10
SD_A5	93	output	8	SDRAM address output bit 5
SD_A0	94	output	8	SDRAM address output bit 0 (LSB)
SD_A4	95	output	8	SDRAM address output bit 4
V _{SSP}	96	ground	–	pad ground
SD_A1	97	output	8	SDRAM address output bit 1
SD_A3	98	output	8	SDRAM address output bit 3
SD_A2	99	output	8	SDRAM address output bit 2
SD_DQM3	100	output	8	reserved (do not connect)
V _{DDP}	101	supply	–	pad ring supply voltage (3.3 V)
SD_DQM2	102	output	8	reserved (do not connect)
SD_DQ31	103	input/output	8	reserved (do not connect)
SD_DQ16	104	input/output	8	reserved (do not connect)
V _{SSP}	105	ground	–	pad ground
SD_DQ30	106	input/output	8	reserved (do not connect)
SD_DQ17	107	input/output	8	reserved (do not connect)
SD_DQ29	108	input/output	8	reserved (do not connect)
V _{DDP}	109	supply	–	pad ring supply voltage (3.3 V)
SD_DQ18	110	input/output	8	reserved (do not connect)
SD_DQ28	111	input/output	8	reserved (do not connect)
SD_DQ19	112	input/output	8	reserved (do not connect)
SD_DQ27	113	input/output	8	reserved (do not connect)
V _{SSP}	114	ground	–	pad ground
SD_DQ20	115	input/output	8	reserved (do not connect)
SD_DQ26	116	input/output	8	reserved (do not connect)


SYMBOL	PIN	INPUT/OUTPUT ⁽¹⁾	I _{max} (mA)	DESCRIPTION
SD_DQ21	117	input/output	8	reserved (do not connect)
SD_DQ25	118	input/output	8	reserved (do not connect)
V _{DDP}	119	supply	–	pad ring supply voltage (3.3 V)
SD_DQ22	120	input/output	8	reserved (do not connect)
SD_DQ24	121	input/output	8	reserved (do not connect)
SD_DQ23	122	input/output	8	reserved (do not connect)
EXTCLK	123	input	–	27 MHz external clock input with internal pull-up resistor
V _{SSP}	124	ground	–	pad ground
V _{SSA}	125	ground	–	oscillator analog ground
XTALI	126	analog input	–	crystal oscillator input (27 MHz); note 2
XTALO	127	analog output	–	crystal oscillator output (27 MHz)
V _{DDA}	128	supply	–	oscillator analog supply voltage (2.5 V)
V _{SSCO}	129	ground	–	core ground
V _{SSCO}	130	ground	–	core ground
V _{DDCO}	131	supply	–	core supply voltage (2.5 V)
V _{DDCO}	132	supply	–	core supply voltage (2.5 V)
V _{DDP}	133	supply	–	pad ring supply voltage (3.3 V)
TDI	134	input	–	boundary scan test data input; pin must float or set to HIGH during normal operating; with internal pull-up resistor; note 3
TMS	135	input	–	boundary scan test mode select; pin must float or set to HIGH during normal operating; with internal pull-up resistor; note 3
TCK	136	input	–	boundary scan test clock; pin must be set to LOW during normal operating; with internal pull-up resistor; note 3
TDO	137	3-state output	4	boundary scan test data output; pin not active during normal operating; with 3-state output; note 3
V _{SSP}	138	ground	–	pad ground
TRST	139	input	–	test reset input (active LOW), for boundary scan test (with internal pull-up); notes 3 and 4
CLKOUT	140	output	4	27 MHz system clock output
TEST0	141	input/output	4	reserved (do not connect)
TEST1	142	input/output	4	reserved (do not connect)
V _{DDP}	143	supply	–	pad ring supply voltage (3.3 V)
TEST2	144	input/output	4	reserved (do not connect)
SDA	145	input/open-drain output	–	serial data input/output (I ² C-bus)
SCL	146	input/open-drain output	–	serial clock input/output (I ² C-bus)
RESET	147	input	–	reset input (active LOW); with internal pull-up resistor
V _{SSP}	148	ground	–	pad ground
RTS	149	output	4	reserved (do not connect); Universal Asynchronous Receiver/Transmitter (UART) request to send output (active LOW)

SYMBOL	PIN	INPUT/OUTPUT ⁽¹⁾	I _{max} (mA)	DESCRIPTION
CTS	150	input	–	reserved (recommended connect to pin V _{DDP}); UART clear to send input; external static memory select input (active LOW); with internal pull-up resistor
RXD	151	input	–	reserved (recommended connect to pin V _{DDP}); UART receive data; internal boot select input; with internal pull-up resistor
TXD	152	output	4	reserved (do not connect); UART transmit data
V _{DDP}	153	supply	–	pad ring supply voltage (3.3 V)
SM_LB	154	input/output	4	reserved (do not connect)
SM_UB	155	input/output	4	reserved (do not connect)
H_IRF	156	3-state output	4	host interrupt ?ag output; with internal pull-up resistor
V _{SSP}	157	ground	–	pad ground
SM_OE	158	output	4	reserved (do not connect), static memory output enable output (active LOW)
SM_A9	159	output	4	reserved (do not connect), static memory address output bit 9
SM_A10	160	output	4	reserved (do not connect), static memory address output bit 10
V _{DDP}	161	supply	–	pad ring supply voltage (3.3 V)
SM_A8	162	output	4	reserved (do not connect), static memory address output bit 8
SM_A11	163	output	4	reserved (do not connect), static memory address output bit 11
SM_A7	164	output	4	reserved (do not connect), static memory address output bit 7
SM_A12	165	output	4	reserved (do not connect), static memory address output bit 12
V _{SSP}	166	ground	–	pad ground
SM_A6	167	output	4	reserved (do not connect), static memory address output bit 6
SM_A13	168	output	4	reserved (do not connect), static memory address output bit 13
SM_A5	169	output	4	reserved (do not connect), static memory address output bit 5
SM_A14	170	output	4	reserved (do not connect), static memory address output bit 14
V _{DDP}	171	supply	–	pad ring supply voltage (3.3 V)
SM_WE	172	output	4	reserved (do not connect), static memory write enable output (active LOW)
SM_D7	173	input/output	4	reserved (do not connect), static memory data input/output bit 7 with internal pull-down resistor
SM_D8	174	input/output	4	reserved (do not connect), static memory data input/output bit 8 with internal pull-down resistor
SM_D6	175	input/output	4	reserved (do not connect), static memory data input/output bit 6 with internal pull-down resistor
V _{SSP}	176	ground	–	pad ground
SM_D9	177	input/output	4	reserved (do not connect), static memory data input/output bit 9 with internal pull-down resistor
SM_D5	178	input/output	4	reserved (do not connect), static memory data input/output bit 5 with internal pull-down resistor
SM_D10	179	input/output	4	reserved (do not connect), static memory data input/output bit 10 with internal pull-down resistor


SYMBOL	PIN	INPUT/OUTPUT ⁽¹⁾	I _{max} (mA)	DESCRIPTION
SM_D4	180	input/output	4	reserved (do not connect), static memory data input/output bit 4 with internal pull-down resistor
V _{SSCO}	181	ground	–	internal pre-driver and substrate ground
V _{SSCO}	182	ground	–	core ground
V _{DDCO}	183	supply	–	core supply voltage (2.5 V)
V _{DDCO}	184	supply	–	internal pre-driver supply voltage (2.5 V)
V _{DDP}	185	supply	–	pad ring supply voltage (3.3 V)
SM_D11	186	input/output	4	reserved (do not connect), static memory data input/output bit 11 with internal pull-down resistor
SM_D3	187	input/output	4	reserved (do not connect), static memory data input/output bit 3 with internal pull-down resistor
SM_D12	188	input/output	4	reserved (do not connect), static memory data input/output bit 12 with internal pull-down resistor
SM_D2	189	input/output	4	reserved (do not connect), static memory data input/output bit 2 with internal pull-down resistor
V _{SSP}	190	ground	–	pad ground
SM_D13	191	input/output	4	reserved (do not connect), static memory data input/output bit 13 with internal pull-down resistor
SM_D1	192	input/output	4	reserved (do not connect), static memory data input/output bit 1 with internal pull-down resistor
SM_D14	193	input/output	4	reserved (do not connect), static memory data input/output bit 14 with internal pull-down resistor
SM_D0	194	input/output	4	reserved (do not connect), static memory data input/output bit 0 (LSB) with internal pull-down resistor
V _{DDP}	195	supply	–	pad ring supply voltage (3.3 V)
SM_D15	196	input/output	4	reserved (do not connect), static memory data input/output bit 15 (MSB) with internal pull-down resistor
SM_CS3	197	output	4	reserved (do not connect), static memory chip select output for external ROM or RAM (active LOW)
SM_A4	198	output	4	reserved (do not connect), static memory address output bit 4
SM_A3	199	output	4	reserved (do not connect), static memory address output bit 3
V _{SSP}	200	ground	–	pad ground
SM_A2	201	output	4	reserved (do not connect), static memory address output bit 2
SM_A15	202	output	4	reserved (do not connect), static memory address output bit 15
SM_A1	203	output	4	reserved (do not connect), static memory address output bit 1
SM_A16	204	output	4	reserved (do not connect), static memory address output bit 16
V _{DDP}	205	supply	–	pad ring supply voltage (3.3 V)
SM_A0	206	output	4	reserved (do not connect), static memory address output bit 0 (LSB)
SM_A17	207	output	4	reserved (do not connect), static memory address output bit 17 (MSB)
SM_CS0	208	output	4	reserved (do not connect)

IC7700: FLI2200, Digital Board 1.5, Deinterlacer

Simplified Block Diagram



Pin description



Pin #	Name	Description
52	NOMEM	No Memory Mode control input. This pin controls the operation of the FLI2200 as follows: When this pin is set low the device is used with external field memories and operates in the full set of deinterlacing modes, i.e., motion adaptive video deinterlacing and full frame film source deinterlacing using 3:2 pulldown detection (2:2 pulldown for 625/50 sources). When this pin is set high the FLI2200 is forced into the intra-field only deinterlacing mode, which requires no external memories, allowing the FLI2200 to be used in low-cost applications where the ultimate video quality is not a requirement. To ensure proper startup of the SDRAMs this pin should be set high during the power-up sequence. This can be overridden by the NMOvr bit, bit 1 in register 05 _H , allowing this function to be set or changed via the I ² C bus. Please refer to the description of register 05 _H for details.
27-18	G/YIN _{9,0}	10-bit green or luminance signal input bus. The mode is set by the IFORMAT _{2,0} pins. This can be overridden by the IFmtOvr bit, bit 3 in register 00 _H , allowing this function to be set or changed via the I ² C bus. Please refer to the description of register 00 _H for details. This signal is sampled on the rising edge of PIXCLK.
15-6	B/CbIN _{9,0}	10-bit blue or Cb chroma signal input bus. The mode is set by the IFORMAT _{2,0} pins. This can be overridden by the IFmtOvr bit, bit 3 in register 00 _H , allowing this function to be set or changed via the I ² C bus. Please refer to the description of register 00 _H for details. Bits 6, 4 and 3 in register 08 _H specify the busses used in the multiplexed modes. In all cases the signals are sampled on the rising edges of PIXCLK. In the Y Cb Cr and Y Pb Pr modes the Cb or Pb signal is sampled on alternate rising edges of PIXCLK in 4:2:2 mode. The frequency of PIXCLK will be 27 MHz in the multiplexed Y/Cb/Cr mode and 13.5 MHz in all other modes. These pins should be tied low when not used.
39-35 32-28	R/CrIN _{9,0}	10-bit red or Cr chroma signal input bus. The mode is set by the IFORMAT _{2,0} pins. This can be overridden by the IFmtOvr bit, bit 3 in register 00 _H , allowing this function to be set or changed via the I ² C bus. Please refer to the description of register 00 _H for details. Bits 6, 4 and 3 in register 08 _H specify the busses used in the multiplexed modes. In all cases the signals are sampled on the rising edges of PIXCLK. In the Y Cb Cr mode the Cr signal is sampled on alternate rising edges of PIXCLK in 4:2:2 mode. The frequency of PIXCLK will be 27 MHz in the multiplexed Y/Cb/Cr mode and 13.5 MHz in all other modes. These pins should be tied low when not used.
3	HSYNCREFI	Horizontal sync or reference. The horizontal sync or reference of the input signal should be connected to this pin. The function is programmed with bit 4 in register 00 _H . The polarity and position of the sync or reference pulse relative to the start of active video are both programmable within a small range. When the FLI2200 is used in the ITU-R BT 601/D1 input mode with embedded syncs (IFormat = 110) this input is not used and should be tied low; in this case all sync information will be derived from the signal.
4	VSYNCREFI	Vertical sync or reference. The vertical sync or reference of the input signal should be connected to this pin. The function is programmed with bit 4 in register 00 _H . The polarity and position of the sync or reference pulse relative to the start of active video are both programmable within a small range. When the FLI2200 is used in the ITU-R BT 601/D1 input mode with embedded syncs (IFormat = 110) this input is not used and should be tied low; in this case all sync information will be derived from the signal.
5	FLDIN	Field identifier input. The field identifier output of the source signal should be connected to this pin. A low setting signifies an even field and a high level signifies an odd field. When bit 4 in register 00 _H is set low, the input timing is based on HREF and VREF and this signal is required. When this bit is set high the input timing is based on HSYNC and VSYNC and this signal is generated internally and is not required. When bit 5 in register 06 is set high this signal is also used as the frame boundary identifier for 30 Hz film sources.


Pin Connections and Functions

Pin #	Name	Description
See list	V _{SS}	Ground connections. Connect to the digital ground plane. Pins: 2, 17, 34, 55, 64, 74, 85, 96, 106, 115, 124, 132, 138, 145, 152, 159, 168
See list	V _{DD33}	Pad Ring digital power connections. Connect to the digital 3.3 volt power supply and decouple to the digital ground plane. Pins: 1, 33, 63, 73, 84, 95, 105, 114, 123, 137, 144, 151, 167
See list	V _{DD25}	Core Logic digital power connections. Connect to the digital 2.5 volt power supply and decouple to the digital ground plane. Pins: 16, 54, 107, 158
43	AV _{SS}	Ground connection for the clock PLL circuits. Connect to the digital ground plane
42	AV _{DD}	Analog power connections for the clock PLL circuit. Connect to a separately decoupled 2.5 volt power supply and decouple directly to the AV _{SS} pin..
49	RESETB	Reset. When this input is set low it will reset all the internal registers to the default states. Refer to the section on the control registers for details of these states. The device must be reset after it is powered-up.
53	OE	When this pin is set high the outputs of the FLI2200 will be enabled; when it is set low the outputs will be set into a high-impedance state.
56-58	IFORMAT ₂₋₀	Input signal format control. The settings of these pins set the format of the input signal. This can be overridden by the IFmtOvr bit, bit 3 in register 00 _H , allowing this function to be set or changed via the I ² C bus. Please refer to the description of register 00 _H for details.
59-61	OFORMAT ₂₋₀	Output signal format control. The settings of these pins set the format of the output signal. This can be overridden by the OFmtOvr bit, bit 3 in register 07 _H , allowing this function to be set or changed via the I ² C bus. Please refer to the description of register 07 _H for details.
44-45	DADDR ₁₋₀	The settings of DADDR ₁₋₀ allow the device address of the control bus to be programmed to prevent conflict with the other devices connected to the bus. DADDR ₁₋₀ allow the device address to be set to any of the following values: C0/C1 _H , C2/C3 _H , E0/E1 _H , E2/E3 _H . Please refer to the section “Control Bus Operation and Protocol” for further information.
46	MODE	When this pin is set low the control bus will operate in the slave mode; allowing the device to be programmed from an external controller. When it is set high the FLI2200 will self-program from an external I ² C memory connected to the bus. Please refer to the “Control Bus Operation and Control Protocol” section for more details.
47	SDA	2-wire serial control bus data. Data can be written to the control registers via this pin when it is in the input mode and data can be read from the status registers when it is in the output mode. Refer to the section on the serial port for timing and format details and to the section on the registers for programming information.
48	SCL	2-wire serial control bus clock. When the control port operates in slave mode this pin will be an input and when it operates in the self programming mode it will be an output.
40	PIXCLK	Pixel clock input. This clock is used to drive all the circuits in the FLI2200. An internal PLL is used to upconvert this clock to provide the master clock signal and other clocks used internally. Note that when the FLI2200 is used in the D1 input mode the PIXCLK input should run at the rate of two cycles per pixel (one for luma and one for chroma).
62	N/P/IN/OUT	NTSC/PAL input or output. The default function of this pin is NTSC/PAL signal indicator output. When the input video signal is a 525 line signal this pin will be set high and when it is a 625 line signal the pin is set low. This function of this pin can be programmed to be an input according to the setting of this pin if the NPop ₁₋₀ bits, bits 5-4 in register 03 _H , are set to 00 _H , overriding the internal line counter. i.e., it will treat the signal as a 525 line signal when it is set high and a 625 line signal when it is set low.

Pin #	Name	Description
65-72 75-76	G/YOUT ₉₋₀	Green or luminance output bus. In the RGB mode this output is the Green signal and in the YCbCr mode it is the Y signal. The mode is set by the OFORMAT ₂₋₀ pins. This can be overridden by the OFmtOvr bit, bit 3 in register 07 _H , allowing this function to be set or changed via the I ² C bus. Please refer to the description of register 07 _H for details. The signal is clocked out on the falling edge of YCLKO.
93-94 97-104	B/CbOUT ₉₋₀	Blue or Cb chrominance output bus. In the RGB mode this output is the Blue signal, in the Y Cb Cr mode it is the Cb signal. The mode is set by the OFORMAT ₂₋₀ pins. This can be overridden by the OFmtOvr bit, bit 3 in register 07 _H , allowing this function to be set or changed via the I ² C bus. Please refer to the description of register 07 _H for details. The busses used in the multiplexed modes are set by means of bit 5 in register 08 _H . The signal is clocked out on the falling edge of YCLKO in the RGB and YUV 4:4:4 modes, on the falling edge of YCLKO prior to the next rising edge of CCLKO in the YUV 4:2:2 mode, and on the rising edge of MEMCLKO in the multiplexed YCbCr (pseudo D1) mode.
77-83 86-88	R/CrOUT ₉₋₀	Red or Cr chrominance output bus. In the RGB mode this output is the Red signal, in the YCbCr mode it is the Cr signal. The mode is set by the OFORMAT ₂₋₀ pins. This can be overridden by the OFmtOvr bit, bit 3 in register 07 _H , allowing this function to be set or changed via the I ² C bus. Please refer to the description of register 07 _H for details. The busses used in the multiplexed modes are set by means of bit 5 in register 08 _H . The signal is clocked out on the falling edge of YCLKO in the RGB and YUV 4:4:4 modes, on the falling edge of YCLKO prior to the next rising edge of CCLKO in the YUV 4:2:2 mode, and on the rising edge of MEMCLKO in the multiplexed YCbCr (pseudo D1) mode.
116	CCLKO	Chroma output sampling clock. This clock is derived from PIXCLK and will be at half the frequency of YCLKO. In 30-bit 4:2:2 output mode the chroma output signals will change on the falling edge of YCLKO prior to the next rising edge this clock.
117	YCLKO	Luma output sampling clock. This clock is derived from PIXCLK and is double the frequency of PIXCLK. In 30-bit and 20-bit output modes the output signals will change on the falling edge of this clock.
89	VREFO	Start of active field or frame indicator. This signal goes high to indicate the first active line in each field or frame and goes low during the vertical blanking interval. The polarity and timing of this signal are programmable.
90	HREFO	Start of active line indicator output. This signal goes high to indicate the first active pixel in each line and goes low during the horizontal blanking interval. The polarity and timing of this signal are programmable.
91	VSYNCR/ CREFO	Vertical sync output. This signal provides the vertical sync function for the outputs. Its polarity is programmable to be active high or active low. It can also be programmed to be a composite reference for applications requiring this instead of sync.
92	H/CSYNCO	Horizontal or composite sync output. This signal provides the horizontal sync function for the outputs. Its polarity is programmable to be active high or active low. This signal can also be programmed to be the composite sync output, CSYNC.
108	FSYNC	Film mode sync output. When film mode is detected this pin will toggle in sync with the 3:2 (NTSC) or 2:2 (PAL and 30 Hz film in NTSC) pulldown sequence detected in the source.
110	FILM	Film mode detector output. This pin will be set high when the FLI2200 detects that the video input was converted from 24 fps film with a teleciné machine. If film mode is not detected this pin will be set low.

Pin #	Name	Description
125-131 133-136	ADDR ₁₀₋₀	SDRAM Address bus. This signal bus is used to address the external SDRAM(s) used for field memories. It should be connected to the A ₁₀₋₀ bus of the memory chip(s). Please refer to the Applications section of this data sheet for further details.
176-169 166-160 157-153 150-146 143-139	DATA ₂₉₋₀	SDRAM Data bus. This signal bus is used to transfer the data to and from the external SDRAM(s) used for field memories. It should be connected to the DQ ₂₉₋₀ bus of the memory chip when using a 64 Mbit SDRAM. When using two 16 Mbit SDRAMs this 30-bit bus may be connected to the two 16-bit data busses of the memories in two ways: either connect 16 lines to one chip and 14 to the other, or connect 15 to both. In all cases the two unused data lines on the memory chip(s) should be connected to ground via 22 k Ω resistors. Please refer to the Applications section of this data sheet for further details.
118	MEMCLKO	SDRAM clock and 2x output sampling clock. This clock is derived from PIXCLK and will be at double the frequency of YCLKO. This active signal should be connected to the CLK pin(s) on the SDRAM(s). When the 10-bit output mode selected the output signals will also change at this clock rate and this should then be used as the output clock..
119	WEN	SDRAM Write Enable. This active low signal should be connected to the WE pin(s) on the SDRAM(s).
120	RASN	SDRAM Row Address Select. This active low signal should be connected to the RAS pin(s) on the SDRAM(s).
121	CASN	SDRAM Column Address Select. This active low signal should be connected to the CAS pin(s) on the SDRAM(s).
122	BSEL	SDRAM Bank Select. When using two 16 Mbit SDRAMs this signal should be connected to the BA (also called BS or A ₁₁) pin on both SDRAMs. When using a 64 Mbit SDRAM this signal should be connected to the BA0 (also called BS0 or A ₁₁) pin on the SDRAM and BA1/BS1 (also called BA when BA0 is referred to as A ₁₁) should be tied low.
41, 50, 51, 109, 111	TEST ₄₋₀	These pins are used for test purposes only and should always be tied low for normal operation.
112, 113	TESTO ₁₋₀	These pins are test outputs and should be left unconnected in normal operation.

9.12.4IC's Divio 1.8

IC7400: uPD72852, DVIO Board, IEEE1394 Physical Layer Chip**BLOCK DIAGRAM**

1.1 Cable Interface Pins

Name	Pin No.	I/O	Function
TpA0p	39	I/O	Port 0 twisted pair cable A positive phase I/O
TpA0n	38	I/O	Port 0 twisted pair cable A negative phase I/O
TpB0p	37	I/O	Port 0 twisted pair cable B positive phase I/O
TpB0n	36	I/O	Port 0 twisted pair cable B negative phase I/O
TpA1p	46	I/O	Port 1 twisted pair cable A positive phase I/O
TpA1n	45	I/O	Port 1 twisted pair cable A negative phase I/O
TpB1p	44	I/O	Port 1 twisted pair cable B positive phase I/O
TpB1n	43	I/O	Port 1 twisted pair cable B negative phase I/O
SUS/RES	19	I	Suspend/Resume function select 1: Suspend/Resume on (IEEE1394a-2000 compliant) 0: Suspend/Resume off (P1394a draft 1.3 compliant)
CPS	32	I	Cable power status Connect to the cable through a 390 k Ω resistor and to GND through a 100 k Ω resistor. 0: Cable power fail 1: Cable power on

1.2 Link Interface Pins

Name	Pin No.	I/O	Function
D0	8	I/O	Data input/output (bit 0)
D1	9	I/O	Data input/output (bit 1)
D2	11	I/O	Data input/output (bit 2)
D3	12	I/O	Data input/output (bit 3)
D4	14	I/O	Data input/output (bit 4)
D5	15	I/O	Data input/output (bit 5)
D6	17	I/O	Data input/output (bit 6)
D7	18	I/O	Data input/output (bit 7)
CTL0	5	I/O	Link interface control (bit 0)
CTL1	6	I/O	Link interface control (bit 1)
LREQ	63	I	Link request input
SCLK	2	O	Link control output clock LPS 1: 49.152 MHz output LPS 0: Clamp to 0 (The clock signal will be output within 25 μ sec after change to "0")
LPS	59	I	Link power status input 0: Link power off 1: Link power on (PHY/Link direct connection)
LKON	58	O	Link-on signal output Link-on signal is 6.144 MHz clock output. Please refer to 4.2 Link-on Indication .
DIRECT	50	I	PHY/Link isolation barrier control input 0: Isolation barrier 1: PHY/Link direct connection

1.3 Control Pins

Name	Pin No.	I/O	Function
PC0	26	I	Power class set input
PC1	27	I	This pin status will be loaded to Pwr_class bit which allocated to PHY register 4H.
PC2	28	I	IEEE1394a-2000 chapter [4.3.4.1]
CMC	30	I	Configuration manager capable setting This pin status will be loaded to Contender bit which allocated to PHY register 4H. 0: Non contender 1: Contender
RESETB	55	I	Power-on reset input Connect to GND through a 0.1 μ F capacitor. 0: Reset 1: Normal
SPD	61	I	Speed select 0: MAX. S200 1: MAX. S400

1.4 IC

Name	Pin No.	I/O	Function
IC(AL)	29, 51	-	Internally Connected (Low Clamped) Connect to GND.
IC(DL)	3	-	Internally Connected (Low Clamped) Connect to GND.

1.5 Power Supply Pins

Name	Pin No.	I/O	Function
AV _{DD}	25, 31, 40, 47, 54	-	Analog power
AGND	24, 33, 35, 42, 49, 52, 53	-	Analog GND
DV _{DD}	4, 10, 20, 56, 60	-	Digital V _{DD}
DGND	1, 7, 13, 16, 21, 57, 64	-	Digital GND


1.6 Other Pins

Name	Pin No.	I/O	Function
TpBias0	41	O	Port 0 twisted pair output
TpBias1	48	O	Port 1 twisted pair output
RI1	34	-	Resistor connection pin1 for reference current generator Connect to GND through a 9.1 k Ω resistor.
XI	23	-	Crystal oscillator connection XI
XO	22	-	Crystal oscillator connection XO
TEST	62	-	Test pin Internally connected (Low clamped). Connect to GND.


IC7431: uPD72893, DVIO Board, IEEE1394 Link Layer Chip and DV Decoder

BLOCK DIAGRAM

μPD72893 Block Diagram



DV Codec Unit Block Diagram



1. PIN FUNCTIONS

(1) Link-related pins

Pin Name	Pin No.	I/O	Function	Active	After Reset	Alternate Function
LINKON	18	I	Link-on signal input. Clock input. Inputs 0 if LPS is active.	—	I	—
LPS	17	O	Link power status output Link power OFF : 0 Link power ON : 2.7 MHz pulse output (54 MHz host clock divided by 20)	—	O	—
LREQ	16	O	Link request output	—	O	—
SCLK	15	I	Clock input for Link control When LPS is active : 49.152 MHz input LPS = 0 : Fixed to 0	—	I	—
CTL[1:0]	12, 13	I/O	PHY/Link control signal I/O	—	I	—
PHY_D[7:0]	2 to 4, 6 to 8, 10, 11	I/O	Data I/O between PHY and Link	—	I	—
STREAM1[7:0]	26 to 19	I/O	ISO data bus of stream interface 1 ^{Note}	—	I	—
PACKETEN1	27	I/O	Packet enable signal I/O to/from stream interface 1 ^{Note}	H/L	I	—
TSERROR1	28	I/O	Packet error signal I/O to/from stream interface 1 ^{Note}	H/L	I	—
TSRW1	29	I/O	Data read/write enable signal I/O to/from stream interface 1 ^{Note}	—	I	—
SYNC1	30	I/O	Frame sync signal I/O to/from stream interface 1 ^{Note}	H/L	I	—
TSSUB1	32	I/O	I : Inputs the packet gap signal when the stream is input through the stream interface O : Not used. Connect this pin to V _{DD} or GND via a resistor.	H/L	I	—
STREAM2[7:0]	47 to 40	I/O	ISO data bus of stream interface 2 ^{Note}	—	I	VD[7:0]
PACKETEN2	33	I/O	Packet enable signal I/O to/from stream interface 2 ^{Note}	H/L	I	VS _{SYNC}
TSERROR2	34	I/O	Packet error signal I/O to/from stream interface 2 ^{Note}	H/L	I	HS _{SYNC}
TSRW2	36	I/O	Data read/write enable signal I/O to/from stream interface 2 ^{Note}	—	I	FLD
SYNC2	37	I/O	Frame sync signal I/O to/from stream interface 2. ^{Note}	H/L	I	—
TSSUB2	38	O	Not used. Leave open.	—	O	—

Note When this signal is switched for transmission or reception to/from IEEE1394, it must be controlled that output does not conflict.

To prevent a floating state, connect a pull-up or pull-down resistor to this pin.

(2) Video interface pins

Pin Name	Pin No.	I/O	Function	Active	After Reset	Alternate Function
VCLKI	50	I	Video clock input (27 MHz)	–	–	–
VCLKO	51	O	Video clock output (27 MHz)	–	–	–
VD[7:0]	47 to 40	I/O	Video data signal	–	–	STREAM2[7:0]
VSYN	33	I/O	Vertical sync video signal ^{Note}	L	–	PACKETEN2
HSYN	34	I/O	Horizontal sync video signal ^{Note}	L	–	TSERROR2
FLD	36	I/O	Field index signal ^{Note}	–	–	TSRW2
VPWM	53	O	PWM signal for video PLL	–	–	–

Note When this signal is switched for transmission or reception to/from IEEE1394, it must be controlled that output does not conflict.

(3) Audio interface pins

Pin Name	Pin No.	I/O	Function	Active	After Reset	Alternate Function
AMCLK48	104	I	Audio master clock input (for 48 kHz sampling frequency)	–	–	–
AMCLK44	103	I	Audio master clock input (for 44.1 kHz sampling frequency)	–	–	–
AMCLKO	101	O	Audio master clock output	–	–	–
PCM1	96	I/O	Audio PCM serial data ^{Note} With 2 channels: CH1 With 4 channels: CH1 or CH1 and CH2 mixed	–	–	–
PCM2	97	I/O	Audio PCM serial data ^{Note} With 2 channels: Mute With 4 channels: CH2	–	–	–
AEMP1	98	O	PCM1 emphasis ON/OFF for PCM1 output	H	–	–
AEMP2	100	O	PCM2 emphasis ON/OFF for PCM2 output	H	–	–
ALRCK	93	I/O	Audio LR clock ^{Note} L-ch: High R-ch: Low	–	–	–
ABCK	94	I/O	Audio bit clock ^{Note}	–	–	–
AFS[1:2]	48, 49	O	Audio sampling frequency AFS2 AFS1 44.1 kHz 0 1 48 kHz 0 0 32 kHz 1 0	–	–	–
APWM	102	O	PWM signal for audio PLL	–	–	–

Note The input changes according to the switching of the encode/decode mode. It must be controlled so that the output does not conflict when the mode is switched.

To prevent a floating state, connect a pull-up or pull-down resistor to this pin.

(4) SDRAM interface pins

Pin Name	Pin No.	I/O	Function	Active	After Reset	Alternate Function
MCLK	77	O	CLK pin connection for SDRAM	–	–	–
MRAS	76	O	RAS pin connection for SDRAM	–	–	–
MCAS	75	O	CAS pin connection for SDRAM	–	–	–
MWE	74	O	WE pin connection for SDRAM	–	–	–
MA[11:0]	92, 90 to 83, 81 to 79	O	Address pin connection for SDRAM	–	–	–
MD[15:0]	73 to 69, 66 to 64, 62 to 57, 55, 54	I/O	Data pin connection for SDRAM These pins must be pulled up or down and then must be directly connected to the SDRAM pins.	–	–	–

(5) Host interface pins

(a) Parallel interface pins

Pin Name	Pin No.	I/O	Function	Active	After Reset	Alternate Function
CS	117	I	Parallel interface chip select input	L	I	–
RWZ	119	I	Parallel interface read/write control input ISA bus, SH-1 bus : Write strobe 68000 bus : Read/write select signal	L	I	–
IOR	120	I	Parallel interface IO read control input ISA bus, SH-1 bus : Read strobe 68000 bus : Data strobe (DS)	L	I	–
IOCHRDY	123	O	Parallel interface ready output	L	O	–
AD[10:1]	116 to 107	I	Parallel interface address input	–	I	–
P_D[15:0]	143 to 141, 139 to 132, 130 to 128, 126, 125	I/O	Parallel interface data input/output	–	I	–
DMAREQ	122	O	DMA request output	L	O	SIO_CNTO
DMAACK	121	I	DMA acknowledge input for parallel interface	L	I	SIO_CNTI

(b) Serial interface pins

Pin Name	Pin No.	I/O	Function	Active	After Reset	Alternate Function
SO	145	O	Serial transmit data output for clocked serial interface (CSI)	–	O	P40
SI	146	I	Serial receive data input for clocked serial interface (CSI)	–	I	P41
SCK	147	O	Clock output for clocked serial interface (CSI)	–	O	P42
TXD	149	O	Serial transmit data output for asynchronous serial interface (UART)	–	O	P43
RXD	150	I	Serial transmit data input for asynchronous serial interface (UART)	–	I	P44
SCS	151	O	Chip select output for clocked serial interface (CSI)	–	O	P45
SIO_CNTI	121	I	Control input for asynchronous serial interface (UART) Externally input data is loaded in synchronization with the end of RXD of UART.	–	I	DMAACK
SIO_CNTO	122	O	Control output for asynchronous serial interface (UART)	–	O	DMAREQ

(c) Others

Pin Name	Pin No.	I/O	Function	Active	After Reset	Alternate Function
INT	124	O	Interrupt output to external device	H	O	–
PSSEL[1:0]	106, 105	I	Parallel/serial interface selection. These signals select a parallel or serial interface as the external interface. <div> PSSEL[1:0] Selected interface 00 Serial interface (UART) 01 Parallel interface (ISA bus) 10 Parallel interface (68000 bus) 11 Parallel interface (SH-1 bus) </div>	–	I	–

(6) Port pins

Pin Name	Pin No.	I/O	Function	Active	After Reset	Alternate Function
P30	204	I/O	Port 3.	–	I	–
P31	152		This is a 4-bit I/O port that can be set in the input or output mode in 1-bit units. P30 : Connect this pin to GND via a resistor. P32 : This pin outputs an interrupt to the external device to read the DV status. It cannot be used as a port pin when DV is used.			–
P32	153					–
P33	154					–
P34	155					–
P40	145	I/O	Port 4.	–	I	SO
P41	146		This is a 6-bit I/O port that can be set in the input or output mode in 1-bit units. P40 to P45 are multiplexed with the pins described under the heading Alternate Function (they cannot be used as general-purpose port pins).			SI
P42	147					SCK
P43	149					TXD
P44	150					RXD
P45	151					SCS

(7) External ROM connection pins

Pin Name	Pin No.	I/O	Function	Active	After Reset	Alternate Function
D[15:0]	196, 194 to 189, 186 to 178	I/O	External ROM data bus External ROM data bus used to access external ROM	–	I	–
A[17:1]	175, 174, 172, 171, 169 to 167, 165 to 156	O	External ROM address bus External ROM address bus used to access external ROM. A space of 256 KB can be addressed.	–	O	–
RDZ	176	O	ROM read This is a strobe signal that indicates a read cycle to the external ROM. It is inactive in the idle state.	L	O	–
WRZ	177	O	ROM write This is a strobe signal that indicates a write cycle to the external ROM.	L	O	–

(8) Clock and reset pins

Pin Name	Pin No.	I/O	Function	Active	After Reset	Alternate Function
RESETB	1	I	Reset. RESETB is asynchronous input. If a signal with a specified low-level width is input to this pin independently of the operating clock, a system reset is effected, taking precedence over all the other operations. This signal can also be used to clear the power-saving mode (HALT or software STOP), as well as for normal initialization and starting. Caution RESETB is active-low.	L	I	—
HS_CLK	202	I	Host clock. This pin inputs the clock that is to be supplied to the CPU core and internal peripheral I/O. This clock is input to the internal clock generator. An internal clock is generated according to the value of HCLKSEL and is supplied to the CPU core and internal peripheral I/O. Usually, input a clock of 27 MHz to this pin.	—	I	—
HCLKSEL	197	I	Host clock selection. This pin inputs the clock that is to be supplied to the CPU core and internal peripheral I/O. The relationship between the clock supplied by the HS_CLK pin (27 MHz) and the clock supplied to the CPU core and internal peripheral I/O is as follows: <div style="display: flex; justify-content: space-between;"> <div>HCLKSEL</div> <div>Internal clock frequency</div> <div>PLL operation</div> </div> <div style="display: flex; justify-content: space-between;"> <div>0</div> <div>54 MHz</div> <div>Multiplied by 2</div> </div> <div style="display: flex; justify-content: space-between;"> <div>1</div> <div>Clock stops.</div> <div>PLL operation stops.</div> </div>	—	I	—

(9) Power supply, ground, and others

Pin Name	Pin No.	I/O	Function	Active	After Reset	Alternate Function
3.3V _{DD}	5, 31, 52, 63, 78, 95, 127, 140, 166, 187	—	3.3 V power supply. Supplies a positive voltage of 3.3 V to the I/O pins of the 3.3 V interface.	—	—	—
2.5V _{DD}	14, 67, 118, 170	—	2.5 V power supply. Supplies a positive voltage of 2.5 V to the respective internal blocks.	—	—	—
2.5GND	39, 91, 144, 195	—	Ground. These are ground pins. Connect all GND pins to a common ground.	—	—	—
3.3GND	9, 35, 56, 68, 82, 99, 131, 148, 173, 188					
PLLAV _{DD}	199	—	Analog power supply to multiplication circuit. Supplies a positive analog voltage to the PLL. Supply 2.5 V to this pin.	—	—	—
PLLAGND	200	—	Analog ground for multiplication circuit. Analog ground pin for PLL.	—	—	—
PLLDV _{DD}	198	—	Digital power supply to multiplication circuit. Supplies a positive digital voltage to the PLL. Supply 2.5 V to this pin.	—	—	—
PLLDGND	201	—	Digital ground for multiplication circuit. Digital ground pin for PLL.	—	—	—
IC(L)	203, 205 to 207	—	Internally connected pins Directly connect these pins to ground.	—	—	—
IFIROME	208	I	Internal ROM/external ROM select input 0: External ROM mode 1: Internal ROM mode	—	I	—

1.2 Connection of Unused Pins

The following table shows how to connect unused pins.

Table 1-1. Connection of Unused Pins (1/2)


Pin Name	I/O	Interface	Recommended Connection of Unused Pin
PHY_D[7:0]	I/O	I/O Buffer (LVTTL) in 9 mA	Connect these pins to V _{DD} or GND via a resistor.
CTL[1:0]		With Bus Holder	
SCLK		I/O Buffer (LVTTL) with bus holder	
LREQ	O	3-state Output Buffer (LVTTL) 9 mA	Leave open
LPS	O	Output Buffer (LVTTL) 9 mA	
LINKON	I	Input Buffer (LVTTL)	Connect these pins to V _{DD} or GND via a resistor.
STREAM1[7:0]	I/O	I/O Buffer (LVTTL) 6 mA	
PACKETEN1			
TSERROR1			
TSRW1			
SYNC1			
STREAM2[7:0]			
PACKETEN2			
TSERROR2			
TSRW2			
SYNC2			
TSSUB1			
TSSUB2	O	Output Buffer (LVTTL) 6 mA	Leave open
P3[4:0]	I/O	I/O Buffer (LVTTL) Schmitt in 6 mA	Connect these pins to V _{DD} or GND via a resistor.
P40/SO			
P41/SI			
P42/SCK			
P43/TXD			
P44/RXD			
P45/SCS			
A[17:1]	O	I/O Buffer (LVTTL) 6 mA	Leave open
RDZ	O	Output Buffer (LVTTL) 6 mA	
WRZ			
D[15:0]	I/O	I/O Buffer (LVTTL) 6 mA	Connect these pins to V _{DD} or GND via a resistor.
AD[10:1]	I	Input Buffer (LVTTL)	
PSSEL[1:0]			
CS			
RWZ			
IOR			
DMAACK/SIO_CNTI			

Table 1-1. Connection of Unused Pins (2/2)

Pin Name	I/O	Interface	Recommended Connection of Unused Pin
INT	O	Output Buffer (LVTTTL) 6 mA	Leave open
IOCHRDY			
DMAREQ/SIO_CNTO			
P_D[15:0]	I/O	I/O Buffer (LVTTTL) 9 mA	Connect these pins to V _{DD} or GND via a resistor.
IFIROME	I	Input Buffer (LVTTTL)	—
HS_CLK			
HCLKSEL			
RESETB	I	Output Buffer (LVTTTL) Schmitt	

IC7802: uPD78F0988A, DVIO Board, Control and Communication

BLOCK DIAGRAM



3. PIN FUNCTIONS

3.1 Port Pins

Pin Name	I/O	Function	After Reset	Alternate Function
P00	I/O	Port 0 4-bit I/O port Input/output can be specified in 1-bit units. Use of an on-chip pull-up resistor can be specified by software setting.	Input	INTP0/TOFF7
P01				INTP1
P02				INTP2
P03				INTP3/ADTRG
P10 to P17	Input	Port 1 8-bit input only port	Input	ANI0 to ANI7
P20	I/O	Port 2 7-bit I/O port Input/output can be specified in 1-bit units. Use of an on-chip pull-up resistor can be specified by software setting.	Input	RxD00
P21				TxD00
P22				RxD01
P23				TxD01
P24				TI50/TO50
P25				TI51/TO51
P26				TI52/TO52
P30 to P37	I/O	Port 3 8-bit I/O port Input/output can be specified in 1-bit units. Use of an on-chip pull-up resistor can be specified by software setting.	Input	RTP0 to RTP7
P40 to P47	I/O	Port 4 8-bit I/O port Input/output can be specified in 1-bit units. Use of an on-chip pull-up resistor can be specified by software setting.	Input	AD0 to AD7
P50	I/O	Port 5 8-bit I/O port Input/output can be specified in 1-bit units. LEDs can be driven directly. Use of an on-chip pull-up resistor can be specified by software setting.	Input	—
P51				SCK
P52				SI
P53				SO
P54				INTP4/TI000/TO00
P55				INTP5/TI010
P56				INTP6/TI001/TO01
P57				INTP7/TI011
P64	I/O	Port 6 4-bit I/O port Input/output can be specified in 1-bit units. Use of an on-chip pull-up resistor can be specified by software setting.	Input	RD
P65				WR
P66				WAIT
P67				ASTB

3.2 Non-Port Pins (1/2)

Pin Name	I/O	Function	After Reset	Alternate Function
INTP0	Input	External interrupt request input for which the valid edge (rising edge, falling edge, or both rising and falling edges) can be specified	Input	P00/TOFF7
INTP1			Input	P01
INTP2			Input	P02
INTP3			Input	P03/ADTRG
INTP4			Input	P54/TI000/TO00
INTP5			Input	P55/TI010
INTP6			Input	P56/TI001/TO01
INTP7			Input	P57/TI011
TI50	Input	External count clock input to 8-bit timer/event counter 50	Input	P24/TO50
TI51		External count clock input to 8-bit timer/event counter 51	Input	P25/TO51
TI52		External count clock input to 8-bit timer/event counter 52	Input	P26/TO52
TI000		External count clock input to 16-bit timer/event counter 00 Capture trigger input to capture register (CR000, CR010) of 16-bit timer/event counter 00	Input	P54/INTP4/TO00
TI010		Capture trigger input to capture register (CR000) of 16-bit timer/event counter 00	Input	P55/INTP5
TI001		External count clock input to 16-bit timer/event counter 01 Capture trigger input to capture register (CR001, CR011) of 16-bit timer/event counter 01	Input	P56/INTP6/TO01
TI011		Capture trigger input to capture register (CR001) of 16-bit timer/event counter 01	Input	P57/INTP7
TO50	Output	8-bit timer/event counter 50 output	Input	P24/TI50
TO51		8-bit timer/event counter 51 output	Input	P25/TI51
TO52		8-bit timer/event counter 52 output	Input	P26/TI52
TO00		16-bit timer/event counter 00 output	Input	P54/INTP4/TI000
TO01		16-bit timer/event counter 01 output	Input	P56/INTP6/TI001
RTP0 to RTP7	Output	Real-time output port that outputs pulses in synchronization with trigger signals outputs from the real-time pulse unit	Input	P30 to P37
TxD00	Output	Asynchronous serial interface serial data output	Input	P21
TxD01			Input	P23
RxD00	Input	Asynchronous serial interface serial data input	Input	P20
RxD01			Input	P22
SCK	I/O	Serial interface serial clock input/output	Input	P51
SI	Input	Serial interface serial data input	Input	P52
SO	Output	Serial interface serial data output	Input	P53
ANI0 to ANI7	Input	A/D converter analog input	Input	P10 to P17
ADTRG	Input	External trigger signal input to the A/D converter	Input	P03/INTP3
TO70 to TO75	Output	Timer output for the 3-phase PWM inverter control	Hi-Z	–
TOFF7	Input	Timer output (TO70 to TO75) stop external input	Input	P00/INTP0
AD0 to AD7	I/O	Address/data bus for expanding memory externally	Input	P40 to P47
RD	Output	Strobe signal output for reading from external memory	Input	P64
WR		Strobe signal output for writing to external memory	Input	P65
WAIT	Input	Wait insertion at external memory access	Input	P66
ASTB	Output	Strobe output that externally latches address information output to ports 4 and 5 to access external memory	Input	P67
AVREF	Input	A/D converter reference voltage input	–	–
AVDD	–	A/D converter analog power supply	–	–

3.2 Non-Port Pins (2/2)

Pin Name	I/O	Function	After Reset	Alternate Function
AV _{SS}	–	A/D converter ground potential	–	–
RESET	Input	System reset input	–	–
X1	Input	Connecting crystal resonator for system clock oscillation	–	–
X2	–		–	–
V _{DD0}	–	Positive power supply for ports	–	–
V _{SS0}	–	Ground potential for ports	–	–
V _{DD1}	–	Positive power supply except for ports	–	–
V _{SS1}	–	Ground potential except for ports	–	–
V _{PP}	–	High-voltage application during program write/verify. In the normal operation mode, connect directly to V _{SS0} .	–	–

3.3 Pin I/O Circuits and Recommended Connection of Unused Pins

The I/O circuit type of each pin and recommended connection of unused pins are shown in Table 3-1.


For the I/O circuit configuration of each type, refer to Figure 3-1.

Table 3-1. Types of Pin I/O Circuits

Pin Name	I/O Circuit Type	I/O	Recommended Connection of Unused Pins
P00/INTP0/TOFF7	8-C	I/O	Input: Independently connect to V _{SS0} via a resistor. Output: Leave open
P01/INTP1			
P02/INTP2			
P03/INTP3/ADTRG			
P10/ANI0 to P17/ANI7	25	Input	Independently connect to V _{DD0} or V _{SS0} via a resistor.
P20/RxD00	8-C	I/O	Input: Independently connect to V _{DD0} or V _{SS0} via a resistor. Output: Leave open.
P21/TxD00	5-H		
P22/RxD01	8-C		
P23/TxD01	5-H		
P24/TI50/TO50	8-C		
P25/TI51/TO51			
P26/TI52/TO52			
P30/RTP0 to P37/RTP7	5-H		
P40/AD0 to P47/AD7			
P50			
P51/SCK	8-C		
P52/SI	5-H		
P53/SO			
P54/INTP4/TI000/TO00			
P55/INTP5/TI010			
P56/INTP6/TI001/TO01			
P57/INTP7/TI011			
P64/RD			
P65/WR			
P66/WAIT			
P67/ASTB			
TO70 to TO75	4	Output	Leave open.
RESET	2	Input	—
AV _{DD}	—	—	Connect to V _{DD0} .
AV _{REF}			Connect to V _{SS0} .
AV _{SS}			
V _{PP}			Connect directly to V _{SS0} .

IC7605: BU2288FV, DVIO Board, Clock Divider

Block Diagram



FSEL1	CLK512FS	CLKA
OPEN	22.5792MHz	16.9344MHz
L	24.576MHz	36.864MHz

Explanation for terminal function

PIN No.	PIN NAME	FUNCTION
1	VDD2	Digital VDD for 27MHz clock output
2	VSS2	Digital GND for 27MHz clock output
3	CLK27M	27MHz clock output
4	TEST	Output for test
5	AVDD	Analog VDD
6	AVSS	Analog GND
7	XTALOUT	Standard crystal output
8	XTALIN	Standard crystal input
9	CLKA	clock output (FSEL1=Open:16.9344MHz, FSEL1=L:36.864MHz)
10	CLK512FS	clock output (FSEL1=Open:22.5792MHz, FSEL1=L:24.576MHz)
11	DVSS	Digital GND
12	DVDD	Digital VDD
13	CLK16M	16.9344MHz clock output
14	FSEL1	Output select :with pull-up Open:16.9344MHz (9pin), 22.5792MHz (10pin) L :36.864MHz (9pin), 24.576MHz (10pin)
15	CLK33M	33.8688MHz clock output
16	OE	Output enable(open:enable, L:disable):with pull-up

1 : VDD2

2 : VSS2

3 : CLK27M


4 : TEST

5 : AVDD

6 : AVSS

7 : XTALOUT

8 : XTALIN



16 : OE

15 : CLK33M

14 : FSEL1

13 : CLK16M

12 : DVDD

11 : DVSS

10 : CLK512FS

9 : CLKA

IC7604: BA7082F, DVIO Board, PLL IC














Fig-2 Block diagram

No.	Symbol	IN	OUT	normal DC Voltage	Internal pin configuration	Description
1	SW1		○	L 0.1V		Pin 1-3 are output pins at LOGIC parts for adjustment frequency sensitivity. These pins are open collector output.
2	SW2			—		
3	SW3			OPEN 5V		
4	BW	○		—		Pin 4,5 are input pins at logic parts for adjustment frequency sensitivity.
5	BWB					
6	1/2FB					Pin 6 is input pin at LOGIC parts for adjustment frequency sensitivity and changing 1/2 Frequency demultiplier. "H" is through output. and "L" is 1/2 Frequency demultiplier output.
7	Fout		○	3.6V		VCO Output.
8	GND	—	—	0V	GND	GND
9	FADJ	—	—	2.5V		Pin9 is a pin to adjust f0. It is possible to adjust f0 by added resistor (RADJ). If Value of RADJ down, oscillation frequency up. (Use to RADJ > 22kΩ).

No.	Symbol	IN	OUT	normal DC Voltage	Internal pin configuration	Description
10	VCC	—	—	5.0V	VCC	VCC
11	CT2	—	—	1.9V		<p>Pin 11,12 are added capacitor pins for oscillation. Use to added capacitor between CT1 and CT2.</p> <p>If value of capacitor down, oscillation frequency up.</p>
12	CT1					
13	VCTL	○		2.5V		<p>Pin13 is control pin for VCO.</p> <p>A regular this pin connect pin14(VO).</p>
14	VO		○	2.5V		<p>Pin14 is output pin at Amplifier for sensitivity adjustment.</p> <p>Adjustment amplifier GAIN by added resistor.</p>
15	IN2	○		2.5V		<p>Pin15,16 are input pins at amplifier for sensitivity adjustment.</p> <p>In1 ; normal input</p> <p>In2 ; inversion input</p>
16	IN1					


9.12.5 ICs Digital Board Chrysalis

IC7106 NCP303LSN29, Digital Board 2.1 Chrysalis, Reset Circuit



IC7501 NCP1570D, Digital Board 2.1 Chrysalis, DC/DC Converter Control

NCP1570




PACKAGE PIN DESCRIPTION

PACKAGE PIN #	PIN SYMBOL	FUNCTION
SO-8		
1	V _{CC}	Power supply input.
2	PWRGD	Open collector output goes low when V _{FB} is out of regulation. User must externally limit current into this pin to less than 20 mA.
3	PGDELAY	External capacitor programs PWRGD low-to-high transition delay.
4	COMP	Error amp output. PWM comparator reference input. A capacitor to LGND provides error amp compensation and Soft Start. Pulling pin < 0.45 locks gate outputs to a zero percent duty cycle state.
5	GATE(H)	High-side switch FET driver pin. Capable of delivering peak currents of 1.5 A.
6	GATE(L)	Low-side synchronous FET driver pin. Capable of delivering peak currents of 1.5 A.
7	V _{FB}	Error amplifier and PWM comparator input.
8	GND	Power supply return.

IC7703 ADV7196A, Digital Board 2.1 Chrysalis, Progressive Scan Video Encoder

FUNCTIONAL BLOCK DIAGRAM



ADV7196A

PIN FUNCTION DESCRIPTIONS

Pin	Mnemonic	Input/Output	Function
1, 12	V _{DD}	P	Digital Power Supply
2–11	Y0–Y9	I	10-Bit Progressive Scan/HDTV Input Port for Y Data. Input for G data when RGB data is input.
13, 52	GND	G	Digital Ground
14–23	Cr0–Cr9	I	10-Bit Progressive Scan/HDTV Input Port for Color Data in 4:4:4 Input Mode. In 4:2:2 mode this input port is not used. Input port for R data when RGB data is input.
24, 35	V _{AA}	P	Analog Power Supply
25	CLKIN	I	Pixel Clock Input. Requires a 27 MHz reference clock for standard operation in Progressive Scan Mode or a 74.25 MHz (74.1758 MHz) reference clock in HDTV mode.
26, 33	AGND	G	Analog Ground
27	DV	I	Video Blanking Control Signal Input
28	$\overline{\text{VSYNC}}$ / TSYNC	I	$\overline{\text{VSYNC}}$, Vertical Sync Control Signal Input or TSYNC Input Control Signal in Async Timing Mode
29	$\overline{\text{HSYNC}}$ / SYNC	I	$\overline{\text{HSYNC}}$, Horizontal Sync Control Signal Input or SYNC Input Control Signal in Async Timing Mode
30	SCL	I	MPU Port Serial Interface Clock Input
31	SDA	I/O	MPU Port Serial Data Input/Output
32	DAC C	O	Color Component Analog Output of Input Data on Cb/Cr9–0 Input Pins
34	DAC A	O	Y Analog Output
36	DAC B	O	Color Component Analog Output of Input Data on Cr9–Cr0 Input Pins
37	COMP	O	Compensation Pin for DACs. Connect 0.1 μF capacitor from COMP pin to V _{AA} .
38	R _{SET}	I	A 2470 Ω resistor (for input ranges 64–940 and 64–960; output standards EIA-770.1–EIA-770.3) must be connected from this pin to ground and is used to control the amplitudes of the DAC outputs. For input ranges 0–1023 (output standards RS-170, RS-343A) the R _{SET} value must be 2820 Ω .
39	V _{REF}	I/O	Optional External Voltage Reference Input for DACs or Voltage Reference Output (1.235 V)
40	$\overline{\text{RESET}}$	I	This input resets the on-chip timing generator and sets the ADV7196A into Default Register setting. Reset is an active low signal.
41	ALSB	I	TTL Address Input. This signal sets up the LSB of the MPU address. When this pin is tied high, the I ² C filter is activated which reduces noise on the I ² C interface. When this pin is tied low, the input bandwidth on the I ² C interface is increased.
42–51	Cb/Cr9–0	I	10-Bit Progressive Scan/HDTV Input Port for Color Data. In 4:2:2 mode the multiplexed CrCb data must be input on these pins. Input port for B data when RGB is input.

9.13 List of Abbreviations

Analog Board

+5VSTBY Permanent Supply 5V
 8SC2 Pin8 Scart2 (only for Europe)
 A_DATA Data from Analog- to Digital-Board
 (UART-Communication)
 A_RDY Analog-board ready (status
 information to digital-board)
 A18 - A19 Parallel Address Bus (CC - Flash-
 ROM and S-RAM)
 A8 - A17 Parallel Address Bus (CC - Flash-
 ROM and S-RAM)
 AD0 - AD7 Parallel Address and Data Bus (CC -
 Flash-ROM and S-RAM)
 AFC Automatic Frequency Control
 AFEL Audio Frontend Left
 AFER Audio Frontend Right
 AGC / WSRI Automatic Gain Control (for Europe),
 Wide Screen Rear In (for NTSC)
 AINFL Audio In Front Left
 AINFR Audio In Front Right
 AKILL Audio Kill Signal
 ALADC Audio Left to ADC
 ALDAC Audio Left from DAC
 ALE Address Latch Enable

AM0 Address-mode 0
 AM1 Address-mode 1
 ARADC Audio Right to ADC
 ARDAC Audio Right from DAC
 ASCC1M Audio Scart 1 Mute (System Clock
 Output for Real time Clock-
 Adjustment)
 AVCC Power Supply for A/D-converter
 AVSS GND-Pin for A/D-converter
 CFIN Chroma Front In
 CS0 Chip Select 0 (CC - S-RAM)
 CS2 Chip Select 2 (CC - Flash-ROM)
 CVBSFIN Video Front In
 D_DATA Data from Digital- to Analog-Board
 (UART-Communication)
 D_RDY Digital-board ready (status information
 from digital-board)
 DAC_MUTE Mute Signal for DAC
 DAOUT Digital Audio Out
 DVAL Audio from Digital Video In Left
 DVAR Audio from Digital Video In Right
 DVCC1 Power Supply Pin
 DVCC2 Power Supply Pin
 DVCC3 Power Supply Pin
 DVSS1 GND Pin
 DVSS2 GND Pin
 DVSS3 GND Pin
 FAN_OFF Fan for Basic engine

FBIN	Fast Blanking input
FOME	FOLLOW ME Status line (matching signals yes/no; only for Europe)
G1...10	DISPLAY GRID
INT	Interrupt OUT for the CC
INT	Interrupt – line from Display Print
ION	Inverse ON-Line
IPFAIL	Inverse Power Fail Detection
IPOR	Inverse Power On Reset
IRESET	Inverse Reset Input
IRR	Signal from IR-Receiver
K1	Key-Input-Line
K2	Key-Input-Line
KILL	Audio Mute
P50 IN	P50 Input-line (only for Europe)
P50 OUT	P50 OUTput-line (only for Europe)
POR_DC	Power On Reset for Display Control Print (Ext_DL)
PSS	Pal/Secam-Select
PWM_FIL	Control line for Filament Voltage Generation
PWONSW	Amplifier Switch Audio A/D Converter
RD_	Output Enable Read (CC - Flash-ROM and S-RAM)
RECLED	Control Signal for REC-LED
RESET_DIG	Reset Line to Digital Board
RP_	Inverse Reset line to Flash-ROM
RSA1/2	Record Selector 1/2
RY/BY	Ready/Busy – input line (from Flash-ROM)
SIF1	Sound intermediate frequency
SB1	Secam Band 1 (PCB-Test entrance)
SCL	I ² C-Bus
SCLSW	Switched I ² C-Bus
SDA	I ² C-Bus
SDASW	Switched I ² C-Bus
SFS_TS	SAW Filter Select Trap Select
STBY	Standby-Line (Flash_Toshiba)
SYNC	Video Sync input
TEMP_SENSE	Temperature Sense Line
VER	HW-version input
VFV	Video from Frontend
VKK	VFT Driver Power Supply
VREFH	Pin for Reference-voltage input to A/D-converter
VREFL	Pin for Reference-voltage input to A/D-converter
VS1/2	View Selector 1/2
WR_	Write Enable (CC - Flash-ROM and S-RAM)
WSFI	Wide Screen Signalling Front In
WU	Wake Up
X1	Oscillator Pin
X2	Oscillator Pin
XIN	Oscillator Pin
XOUT	Oscillator Pin
XT1	Low Frequency Oscillator Pin
XT2	Low Frequency Oscillator Pin
YFIN	Luminance Front In

Digital Board

+12V	+12V Power Supply
+2V5_FLI	+2V5 Power Supply for FLI
+2V5_PLL	+2V5 Power Supply for PLL
+3V3	+3V3 Power Supply
+3V3_ANA	+3V3 Power Supply Analogue
+3V3_DD	+3V3 Power Supply Digital
+3V3_FLI	+3V3 Power Supply for FLI
+5V	+5V Power Supply
+5V_BUFFER	+5V Power Supply for Video Filters
5508_HS	Horizontal Synchronisation from Host Decoder to Progressive Scan

5508_ODD_EVEN	Odd - Even control from Host Decoder to Progressive Scan
-5V	-5V Power Supply
-5V_BUFFER	-5V Power Supply for Video Filters
A_EMPRESS(13:0)	EMPRESS address output to SDRAM
ACC_ACLK_OSC	Audio Clock PLL output sync with incoming video for record
ACC_ACLK_PLL	Audio Clock PLL output for play back
ACLK_EMP	EMPRESS audio clock output
AD_ACLK	Audio Decoder Clock
AD_BCLK	Audio Decoder I2S bit clock
AD_DATAO	Audio Decoder Output data (PCM)
AD_SPDIF33	Audio digital output to the analog board
AD_WCLK	Audio Decoder I2S word clock
AE_ACLK	Audio Encoder Clock
AE_ACLK_OEN	Audio Encoder Clock Output Enable
AE_BCLK	Audio Encoder I2S bit clock
AE_BCLK_DV	Audio Encoder I2S bit clock to DVIO
AE_BCLK_VSM	Audio Encoder I2S bit clock to VSM
AE_DATAI	Audio Encoder Input data (PCM)
AE_DATAI_DV	Audio Encoder Input data (PCM) from DVIO
AE_DATAO	Audio Encoder Output data (PCM)
AE_WCLK	Audio Encoder I2S word clock
AE_WCLK_DV	Audio Encoder I2S word clock to DVIO
AE_WCLK_VSM	Audio Encoder I2S word clock to VSM
ANA_WE	Analogue write enable
ANA_WE_LV	Analogue write enable Low Voltage
B_IN_VIP	Video blue input to Video Input Processor
B_OUT	Video blue output from Host Decoder
B_OUT_B	Filtered blue video output
BA	Bank Address
BCLK_CTL_SERVICE	Bitclock control Service Interface
BE_BCLK	Basic Engine I2S bit clock
BE_BCLK_VSM	Basic Engine I2S bit clock to VSM
BE_CPR	Basic Engine Control Processor ready to accept data
BE_DATA_RD	Basic Engine Data read
BE_DATA_WR	Basic Engine Data write
BE_FAN	Basic Engine FAN
BE_FLAG	Basic Engine error flag
BE_IRQN	Basic Engine interrupt request
BE_LOADN	Basic Engine LOAD(LOW active)
BE_RXD	Basic Engine S2B received data
BE_SUR	Basic Engine servo unit ready to accept data (S2B)
BE_SYNC	Basic Engine sector/abs time sync
BE_TXD	Basic Engine S2B transmitted data
BE_V4	Basic Engine versatile input pin
BE_WCLK	Basic Engine I2S word clock
C_IN	Video Chrominance input
C_IN_VIP	Chrominance input to Video Input Processor
C_OUT	Chrominance output from Host Decoder
C_OUT_B	Filtered Chrominance output
CAS	Column Address strobe
CB_OUT(9:0)	Chrominance Blue out
CLK4	SDRAM clock
CPUINT0	Control processor unit interrupt
CPUINT1	Control processor unit interrupt
CR_OUT(9:0)	Chrominance Red out
CTS1P	Clear to send (Service Interface)
CVBS_OUT	Composite video output out of the Host Decoder
CVBS_OUT_B	Filtered Composite video output
CVBS_OUT_B_VIP	Composite video output to Video Input Processor(digital board video loop)
CVBS_Y_IN	Composite video/Luminance input
CVBS_Y_IN_A	Composite video/Luminance input to Video Input Processor
CVBS_Y_IN_B	Composite video/Luminance input to Video Input Processor

CVBS_Y_IN_C	Composite video/Luminance input to Video Input Processor	JTAG3_TRSTN	JTAG Test part ResetN
D_ADDR(10:0)	Address bus	LOAD_DVN	LOAD Digital Video(LOW active)
D_DATA(29:0)	Data bus	MUTEN	Mute enable
D_EMPRESS(15:0)	SDRAM data input/output of EMPRESS	MUTEN_LV	Mute enable Low Voltage
D_PAR_D(7:0)	Front-end parallel interface data (record)	P_SCAN_YUV(7:0)	Progressive Scan digital video bus
D_PAR_DVALID	Front-end parallel interface data valid	R_IN_VIP	Video Red input to Video Input Processor
D_PAR_REQ	Front-end parallel interface request	R_OUT	Video Red output from Host Decoder
D_PAR_STR	Front-end parallel interface strobe	R_OUT_B	Filtered Red Video output from Host Decoder
D_PAR_SYNC	Front-end parallel interface sync	RAS	Row Address Strobe
DV_IN_CLK	Digital Video in clock from DVIO board	RESETN	Reset Host Decoder
DV_IN_DATA(7:0)	Digital Video in data bus from DVIO board	RESETN_BE	System reset basic engine (buffered)
DV_IN_HS	Digital Video in horizontal synchronisation from DVIO board	RESETN_DVIO	System reset Digital Video Input Output (buffered)
DV_IN_VS	Digital Video in vertical synchronisation from DVIO board	RESETN_VE	System reset Video Encoder
EMI_A(21:1)	External Memory Interface Address Bus(Host Decoder)	ROMH_CEN	Flash 2 chip enable
EMI_BE0N	External Memory Interface Lower byte enable(Host Decoder)	ROML_CEN	Flash 1 chip enable
EMI_BE1N	External Memory Interface Upper byte enable(Host Decoder)	RSTN_BE	Reset control of basic engine
EMI_CAS0N	External Memory Interface SDRAM column address strobe(Host Decoder)	RSTN_DVIO	Reset control of DVIO
EMI_CE1N	External Memory Interface VSM Lower bank enable	RTS1P	Ready To Send data to service serial interface
EMI_CE2N	External Memory Interface VSM Higher bank enable	RX1P	Receive data from service serial interface
EMI_CE3N	External Memory Interface flash IC's enable	SCL	I2C bus clock
EMI_D(15:0)	External Memory Interface Data Bus(Host Decoder)	SD_CASN	SDRAM Column Address strobe output (active LOW)
EMI_PROCCLK	External Memory Interface Processor Clock(Host Decoder)	SD_CLK	SDRAM clock output
EMI_RWN	External Memory Interface Read/Write control signal(Host Decoder)	SD_CLKE	SDRAM clock enable output
EMI_WAIT	External Memory Interface Wait state request(Host Decoder)	SD_CSN	SDRAM
EMPRESS_BOOT	EMPRESS BOOT select input	SD_DQM(1:0)	SDRAM data mask enable output
EMPRESS_IRQN	EMPRESS Interrupt request output	SD_RASN	SDRAM row address strobe output
FLASH_OEN	FLASH output enable control signal	SD_WEN	SDRAM write enable output
G_IN_VIP	Video green input to Video Input Processor	SDA	I2C bus data SEL_ACLK1 Select audio clock(playback)
G_OUT	Video green output from Host Decoder	SM_CS3N	SRAM chip select
G_OUT_B	Filtered green video output from Host Decoder	SM_LBN	SRAM lower bank
GNDD	Digital Ground	SM_OEN	SRAM output enable
HD_M_AD(13:0)	Host Decoder SDRAM address bus	SM_UBN	SRAM upper bank
HD_M_CASN	Host Decoder SDRAM column address strobe	SM_WEN	SRAM write enable
HD_M_CLK	Host Decoder SDRAM clock	SMA(17:0)	SRAM address output
HD_M_CSON	Host Decoder SDRAM chip select	SMD(15:0) SRAM	data input/output
HD_M_DQ(15:0)	Host Decoder SDRAM data bus	SYSCLK_EMPRESS	System clock EMPRESS
HD_M_DQML	Host Decoder SDRAM data mask enable(Lower)	SYSCLK_PROGSCAN	System clock Progressive Scan
HD_M_DQMU	Host Decoder SDRAM data mask enable(Upper)	SYSCLK_VSM_5508	System clock VSM and Host decoder
HD_M_RASN	Host Decoder SDRAM row address strobe	TX1P	Transmit data to service serial interface
HD_M_WEN	Host Decoder SDRAM write enable	U_IN	Video U input
HSOUT	Horizontal synchronisation OUT	U_IN_VIP	Video U input to Video Input Processor
ION	Inverted ON: Enable the power supply for the digital board when LOW	V_IN	Video V input
IRESET_DIG	Initialisation of the digital board, HIGH when power ON	V_IN_VIP	Video V input to Video Input Processor
JTAG3_TCK	JTAG Test Clock	VCC3_CLK_BUF	Power supply 3V3 clock buffer
JTAG3_TD_VIP_TO_VE	JTAG Transmitted Data Video Input Processor to Video Encoder	VCC3_VSM	Power supply 3V3 Versatile Stream Manager
JTAG3_TD_VSM_TO_VIP	JTAG Transmitted Data Versatile Stream Manager to Video Input Processor	VCC3_VSM_MEM	Power supply 3V3 Versatile Stream Manager Memory
JTAG3_TMS	JTAG Test Mode Select	VCC5_4046	Power supply 5V to PLL IC
		VDD_125	Power supply 5V to buffer 7202
		VDD_CORE	Sti5508 Core supply voltage 2.5V
		VDD_EMP	Empress supply voltage 3.3V
		VDD_EMP_CORE	Empress Core supply voltage 2.5V
		VDD_FLASH_H	Flash 7301 supply voltage
		VDD_FLASH_L	Flash 7302 supply voltage
		VDD_LVC32	Power supply LVC32
		VDD_PCM	Power supply Audio decoder of Sti5508
		VDD_PLL	Power supply PLL audio decoder of Sti5508
		VDD_RGB	Power supply video encoder of Sti5508
		VDD_STI	Power supply of Sti5508
		VDD_YCC	Power supply video encoder of Sti5508
		VDD5_MK2703	Power supply MK2703
		VDD5_OSC	Power supply Oscillator

VDDA1A_7118	Power supply for analog input of VIP
VDDA2A_7118	Power supply for analog input of VIP
VDDA3A_7118	Power supply for analog input of VIP
VDDA4A_7118	Power supply for analog input of VIP
VDDE_7118	Power supply digital for peripheral cells of VIP
VDDI_7118	Power supply digital for core of VIP
VDDX_7118	Power supply for crystal oscillator of VIP
VE_DATA(7:0)	Video Encoder data Bus
VE_DSN	Video Encoder Data Strobe
VE_DTACKN	Video Encoder Data Transfer acknowledge
VIP_ERROR	Video Input Processor error
VIP_FB	Video Input Processor Fast Blanking
VIP_FID_FF	Video Input Processor field identifier to Flip Flop
VIP_HS	Video Input Processor horizontal synchronisation
VIP_ICLK	Video Input Processor input Clock
VIP_IDQ	Video Input Processor output data qualifier
VIP_IGP1	Video Input Processor input general purpose 1
VIP_INT	Video Input Processor interrupt
VIP_RTS1	Video Input Processor ready to send
VIP_VS	Video Input Processor vertical synchronisation
VIP_YUV(7:0)	Video Input Processor digital video(CCIR 656)
VS_IN	Vertical synchronisation IN
VSM_M_A(13:0))Versatile Stream Manager SDRAM address bus
VSM_M_CASN	Versatile Stream Manager SDRAM column address strobe
VSM_M_CLKEN	Versatile Stream Manager SDRAM clock enable
VSM_M_CLKOUT	Versatile Stream Manager SDRAM clock out
VSM_M_D(15:0)	Versatile Stream Manager SDRAM data bus
VSM_M_LDQM	Versatile Stream Manager SDRAM lower data mask enable
VSM_M_RASN	Versatile Stream Manager SDRAM row address strobe
VSM_M_UDQM	Versatile Stream Manager SDRAM upper data mask enable
VSM_M_WEN	Versatile Stream Manager SDRAM write enable
VSM_UART1_CTSN	Versatile Stream Manager UART1 clear to send to analog board (UART1 is gateway to analog board)
VSM_UART1_RTSN	Versatile Stream Manager UART2 clear to send to DVIO board (UART2 is gateway to DVIO board)
VSM_UART1_RX	Versatile Stream Manager UART1 ready to send to analog board
VSM_UART1_TX	Versatile Stream Manager UART2 ready to send to DVIO board
VSM_UART2_CTSN	Versatile Stream Manager UART1 received data to analog board
VSM_UART2_RTSN	Versatile Stream Manager UART2 received data to DVIO board
VSM_UART2_RX	Versatile Stream Manager UART1 transmitted data to analog board
VSM_UART2_TX	Versatile Stream Manager UART2 transmitted data to DVIO board
VSOUT	Vertical synchronisation OUT
WE	Write Enable
Y_IN	Luminance input from analog board
Y_OUT	Luminance output from Host Decoder
Y_OUT_B	Filtered luminance output
YY_OUT(9:0)	Luminance output from FLI

Digital Board Chrysalis

ADC	:Analog to Digital Converter
DAC	:Digital to Analog Converter
DENC	:Digital (Video) Encoder (Video DAC)
DV	: Digital Video (Camcorder)
EF	: Emitter Follower
OSD	:On-Screen Display
VIP	:Video Input Processor (Video ADC)
2Fh	: Progressive scan video
2V5	+2V5 Power supply for Link+Codec IC7431
3V3	+3V3 Power supply
3V3_A	+3V3 Analog power supply for PHY IC7400
3V3_D	+3V3 Digital power supply for PHY IC7400
3V3_DLY	+3V3 Power supply for IC7500
3V3_LINK	+3V3 Power supply for Link+Codec IC7431
3V3_F	+3V3 Power supply for optional Flash memory IC7432
3V3_RAM	+3V3 Power supply for SDRAM IC7430
3V3_uP	+3V3 Power supply for Micro-controller IC7802
3V3_32kHz	+3V3 Power supply for audio format adaptation circuitry IC7507 and IC7508
3V3_AC	+3V3 Power supply for audio system clock generator IC7605 and IC7606
+5V	+5V Power supply
5V_PLL	+5V Power supply for VCO of audio PLL IC7604
A (1:17)	Flash address lines of uPD72893
A_MUTE	Audio Mute
ABCK	Audio Bit Clock
AD (1:10)	Address bus lines for Host I/F of Link+Codec IC7431
AEMP1	PCM1 emphasis ON/OFF for PCM1 output
AFS1	Audio sampling frequency indication signal
ALRCLK	Audio Word Select
AMCLK44	11.2896MHz (=256 * 44.1 kHz) audio master clock signal for 44.1 kHz audio
AMCLK48	12.288MHz (=256 * 48 kHz) audio master clock signal for 32 kHz and 48 kHz audio
APWM	PWM signal for audio PLL
ASIC	Application Specific Integrated Circuit
BUFENn_AUD	Buffer Enable Audio
BUFENn_VID	Buffer Enable Video
CLK27M_CON	27MHz Clock to Digital Board
CS	Parallel interface chip select input of Link+Codec IC7431
CTL (0:1)	Link interface control lines
CTSN	Clear to Send
D (0:15)	Flash data lines of Link+Codec IC7431
DCDi	Directional Correlational Deinterlacing. Circuitry that reduces jaggies on diagonal edges when deinterlacing video-sourced material.
DV_STATUS	Interrupt pin for reading DV-status
HS_CLK	Video clock input of Link+Codec IC7431
INT	Interrupt request output of Link+Codec IC7431 (input to Micro-Controller)
IOR	Parallel interface IO read control input of Link+Codec IC7431
ISPN	In System Programming signal (used for programming IC7802)

LKON	Link-on signal output
LPS	Link power status input
LREQ	Link request input
MA (0:10)	SDRAM address lines of Link+Codec IC7431
MCAS	SDRAM column address strobe signal
MCLK	SDRAM clock signal
MD (0:15)	SDRAM data lines of Link+Codec IC7431
MRAS	SDRAM row-address strobe signal
MWE	SDRAM write enable signal
PCM1	Audio Serial Data Output of Link+Codec IC7431
PCM1_NEW	'MSB justified' to I2S converted audio serial data; audio serial data input of audio DAC UDA1334A
PD (0:15)	Data bus lines for Host I/F of Link+Codec IC7431
PHY_D (0:7)	Data bus connection between PHY and LINK device
RESETn	DVIO board reset
RESET_FM	Reset signal driven by Flashmaster programming device
RESTB	Reset input of Link+Codec IC7431
RTSN	Request to Send
RWZ	Parallel interface read/write control input of Link+Codec IC7431
RXD	Receive Data
SCLK	Link control output clock
TXD	Transmit Data
VPP	+10V switchable programming voltage of microcontroller
YUV (0:7)	Digital Video

Divio 1.8 Board


2V5	+2V5 Power supply for Link+Codec IC7431
3V3	+3V3 Power supply
3V3_A	+3V3 Analog power supply for PHY IC7400
3V3_D	+3V3 Digital power supply for PHY IC7400
3V3_DLY	+3V3 Power supply for IC7500
3V3_LINK	+3V3 Power supply for Link+Codec IC7431
3V3_F	+3V3 Power supply for optional Flash memory IC7432
3V3_RAM	+3V3 Power supply for SDRAM IC7430
3V3_uP	+3V3 Power supply for Micro-controller IC7802
3V3_32kHz	+3V3 Power supply for audio format adaptation circuitry IC7507 & IC7508
3V3_AC	+3V3 Power supply for audio system clock generator IC7605 & IC7606
+5V	+5V Power supply
5V_PLL	+5V Power supply for VCO of audio PLL IC7604
A(1:17)	Flash address lines of uPD72893
A_MUTE	Audio Mute
ABCK	Audio Bit Clock
AD(1:10)	Address bus lines for Host I/F of Link+Codec IC7431
AEMP1	PCM1 emphasis ON/OFF for PCM1 output
AFS1	Audio sampling frequency indication signal
ALRCLK	Audio Word Select
AMCLK44	11,2896MHz (=256*44.1kHz) audio master clock signal for 44.1kHz audio
AMCLK48	12,288MHz (=256*48kHz) audio master clock signal for 32kHz and 48kHz audio

APWM	PWM signal for audio PLL
BUFENn_AUD	Buffer Enable Audio
BUFENn_VID	Buffer Enable Video
CLK27M_CON	27MHz Clock to Digital Board
CS	Parallel interface chip select input of Link+Codec IC7431
CTL(0:1)	Link interface control lines
CTSN	Clear to Send
D(0:15)	Flash data lines of Link+Codec IC7431
DV_STATUS	Interrupt pin for reading DV-status
HS_CLK	Video clock input of Link+Codec IC7431
INT	Interrupt request output of Link+Codec IC7431 (input to Micro-Controller)
IOR	Parallel interface IO read control input of Link+Codec IC7431
ISPN	In System Programming signal (used for programming IC7802)
LKON	Link-on signal output
LPS	Link power status input
LREQ	Link request input
MA(0:10)	SDRAM address lines of Link+Codec IC7431
MCAS	SDRAM column address strobe signal
MCLK	
MD(0:15)	SDRAM data lines of Link+Codec IC7431
MRAS	SDRAM row-address strobe signal
MWE	SDRAM write enable signal
PCM1	Audio Serial Data Output of Link+Codec IC7431
PCM1_NEW	"MSB justified" to I2S converted audio serial data; audio serial data input of audio DAC UDA1334A
PD(0:15)	Data bus lines for Host I/F of Link+Codec IC7431
PHY_D(0:7)	Data bus connection between PHY and LINK device
RESETn	DVIO board reset
RESET_FM	Reset signal driven by Flashmaster programming device
RESTB	Reset input of Link+Codec IC7431
RTSN	Request to Send
RWZ	Parallel interface read/write control input of Link+Codec IC7431
RXD	Receive Data
SCLK	Link control output clock
TXD	Transmit Data
VPP	+10V switchable programming voltage of microcontroller
YUV(0:7)	Digital Video

TR 06016_001
060203

Figure 10-1


10.2 Exploded View of the Front Panel Complete



TR 06017_001
040203

Figure 10-2

10.3 Exploded View of the Front without PWBs



TR 06018_001
040203

Figure 10-3

Mechanical**Various**

0001	3103 607 90601	FRONT DVDR70/001 AV3
0001	3103 607 90611	FRONT DVDR70/051 AV3
0001	3103 607 90621	FRONT DVDR75/001 AV3
0001	3103 607 90631	FRONT DVDR75/051 AV3
0001	3139 247 57931	FRONT DVDR70/001
0001	3139 247 58111	FRONT DVDR75/051
0001	3139 247 58121	FRONT DVDR75/001
0001	3139 247 58131	FRONT DVDR70/051
0011	3103 607 50341	BUTTON CAP STAND BY
0013	3103 607 50361	BUTTON CAP OPEN CL.
0020	3139 247 58041	WINDOW DISP DVDR75
0026	3139 247 58581	DOOR AV DVDR7X/051
0026	3139 247 58591	DOOR AV DVDR7X/001/021
0033	3103 604 00441	HINGE DOOR FRONT AV
0046	3139 247 58021	RING RECORD DVDR75
0047	3103 607 50411	BUTTON CAP RECORD
0048	3139 247 58001	RING ROCKER PLAY/P DVDR7x
0070	3103 607 90641	TRAY COVER DVDR7X AV3
0070	3139 247 57981	TRAY COVER DVDR7x
0105	3103 607 50491	FOOT ASSY
0164	3103 308 52950	FAN KD120 6PTS 3 - C112
0300	3103 607 50461	COVER ASSY
0350	3128 147 14551	REMOTE RC25115/05
0351▲	2422 070 98133	MAINSCORD EURO
0351▲	4822 321 10713	MAINS CORD UK
0352	3103 601 00111	SCART CABLE EU
0357	4822 320 50377	CONNECT. CABLE PAL
8001	3103 601 00190	FFC 22-POL-A-TYP 225MM (AB-DB)
8004	3103 601 00220	FFC 10-POL-D-TYP 350MM (UP-DB)
8005	3103 601 00230	FFC 22-POL-A-TYP 210MM (AB-DB)
8007	3103 601 00250	KR 4POL GESCH 180MM
8008	3103 601 00062	CBLE KR 12P/115/12P KR UL
8008	3103 601 00441	CBLE KR 12P/130/12P UL
8009	3103 601 00270	FFC 30/15-15-POL-A-TYP 400MM
8010	3103 601 00280	FFC 10-POL-A-TYP 650MM (AB-DC)
8012	3103 601 00400	CBLE KR 8P/125/8P KR UL
8013	3103 601 00310	KR 9POL GESCH 370MM
8018	3103 601 00350	IEEE 1394 DVIO
8019	3103 601 00360	IEEE 1394 CHRYSALIS 350MM
8026	3103 601 00431	FFC 22-POL-A-TYP 245MM (AB-DB)
8030	3103 601 00541	CBLE IDE 40P/380/40P UL

Display Board**Various**

1110	4822 242 82114	EFOEC8004/T4
1130	4822 276 13732	Tact switch
1165	4822 276 13732	Tact switch
1166	4822 276 13732	Tact switch
1167	4822 276 13732	Tact switch
1168	4822 276 13732	Tact switch
1169	4822 276 13732	Tact switch
1170	4822 276 13732	Tact switch
1910	4822 267 11031	10P. FEM. V
1911	3103 601 00160	CABLE TREE ASSY 4 POL
1920	2422 026 05301	SOC CINCH V 3P
1921	2422 026 05307	CON MDIN H 4P F YKF51 B
1922	2422 025 10185	CON BM H 9P M 2.00 PH B



2100	5322 126 11583	10nF 10% 50V 0603
2101	3198 017 34730	47nF 16V 0603
2102	4822 124 11946	22µF 20% 16V
2103	5322 126 11583	10nF 10% 50V 0603
2104	2238 586 59812	100nF 20-80% 50V 0603
2110	4822 124 21732	10µF 20% 25V
2111	3198 017 34730	47nF 16V 0603
2112	4822 126 13879	220nF 20% 16V
2113	5322 121 42498	680nF 5% 63V
2114	5322 126 11578	1nF 10% 50V 0603
2115	3198 024 44730	47nF 50V 0603
2116	4822 124 11946	22µF 20% 16V
2117	4822 124 81151	22µF 50V
2118	2020 552 94427	100pF 5% 50v 0603
2119	2020 552 94427	100pF 5% 50v 0603

2120	2020 552 94427	100pF 5% 50v 0603
2121	2020 552 94427	100pF 5% 50v 0603
2122	2020 552 94427	100pF 5% 50v 0603
2123	2020 552 94427	100pF 5% 50v 0603
2124	2020 552 94427	100pF 5% 50v 0603
2125	2020 552 94427	100pF 5% 50v 0603
2126	2020 552 94427	100pF 5% 50v 0603
2200	4822 126 14241	330pF 50V 0603
2201	4822 126 14241	330pF 50V 0603
2202	2238 586 59812	100nF 20-80% 50V 0603



3100	4822 051 30223	22kΩ 5% 0.062W
3101	4822 051 30223	22kΩ 5% 0.062W
3102	4822 051 30222	2.2kΩ 5% 0.062W
3103	4822 051 30221	220Ω 5% 0.062W
3104	4822 051 30103	10kΩ 5% 0.062W
3106	4822 117 12925	47kΩ 1% 0.063W 0603
3107	4822 051 30222	2.2kΩ 5% 0.062W
3108	4822 117 12925	47kΩ 1% 0.063W 0603
3110	4822 051 30221	220Ω 5% 0.062W
3111	4822 051 30223	22kΩ 5% 0.062W
3112	4822 050 11002	1kΩ 1% 0.4W
3113	4822 051 30102	1kΩ 5% 0.062W
3114	4822 051 30101	100Ω 5% 0.062W
3115	4822 051 30101	100Ω 5% 0.062W
3116	4822 051 30331	330Ω 5% 0.062W
3117	4822 051 30103	10kΩ 5% 0.062W
3118	4822 051 30331	330Ω 5% 0.062W
3119	4822 051 30471	470Ω 5% 0.062W
3120	4822 051 30102	1kΩ 5% 0.062W
3121	4822 116 83872	220Ω 5% 0.5W
3122	4822 051 30103	10kΩ 5% 0.062W
3123	4822 051 30471	470Ω 5% 0.062W
3124	4822 051 30103	10kΩ 5% 0.062W
3125	4822 051 30471	470Ω 5% 0.062W
3126	4822 051 30101	100Ω 5% 0.062W
3127	4822 117 13632	100kΩ 1% 0603 0.62W
3128	4822 117 13632	100kΩ 1% 0603 0.62W
3130	4822 051 30103	10kΩ 5% 0.062W
3132	4822 051 30102	1kΩ 5% 0.062W
3134	4822 117 12063	NTC DC 5W 10K 5%
3137	4822 116 83876	270Ω 5% 0.5W
3139	4822 116 83876	270Ω 5% 0.5W
3141	4822 117 12925	47kΩ 1% 0.063W 0603
3144	4822 051 30103	10kΩ 5% 0.062W
3147	4822 116 52257	22kΩ 5% 0.5W
3148	4822 116 52257	22kΩ 5% 0.5W
3149	4822 116 52257	22kΩ 5% 0.5W
3150	4822 051 30223	22kΩ 5% 0.062W
3151	4822 051 30223	22kΩ 5% 0.062W
3152	4822 051 30223	22kΩ 5% 0.062W
3153	4822 051 30223	22kΩ 5% 0.062W
3200	4822 051 30102	1kΩ 5% 0.062W
3201	4822 051 30105	1MΩ 5% 0.062W
3202	4822 051 30102	1kΩ 5% 0.062W
3203	4822 051 30105	1MΩ 5% 0.062W
3204	4822 051 30689	68Ω 5% 0.063W 0603
3205	4822 051 30759	75Ω 5% 0.062W
3206	4822 051 30759	75Ω 5% 0.062W
3207	4822 051 30759	75Ω 5% 0.062W
3300	4822 051 30472	4.7kΩ 5% 0.062W
4111	4822 051 30008	Jumper 0603
4121	4822 051 30008	Jumper 0603
4122	4822 051 30008	Jumper 0603
4123	4822 051 30008	Jumper 0603



5100	4822 157 11706	10µH 5%
5101	2422 549 44607	Bead 600Ω at 100MHz
5103	2422 549 44607	Bead 600Ω at 100MHz
5104	4822 157 50964	100µH 20%



6100	4822 130 11416	PDZ6.8B
6101	9322 190 44676	LTL-1MHHR
6102	9322 190 44676	LTL-1MHHR
6103	9322 190 44676	LTL-1MHHR
6105	4822 130 11397	BAS316
6106	4822 130 11397	BAS316
6111	4822 130 11397	BAS316
6200	9322 146 61685	DF3A6.8FU
6201	9322 146 61685	DF3A6.8FU
6202	9322 146 61685	DF3A6.8FU
6203	9322 146 61685	DF3A6.8FU
6204	9322 146 61685	DF3A6.8FU



7100	2722 171 07736	VFD BJ900GNK
7101	3198 010 42310	BC847BW
7102	3198 010 42310	BC847BW
7103	3103 165 13731	TMP87C874F/LDCP1
7104	3198 010 42310	BC847BW
7105	3198 010 42310	BC847BW
7106	4822 130 40981	BC337-25
7107	9322 185 97667	TSOP4836ZC1
7108	4822 130 41246	BC327-25
7109	3198 010 42310	BC847BW
7112	4822 130 60854	DTA124EU-W

Analog Board**Various**

1001▲	2422 086 10919	Fuse 65V 125mA
1300▲	2422 086 10899	FUSE5X20ET1A25 250V IEC B
1302▲	4822 252 11215	Spark gap
1303▲	4822 071 51002	19372(1A)
1304▲	2422 086 10786	FUSE 4A
1304▲	9965 000 07786	Fuse T4.0A 250V
1306▲	2422 086 10919	Fuse 65V 125mA
1307▲	4822 071 51002	19372(1A)
1308▲	2422 086 10951	PROT DEV 65V 500MA PSC
1308▲	4822 252 51187	19398E1(0,500A)
1309▲	2422 086 10783	LT 2A 250V IEC A
1309▲	4822 071 58001	19372(800MA)
1309▲	9965 000 07788	FUSE RAD T2A IEC UL250V
1600	4822 242 10434	Crystal 18.432 MHz
1701	4822 242 81436	Filter OFWK3953M
1702	2422 549 44341	SAW 38.9MHz OFWK9656M
1703	4822 242 10307	OFWK3956M
1703	4822 242 81436	Filter OFWK3953M
1704	2422 549 44611	5MHZ5 TPSR*MBQ2 BS A
1704	4822 242 72586	TPS5,5MB-TF20
1705	3139 147 17001	TUNER UV1316MK3
1706	2422 549 44612	6MHZ TPSR*MBQ2 BS A
1706	4822 242 81572	TPS6,0MB-TF21
1900	2422 025 18009	V 22P F 1.00 FFC 0.3 Y
1900	4822 265 11154	Connector 22p
1931▲	2422 030 00304	Socket 2P m h mains
1932	2422 025 10772	CON BM V 12P M 2.00 PH B
1933	4822 265 11352	Connector 8p
1934	4822 267 10565	Connector 4p
1940	2422 033 00334	CON BM EURO H 42P
1942	2422 025 10769	CON BMT 9P VERT PH-B
1943	2422 025 18143	CON V 10P F 1.00 FFC 0.3
1943	4822 267 11031	10P. FEM. V
1947	2422 025 18009	V 22P F 1.00 FFC 0.3 Y
1947	4822 265 11154	Connector 22p
1948	4822 267 10994	Socket SVHS
1949	2422 026 05308	SOC CINCH H 3P
1951	4822 267 31729	CONNECTOR
1960	2422 025 09406	Connector 4p
1990	4822 242 73552	13,875 000 MC



2000	4822 124 80483	47µF20% 6,3V
2001	4822 124 42234	100µF 20% 6,3V
2001	4822 124 80483	47µF20% 6,3V
2002	2238 586 59812	100nF 20-80% 50V 0603
2002	4822 124 42234	100µF 20% 6,3V
2003	2238 586 59812	100nF 20-80% 50V 0603
2004	2238 586 59812	100nF 20-80% 50V 0603
2004	4822 124 80483	47µF20% 6,3V
2005	4822 124 42234	100µF 20% 6,3V
2006	2238 916 11449	1nF 2% NPO 25V 0603
2006	3198 016 31020	1nF 10% 25V 0603
2006	4822 126 11785	47pF 5% 50V 0603
2007	4822 124 21732	10µF 20% 25V
2008	2238 916 11449	1nF 2% NPO 25V 0603
2008	3198 016 31020	1nF 10% 25V 0603
2009	2020 552 94427	100pF 5% 50v 0603
2009	2238 586 59812	100nF 20-80% 50V 0603
2010	4822 124 80483	47µF20% 6,3V
2011	2238 586 59812	100nF 20-80% 50V 0603
2011	4822 124 21732	10µF 20% 25V
2012	2238 586 59812	100nF 20-80% 50V 0603
2013	4822 124 42234	100µF 20% 6,3V
2014	2238 586 59812	100nF 20-80% 50V 0603
2015	2238 586 59812	100nF 20-80% 50V 0603
2016	4822 124 22652	2.2µF 20% 50V
2017	2020 552 94427	100pF 5% 50v 0603
2018	2238 586 59812	100nF 20-80% 50V 0603
2018	4822 124 21732	10µF 20% 25V

2019	2238 586 59812	100nF 20-80% 50V 0603	2340▲	2020 554 90169	470pF 250V 10%	2585	2238 586 59812	100nF 20-80% 50V 0603
2019	4822 124 21732	10µF 20% 25V	2341	3198 017 41050	1µF 10V 0603	2586	5322 126 11578	1nF 10% 50V 0603
2020	4822 124 21732	10µF 20% 25V	2342	3198 017 41050	1µF 10V 0603	2587	3198 017 41050	1µF 10V 0603
2020	4822 124 80483	47µF20% 6,3V	2343	2238 586 59812	100nF 20-80% 50V 0603	2590	4822 122 33753	150pF 5% 50V
2021	2238 586 59812	100nF 20-80% 50V 0603	2402	2238 586 59812	100nF 20-80% 50V 0603	2600	4822 124 21732	10µF 20% 25V
2023	2238 916 11449	1nF 2% NPO 25V 0603	2403	4822 124 80483	47µF20% 6,3V	2601	5322 126 11583	10nF 10% 50V 0603
2023	3198 016 31020	1nF 10% 25V 0603	2404	2238 586 59812	100nF 20-80% 50V 0603	2602	4822 124 21732	10µF 20% 25V
2023	4822 124 12392	47?F 20% 16V	2405	4822 124 80483	47µF20% 6,3V	2603	2238 586 59812	100nF 20-80% 50V 0603
2023	4822 124 80483	47µF20% 6,3V	2406	5322 126 11583	10nF 10% 50V 0603	2604	5322 126 11583	10nF 10% 50V 0603
2024	4822 126 11669	27pF 5% 50V 0603	2407	4822 122 33741	10pF 10% 50V	2605	4822 124 21732	10µF 20% 25V
2025	2238 916 11449	1nF 2% NPO 25V 0603	2408	3198 017 41050	1µF 10V 0603	2606	2238 586 59812	100nF 20-80% 50V 0603
2025	3198 016 31020	1nF 10% 25V 0603	2409	2238 586 59812	100nF 20-80% 50V 0603	2607	4822 126 14225	56pF 5% 50V 0603
2026	4822 126 11669	27pF 5% 50V 0603	2410	3198 017 41050	1µF 10V 0603	2608	4822 124 21732	10µF 20% 25V
2029	4822 124 12392	47?F 20% 16V	2411	2238 586 59812	100nF 20-80% 50V 0603	2609	4822 126 14225	56pF 5% 50V 0603
2029	4822 124 80483	47µF20% 6,3V	2412	4822 122 33741	10pF 10% 50V	2610	5322 126 11583	10nF 10% 50V 0603
2030	2238 916 11449	1nF 2% NPO 25V 0603	2413	4822 124 80483	47µF20% 6,3V	2611	4822 124 80231	47µF20% 16V
2030	3198 016 31020	1nF 10% 25V 0603	2414	2238 586 59812	100nF 20-80% 50V 0603	2612	4822 124 40769	4.7µF 20% 100V
2031	4822 124 22652	2.2µF 20% 50V	2416	3198 017 41050	1µF 10V 0603	2616	5322 126 11578	1nF 10% 50V 0603
2032	2238 916 11449	1nF 2% NPO 25V 0603	2417	4822 124 11947	10?F 20% 16V	2617	5322 126 11578	1nF 10% 50V 0603
2032	3198 016 31020	1nF 10% 25V 0603	2418	3198 017 41050	1µF 10V 0603	2620	3198 016 33380	3.3pF 50V 0603
2032	5322 126 11583	10nF 10% 50V 0603	2419	3198 017 41050	1µF 10V 0603	2621	3198 016 33380	3.3pF 50V 0603
2033	2020 552 94427	100pF 5% 50v 0603	2420	2238 586 59812	100nF 20-80% 50V 0603	2623	2238 586 59812	100nF 20-80% 50V 0603
2033	4822 126 13881	470pF 5% 50V	2421	4822 124 11947	10?F 20% 16V	2626	4822 124 22652	2.2µF 20% 50V
2034	4822 126 13881	470pF 5% 50V	2422	5322 126 11583	10nF 10% 50V 0603	2627	4822 124 22652	2.2µF 20% 50V
2035	2238 586 59812	100nF 20-80% 50V 0603	2423	3198 017 41050	1µF 10V 0603	2713	4822 124 11946	22µF 20% 16V
2037	2238 586 59812	100nF 20-80% 50V 0603	2424	4822 124 80483	47µF20% 6,3V	2719	4822 126 13883	220pF 5% 50V
2037	4822 126 13193	4.7nF 10% 63V	2425	2238 586 59812	100nF 20-80% 50V 0603	2720	4822 124 42234	100µF 20% 6,3V
2038	4822 124 42234	100µF 20% 6,3V	2427	3198 017 41050	1µF 10V 0603	2721	5322 122 33861	120pF10% 50V
2038	4822 126 13193	4.7nF 10% 63V	2428	4822 124 11947	10?F 20% 16V	2722	2022 020 00861	2.2µF 50V 20%
2039	4822 126 13193	4.7nF 10% 63V	2429	4822 124 11946	22µF 20% 16V	2722	5322 124 41379	2.2?F 20% 50V
2040	4822 126 13193	4.7nF 10% 63V	2430	2238 586 59812	100nF 20-80% 50V 0603	2723	4822 126 13881	470pF 5% 50V
2041	2020 552 94427	100pF 5% 50v 0603	2432	4822 124 42234	100µF 20% 6,3V	2724	2238 586 59812	100nF 20-80% 50V 0603
2042	2238 586 59812	100nF 20-80% 50V 0603	2433	3198 017 34730	47nF 16V 0603	2725	4822 122 33761	22pF 5% 50V
2043	4822 124 80483	47µF20% 6,3V	2434	4822 124 80483	47µF20% 6,3V	2727	2238 586 59812	100nF 20-80% 50V 0603
2045	2238 916 11449	1nF 2% NPO 25V 0603	2435	2238 586 59812	100nF 20-80% 50V 0603	2728	5322 126 11583	10nF 10% 50V 0603
2045	3198 016 31020	1nF 10% 25V 0603	2436	3198 017 41050	1µF 10V 0603	2729	4822 124 21732	10µF 20% 25V
2047	2238 916 11449	1nF 2% NPO 25V 0603	2437	3198 017 41050	1µF 10V 0603	2730	4822 126 13879	220nF 20% 16V
2047	3198 016 31020	1nF 10% 25V 0603	2438	3198 017 41050	1µF 10V 0603	2731	2020 552 94523	8.2pF 50V 0603
2048	2020 009 90097	100µF BP 16V 20%	2439	2238 586 59812	100nF 20-80% 50V 0603	2732	4822 124 22652	2.2µF 20% 50V
2048	2022 036 00005	10µF 16V 20%	2440	3198 017 41050	1µF 10V 0603	2733	2238 586 59812	100nF 20-80% 50V 0603
2048	4822 124 12392	47?F 20% 16V	2441	3198 017 41050	1µF 10V 0603	2734	5322 126 11578	1nF 10% 50V 0603
2048	4822 124 80483	47µF20% 6,3V	2442	4822 124 11946	22µF 20% 16V	2735	4822 126 14225	56pF 5% 50V 0603
2049	5322 126 11583	10nF 10% 50V 0603	2443	4822 124 42234	100µF 20% 6,3V	2736	4822 126 14225	56pF 5% 50V 0603
2050	2020 009 90097	100µF BP 16V 20%	2444	4822 126 13881	470pF 5% 50V	2737	4822 124 80483	47µF20% 6,3V
2050	2022 036 00005	10µF 16V 20%	2445	4822 126 13881	470pF 5% 50V	2740	4822 124 22652	2.2µF 20% 50V
2050	4822 124 12392	47?F 20% 16V	2446	3198 017 41050	1µF 10V 0603	2741	5322 126 11578	1nF 10% 50V 0603
2050	4822 124 80483	47µF20% 6,3V	2447	4822 126 13881	470pF 5% 50V	2742	5322 126 11578	1nF 10% 50V 0603
2301▲	2020 554 90173	2.2nF 20% 250V	2448	4822 126 13881	470pF 5% 50V	2932	2238 586 59812	100nF 20-80% 50V 0603
2301▲	4822 126 14088	2,2nF 20% 250V	2449	4822 126 13956	68pF 5% 63V 0603	2933	4822 124 80483	47µF20% 6,3V
2302▲	4822 121 10512	220nF 275V 20%	2450	2238 586 59812	100nF 20-80% 50V 0603	2934	2238 586 59812	100nF 20-80% 50V 0603
2303	4822 122 31175	1nF 10% 500V	2459	3198 017 41050	1µF 10V 0603	2935	2238 586 59812	100nF 20-80% 50V 0603
2304▲	4822 121 51598	2.2nF 5% 400V	2460	4822 124 40769	4.7µF 20% 100V	2936	4822 122 33761	22pF 5% 50V
2304	4822 126 10206	2.2nF 10% 500V	2461	4822 124 40769	4.7µF 20% 100V	2937	4822 122 33761	22pF 5% 50V
2305	2020 021 91506	1000µF 20% 16V	2462	4822 124 11947	10?F 20% 16V	2938	2238 586 59812	100nF 20-80% 50V 0603
2305	4822 124 40849	330µF 20% 16V	2463	4822 124 11947	10?F 20% 16V	2940	2238 586 59812	100nF 20-80% 50V 0603
2306	2020 021 91528	560µF 6V3 20%	2464	4822 124 21732	10µF 20% 25V	2941	4822 124 21732	10µF 20% 25V
2306	4822 124 40184	1000µF 20% 10V	2501	3198 017 41050	1µF 10V 0603	2942	4822 126 14238	2.2nF 50V 0603
2307	4822 122 31175	1nF 10% 500V	2502	2238 586 59812	100nF 20-80% 50V 0603	2943	4822 126 14508	180pF 5% 50V
2308	2022 318 00108	47nF 250V 10%	2503	2238 586 59812	100nF 20-80% 50V 0603	2944	4822 126 14238	2.2nF 50V 0603
2308	4822 121 70386	47nF 10% 250V	2504	3198 017 41050	1µF 10V 0603	2945	4822 126 14508	180pF 5% 50V
2309▲	2222 151 90053	68µF 400V 20%	2505	3198 017 41050	1µF 10V 0603	2946	3198 017 41050	1µF 10V 0603
2310	5322 126 11578	1nF 10% 50V 0603	2506	3198 017 41050	1µF 10V 0603	2947	3198 017 41050	1µF 10V 0603
2311	5322 126 11578	1nF 10% 50V 0603	2507	3198 017 41050	1µF 10V 0603			
2312	2020 021 91506	1000µF 20% 16V	2508	3198 017 41050	1µF 10V 0603			
2313	2020 021 91528	560µF 6V3 20%	2509	2238 586 59812	100nF 20-80% 50V 0603			
2313	4822 124 40184	1000µF 20% 10V	2510	4822 124 42234	100µF 20% 6,3V			
2315▲	4822 126 14525	47pF 5% 1kV	2511	2020 009 90097	100µF BP 16V 20%			
2317	5322 126 11578	1nF 10% 50V 0603	2511	2022 036 00005	10µF 16V 20%			
2318	4822 126 10206	2.2nF 10% 500V	2512	2238 586 59812	100nF 20-80% 50V 0603			
2319	2020 021 91506	1000µF 20% 16V	2513	2020 552 96807	1µF 10V 0603 X5R			
2319	4822 124 40849	330µF 20% 16V	2513	3198 017 41050	1µF 10V 0603			
2320	4822 124 40849	330µF 20% 16V	2514	2238 586 59812	100nF 20-80% 50V 0603			
2320	4822 124 80791	470µF 20% 16V	2515	2020 552 96807	1µF 10V 0603 X5R			
2321	2238 586 59812	100nF 20-80% 50V 0603	2515	3198 017 41050	1µF 10V 0603			
2322▲	2020 021 91506	1000µF 20% 16V	2516	2020 009 90097	100µF BP 16V 20%			
2322	2020 021 91569	470µF 10V	2516	2022 036 00005	10µF 16V 20%			
2322	4822 124 41584	100µF 20% 10V	2517	5322 126 11578	1nF 10% 50V 0603			
2323	4822 124 42234	100µF 20% 6,3V	2518	2238 586 59812	100nF 20-80% 50V 0603			
2324	2238 586 59812	100nF 20-80% 50V 0603	2519	4822 124 42234	100µF 20% 6,3V			
2325	4822 124 81151	22µF 50V	2520	5322 126 11578	1nF 10% 50V 0603			
2326	4822 121 41857	10nF 5% 250V	2521	2238 586 59812	100nF 20-80% 50V 0603			
2327	2238 586 59812	100nF 20-80% 50V 0603	2522	2020 009 90097	100µF BP 16V 20%			
2328	4822 124 81151	22µF 50V	2522	2022 036 00005	10µF 16V 20%			
2329	2238 586 59812	100nF 20-80% 50V 0603	2523	5322 126 11578	1nF 10% 50V 0603			
2330	5322 126 11578	1nF 10% 50V 0603	2524	3198 017 41050	1µF 10V 0603			
2331	2238 586 59812	100nF 20-80% 50V 0603	2525	3198 017 41050	1µF 10V 0603			
2332	4822 124 22651	1µF 20% 50V	2526	2020 009 90097	100µF BP 16V 20%			
2334	2238 586 59812	100nF 20-80% 50V 0603	2526	2022 036 00005	10µF 16V 20%			
2335	4822 124 21732	10µF 20% 25V	2527	5322 126 11578	1nF 10% 50V 0603			
2336	2238 586 59812	100nF 20-80% 50V 0603	2530	2238 586				

3013	2322 704 67502	7.5K 1% 0.5W	3318	4822 116 52175	100Ω 5% 0.5W	3437	4822 051 30103	10kΩ 5% 0.062W
3013	4822 117 12139	22Ω 5% 0.062W	3321	2322 193 14477	0.47Ω PR01 PM5	3438	4822 051 30103	10kΩ 5% 0.062W
3013	5322 117 13053	6.8kΩ 1% 0.063W 0603	3323	4822 117 12891	220kΩ 1% 0.063W 0603	3439	4822 051 30103	10kΩ 5% 0.062W
3014	2120 108 93941	5.62kΩ 1% 0603	3324	2322 702 60564	560kΩ 5% 0603	3440	4822 051 30103	10kΩ 5% 0.062W
3014	4822 051 30103	10kΩ 5% 0.062W	3325	4822 117 12925	47kΩ 1% 0.063W 0603	3441	4822 116 52201	75Ω 5% 0.5W
3014	5322 117 13031	5.6kΩ 1% 0603	3326	4822 116 52175	100Ω 5% 0.5W	3442	4822 051 30154	150kΩ 5% 0.062W
3015	4822 051 30471	470Ω 5% 0.062W	3326	4822 116 52195	47Ω 5% 0.5W	3443	4822 117 13632	100kΩ 1% 0603 0.62W
3015	4822 117 13613	2R2 5% 0603	3327	4822 051 30105	1MΩ 5% 0.062W	3444	4822 117 13632	100kΩ 1% 0603 0.62W
3016	5322 117 13038	27K 1% 0.063W 0603	3328	4822 051 30103	10kΩ 5% 0.062W	3445	4822 051 30151	150Ω 5% 0.062W
		RC22H	3329	3198 021 32250	2.2MΩ 5% 0603	3446	4822 117 12925	47kΩ 1% 0.063W 0603
3017	4822 117 13613	2R2 5% 0603	3330	4822 051 30471	470Ω 5% 0.062W	3447	4822 116 83884	47kΩ 5% 0.5W
3017	5322 117 13024	33kΩ 1% 0.063W 0603	3331	4822 051 30109	10Ω 5% 0.062W	3448	4822 051 30271	270Ω 5% 0.062W
3018	2120 108 93941	5.62kΩ 1% 0603	3332	2120 108 93941	5.62kΩ 1% 0603	3448	4822 051 30471	470Ω 5% 0.062W
3018	4822 117 12139	22Ω 5% 0.062W	3332	5322 117 13031	5.6kΩ 1% 0603	3449	4822 051 30151	150Ω 5% 0.062W
3018	5322 117 13031	5.6kΩ 1% 0603	3333	5322 117 13026	4.7kΩ 1% 0.063W 0603	3450	4822 051 30271	270Ω 5% 0.062W
3019	4822 116 52186	22Ω 5% 0.5W	3334	4822 051 30563	56kΩ 5% 0.062W	3450	4822 051 30471	470Ω 5% 0.062W
3019	4822 117 12139	22Ω 5% 0.062W	3335	4822 051 30471	470Ω 5% 0.062W	3451	4822 050 21003	10kΩ 1% 0.6W
3020	4822 051 30472	4.7kΩ 5% 0.062W	3336	4822 051 30471	470Ω 5% 0.062W	3452	4822 051 30151	150Ω 5% 0.062W
3020	4822 117 12139	22Ω 5% 0.062W	3337	4822 051 30102	1kΩ 5% 0.062W	3454	4822 050 11002	1kΩ 1% 0.4W
3021	4822 051 30103	10kΩ 5% 0.062W	3338	4822 051 30221	220Ω 5% 0.062W	3455	4822 051 30103	10kΩ 5% 0.062W
3022	4822 117 12139	22Ω 5% 0.062W	3339	5322 117 13026	4.7kΩ 1% 0.063W 0603	3458	4822 051 30472	4.7kΩ 5% 0.062W
3023	4822 117 12139	22Ω 5% 0.062W	3340	5322 117 13026	4.7kΩ 1% 0.063W 0603	3459	4822 051 30103	10kΩ 5% 0.062W
3024	4822 117 12139	22Ω 5% 0.062W	3341	4822 051 30683	68kΩ 5% 0.062W	3460	4822 051 30472	4.7kΩ 5% 0.062W
3024	4822 117 12925	47kΩ 1% 0.063W 0603	3342	4822 116 52283	4.7kΩ 5% 0.5W	3461	2122 551 00031	VDR 0805 1mA/6V4 21V
3025	4822 117 13632	100kΩ 1% 0603 0.62W	3342	5322 117 13026	4.7kΩ 1% 0.063W 0603	3461	2322 574 10402	VDR 0805 1mA/6V4 21V
3026	4822 117 12139	22Ω 5% 0.062W	3343	5322 117 13026	4.7kΩ 1% 0.063W 0603	3462	2122 551 00031	VDR 0805 1mA/6V4 21V
3026	4822 117 12925	47kΩ 1% 0.063W 0603	3344	4822 051 30683	68kΩ 5% 0.062W	3462	2322 574 10402	VDR 0805 1mA/6V4 21V
3027	5322 117 13024	33kΩ 1% 0.063W 0603	3344	4822 117 12925	47kΩ 1% 0.063W 0603	3463	2122 551 00031	VDR 0805 1mA/6V4 21V
3027	5322 117 13026	4.7kΩ 1% 0.063W 0603	3346	4822 051 30222	2.2kΩ 5% 0.062W	3463	2322 574 10402	VDR 0805 1mA/6V4 21V
3028	4822 117 12139	22Ω 5% 0.062W	3347	4822 051 30472	4.7kΩ 5% 0.062W	3464	2122 551 00031	VDR 0805 1mA/6V4 21V
3029	4822 051 30101	100Ω 5% 0.062W	3348	4822 051 30681	680Ω 5% 0.062W	3464	2322 574 10402	VDR 0805 1mA/6V4 21V
3029	4822 117 12917	1Ω 5% 0.062W 0603	3349	4822 051 30479	47Ω 5% 0.062W	3465	2122 551 00031	VDR 0805 1mA/6V4 21V
3030	5322 117 13038	27K 1% 0.063W 0603	3350	4822 051 30102	1kΩ 5% 0.062W	3465	2322 574 10402	VDR 0805 1mA/6V4 21V
		RC22H	3351	2322 702 60564	560kΩ 5% 0603	3466	2122 551 00031	VDR 0805 1mA/6V4 21V
3030	5322 117 13047	330Ω 1% 0.063W 0603	3351	4822 051 30105	1MΩ 5% 0.062W	3466	2322 574 10402	VDR 0805 1mA/6V4 21V
3031	4822 051 30103	10kΩ 5% 0.062W	3352	2322 193 14687	0.68Ω PR01 PM5	3467	2122 551 00031	VDR 0805 1mA/6V4 21V
3032	2322 704 67502	7.5K 1% 0.5W	3353	4822 051 30272	2.7kΩ 5% 0.062W	3467	2322 574 10402	VDR 0805 1mA/6V4 21V
3032	5322 117 13053	6.8kΩ 1% 0.063W 0603	3354	4822 051 30272	2.7kΩ 5% 0.062W	3468	2122 551 00031	VDR 0805 1mA/6V4 21V
3033	4822 117 12139	22Ω 5% 0.062W	3355	4822 051 30479	47Ω 5% 0.062W	3468	2322 574 10402	VDR 0805 1mA/6V4 21V
3034	4822 117 12925	47kΩ 1% 0.063W 0603	3356	4822 116 52231	820Ω 5% 0.5W	3469	4822 117 13632	100kΩ 1% 0603 0.62W
3034	4822 117 13613	2R2 5% 0603	3357	4822 051 30472	4.7kΩ 5% 0.062W	3470	4822 117 13632	100kΩ 1% 0603 0.62W
3035	4822 050 21003	10kΩ 1% 0.6W	3358	4822 051 30109	10Ω 5% 0.062W	3471	4822 117 13632	100kΩ 1% 0603 0.62W
3035	4822 117 13613	2R2 5% 0603	3360	4822 116 52231	820Ω 5% 0.5W	3472	4822 117 13632	100kΩ 1% 0603 0.62W
3036	2322 704 67502	7.5K 1% 0.5W	3361	4822 051 30102	1kΩ 5% 0.062W	3473	4822 051 30101	100Ω 5% 0.062W
3036	5322 117 13053	6.8kΩ 1% 0.063W 0603	3362	4822 051 30681	680Ω 5% 0.062W	3474	4822 051 30101	100Ω 5% 0.062W
3039	4822 050 21003	10kΩ 1% 0.6W	3363	4822 051 30222	2.2kΩ 5% 0.062W	3475	4822 051 30101	100Ω 5% 0.062W
3039	5322 117 13038	27K 1% 0.063W 0603	3364	4822 051 30103	10kΩ 5% 0.062W	3476	4822 051 30101	100Ω 5% 0.062W
		RC22H	3365	4822 051 30332	3.3kΩ 5% 0.062W	3477	4822 051 30101	100Ω 5% 0.062W
3040	5322 117 13024	33kΩ 1% 0.063W 0603	3366	4822 051 30152	1.5kΩ 5% 0.062W	3478	4822 051 30101	100Ω 5% 0.062W
3041	4822 050 21003	10kΩ 1% 0.6W	3367	4822 117 12903	1.8kΩ 1% 0.063W 0603	3478	4822 117 13632	100kΩ 1% 0603 0.62W
3042	4822 050 21003	10kΩ 1% 0.6W	3368	4822 051 30152	1.5kΩ 5% 0.062W	3488	4822 117 13632	100kΩ 1% 0603 0.62W
3043	4822 117 12139	22Ω 5% 0.062W	3368	4822 051 30332	3.3kΩ 5% 0.062W	3489	4822 117 12864	82kΩ 5% 0.6W
3043	4822 117 12925	47kΩ 1% 0.063W 0603	3371	4822 051 30479	47Ω 5% 0.062W	3490	4822 051 30151	150Ω 5% 0.062W
3044	4822 051 30103	10kΩ 5% 0.062W	3372	4822 051 30339	33Ω 5% 0.062W	3491	4822 051 30151	150Ω 5% 0.062W
3044	4822 117 12925	47kΩ 1% 0.063W 0603	3373	4822 051 30339	33Ω 5% 0.062W	3492	4822 051 30151	150Ω 5% 0.062W
3045	4822 051 30102	1kΩ 5% 0.062W	3374	4822 051 30471	470Ω 5% 0.062W	3493	4822 051 30151	150Ω 5% 0.062W
3045	4822 117 12925	47kΩ 1% 0.063W 0603	3375	4822 051 30471	470Ω 5% 0.062W	3494	4822 051 30151	150Ω 5% 0.062W
3045	4822 117 13632	100kΩ 1% 0603 0.62W	3376	4822 051 30471	470Ω 5% 0.062W	3495	4822 051 30471	470Ω 5% 0.062W
3046	4822 051 30471	470Ω 5% 0.062W	3378	4822 051 30152	1.5kΩ 5% 0.062W	3495	4822 051 30472	4.7kΩ 5% 0.062W
3046	4822 116 52257	22kΩ 5% 0.5W	3401	5322 117 13055	75R 1% 0.063W 0603	3496	4822 051 30471	470Ω 5% 0.062W
3047	4822 050 21003	10kΩ 1% 0.6W	3402	5322 117 13055	75R 1% 0.063W 0603	3496	4822 051 30472	4.7kΩ 5% 0.062W
3047	4822 117 13632	100kΩ 1% 0603 0.62W	3403	5322 117 13055	75R 1% 0.063W 0603	3501	4822 051 30102	1kΩ 5% 0.062W
3048	4822 051 30101	100Ω 5% 0.062W	3404	4822 051 30759	75Ω 5% 0.062W	3502	4822 050 11002	1kΩ 1% 0.4W
3049	4822 051 30472	4.7kΩ 5% 0.062W	3405	4822 051 30223	22kΩ 5% 0.062W	3503	4822 117 13632	100kΩ 1% 0603 0.62W
3050	4822 117 13632	100kΩ 1% 0603 0.62W	3406	4822 117 12891	220kΩ 1% 0.063W 0603	3504	4822 117 13632	100kΩ 1% 0603 0.62W
3051	4822 051 30223	22kΩ 5% 0.062W	3407	4822 051 30332	3.3kΩ 5% 0.062W	3505	4822 117 13632	100kΩ 1% 0603 0.62W
3051	4822 117 13632	100kΩ 1% 0603 0.62W	3408	4822 051 30392	3.9kΩ 5% 0.063W 0603	3506	4822 117 13632	100kΩ 1% 0603 0.62W
3052	4822 051 30223	22kΩ 5% 0.062W	3409	5322 117 13055	75R 1% 0.063W 0603	3507	4822 117 13632	100kΩ 1% 0603 0.62W
3052	4822 051 30332	3.3kΩ 5% 0.062W	3410	5322 117 13055	75R 1% 0.063W 0603	3508	4822 051 30102	1kΩ 5% 0.062W
3053	4822 050 21003	10kΩ 1% 0.6W	3411	4822 051 30759	75Ω 5% 0.062W	3509	4822 050 11002	1kΩ 1% 0.4W
3053	4822 117 13632	100kΩ 1% 0603 0.62W	3412	4822 116 52201	75Ω 5% 0.5W	3510	4822 117 13632	100kΩ 1% 0603 0.62W
3054	4822 051 30332	3.3kΩ 5% 0.062W	3413	5322 117 13055	75R 1% 0.063W 0603	3511	4822 117 13632	100kΩ 1% 0603 0.62W
3054	4822 117 12139	22Ω 5% 0.062W	3414	4822 051 30759	75Ω 5% 0.062W	3512	4822 051 30102	1kΩ 5% 0.062W
3300▲	4822 053 21335	3.3MΩ 5% 0.5W	3415	4822 051 30102	1kΩ 5% 0.062W	3513	4822 051 30102	1kΩ 5% 0.062W
3301▲	4822 053 21335	3.3MΩ 5% 0.5W	3416	4822 051 30472	4.7kΩ 5% 0.062W	3514	4822 117 13632	100kΩ 1% 0603 0.62W
3302	4822 051 30102	1kΩ 5% 0.062W	3417	4822 051 30759	75Ω 5% 0.062W	3515	4822 050 11002	1kΩ 1% 0.4W
3303	4822 051 30102	1kΩ 5% 0.062W	3418	4822 117 13632	100kΩ 1% 0603 0.62W	3516	4822 117 13632	100kΩ 1% 0603 0.62W
3304	4822 051 30103	10kΩ 5% 0.062W	3419	4822 051 30223	22kΩ 5% 0.062W	3517	4822 116 52283	4.7kΩ 5% 0.5W
3305▲	4822 053 21684	680kΩ 5% 0.5W	3420	4822 051 30151	150Ω 5% 0.062W	3518	4822 051 30102	1kΩ 5% 0.062W
3306	4822 116 83872	220Ω 5% 0.5W	3421	4822 051 30273	27kΩ 5% 0.062W	3519	4822 116 52283	4.7kΩ 5% 0.5W
3307	4822 051 30103	10kΩ 5% 0.062W	3422	4822 116 52231	820Ω 5% 0.5W	3520	4822 051 30221	220Ω 5% 0.062W
3308	4822 116 52272	330k 5% 0.5W	3423	4822 051 30391	390Ω 5% 0.062W	3521	4822 051 30221	220Ω 5% 0.062W
3309	4822 116 52272	330k 5% 0.5W	3424	4822 051 30333	33kΩ 5% 0			

3534	4822 117 13632	100kΩ 1% 0603 0.62W	4425	4822 051 30008	Jumper 0603	6303	9322 182 65682	DIO REC STTH302-C2 (ST00) B
3580	4822 051 30759	75Ω 5% 0.062W	4426	4822 051 30008	Jumper 0603	6304	4822 130 31878	1N4003G
3581	4822 051 30222	2.2kΩ 5% 0.062W	4427	4822 051 30008	Jumper 0603	6305	4822 130 31603	1N4006
3582	4822 051 30331	330Ω 5% 0.062W	4428	4822 051 30008	Jumper 0603	6306	4822 130 31603	1N4006
3584	4822 051 30471	470Ω 5% 0.062W	4429	4822 051 30008	Jumper 0603	6307	4822 130 82627	SB540
3585	4822 051 30561	560Ω 5% 0.062W	4430	4822 051 30008	Jumper 0603	6307	9322 161 77682	SB540L-7024
3600	4822 051 30103	10kΩ 5% 0.062W	4431	4822 051 30008	Jumper 0603	6307	9322 184 68682	STPS5L40-C2
3601	4822 116 52175	100Ω 5% 0.5W	4433	4822 051 30008	Jumper 0603	6308	4822 130 82627	SB540
3602	4822 051 30472	4.7kΩ 5% 0.062W	4434	4822 051 30008	Jumper 0603	6308	9322 161 77682	SB540L-7024
3603	4822 116 52175	100Ω 5% 0.5W	4435	4822 051 30008	Jumper 0603	6308	9322 184 68682	STPS5L40-C2
3606	4822 051 30102	1kΩ 5% 0.062W	4437	4822 051 30008	Jumper 0603	6309	9322 126 71673	BYT42M
3607	4822 051 30102	1kΩ 5% 0.062W	4442	4822 051 30008	Jumper 0603	6310	9322 161 78682	SB360L-7024
3611	4822 051 30101	100Ω 5% 0.062W	4443	4822 051 30008	Jumper 0603	6310	9322 182 65682	DIO REC STTH302-C2
3612	4822 051 30101	100Ω 5% 0.062W	4444	4822 051 30008	Jumper 0603	6310	9322 188 34682	STPS3L60-C2
3701	4822 116 52228	680Ω 5% 0.5W	4445	4822 051 30008	Jumper 0603	6311	4822 130 31878	1N4003G
3702	4822 051 30471	470Ω 5% 0.062W	4446	4822 051 30008	Jumper 0603	6312	4822 130 11416	PDZ6.8B
3703	4822 116 52245	150kΩ 5% 0.5W	4447	4822 051 30008	Jumper 0603	6313	4822 130 10871	SBYV27-200
3704	4822 051 30221	220Ω 5% 0.062W	4448	4822 051 30008	Jumper 0603	6313	9322 199 50673	UF202G
3705	4822 051 30103	10kΩ 5% 0.062W	4449	4822 051 30008	Jumper 0603	6314	4822 130 10837	UDZS8.2B
3710	4822 051 30562	5.6kΩ 5% 0.063W 0603	4452	4822 051 30008	Jumper 0603	6315	4822 130 11397	BAS316
3711	4822 051 30333	33kΩ 5% 0.062W	4453	4822 051 30008	Jumper 0603	6316	4822 130 30842	BAV21
3714	4822 051 30183	18kΩ 5% 0.062W	4454	4822 051 30008	Jumper 0603	6317	4822 130 42488	BYD33D
3715	4822 051 30103	10kΩ 5% 0.062W	4455	4822 051 30008	Jumper 0603	6317	9322 126 71673	BYT42M
3716	4822 051 30472	4.7kΩ 5% 0.062W	4456	2422 549 43062	Bead 600Ω at 100MHz	6317	9322 196 45673	PG102R
3717	4822 051 30472	4.7kΩ 5% 0.062W	4456	4822 051 30008	Jumper 0603	6318	3198 010 53390	BZX79-B33
3720	4822 051 30331	330Ω 5% 0.062W	4457	4822 051 30008	Jumper 0603	6318	4822 130 34142	BZX79-B33
3724	4822 100 12158	22K 30%	4459	4822 051 30008	Jumper 0603	6319	4822 130 42488	BYD33D
3725	4822 117 12902	8.2kΩ 1% 0.063W 0603	4460	4822 051 10008	Jumper 1206	6319	9322 126 71673	BYT42M
3726	4822 051 30101	100Ω 5% 0.062W	4461	4822 051 30008	Jumper 0603	6319	9322 196 45673	PG102R
3727	4822 117 12917	1Ω 5% 0.062W 0603	4601	4822 051 30008	Jumper 0603	6320	4822 130 11397	BAS316
3728	4822 051 30101	100Ω 5% 0.062W	4700	4822 051 30008	Jumper 0603	6321	4822 130 10654	BAT254
3729	4822 117 12917	1Ω 5% 0.062W 0603	4701	4822 051 30008	Jumper 0603	6321	4822 130 80622	BAT54
3730	4822 051 30472	4.7kΩ 5% 0.062W	4999	4822 051 30008	Jumper 0603	6322	4822 130 11416	PDZ6.8B
3731	4822 051 30271	270Ω 5% 0.062W				6324	9340 548 69115	PDZ27B
3731	4822 051 30331	330Ω 5% 0.062W				6325	4822 130 10871	SBYV27-200
3732	4822 051 30102	1kΩ 5% 0.062W				6325	4822 130 81234	1N5819
3733	4822 051 30472	4.7kΩ 5% 0.062W	5001	2422 549 43062	Bead 600Ω at 100MHz	6401	9340 548 61115	PDZ12B
3734	4822 051 30272	2.7kΩ 5% 0.062W	5002	2422 549 43062	Bead 600Ω at 100MHz	6402	9340 548 61115	PDZ12B
3735	4822 051 30332	3.3kΩ 5% 0.062W	5300▲	2422 531 02546	SRW28EC9-E01V0* B	6403	9340 548 61115	PDZ12B
3736	4822 051 30331	330Ω 5% 0.062W	5300▲	3128 138 40782	CT286D8 B	6404	9340 548 61115	PDZ12B
3737	4822 051 30222	2.2kΩ 5% 0.062W	5302▲	2422 549 44509	25MH 0A4 HF2022R Y	6409	4822 130 11416	PDZ6.8B
3738	4822 051 30682	6.8kΩ 5% 0.062W	5304	4822 157 70826	2.4μH	6414	4822 130 11416	PDZ6.8B
3739	4822 051 30562	5.6kΩ 5% 0.063W 0603	5305	4822 157 70826	2.4μH	6415	9340 548 61115	PDZ12B
3740	4822 051 30681	680Ω 5% 0.062W	5306	2422 535 94634	2.2μH LHL08 20%	6416	9340 548 61115	PDZ12B
3741	4822 051 30472	4.7kΩ 5% 0.062W	5307	4822 157 11737	22μH 10%	6417	9340 548 61115	PDZ12B
3742	4822 051 30472	4.7kΩ 5% 0.062W	5308	4822 157 11737	22μH 10%	6418	9340 548 61115	PDZ12B
3743	4822 051 30563	56kΩ 5% 0.062W	5309	4822 157 11737	22μH 10%	6419	9340 548 61115	PDZ12B
3744	4822 117 13632	100kΩ 1% 0603 0.62W	5401	4822 157 11706	10μH 5%	6420	9340 548 61115	PDZ12B
3745	4822 051 30562	5.6kΩ 5% 0.063W 0603	5402	4822 157 11706	10μH 5%	6422	4822 130 11564	UDZ3.9B
3746	4822 051 30562	5.6kΩ 5% 0.063W 0603	5403	4822 157 11706	10μH 5%	6423	9340 548 61115	PDZ12B
3758	4822 051 30103	10kΩ 5% 0.062W	5404	4822 157 11706	10μH 5%	6424	9340 548 61115	PDZ12B
3931	4822 117 12925	47kΩ 1% 0.063W 0603	5405	2422 549 43062	Bead 600Ω at 100MHz	6425	9340 548 61115	PDZ12B
3932	4822 117 12925	47kΩ 1% 0.063W 0603	5406	4822 157 11706	10μH 5%	6426	9340 548 61115	PDZ12B
3933	4822 117 12925	47kΩ 1% 0.063W 0603	5407	2422 549 43062	Bead 600Ω at 100MHz	6427	9340 548 61115	PDZ12B
3934	4822 051 30101	100Ω 5% 0.062W	5580	2422 536 00019	TRANSFORMER 6RG	6428	9340 548 61115	PDZ12B
3935	4822 051 30101	100Ω 5% 0.062W	5581	4822 157 11706	10μH 5%	6429	9340 548 61115	PDZ12B
3936	4822 051 30103	10kΩ 5% 0.062W	5600▲	4822 157 11706	10μH 5%	6600	4822 130 11397	BAS316
3937	4822 051 30222	2.2kΩ 5% 0.062W	5601▲	4822 157 11706	10μH 5%	6703	9340 552 30115	BA591
3938	4822 051 30222	2.2kΩ 5% 0.062W	5602▲	4822 157 11706	10μH 5%	6704	9340 552 30115	BA591
3939	4822 051 30472	4.7kΩ 5% 0.062W	5701	2422 549 43062	Bead 600Ω at 100MHz	6705	9340 552 30115	BA591
3940	3198 021 31060	10MΩ 5% 0.062W 0603	5702	2422 549 43062	Bead 600Ω at 100MHz			
3941	3198 021 31060	10MΩ 5% 0.062W 0603	5705	4822 157 11139	6.8μH 5%			
3942	4822 051 30333	33kΩ 5% 0.062W	5709	4822 157 11139	6.8μH 5%			
3943	4822 051 30333	33kΩ 5% 0.062W	5710	2422 549 44162	IND VAR 7MM 7KMY 77M8			
3944	4822 051 30333	33kΩ 5% 0.062W	5711	2422 549 44162	IND VAR 7MM 7KMY 77M8			
3945	4822 051 30333	33kΩ 5% 0.062W	5711	2422 549 45833	IND VAR 7MM 7KLY 77MHZ8			
3946	4822 051 30333	33kΩ 5% 0.062W	5713	4822 157 11747	15UH 5%			
3947	4822 051 30333	33kΩ 5% 0.062W	5714	4822 157 11747	15UH 5%			
3948	4822 051 30472	4.7kΩ 5% 0.062W	5931	4822 157 11706	10μH 5%			
3950	4822 117 13632	100kΩ 1% 0603 0.62W	5932	2422 549 43062	Bead 600Ω at 100MHz			
3951	4822 051 30223	22kΩ 5% 0.062W						
3952	4822 051 30153	15kΩ 5% 0.062W						
3953	4822 051 30472	4.7kΩ 5% 0.062W						
3954	4822 051 30472	4.7kΩ 5% 0.062W						
3955	4822 051 30103	10kΩ 5% 0.062W						
4001	4822 051 30008	Jumper 0603						
4002	4822 051 30008	Jumper 0603						
4003	4822 051 30008	Jumper 0603						
4004	4822 051 30008	Jumper 0603						
4402	4822 051 30008	Jumper 0603						
4411	4822 051 30008	Jumper 0603						
4412	4822 051 30008	Jumper 0603						
4413	4822 051 30008	Jumper 0603						
4414	4822 051 30008	Jumper 0603						
4415	4822 051 30008	Jumper 0603						
4416	4822 051 30008	Jumper 0603						
4417	4822 051 30008	Jumper 0603						
4418	4822 051 30008	Jumper 0603						
4419	4822 051 30008	Jumper 0603						
4420	4822 051 30008	Jumper 0603						
4421	4822 051 30008	Jumper 0603						
4422	4822 051 30008	Jumper 0603						
4423	4822 051 30008	Jumper 0603						
4424	4822 051 30008	Jumper 0603						

7309	9322 180 12685	SI2312DS
7310	3198 010 42310	BC847BW
7311	3198 010 42310	BC847BW
7312	4822 130 41782	BF422
7313	9352 673 56112	TEA1507P/N1
7314▲	9322 153 43682	LTV817BM-V
7314▲	9965 000 09548	TCET1108G
7315	4822 209 14933	TL431IZ
7317	9322 163 75685	SI2306DS
7317	9322 191 71687	STD17NF03L-1
7318	9322 163 75685	SI2306DS
7319	5322 130 60159	BC846B
7320	9322 163 75685	SI2306DS
7321	4822 130 61553	DTC124EU
7322	3198 010 42320	BC857BW
7401	3198 010 42320	BC857BW
7402	3198 010 42310	BC847BW
7403	3198 010 42320	BC857BW
7404	3198 010 42320	BC857BW
7405	3198 010 42310	BC847BW
7406	3198 010 42320	BC857BW
7407	3198 010 42310	BC847BW
7408	9322 173 41668	ST6618
7409	3198 010 42310	BC847BW
7410	9322 174 76668	NJM2267M
7411	9322 179 71668	NJM2285M
7412	4822 130 61553	DTC124EU
7415	9340 219 30115	BC817-25W
7416	9340 219 30115	BC817-25W
7419	9340 560 36235	BSH111
7420	9340 560 36235	BSH111
7421	3198 010 42310	BC847BW
7501	5322 209 11102	HEF4052BT
7502	4822 209 32071	MC33079D
7503	5322 209 11102	HEF4052BT
7504	5322 209 11102	HEF4052BT
7505	4822 209 62312	MC33078D
7506	9340 219 30115	BC817-25W
7508	9340 219 30115	BC817-25W
7509	9340 219 30115	BC817-25W
7511	9340 219 30115	BC817-25W
7580	5322 209 11517	PC74HCU04T
7600	9322 186 87668	MSP3415G-QG-B8V3
7701	4822 130 61553	DTC124EU
7702	4822 130 61553	DTC124EU
7704	4822 130 61553	DTC124EU
7705	4822 130 61553	DTC124EU
7706	4822 130 61553	DTC124EU
7710	9352 606 11118	TDA9818T/V1
7710	9352 621 13118	IC SM TDA9817T/V1
7711	3198 010 42320	BC857BW
7712	4822 130 61553	DTC124EU
7713	3198 010 42320	BC857BW
7714	3198 010 42310	BC847BW
7716	3198 010 42320	BC857BW
7717	3198 010 42310	BC847BW
7717	5322 130 42755	BC847C
7931	4822 209 17505	STV5348D
7932	3198 010 42310	BC847BW
7933	3198 010 42310	BC847BW
7934	4822 209 60177	LM339D

Up Sub Board

Various

1801	2422 543 01115	24.576MHz 12P QS06
1805	4822 242 70938	TA252E00 (32,768KHZ)
1901	2422 025 12488	CON BM H 2P M 2.50 EH B
1980	2422 025 17723	CON BM V 8P M2.00 C36 B
1980	2422 025 18217	CON V 8P M 2.00
1984	2422 025 17723	CON BM V 8P M2.00 C36 B
1984	2422 025 18217	CON V 8P M 2.00
1986	2422 025 16677	Connector 10P
1987	2422 025 17723	CON BM V 8P M2.00 C36 B
1987	2422 025 18217	CON V 8P M 2.00
1988	2422 025 17723	CON BM V 8P M2.00 C36 B
1988	2422 025 18217	CON V 8P M 2.00

—||—

2800	2238 586 59812	100nF 20-80% 50V 0603
2801	4822 122 33752	15pF 5% 50V
2802	4822 122 33752	15pF 5% 50V
2803	2238 586 59812	100nF 20-80% 50V 0603
2804	2238 586 59812	100nF 20-80% 50V 0603
2805	2238 586 59812	100nF 20-80% 50V 0603
2806	2238 586 59812	100nF 20-80% 50V 0603
2807	4822 126 13879	220nF 20% 16V
2808	2238 586 59812	100nF 20-80% 50V 0603
2809	2238 586 59812	100nF 20-80% 50V 0603

2810	4822 122 33741	10pF 10% 50V
2811	4822 122 33741	10pF 10% 50V
2812	5322 126 11583	10nF 10% 50V 0603
2813	4822 122 33741	10pF 10% 50V
2814	4822 122 33741	10pF 10% 50V
2815	4822 126 13883	220pF 5% 50V
2816	4822 124 11968	220mF +80-20% 5.5V
2817	2238 586 59812	100nF 20-80% 50V 0603
2818	4822 126 13883	220pF 5% 50V
2819	4822 124 42234	100μF 20% 6.3V
2820	5322 126 11583	10nF 10% 50V 0603
2821	5322 126 11583	10nF 10% 50V 0603
2822	2238 586 59812	100nF 20-80% 50V 0603
2823	5322 126 11578	1nF 10% 50V 0603
2824	3198 017 41050	1μF 10V 0603
2825	2020 552 94427	100pF 5% 50v 0603
2828	2238 586 59812	100nF 20-80% 50V 0603
2829	4822 124 21732	10μF 20% 25V
2830	2238 586 59812	100nF 20-80% 50V 0603
2831	5322 126 11583	10nF 10% 50V 0603
2912	4822 124 23052	100UF20% 16V
2913	4822 124 23052	100UF20% 16V

—W—

3800	4822 051 30101	100Ω 5% 0.062W
3800	4822 051 30223	22kΩ 5% 0.062W
3801	4822 051 30103	10kΩ 5% 0.062W
3802	4822 051 30101	100Ω 5% 0.062W
3802	4822 051 30223	22kΩ 5% 0.062W
3803	4822 051 30102	1kΩ 5% 0.062W
3804	4822 051 30103	10kΩ 5% 0.062W
3805	4822 051 30101	100Ω 5% 0.062W
3806	4822 051 30223	22kΩ 5% 0.062W
3807	4822 117 13632	100kΩ 1% 0603 0.62W
3808	4822 117 13632	100kΩ 1% 0603 0.62W
3809	4822 117 13632	100kΩ 1% 0603 0.62W
3810	4822 117 13632	100kΩ 1% 0603 0.62W
3811	4822 051 30101	100Ω 5% 0.062W
3812	4822 051 30223	22kΩ 5% 0.062W
3813	4822 051 30103	10kΩ 5% 0.062W
3814	4822 051 30103	10kΩ 5% 0.062W
3815	4822 051 30183	18kΩ 5% 0.062W
3816	4822 051 30103	10kΩ 5% 0.062W
3817	4822 051 30222	2.2kΩ 5% 0.062W
3818	4822 051 30472	4.7kΩ 5% 0.062W
3819	4822 051 30103	10kΩ 5% 0.062W
3820	4822 051 30102	1kΩ 5% 0.062W
3821	4822 051 30103	10kΩ 5% 0.062W
3822	4822 051 30103	10kΩ 5% 0.062W
3823	4822 117 13632	100kΩ 1% 0603 0.62W
3824	4822 051 30102	1kΩ 5% 0.062W
3825	4822 051 30103	10kΩ 5% 0.062W
3826	4822 051 30102	1kΩ 5% 0.062W
3827	4822 051 30102	1kΩ 5% 0.062W
3828	4822 051 30103	10kΩ 5% 0.062W
3829	4822 051 30103	10kΩ 5% 0.062W
3830	4822 051 30102	1kΩ 5% 0.062W
3831	4822 051 30102	1kΩ 5% 0.062W
3832	4822 051 30333	33kΩ 5% 0.062W
3833	4822 051 30102	1kΩ 5% 0.062W
3834	4822 051 30102	1kΩ 5% 0.062W
3835	4822 051 30102	1kΩ 5% 0.062W
3836	4822 051 30101	100Ω 5% 0.062W
3837	4822 051 30123	12kΩ 5% 0.062W
3838	4822 051 30102	1kΩ 5% 0.062W
3839	4822 051 30273	27kΩ 5% 0.062W
3840	4822 051 30472	4.7kΩ 5% 0.062W
3841	4822 117 13632	100kΩ 1% 0603 0.62W
3842	4822 117 12891	220kΩ 1% 0.063W 0603
3843	4822 051 30333	33kΩ 5% 0.062W
3844	4822 051 30221	220Ω 5% 0.062W
3845	4822 051 30102	1kΩ 5% 0.062W
3846	4822 051 30333	33kΩ 5% 0.062W
3847	4822 051 30103	10kΩ 5% 0.062W
3849	4822 117 12925	47kΩ 1% 0.063W 0603
3850	4822 051 30183	18kΩ 5% 0.062W
3851	4822 051 30103	10kΩ 5% 0.062W
3852	4822 051 30103	10kΩ 5% 0.062W
3854	4822 051 30102	1kΩ 5% 0.062W
3855	4822 051 30471	470Ω 5% 0.062W
3856	4822 051 30103	10kΩ 5% 0.062W
3857	4822 051 30103	10kΩ 5% 0.062W
3858	4822 117 13632	100kΩ 1% 0603 0.62W
3860	4822 051 30222	2.2kΩ 5% 0.062W
3861	3198 021 32250	2.2MΩ 5% 0603
3862	4822 051 30103	10kΩ 5% 0.062W
3863	4822 117 13608	4.7Ω 5% 0603 0.62W
3864	4822 117 13608	4.7Ω 5% 0603 0.62W
3865	4822 117 13608	4.7Ω 5% 0603 0.62W
3866	4822 117 13608	4.7Ω 5% 0603 0.62W
3867	4822 051 30759	75Ω 5% 0.062W
3868	4822 051 30103	10kΩ 5% 0.062W

3869	4822 051 30331	330Ω 5% 0.062W
3870	4822 117 13632	100kΩ 1% 0603 0.62W
3871	4822 051 30103	10kΩ 5% 0.062W
3872	4822 051 30103	10kΩ 5% 0.062W
3873	4822 051 30472	4.7kΩ 5% 0.062W
3874	4822 051 30103	10kΩ 5% 0.062W
3875	4822 051 30103	10kΩ 5% 0.062W
3876	4822 051 30103	10kΩ 5% 0.062W
3878	4822 051 30102	1kΩ 5% 0.062W
3879	4822 051 30102	1kΩ 5% 0.062W
3881	4822 117 12925	47kΩ 1% 0.063W 0603
3882	4822 117 12925	47kΩ 1% 0.063W 0603
3884	4822 051 30101	100Ω 5% 0.062W
3885	4822 051 30101	100Ω 5% 0.062W
3886	4822 051 30472	4.7kΩ 5% 0.062W
3887	4822 051 30472	4.7kΩ 5% 0.062W
3888	4822 051 30471	470Ω 5% 0.062W
3889	4822 051 30183	18kΩ 5% 0.062W
3913	4822 051 30102	1kΩ 5% 0.062W
3914	4822 051 30102	1kΩ 5% 0.062W
3915	4822 051 30102	1kΩ 5% 0.062W
3916	4822 051 30273	27kΩ 5% 0.062W
3917	2322 704 63603	36kΩ 0603 RC22H 1%
3918	4822 051 30102	1kΩ 5% 0.062W
3919	5322 117 13024	33kΩ 1% 0.063W 0603
3920	4822 051 30562	5.6kΩ 5% 0.063W 0603
3921	4822 051 30471	470Ω 5% 0.062W
3922	4822 051 30102	1kΩ 5% 0.062W
3923	4822 051 30103	10kΩ 5% 0.062W
3924	4822 051 30103	10kΩ 5% 0.062W
3925	4822 117 12706	10kΩ 1% 0.063W 0603
3926	4822 051 30472	4.7kΩ 5% 0.062W
3927	4822 051 30333	33kΩ 5% 0.062W
3929	4822 051 30008	Jumper 0603
3931	4822 051 30008	Jumper 0603
3933	4822 051 30008	Jumper 0603
4901	4822 051 30008	Jumper 0603
4902	4822 051 30008	Jumper 0603
4903	4822 051 30008	Jumper 0603
4904	4822 051 10008	Jumper 1206

—W—

5801	2422 549 44607	Bead 600Ω at 100MHz
5802	2422 549 44607	Bead 600Ω at 100MHz
5803	2422 549 44607	Bead 600Ω at 100MHz
5804	2422 549 44607	Bead 600Ω at 100MHz

—D—

6800	4822 130 11397	BAS316
6801	4822 130 11564	UDZ3.9B
6802	4822 130 10654	BAT254
6803	4822 130 10654	BAT254
6804	4822 130 10654	BAT254
6805	4822 130 10654	BAT254
6901	5322 130 34331	BAV70
6903	5322 130 34331	BAV70

—D—

7801	9352 190 00118	74LVC573AD
7802	4822 130 61553	DTC124EU
7803	9322 186 16668	CY62128VLL-70SC
7804	3103 165 13721	TMP91CW12AF/LIRP1
7805	9965 000 17112	M29W800DT-70N6/ AN130067
7806	9322 163 26685	NCP301LSN30
7807	4822 209 73852	PMBT2369
7808	4822 209 16907	M24C16-MN6T
7813	3198 010 42310	BC847BW
7814	3198 010 42310	BC847BW
7815	3198 010 42310	BC847BW
7816	3198 010 42310	BC847BW
7817	3198 010 42310	BC847BW
7818	4822 130 60854	DTA124EU-W
7821	9340 560 36235	BSH111
7822	9340 560 36235	BSH111
7825	9322 181 92682	LA7213
7902	4822 209 63709	LM324D
7903	4822 130 61553	DTC124EU
7904	4822 130 60854	DTA124EU-W
7905	4822 130 61553	DTC124EU
7906	4822 130 61553	DTC124EU
7907	4822 130 61553	DTC124EU
7908	4822 130 61553	DTC124EU
7909	4822 130 41087	BC638
7910	4822 130 61553	DTC124EU

DVIO Board

Various

1400	2422 543 01115	24.576MHz 12P QS06
1500	2422 025 17084	CON BM V 60P F 0.80 179161 R
1501	2422 025 16543	Connector 4P m h 2.00 SMD
1502	2422 086 11075	FUSE 750mA 125V
1800	2422 543 89022	Crystal 6MHz 20pF CX5F
1901	2422 025 17106	CON BM H 4P F 0.8 IEEE R
1903	2422 025 16542	CON BM H 2P M 2.00 PH SMD R

—||—

2400	2238 586 59812	100nF 20-80% 50V 0603
2401	3198 017 41050	1µF 10V 0603
2402	4822 126 14506	270pF 5% 50V 0603
2403	4822 124 80151	47µF 20% 16V
2404	2238 586 59812	100nF 20-80% 50V 0603
2405	2238 586 59812	100nF 20-80% 50V 0603
2406	2238 586 59812	100nF 20-80% 50V 0603
2407	2238 586 59812	100nF 20-80% 50V 0603
2408	2238 586 59812	100nF 20-80% 50V 0603
2412	4822 122 33741	10pF 10% 50V
2413	4822 122 33741	10pF 10% 50V
2415	4822 124 80151	47µF 20% 16V
2416	2238 586 59812	100nF 20-80% 50V 0603
2417	2238 586 59812	100nF 20-80% 50V 0603
2418	2238 586 59812	100nF 20-80% 50V 0603
2419	2238 586 59812	100nF 20-80% 50V 0603
2420	2238 586 59812	100nF 20-80% 50V 0603
2431	4822 124 80151	47µF 20% 16V
2432	2238 586 59812	100nF 20-80% 50V 0603
2433	2238 586 59812	100nF 20-80% 50V 0603
2434	2238 586 59812	100nF 20-80% 50V 0603
2435	2238 586 59812	100nF 20-80% 50V 0603
2436	2238 586 59812	100nF 20-80% 50V 0603
2437	2238 586 59812	100nF 20-80% 50V 0603
2438	2238 586 59812	100nF 20-80% 50V 0603
2439	2238 586 59812	100nF 20-80% 50V 0603
2440	2238 586 59812	100nF 20-80% 50V 0603
2441	2238 586 59812	100nF 20-80% 50V 0603
2442	2238 586 59812	100nF 20-80% 50V 0603
2443	2238 586 59812	100nF 20-80% 50V 0603
2444	2238 586 59812	100nF 20-80% 50V 0603
2445	2238 586 59812	100nF 20-80% 50V 0603
2446	2238 586 59812	100nF 20-80% 50V 0603
2447	2238 586 59812	100nF 20-80% 50V 0603
2449	2238 586 59812	100nF 20-80% 50V 0603
2450	4822 124 23002	10µF 20% 16V
2451	2238 586 59812	100nF 20-80% 50V 0603
2452	2238 586 59812	100nF 20-80% 50V 0603
2453	2238 586 59812	100nF 20-80% 50V 0603
2454	2238 586 59812	100nF 20-80% 50V 0603
2455	2238 586 59812	100nF 20-80% 50V 0603
2456	2238 586 59812	100nF 20-80% 50V 0603
2501	2238 586 59812	100nF 20-80% 50V 0603
2502	2238 586 59812	100nF 20-80% 50V 0603
2503	2238 586 59812	100nF 20-80% 50V 0603
2504	2238 586 59812	100nF 20-80% 50V 0603
2505	2238 586 59812	100nF 20-80% 50V 0603
2506	4822 124 80151	47µF 20% 16V
2507	4822 124 80151	47µF 20% 16V
2508	2238 586 59812	100nF 20-80% 50V 0603
2512	2238 586 59812	100nF 20-80% 50V 0603
2513	2238 586 59812	100nF 20-80% 50V 0603
2514	4822 124 80151	47µF 20% 16V
2520	2238 586 59812	100nF 20-80% 50V 0603
2521	4822 124 80151	47µF 20% 16V
2522	4822 124 80151	47µF 20% 16V
2523	5322 126 11583	10nF 10% 50V 0603
2524	5322 126 11583	10nF 10% 50V 0603
2525	4822 124 80151	47µF 20% 16V
2526	2238 586 59812	100nF 20-80% 50V 0603
2527	2238 586 59812	100nF 20-80% 50V 0603
2528	2238 586 59812	100nF 20-80% 50V 0603
2529	2238 586 59812	100nF 20-80% 50V 0603
2534	2238 586 59812	100nF 20-80% 50V 0603
2600	2238 586 59812	100nF 20-80% 50V 0603
2601	4822 124 23002	10µF 20% 16V
2602	3198 017 44740	470nF 10V 0603
2603	2238 586 59812	100nF 20-80% 50V 0603
2605	2238 586 59812	100nF 20-80% 50V 0603
2606	3198 016 31020	1nF 10% 25V 0603
2607	2238 586 59812	100nF 20-80% 50V 0603
2608	2238 586 59812	100nF 20-80% 50V 0603
2609	2238 586 59812	100nF 20-80% 50V 0603
2610	2238 586 59812	100nF 20-80% 50V 0603
2611	2238 586 59812	100nF 20-80% 50V 0603

2612	2238 586 59812	100nF 20-80% 50V 0603
2613	2238 586 59812	100nF 20-80% 50V 0603
2614	3198 017 44740	470nF 10V 0603
2617	2238 586 59812	100nF 20-80% 50V 0603
2618	2238 861 18229	22pF 1% 50V 0805
2801	4822 126 11669	27pF 5% 50V 0603
2802	4822 126 11669	27pF 5% 50V 0603
2803	2238 586 59812	100nF 20-80% 50V 0603
2804	2238 586 59812	100nF 20-80% 50V 0603
2805	4822 124 80151	47µF 20% 16V
2806	2238 586 59812	100nF 20-80% 50V 0603
2807	4822 124 80151	47µF 20% 16V
2808	2238 586 59812	100nF 20-80% 50V 0603
2809	2238 586 59812	100nF 20-80% 50V 0603
2810	2238 586 59812	100nF 20-80% 50V 0603
2812	2238 586 59812	100nF 20-80% 50V 0603
2813	2238 586 59812	100nF 20-80% 50V 0603
2814	5322 124 41945	22µF 20% 35V SMD
2816	2238 586 59812	100nF 20-80% 50V 0603
2818	2238 586 59812	100nF 20-80% 50V 0603
2820	2238 586 59812	100nF 20-80% 50V 0603
2822	3198 016 31020	1nF 10% 25V 0603

—WW—

3400	4822 051 30103	10kΩ 5% 0.062W
3401	2322 734 65609	56Ω 1% 0.125W 0805
3402	2322 734 65609	56Ω 1% 0.125W 0805
3403	4822 117 12139	22Ω 5% 0.062W
3404	2322 734 65609	56Ω 1% 0.125W 0805
3405	2322 734 65609	56Ω 1% 0.125W 0805
3406	2322 704 65102	5.1kΩ 1% 0603
3407	4822 051 30103	10kΩ 5% 0.062W
3408	4822 117 13632	100kΩ 1% 0603 0.62W
3409	2350 546 09102	9.1kΩ 0603 RC23H 5%
3409	4822 117 12902	8.2kΩ 1% 0.063W 0603
3410	4822 117 12139	22Ω 5% 0.062W
3413	4822 117 12139	22Ω 5% 0.062W
3414	4822 117 12139	22Ω 5% 0.062W
3415	4822 117 12139	22Ω 5% 0.062W
3416	4822 117 12139	22Ω 5% 0.062W
3417	4822 117 12139	22Ω 5% 0.062W
3418	4822 117 12139	22Ω 5% 0.062W
3419	4822 117 12139	22Ω 5% 0.062W
3420	4822 117 12139	22Ω 5% 0.062W
3421	4822 117 12139	22Ω 5% 0.062W
3422	4822 117 12139	22Ω 5% 0.062W
3423	4822 117 12139	22Ω 5% 0.062W
3424	4822 117 12139	22Ω 5% 0.062W
3425	4822 051 30103	10kΩ 5% 0.062W
3426	4822 051 30103	10kΩ 5% 0.062W
3427	4822 051 30103	10kΩ 5% 0.062W
3428	4822 051 30103	10kΩ 5% 0.062W
3429	4822 051 30103	10kΩ 5% 0.062W
3430	4822 051 30103	10kΩ 5% 0.062W
3431	4822 051 30103	10kΩ 5% 0.062W
3432	4822 051 30103	10kΩ 5% 0.062W
3433	4822 051 30103	10kΩ 5% 0.062W
3434	4822 051 30103	10kΩ 5% 0.062W
3435	4822 051 30103	10kΩ 5% 0.062W
3436	4822 051 30103	10kΩ 5% 0.062W
3437	4822 051 30103	10kΩ 5% 0.062W
3438	4822 051 30103	10kΩ 5% 0.062W
3439	4822 051 30103	10kΩ 5% 0.062W
3440	4822 051 30103	10kΩ 5% 0.062W
3441	4822 051 30103	10kΩ 5% 0.062W
3442	4822 051 30103	10kΩ 5% 0.062W
3443	4822 051 30103	10kΩ 5% 0.062W
3444	4822 051 30103	10kΩ 5% 0.062W
3445	4822 051 30103	10kΩ 5% 0.062W
3446	4822 051 30103	10kΩ 5% 0.062W
3447	4822 051 30103	10kΩ 5% 0.062W
3448	4822 051 30103	10kΩ 5% 0.062W
3449	4822 051 30103	10kΩ 5% 0.062W
3450	4822 051 30103	10kΩ 5% 0.062W
3451	4822 051 30103	10kΩ 5% 0.062W
3452	4822 051 30103	10kΩ 5% 0.062W
3453	4822 051 30102	1kΩ 5% 0.062W
3454	4822 051 30103	10kΩ 5% 0.062W
3455	4822 051 30103	10kΩ 5% 0.062W
3456	4822 051 30103	10kΩ 5% 0.062W
3457	4822 051 30103	10kΩ 5% 0.062W
3458	4822 051 30103	10kΩ 5% 0.062W
3459	4822 051 30103	10kΩ 5% 0.062W
3460	4822 051 30103	10kΩ 5% 0.062W
3461	4822 117 12925	47kΩ 1% 0.063W 0603
3462	4822 051 30103	10kΩ 5% 0.062W
3463	4822 051 30103	10kΩ 5% 0.062W
3464	4822 051 30103	10kΩ 5% 0.062W
3465	4822 051 30103	10kΩ 5% 0.062W
3466	4822 051 30103	10kΩ 5% 0.062W
3467	4822 051 30103	10kΩ 5% 0.062W
3468	4822 051 30103	10kΩ 5% 0.062W

3469	4822 051 30103	10kΩ 5% 0.062W	
3470	4822 051 30103	10kΩ 5% 0.062W	
3471	4822 051 30103	10kΩ 5% 0.062W	
3472	4822 051 30102	1kΩ 5% 0.062W	
3473	4822 051 30103	10kΩ 5% 0.062W	
3474	4822 051 30102	1kΩ 5% 0.062W	
3475	4822 051 30103	10kΩ 5% 0.062W	
3476	4822 051 30103	10kΩ 5% 0.062W	
3477	4822 051 30103	10kΩ 5% 0.062W	
3478	4822 051 30102	1kΩ 5% 0.062W	
3481	4822 051 30103	10kΩ 5% 0.062W	
3482	4822 051 30103	10kΩ 5% 0.062W	
3483	4822 051 30103	10kΩ 5% 0.062W	
3484	4822 051 30103	10kΩ 5% 0.062W	
3485	4822 051 30103	10kΩ 5% 0.062W	
3486	4822 051 30103	10kΩ 5% 0.062W	
3487	4822 051 30103	10kΩ 5% 0.062W	
3488	4822 051 30103	10kΩ 5% 0.062W	
3489	4822 051 30103	10kΩ 5% 0.062W	
3490	4822 051 30103	10kΩ 5% 0.062W	
3491	4822 051 30103	10kΩ 5% 0.062W	
3492	4822 051 30103	10kΩ 5% 0.062W	
3493	4822 051 30103	10kΩ 5% 0.062W	
3494	4822 051 30103	10kΩ 5% 0.062W	
3495	4822 051 30103	10kΩ 5% 0.062W	
3496	4822 051 30103	10kΩ 5% 0.062W	
3497	4822 051 30103	10kΩ 5% 0.062W	
3498	4822 051 30103	10kΩ 5% 0.062W	
3499	4822 051 30103	10kΩ 5% 0.062W	
3502	4822 051 30479	47Ω 5% 0.062W	
3503	4822 051 30479	47Ω 5% 0.062W	
3504	4822 051 30479	47Ω 5% 0.062W	
3505	4822 051 30479	47Ω 5% 0.062W	
3506	4822 051 30479	47Ω 5% 0.062W	
3507	4822 051 30479	47Ω 5% 0.062W	
3508	4822 051 30479	47Ω 5% 0.062W	
3509	4822 051 30479	47Ω 5% 0.062W	
3510	4822 051 30479	47Ω 5% 0.062W	
3514	4822 051 30479	47Ω 5% 0.062W	
3515	4822 051 30479	47Ω 5% 0.062W	
3516	4822 051 30479	47Ω 5% 0.062W	
3517	4822 051 30101	100Ω 5% 0.062W	
3518	4822 051 30101	100Ω 5% 0.062W	
3519	4822 117 12891	220kΩ 1% 0.063W	0603
3520	4822 117 12891	220kΩ 1% 0.063W	0603
3530	4822 117 12139	22Ω 5% 0.062W	
3531	4822 117 12139	22Ω 5% 0.062W	
3532	4822 117 12139	22Ω 5% 0.062W	
3533	4822 117 12139	22Ω 5% 0.062W	
3534	4822 117 12139	22Ω 5% 0.062W	
3535	4822 117 12139	22Ω 5% 0.062W	
3536	4822 117 12139	22Ω 5% 0.062W	
3537	4822 117 12139	22Ω 5% 0.062W	
3538	4822 117 12139	22Ω 5% 0.062W	
3539	4822 117 12139	22Ω 5% 0.062W	
3540	4822 117 12139	22Ω 5% 0.062W	
3541	4822 117 12139	22Ω 5% 0.062W	
3542	4822 117 12139	22Ω 5% 0.062W	
3543	4822 117 12139	22Ω 5% 0.062W	
3544	4822 117 12139	22Ω 5% 0.062W	
3545	4822 117 12139	22Ω 5% 0.062W	
3546	4822 117 12139	22Ω 5% 0.062W	
3547	4822 117 12139	22Ω 5% 0.062W	
3548	4822 117 12139	22Ω 5% 0.062W	
3549	4822 117 12139	22Ω 5% 0.062W	
3550	4822 117 12139	22Ω 5% 0.062W	
3551	4822 117 12139	22Ω 5% 0.062W	
3552	4822 117 12139	22Ω 5% 0.062W	
3553	4822 117 12139	22Ω 5% 0.062W	
3554	4822 117 12139	22Ω 5% 0.062W	
3555	4822 117 12139	22Ω 5% 0.062W	
3556	4822 117 12139	22Ω 5% 0.062W	
3557	4822 117 12139	22Ω 5% 0.062W	
3558	4822 117 12139	22Ω 5% 0.062W	
3559	4822 117 12139	22Ω 5% 0.062W	
3560	4822 117 12139	22Ω 5% 0.062W	
3561	4822 117 12139	22Ω 5% 0.062W	
3562	4822 051 30103	10kΩ 5% 0.062W	
3563	4822 117 12917	1Ω 5% 0.062W	0603
3564	4822 117 12139	22Ω 5% 0.062W	
3600	4822 117 12891	220kΩ 1% 0.063W	0603
3601	4822 117 12917	1Ω 5% 0.062W	0603
3602	4822 051 30103	10kΩ 5% 0.062W	
3603	4822 117 12917	1Ω 5% 0.062W	0603
3605	2120 358 90533	RTRM 22K RH03ADC	
3606	4822 117 12706	10kΩ 1% 0.063W	0603
3607	2322 702 60184	180kΩ 5% 0603	
3608	4822 117 12891	220kΩ 1% 0.063W	0603
3609	2322 704 65604	560kΩ 1% 0603	
3610	2322 704 62003	20KΩ 0603 RC22H1%	
3610	5322 117 13024	33kΩ 1% 0.063W	0603
3612	4822 117 12706	10kΩ 1% 0.063W	0603
3613	2322 704 65102	5.1kΩ 1% 0603	
3614	4822 117 13632	100kΩ 1% 0603	0.62W

3617	4822 051 30103	10kΩ 5% 0.062W
3618	4822 051 30103	10kΩ 5% 0.062W
3800	4822 051 30331	330Ω 5% 0.062W
3801	4822 051 30103	10kΩ 5% 0.062W
3802	4822 051 30223	22kΩ 5% 0.062W
3803	4822 051 30103	10kΩ 5% 0.062W
3804	4822 051 30103	10kΩ 5% 0.062W
3806	4822 051 30103	10kΩ 5% 0.062W
3807	4822 051 30103	10kΩ 5% 0.062W
3808	4822 051 30008	Jumper 0603
3809	4822 051 30103	10kΩ 5% 0.062W
3810	4822 051 30103	10kΩ 5% 0.062W
3812	4822 051 30103	10kΩ 5% 0.062W
3814	4822 051 30472	4.7kΩ 5% 0.062W
3815	5322 117 13047	330Ω 1% 0.063W 0603
3816	5322 117 13018	1kΩ 1% 0.063W 0603
3817	4822 051 30103	10kΩ 5% 0.062W
3818	4822 051 30103	10kΩ 5% 0.062W
3819	4822 051 30102	1kΩ 5% 0.062W
3820	4822 117 12925	47kΩ 1% 0.063W 0603
3821	4822 051 30103	10kΩ 5% 0.062W
3822	4822 117 13632	100kΩ 1% 0.063W 0.62W
3823	5322 117 13018	1kΩ 1% 0.063W 0603
3824	5322 117 13042	3.9kΩ 1% 0.063W 0603
3825	4822 051 30101	100Ω 5% 0.062W
3826	4822 051 30101	100Ω 5% 0.062W
3827	4822 051 30103	10kΩ 5% 0.062W
3828	4822 051 30101	100Ω 5% 0.062W
3829	4822 117 12925	47kΩ 1% 0.063W 0603
3831	4822 117 13632	100kΩ 1% 0.063 0.62W
3832	4822 051 30103	10kΩ 5% 0.062W
3833	4822 051 30103	10kΩ 5% 0.062W
3834	4822 051 30103	10kΩ 5% 0.062W
3835	4822 051 30102	1kΩ 5% 0.062W
3836	4822 051 30472	4.7kΩ 5% 0.062W
3837	4822 051 30103	10kΩ 5% 0.062W
3838	4822 051 30102	1kΩ 5% 0.062W
3839	4822 051 30222	2.2kΩ 5% 0.062W
4401	4822 051 30008	Jumper 0603
4402	4822 051 30008	Jumper 0603
4501	4822 051 30008	Jumper 0603
4503	4822 051 30008	Jumper 0603
4602	4822 051 30008	Jumper 0603
4603	4822 051 30008	Jumper 0603
4605	4822 051 30008	Jumper 0603
4606	4822 051 30008	Jumper 0603
4608	4822 051 30008	Jumper 0603
4609	4822 051 30008	Jumper 0603



5400	4822 157 11499	BLM11P600SPT
5401	4822 157 11499	BLM11P600SPT
5431	4822 157 11499	BLM11P600SPT
5432	4822 157 11499	BLM11P600SPT
5433	4822 157 11499	BLM11P600SPT
5501	4822 157 11499	BLM11P600SPT
5503	4822 157 11499	BLM11P600SPT
5504	4822 157 11499	BLM11P600SPT
5505	4822 157 11499	BLM11P600SPT
5600	4822 157 11499	BLM11P600SPT
5601	4822 157 11499	BLM11P600SPT
5602	4822 157 11499	BLM11P600SPT
5603	4822 157 11499	BLM11P600SPT
5800	4822 157 11499	BLM11P600SPT
5801	4822 157 11499	BLM11P600SPT
5802	4822 157 71593	10μH 10% 0805



6801	9340 548 52115	PDZ5.1B
6802	4822 130 11397	BAS316
6803	4822 130 11397	BAS316
6804	4822 130 11397	BAS316



7400	9322 182 04671	UPD72852GB-8EU
7430	9322 144 59668	MT48LC1M16A1TG-7S
7431	9322 184 70671	UPD72893GD-LML
7433	9322 142 88668	LF25CDT
7501	9352 685 96115	74LVC1GU04GW
7505	9352 029 90118	74LVT16244BDGG
7506	9352 668 39118	UDA1334ATS/N2
7507	9351 751 40118	74LV74PW
7508	9352 685 96115	74LVC1GU04GW
7601	2722 171 08709	27MHZ 120P FXO-31
7602	9352 456 40115	74HCT1G04GW
7604	9322 186 60668	BA7082F
7605	9322 186 59668	BU2288FV
7606	9351 751 40118	74LV74PW
7608	9352 685 96115	74LVC1GU04GW

7800	9340 310 30215	PDTC144ET
7801	9322 186 70668	LM2931D
7802	3103 607 40011	UPD78F0988AGC
		DV91XX0105
7803	3198 010 42310	BC847BW
7804	3198 010 42310	BC847BW
7805	3198 010 42310	BC847BW
7806	9340 310 30215	PDTC144ET
7807	9352 683 81115	74LVC1G32GW
7808	9340 560 36235	BSH111
7809	9352 683 81115	74LVC1G32GW
7810	3198 010 42320	BC857BW
7811	3198 010 42310	BC847BW

Digital Board 1.5 (Empress)

Various

1100	2422 025 17018	V 15P F 1.00 FFC 0.3 R
1101	2422 025 17018	V 15P F 1.00 FFC 0.3 R
1200	2422 025 16794	V 7P F 1.00 FFC 0.3 R
1500	2422 543 01115	24.576MHz 12P QS06
1600	2422 025 16729	Connector FFC 10p m
1601	2422 025 16389	BM V 22P F 1.00 FFC 0.3 R
1602	2422 025 16389	BM V 22P F 1.00 FFC 0.3 R
1603	2422 025 16939	BM V 60P F 0.80 84616 R
1900	2422 025 17441	BM V 12P M 2.00 PH SMD R



2100	2238 586 59812	100nF 20-80% 50V 0603
2101	2238 586 59812	100nF 20-80% 50V 0603
2102	2238 586 59812	100nF 20-80% 50V 0603
2103	2238 586 59812	100nF 20-80% 50V 0603
2104	2238 586 59812	100nF 20-80% 50V 0603
2105	2238 586 59812	100nF 20-80% 50V 0603
2106	2238 586 59812	100nF 20-80% 50V 0603
2107	2238 586 59812	100nF 20-80% 50V 0603
2108	2238 586 59812	100nF 20-80% 50V 0603
2109	2238 586 59812	100nF 20-80% 50V 0603
2110	2238 586 59812	100nF 20-80% 50V 0603
2111	2238 586 59812	100nF 20-80% 50V 0603
2112	2238 586 59812	100nF 20-80% 50V 0603
2113	2238 586 59812	100nF 20-80% 50V 0603
2114	2238 586 59812	100nF 20-80% 50V 0603
2115	2238 586 59812	100nF 20-80% 50V 0603
2116	2238 586 59812	100nF 20-80% 50V 0603
2117	2238 586 59812	100nF 20-80% 50V 0603
2118	2238 586 59812	100nF 20-80% 50V 0603
2119	3198 030 74780	4u7 20% 35V
2120	2238 586 59812	100nF 20-80% 50V 0603
2121	2238 586 59812	100nF 20-80% 50V 0603
2122	2238 586 59812	100nF 20-80% 50V 0603
2123	2238 586 59812	100nF 20-80% 50V 0603
2124	2238 586 59812	100nF 20-80% 50V 0603
2125	2238 586 59812	100nF 20-80% 50V 0603
2126	2238 586 59812	100nF 20-80% 50V 0603
2127	3198 030 74780	4u7 20% 35V
2128	3198 016 31020	1nF 10% 25V 0603
2129	2222 867 15339	33pF 5% 50V 0603
2129	4822 126 13956	68pF 5% 63V 0603
2130	3198 030 82280	2.2μF 10% 50V
2131	3198 030 74780	4u7 20% 35V
2131	5322 124 41945	22μF 20% 35V SMD
2132	2238 586 59812	100nF 20-80% 50V 0603
2135	3198 030 74780	4u7 20% 35V
2136	4822 126 11785	47pF 5% 50V 0603
2137	2238 586 59812	100nF 20-80% 50V 0603
2139	2238 586 59812	100nF 20-80% 50V 0603
2141	4822 126 11785	47pF 5% 50V 0603
2146	2238 586 59812	100nF 20-80% 50V 0603
2154	4822 126 13879	220nF 20% 16V
2200	3198 016 31020	1nF 10% 25V 0603
2201	4822 126 14494	22nF 10% 25V 0603
2202	2238 586 59812	100nF 20-80% 50V 0603
2203	3198 030 74780	4u7 20% 35V
2204	2222 867 15339	33pF 5% 50V 0603
2205	2238 586 59812	100nF 20-80% 50V 0603
2206	2238 586 59812	100nF 20-80% 50V 0603
2207	2222 867 15339	33pF 5% 50V 0603
2208	2238 586 59812	100nF 20-80% 50V 0603
2209	2238 586 59812	100nF 20-80% 50V 0603
2210	2238 586 59812	100nF 20-80% 50V 0603
2211	2238 586 59812	100nF 20-80% 50V 0603
2212	2238 586 59812	100nF 20-80% 50V 0603
2213	2238 586 59812	100nF 20-80% 50V 0603
2214	2238 586 59812	100nF 20-80% 50V 0603
2215	2238 586 59812	100nF 20-80% 50V 0603
2216	2238 586 59812	100nF 20-80% 50V 0603
2217	2238 586 59812	100nF 20-80% 50V 0603
2218	3198 030 74780	4u7 20% 35V

2219	2238 586 59812	100nF 20-80% 50V 0603
2220	2238 586 59812	100nF 20-80% 50V 0603
2221	2238 586 59812	100nF 20-80% 50V 0603
2222	2238 586 59812	100nF 20-80% 50V 0603
2223	2238 586 59812	100nF 20-80% 50V 0603
2224	2238 586 59812	100nF 20-80% 50V 0603
2225	2238 586 59812	100nF 20-80% 50V 0603
2226	2238 586 59812	100nF 20-80% 50V 0603
2227	2238 586 59812	100nF 20-80% 50V 0603
2228	2238 586 59812	100nF 20-80% 50V 0603
2229	2238 586 59812	100nF 20-80% 50V 0603
2230	3198 030 74780	4u7 20% 35V
2231	2238 586 59812	100nF 20-80% 50V 0603
2230	2238 586 59812	100nF 20-80% 50V 0603
2231	2238 586 59812	100nF 20-80% 50V 0603
2302	2238 586 59812	100nF 20-80% 50V 0603
2303	2238 586 59812	100nF 20-80% 50V 0603
2304	3198 030 74780	4u7 20% 35V
2305	3198 030 74780	4u7 20% 35V
2306	2238 586 59812	100nF 20-80% 50V 0603
2307	2238 586 59812	100nF 20-80% 50V 0603
2308	2238 586 59812	100nF 20-80% 50V 0603
2309	2238 586 59812	100nF 20-80% 50V 0603
2310	2238 586 59812	100nF 20-80% 50V 0603
2311	3198 030 74780	4u7 20% 35V
2312	2238 586 59812	100nF 20-80% 50V 0603
2402	2238 586 59812	100nF 20-80% 50V 0603
2403	3198 030 74780	4u7 20% 35V
2404	2238 586 59812	100nF 20-80% 50V 0603
2405	2238 586 59812	100nF 20-80% 50V 0603
2406	2238 586 59812	100nF 20-80% 50V 0603
2407	2238 586 59812	100nF 20-80% 50V 0603
2408	2238 586 59812	100nF 20-80% 50V 0603
2409	2238 586 59812	100nF 20-80% 50V 0603
2410	2238 586 59812	100nF 20-80% 50V 0603
2411	3198 030 74780	4u7 20% 35V
2412	2238 586 59812	100nF 20-80% 50V 0603
2413	2238 586 59812	100nF 20-80% 50V 0603
2414	2238 586 59812	100nF 20-80% 50V 0603
2415	2238 586 59812	100nF 20-80% 50V 0603
2416	2238 586 59812	100nF 20-80% 50V 0603
2417	2238 586 59812	100nF 20-80% 50V 0603
2418	2238 586 59812	100nF 20-80% 50V 0603
2419	2238 586 59812	100nF 20-80% 50V 0603
2420	2238 586 59812	100nF 20-80% 50V 0603
2421	2238 586 59812	100nF 20-80% 50V 0603
2422	2238 586 59812	100nF 20-80% 50V 0603
2423	2238 586 59812	100nF 20-80% 50V 0603
2424	2238 586 59812	100nF 20-80% 50V 0603
2425	2238 586 59812	100nF 20-80% 50V 0603
2426	2238 586 59812	100nF 20-80% 50V 0603
2427	2238 586 59812	100nF 20-80% 50V 0603
2428	2238 586 59812	100nF 20-80% 50V 0603
2429	2238 586 59812	100nF 20-80% 50V 0603
2430	2238 586 59812	100nF 20-80% 50V 0603
2431	3198 030 74780	4u7 20% 35V
2432	2238 586 59812	100nF 20-80% 50V 0603
2433	2238 586 59812	100nF 20-80% 50V 0603
2434	2238 586 59812	10

2522	2238 586 59812	100nF 20-80% 50V 0603	3119	4822 051 30222	2.2kΩ 5% 0.062W	3607	5322 117 13059	560Ω 1% 0.063W 0603
2523	2238 586 59812	100nF 20-80% 50V 0603	3120	4822 051 30153	15kΩ 5% 0.062W	3608	4822 051 30102	1kΩ 5% 0.062W
2524	2238 586 59812	100nF 20-80% 50V 0603	3121	4822 117 12917	1Ω 5% 0.062W 0603	3610	4822 117 12917	1Ω 5% 0.062W 0603
2525	2238 586 59812	100nF 20-80% 50V 0603	3122	4822 051 30123	12kΩ 5% 0.062W	3611	5322 117 13059	560Ω 1% 0.063W 0603
2526	2238 586 59812	100nF 20-80% 50V 0603	3122	5322 117 13033	15kΩ 1% 0.063W 0603	3612	5322 117 13059	560Ω 1% 0.063W 0603
2527	2238 586 59812	100nF 20-80% 50V 0603	3123	2322 704 61103	11kΩ 0603 RC22H 1%	3613	4822 051 30102	1kΩ 5% 0.062W
2528	2238 586 59812	100nF 20-80% 50V 0603	3123	2322 704 62002	2kΩ 1% 0603	3615	4822 051 30101	100Ω 5% 0.062W
2529	2238 586 59812	100nF 20-80% 50V 0603	3124	2322 704 63002	3kΩ 1% 0603	3616	5322 117 13059	560Ω 1% 0.063W 0603
2530	2238 586 59812	100nF 20-80% 50V 0603	3124	4822 051 30562	5.6kΩ 5% 0.063W 0603	3617	5322 117 13059	560Ω 1% 0.063W 0603
2531	2238 586 59812	100nF 20-80% 50V 0603	3125	4822 117 12139	22Ω 5% 0.062W	3618	4822 051 30102	1kΩ 5% 0.062W
2532	2238 586 59812	100nF 20-80% 50V 0603	3126	4822 117 12891	220kΩ 1% 0.063W 0603	3619	4822 051 30561	560Ω 5% 0.062W
2533	2238 586 59812	100nF 20-80% 50V 0603	3127	4822 051 30479	47Ω 5% 0.062W	3620	4822 051 30222	2.2kΩ 5% 0.062W
2534	2238 586 59812	100nF 20-80% 50V 0603	3128	4822 051 30479	47Ω 5% 0.062W	3621	5322 117 13059	560Ω 1% 0.063W 0603
2535	2238 586 59812	100nF 20-80% 50V 0603	3129	4822 051 30479	47Ω 5% 0.062W	3622	5322 117 13059	560Ω 1% 0.063W 0603
2536	2238 586 59812	100nF 20-80% 50V 0603	3130	2120 611 00019	4.7kΩ NTC 0603 0.1W 5%	3623	4822 051 30101	100Ω 5% 0.062W
2537	2238 586 59812	100nF 20-80% 50V 0603	3131	4822 117 12917	1Ω 5% 0.062W 0603	3624	4822 051 30102	1kΩ 5% 0.062W
2538	2238 586 59812	100nF 20-80% 50V 0603	3132	4822 117 12917	1Ω 5% 0.062W 0603	3625	4822 051 30101	100Ω 5% 0.062W
2539	3198 030 74780	4u7 20% 35V	3133	4822 117 12917	1Ω 5% 0.062W 0603	3626	5322 117 13059	560Ω 1% 0.063W 0603
2540	3198 030 74780	4u7 20% 35V	3134	4822 117 12917	1Ω 5% 0.062W 0603	3627	5322 117 13059	560Ω 1% 0.063W 0603
2541	3198 030 74780	4u7 20% 35V	3135	4822 117 12917	1Ω 5% 0.062W 0603	3628	4822 051 30102	1kΩ 5% 0.062W
2542	3198 030 74780	4u7 20% 35V	3136	4822 117 12917	1Ω 5% 0.062W 0603	3629	4822 051 30181	180Ω 5% 0.062W
2543	2238 586 59812	100nF 20-80% 50V 0603	3137	4822 051 30472	4.7kΩ 5% 0.062W	3630	4822 051 30181	180Ω 5% 0.062W
2544	2238 586 59812	100nF 20-80% 50V 0603	3138	4822 051 30472	4.7kΩ 5% 0.062W	3631	4822 117 12917	1Ω 5% 0.062W 0603
2565	4822 122 33753	150pF 5% 50V	3200	4822 051 30332	3.3kΩ 5% 0.062W	3632	4822 051 30561	560Ω 5% 0.062W
2600	2238 586 59812	100nF 20-80% 50V 0603	3201	4822 051 30152	1.5kΩ 5% 0.062W	3633	4822 051 30561	560Ω 5% 0.062W
2601	4822 126 11785	47pF 5% 50V 0603	3202	4822 051 30103	10kΩ 5% 0.062W	3635	4822 051 30101	100Ω 5% 0.062W
2602	4822 126 11785	47pF 5% 50V 0603	3203	4822 117 12139	22Ω 5% 0.062W	3636	4822 051 30181	180Ω 5% 0.062W
2605	2238 586 59812	100nF 20-80% 50V 0603	3204	4822 051 30101	100Ω 5% 0.062W	3637	4822 051 30101	100Ω 5% 0.062W
2606	4822 126 11785	47pF 5% 50V 0603	3205	4822 051 30101	100Ω 5% 0.062W	3638	4822 051 30222	2.2kΩ 5% 0.062W
2607	4822 126 11785	47pF 5% 50V 0603	3206	4822 051 30101	100Ω 5% 0.062W	3639	4822 051 20008	Jumper 0805
2608	2238 586 59812	100nF 20-80% 50V 0603	3207	4822 051 30103	10kΩ 5% 0.062W	3639	4822 051 30008	Jumper 0603
2609	2238 586 59812	100nF 20-80% 50V 0603	3208	4822 117 12139	22Ω 5% 0.062W	3900	4822 051 30103	10kΩ 5% 0.062W
2610	2238 586 59812	100nF 20-80% 50V 0603	3209	4822 051 30103	10kΩ 5% 0.062W	3901	4822 117 12139	22Ω 5% 0.062W
2611	4822 126 11785	47pF 5% 50V 0603	3211	4822 051 30222	2.2kΩ 5% 0.062W	3902	4822 051 30472	4.7kΩ 5% 0.062W
2612	4822 126 11785	47pF 5% 50V 0603	3212	4822 051 30152	1.5kΩ 5% 0.062W	3902	4822 117 12925	47kΩ 1% 0.063W 0603
2613	2238 586 59812	100nF 20-80% 50V 0603	3213	4822 051 30103	10kΩ 5% 0.062W	3903	4822 051 30472	4.7kΩ 5% 0.062W
2614	2238 586 59812	100nF 20-80% 50V 0603	3214	4822 051 30103	10kΩ 5% 0.062W	3903	4822 117 13632	100kΩ 1% 0603 0.62W
2615	2238 586 59812	100nF 20-80% 50V 0603	3215	4822 051 30103	10kΩ 5% 0.062W	3904	4822 117 12139	22Ω 5% 0.062W
2616	4822 126 11785	47pF 5% 50V 0603	3216	4822 051 30103	10kΩ 5% 0.062W	3906	4822 051 30479	47Ω 5% 0.062W
2617	4822 126 11785	47pF 5% 50V 0603	3217	4822 051 30101	100Ω 5% 0.062W	3908	4822 117 12139	22Ω 5% 0.062W
2618	2238 586 59812	100nF 20-80% 50V 0603	3218	4822 051 30101	100Ω 5% 0.062W	3910	4822 051 30101	100Ω 5% 0.062W
2619	2238 586 59812	100nF 20-80% 50V 0603	3219	4822 051 30103	10kΩ 5% 0.062W	3911	4822 051 30103	10kΩ 5% 0.062W
2620	2238 586 59812	100nF 20-80% 50V 0603	3220	4822 051 30103	10kΩ 5% 0.062W	3913	4822 051 30682	6.8kΩ 5% 0.062W
2621	4822 126 11785	47pF 5% 50V 0603	3221	4822 051 30103	10kΩ 5% 0.062W	3914	4822 051 30479	47Ω 5% 0.062W
2622	4822 126 11785	47pF 5% 50V 0603	3222	4822 051 30103	10kΩ 5% 0.062W	3915	4822 051 30479	47Ω 5% 0.062W
2625	2238 586 59812	100nF 20-80% 50V 0603	3223	4822 051 30222	2.2kΩ 5% 0.062W	3916	4822 117 13632	100kΩ 1% 0603 0.62W
2626	4822 126 11785	47pF 5% 50V 0603	3224	4822 051 30103	10kΩ 5% 0.062W	3917	4822 117 12139	22Ω 5% 0.062W
2627	4822 126 11785	47pF 5% 50V 0603	3225	4822 051 30103	10kΩ 5% 0.062W	3918	4822 117 13632	100kΩ 1% 0603 0.62W
2628	2238 586 59812	100nF 20-80% 50V 0603	3226	4822 051 30103	10kΩ 5% 0.062W	3919	4822 051 30101	100Ω 5% 0.062W
2629	2238 586 59812	100nF 20-80% 50V 0603	3227	4822 117 12139	22Ω 5% 0.062W	3920	4822 117 12139	22Ω 5% 0.062W
2630	3198 030 74780	4u7 20% 35V	3228	4822 117 12139	22Ω 5% 0.062W	3921	4822 051 30103	10kΩ 5% 0.062W
2632	2238 586 59812	100nF 20-80% 50V 0603	3229	2322 704 61303	13kΩ 1% 0603	3922	4822 051 30682	6.8kΩ 5% 0.062W
2633	2238 586 59812	100nF 20-80% 50V 0603	3230	2322 704 61303	13kΩ 1% 0603	3923	4822 117 13632	100kΩ 1% 0603 0.62W
2634	4822 126 14494	22nF 10% 25V 0603	3231	5322 117 13042	3.9kΩ 1% 0.063W 0603	3924	4822 051 30152	1.5kΩ 5% 0.062W
2635	2238 586 59812	100nF 20-80% 50V 0603	3232	5322 117 13042	3.9kΩ 1% 0.063W 0603	3925	4822 051 30472	4.7kΩ 5% 0.062W
2636	3198 030 74780	4u7 20% 35V	3234	3198 031 14720	1206 4X4K7 PM5	4100	4822 051 30008	Jumper 0603
2722	2238 586 59812	100nF 20-80% 50V 0603	3235	4822 117 12917	1Ω 5% 0.062W 0603	4103	4822 051 30008	Jumper 0603
2900	2238 586 59812	100nF 20-80% 50V 0603	3236	4822 117 13576	NETW 4 X 33R 5% 1206	4104	4822 051 30008	Jumper 0603
2901	2238 586 59812	100nF 20-80% 50V 0603	3237	4822 117 13576	NETW 4 X 33R 5% 1206	4106	4822 051 30008	Jumper 0603
2902	2238 586 59812	100nF 20-80% 50V 0603	3239	4822 051 30103	10kΩ 5% 0.062W	4107	4822 051 30008	Jumper 0603
2903	2238 586 59812	100nF 20-80% 50V 0603	3241	4822 051 30103	10kΩ 5% 0.062W	4108	4822 051 30008	Jumper 0603
2904	2238 586 59812	100nF 20-80% 50V 0603	3243	4822 051 30103	10kΩ 5% 0.062W	4109	4822 051 30008	Jumper 0603
2906	2238 586 59812	100nF 20-80% 50V 0603	3244	4822 051 30103	10kΩ 5% 0.062W	4110	4822 051 30008	Jumper 0603
2907	3198 030 74780	4u7 20% 35V	3245	4822 051 30103	10kΩ 5% 0.062W	4111	4822 051 30008	Jumper 0603
2908	2238 586 59812	100nF 20-80% 50V 0603	3300	4822 051 30479	47Ω 5% 0.062W	4406	4822 051 30008	Jumper 0603
2909	4822 126 14247	1.5nF 50V 0603	3301	4822 051 30479	47Ω 5% 0.062W	4409	4822 051 30008	Jumper 0603
2911	2238 586 59812	100nF 20-80% 50V 0603	3400	4822 051 30101	100Ω 5% 0.062W	4501	4822 051 30008	Jumper 0603
2912	4822 126 14247	1.5nF 50V 0603	3401	4822 051 30101	100Ω 5% 0.062W			
2914	3198 030 74780	4u7 20% 35V	3403	4822 051 30103	10kΩ 5% 0.062W			
2915	2238 586 59812	100nF 20-80% 50V 0603	3404	4822 051 30008	Jumper 0603			
2916	4822 126 14494	22nF 10% 25V 0603	3405	4822 051 30332	3.3kΩ 5% 0.062W	5100	4822 157 11717	BLM31P500SPT
			3406	4822 051 30479	47Ω 5% 0.062W	5101	4822 157 11717	BLM31P500SPT
			3407	4822 051 30181	180Ω 5% 0.062W	5102	4822 157 11499	BLM11P600SPT
			3408	4822 117 12139	22Ω 5% 0.062W	5103	4822 157 11499	BLM11P600SPT
			3409	4822 117 12139	22Ω 5% 0.062W	5200	4822 157 11499	BLM11P600SPT
			3410	4822 117 12139	22Ω 5% 0.062W	5201	4822 157 11499	BLM11P600SPT
3100	4822 051 30103	10kΩ 5% 0.062W	3500	4822 051 30101	100Ω 5% 0.062W	5202	4822 157 11499	BLM11P600SPT
3101	4822 051 30222	2.2kΩ 5% 0.062W	3501	4822 051 30101	100Ω 5% 0.062W	5203	4822 157 11499	BLM11P600SPT
3102	4822 051 30103	10kΩ 5% 0.062W	3502	4822 051 30222	2.2kΩ 5% 0.062W	5204	4822 157 11499	BLM11P600SPT
3103	4822 051 30103	10kΩ 5% 0.062W	3503	4822 051 30102	1kΩ 5% 0.062W	5205	4822 157 11499	BLM11P600SPT
3104	4822 051 30479	47Ω 5% 0.062W	3504	4822 051 30681	680Ω 5% 0.062W	5206	4822 157 11499	BLM11P600SPT
3105	4822 051 30479	47Ω 5% 0.062W	3505	4822 117 12139	22Ω 5% 0.062W	5207	4822 157 11499	BLM11P600SPT
3106	4822 051 30479	47Ω 5% 0.062W	3506	4822 051 30222	2.2kΩ 5% 0.062W	5208	4822 157 11499	BLM11P600SPT
3107	4822 051 30109	10Ω 5% 0.062W	3507	4822 051 30472	4.7kΩ 5% 0.062W	5209	4822 157 11499	BLM11P600SPT
3108	4822 051 30479							

5503	4822 157 11499	BLM11P600SPT
5504	4822 157 11499	BLM11P600SPT
5505	4822 157 11499	BLM11P600SPT
5506	4822 157 11499	BLM11P600SPT
5507	4822 157 11499	BLM11P600SPT
5508	4822 157 11499	BLM11P600SPT
5600	4822 157 70651	12μH (NL322522T-120J)
5601	4822 157 70651	12μH (NL322522T-120J)
5602	4822 157 70651	12μH (NL322522T-120J)
5603	4822 157 70651	12μH (NL322522T-120J)
5604	4822 157 70651	12μH (NL322522T-120J)
5605	4822 157 70651	12μH (NL322522T-120J)
5606	4822 157 70649	4,7μH (NL322522T-4R7J)
5607	4822 157 70649	4,7μH (NL322522T-4R7J)
5900	4822 157 11717	BLM31P500SPT
5901	4822 157 11717	BLM31P500SPT
5903	4822 157 11499	BLM11P600SPT
5904	4822 157 11717	BLM31P500SPT
5905	4822 157 11499	BLM11P600SPT
5907	4822 157 11499	BLM11P600SPT



6500	4822 130 80622	BAT54
6900	4822 130 80622	BAT54



7100	9352 692 48557	SAA7333HL/M1
7101	9322 166 67668	MT48LC4M16A2TG-7E
7102	5322 209 16384	PC74HCT9046AD
7103	9322 170 16685	NCS7SZ58
7104	9352 456 50115	HC1G04
7200	9322 169 81671	STI5508EVB
7201	9322 130 41668	M24C64-WMN6
7202	4822 209 30212	PC74HCT125T
7203	9322 142 88668	LF25CDT
7204	9322 142 88668	LF25CDT
7300	9322 166 67668	MT48LC4M16A2TG-7E
7301	3104 123 96771	FL.2 DVDR 1.5 DIG2.BIN
7302	3104 123 96761	FL.1 DVDR 1.5 DIG1.BIN
7303	9352 499 60118	74LVC00AD
7402	9322 166 67668	MT48LC4M16A2TG-7E
7403	9352 701 80557	SAA6752HS/V101
7404	9322 142 88668	LF25CDT
7500	9352 673 95518	SAA7118E/V1
7501	9352 500 60118	74LVC32AD
7502	5322 209 71589	74HC74D
7504	5322 130 60159	BC846B
7600	5322 130 60159	BC846B
7601	5322 130 60159	BC846B
7602	5322 130 60159	BC846B
7603	5322 130 60159	BC846B
7604	5322 130 60159	BC846B
7605	5322 130 60159	BC846B
7606	5322 130 60159	BC846B
7702	9352 501 00118	74LVC86ADB
7900	9322 151 71668	MK2703STR
7901	5322 130 60159	BC846B
7902	9322 165 15685	NCP303LSN30
7904	4822 209 16399	74LVC04AD
7905	5322 209 71568	PC74HCT14T
7906	4822 242 10838	27MHZ 120P FX0-31FT

Digital Board 2.1 (Chrysalis)

Various

1001	2422 543 01115	24.576MHz 12P QS06
1001	2422 543 89017	24M576 18P CX-11F
1100	2422 025 17018	BM V 15P F 1.00 FFC 0.3 R
1102	2422 025 18185	CON V 40P M 2.54
1103	2422 025 17104	Connector 7p m
1104	2422 025 16729	Connector FFC 10p m
1105	2422 025 17018	BM V 15P F 1.00 FFC 0.3 R
1201	2422 543 01115	24.576MHz 12P QS06
1203	2422 025 17955	V 6P M 1.00 SM SR R
1400	8203 107 92221	CON BM V 28P SMD 1.27
1500	2422 025 17441	BM V 12P M 2.00 PH SMD R
1505▲	2422 086 11087	FUSE F 1A 125V
1506▲	2422 086 11087	FUSE F 1A 125V
1507▲	2422 086 11087	FUSE F 1A 125V
1900	2422 025 16389	BM V 22P F 1.00 FFC 0.3 R
1901	2422 025 16987	V 6P F 1.00 SM FFC 0.3 R
1904	2422 025 16389	BM V 22P F 1.00 FFC 0.3 R



2014	4822 124 80151	47μF 20% 16V
2015	2238 586 59812	100nF 20-80% 50V 0603

2016	2238 586 59812	100nF 20-80% 50V 0603
2017	2238 586 59812	100nF 20-80% 50V 0603
2018	2238 586 59812	100nF 20-80% 50V 0603
2019	2238 586 59812	100nF 20-80% 50V 0603
2020	2238 586 59812	100nF 20-80% 50V 0603
2021	2238 586 59812	100nF 20-80% 50V 0603
2022	2020 021 91729	4.7μF 20% 35V
2026	2238 586 59812	100nF 20-80% 50V 0603
2027	2238 586 59812	100nF 20-80% 50V 0603
2028	2238 586 59812	100nF 20-80% 50V 0603
2029	2238 586 59812	100nF 20-80% 50V 0603
2030	2238 586 59812	100nF 20-80% 50V 0603
2031	2238 586 59812	100nF 20-80% 50V 0603
2032	2238 586 59812	100nF 20-80% 50V 0603
2033	2020 021 91729	4.7μF 20% 35V
2035	2238 586 59812	100nF 20-80% 50V 0603
2036	4822 126 14506	270pF 5% 50V 0603
2037	2238 586 59812	100nF 20-80% 50V 0603
2038	2238 586 59812	100nF 20-80% 50V 0603
2039	2238 586 59812	100nF 20-80% 50V 0603
2040	2238 586 59812	100nF 20-80% 50V 0603
2041	2238 586 59812	100nF 20-80% 50V 0603
2042	2238 586 59812	100nF 20-80% 50V 0603
2043	2238 586 59812	100nF 20-80% 50V 0603
2044	2020 021 91729	4.7μF 20% 35V
2046	4822 122 33761	22pF 5% 50V
2048	4822 122 33753	150pF 5% 50V
2049	2020 021 91729	4.7μF 20% 35V
2050	2238 586 59812	100nF 20-80% 50V 0603
2052	2238 586 59812	100nF 20-80% 50V 0603
2053	2238 586 59812	100nF 20-80% 50V 0603
2054	2238 586 59812	100nF 20-80% 50V 0603
2056	2238 586 59812	100nF 20-80% 50V 0603
2058	2238 586 59812	100nF 20-80% 50V 0603
2059	4822 126 14507	18pF 5% 50V 0603
2060	4822 126 14507	18pF 5% 50V 0603
2061	2238 586 59812	100nF 20-80% 50V 0603
2063	2238 586 59812	100nF 20-80% 50V 0603
2064	2238 586 59812	100nF 20-80% 50V 0603
2065	2238 586 59812	100nF 20-80% 50V 0603
2066	3198 016 31020	1nF 10% 25V 0603
2067	2238 586 59812	100nF 20-80% 50V 0603
2071	2238 586 59812	100nF 20-80% 50V 0603
2101	2238 916 15641	22nF 10% 25V 0603
2103	2238 586 59812	100nF 20-80% 50V 0603
2108	4822 126 14585	100nF 10% 50V
2112	4822 126 14247	1.5nF 50V 0603
2113	4822 126 13881	470pF 5% 50V
2116	2238 586 59812	100nF 20-80% 50V 0603
2119	4822 126 14247	1.5nF 50V 0603
2120	2238 586 59812	100nF 20-80% 50V 0603
2125	2238 586 59812	100nF 20-80% 50V 0603
2200	3198 017 41050	1μF 10V 0603
2201	4822 126 14506	270pF 5% 50V 0603
2202	4822 126 11663	12pF 5% 50V 0603
2203	4822 126 11663	12pF 5% 50V 0603
2206	2238 586 59812	100nF 20-80% 50V 0603
2207	2238 586 59812	100nF 20-80% 50V 0603
2209	2238 586 59812	100nF 20-80% 50V 0603
2210	2238 586 59812	100nF 20-80% 50V 0603
2212	4822 124 12095	100μF 20% 16V
2214	2238 586 59812	100nF 20-80% 50V 0603
2215	2238 586 59812	100nF 20-80% 50V 0603
2217	2238 586 59812	100nF 20-80% 50V 0603
2218	2238 586 59812	100nF 20-80% 50V 0603
2219	2238 586 59812	100nF 20-80% 50V 0603
2220	2238 586 59812	100nF 20-80% 50V 0603
2221	2238 586 59812	100nF 20-80% 50V 0603
2222	2238 586 59812	100nF 20-80% 50V 0603
2223	2238 586 59812	100nF 20-80% 50V 0603
2224	2238 586 59812	100nF 20-80% 50V 0603
2225	2238 586 59812	100nF 20-80% 50V 0603
2226	2238 586 59812	100nF 20-80% 50V 0603
2227	2238 586 59812	100nF 20-80% 50V 0603
2228	2238 586 59812	100nF 20-80% 50V 0603
2229	2238 586 59812	100nF 20-80% 50V 0603
2230	2238 586 59812	100nF 20-80% 50V 0603
2231	2238 586 59812	100nF 20-80% 50V 0603
2232	2238 586 59812	100nF 20-80% 50V 0603
2233	2238 586 59812	100nF 20-80% 50V 0603
2234	2238 586 59812	100nF 20-80% 50V 0603
2235	3198 016 31020	1nF 10% 25V 0603
2236	2020 021 91729	4.7μF 20% 35V
2237	2238 586 59812	100nF 20-80% 50V 0603
2238	2238 586 59812	100nF 20-80% 50V 0603
2308	2238 586 59812	100nF 20-80% 50V 0603
2310	2238 586 59812	100nF 20-80% 50V 0603
2403	2238 586 59812	100nF 20-80% 50V 0603
2404	4822 124 23002	10μF 20% 16V
2405	2238 586 59812	100nF 20-80% 50V 0603
2406	2238 586 59812	100nF 20-80% 50V 0603
2407	2238 586 59812	100nF 20-80% 50V 0603
2408	4822 124 23002	10μF 20% 16V
2409	2238 586 59812	100nF 20-80% 50V 0603

2410	2238 586 59812	100nF 20-80% 50V 0603
2411	2238 586 59812	100nF 20-80% 50V 0603
2412	2238 586 59812	100nF 20-80% 50V 0603
2413	2238 586 59812	100nF 20-80% 50V 0603
2414	2238 586 59812	100nF 20-80% 50V 0603
2415	2238 586 59812	100nF 20-80% 50V 0603
2416	2238 586 59812	100nF 20-80% 50V 0603
2417	2238 586 59812	100nF 20-80% 50V 0603
2418	4822 124 23002	10μF 20% 16V
2419	2238 586 59812	100nF 20-80% 50V 0603
2420	4822 124 23002	10μF 20% 16V
2421	2238 586 59812	100nF 20-80% 50V 0603
2422	2238 586 59812	100nF 20-80% 50V 0603
2423	2238 586 59812	100nF 20-80% 50V 0603
2424	2238 586 59812	100nF 20-80% 50V 0603
2425	2238 586 59812	100nF 20-80% 50V 0603
2426	2238 586 59812	100nF 20-80% 50V 0603
2427	2238 586 59812	100nF 20-80% 50V 0603
2428	2238 586 59812	100nF 20-80% 50V 0603
2429	2238 586 59812	100nF 20-80% 50V 0603
2432	2238 586 59812	100nF 20-80% 50V 0603
2433	2238 586 59812	100nF 20-80% 50V 0603
2512	2020 001 90085	82μF 6V3 20%
2512	2020 021 91672	100μF 6V3 20%
2512	2020 021 91857	100μF 6V3 20%
2514	2238 586 59812	100nF 20-80% 50V 0603
2515	3198 017 44740	470nF 10V 0603
2516	2020 001 90085	82μF 6V3 20%
2516	2020 021 91672	100μF 6V3 20%
2516	2020 021 91857	100μF 6V3 20%
2518	2020 552 94427	100pF 5% 50V 0603
2519	2238 586 59812	100nF 20-80% 50V 0603
2521	2238 586 59812	100nF 20-80% 50V 0603
2524	2238 586 59812	100nF 20-80% 50V 0603
2525	2238 586 59812	100nF 20-80% 50V 0603
2526	2238 586 59812	100nF 20-80% 50V 0603
2527	5322 126 11583	10nF 10% 50V 0603
2806	2238 586 59812	100nF 20-80% 50V 0603
2807	2238 586 59812	100nF 20-80% 50V 0603
2808	2238 586 59812	100nF 20-80% 50V 0603
2809	2238 586 59812	100nF 20-80% 50V 0603
2810	2238 586 59812	100nF 20-80% 50V 0603
2811	2238 586 59812	100nF 20-80% 50V 0603
2812	2238 586 59812	100nF 20-80% 50V 0603
2820	2238 586 59812	100nF 20-80% 50V 0603
2821	2238 586 59812	100nF 20-80% 50V 0603
2822	2238 586 59812	100nF 20-80% 50V 0603
2823	2238 586 59812	100nF 20-80% 50V 0603
2824	2238 586 59812	100nF 20-80% 50V 0603
2825	2238 586 59812	100nF 20-80% 50V 0603
2826	2238 586 59812	100nF 20-80% 50V 0603
2830	2238 586 59812	100nF 20-80% 50V 060

[illegible]

11. Revision List

11.1 3122 785 13321

- May 19th 2003.
Added Digital Board Chrysalis 2.1.
The Digital Board Chrysalis 2.1_E1 replaces Digital Board 1.5
Empress and DVIO 1.8 board in DVDR75/0x1.
The Digital Board Chrysalis 2.1_E2 replaces Digital Board 1.5
Empress in DVDR70/0x1.

11.2 3122 785 13322

- Sep 22th 2003.
Added parts for drive AV3 / VAD8031
The AV3 is used as alternative to the AV2 / VAE8020.